MILITARY SPECIFICATION

COMPUTER, ATTACK TYPE CPU-73 A/P

This amendment forms a part of MIL-C-83856(USAF), dated 2 MAY 1969, and is approved for use within the Department of the Air Force and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

* Delete "2.1" and add:
"2.1 Government documents."

* Add:
"2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation."

* Under SPECIFICATIONS, Federal, add: "PPP-B-601 Boxes, Wood, Cleated Plywood" and "PPP-B-636 Box, Shipping, Fiberboard".

* Under STANDARDS, Military, delete "MIL-STD-831"; "MS63033" and substitute: "MIL-E-20652/1 Eyelet, Metallic, Rolled Flange Type, and Eyelet Washer".

Add boxed paragraph at bottom center of page.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Oklahoma City Air Logistics Center/MMEDO, Tinker AFB OK 73145-5990 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

PAGE 2

* Add:
"2.2 Other publications. The following document(s) form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted shall be those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS shall be the issues of the nongovernment documents which is current on the date of the solicitation.

ASTM D3951 Packaging, Commercial

(Application for copies should be addressed to: ASTM, 1916 Race St, Philadelphia PA 19103.)

AMSC N/A

FSC 6605

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-02-28 03:44:42
Check the source to verify that this is the current version before use.

(Nongovernment standards and other publications are normally available from the organizations which prepare or which distribute the documents. These documents also may be available in or through libraries or other informational services.)"

3.3.1 Delete and substitute:
"3.3.1 Discs. The computer discs shall be constructed of vinyl chloride in accordance with the Composition B, Type II, Class 3 of L-P-535. The material shall be flat, homogenous, and resistant to water and warpage. The front and rear discs shall be .040 inch thick. The center disc shall be .060 inch thick."

* Add:
"3.3.1.1 Recovered materials. Recovered materials shall be used to the maximum extent possible without jeopardizing the end use of the item."

3.3.2 Line 2 delete "MS63033" and add: "MIL-E-20652/1".

PAGE 3

3.3.5 Delete and substitute the following:
"3.3.5 Operational manual. One copy of the current operational manual, technical order 5N5-14-14-1, shall be packed in the pocket of the case (reference paragraph 3.3.4). The contractor must request the government to supply current printed copies for backup."

3.4.2.1 Line 7, change "like" to "line".

PAGE 4

3.4.2.3 Last line, change "Grade C" to "Class 3".

PAGE 38

3.4.3.1.3.4 In line 3 change "0.0005" to "0.005". In line 7 change "clockwise" to "counterclockwise".

PAGE 62

* Add:
"4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material."

PAGE 64

4.4.3 Delete and substitute the following:
"4.4.3 First article tests. The first article test shall consist of tests of 4.5.1 and all of the functional accuracy tests specified in 4.4.4.1 through 4.4.4.8."

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:49Z
Check the source to verify that this is the current version before use.

* Delete "4.4.2, a, b, c".

PAGE 66

TABLE XXXI, first column, last line: Change "75.00" to "70.00".

PAGE 67

TABLE XXXIV: Change TARGET TAS INDICATION for PRESSURE ALTITUDES of 15 and 30 as shown.

PRESSURE ALTITUDE	TARGET TAS INDICATION MINIMUM	MAXIMUM
15	13.29	13.33
30	18.32	18.38

PAGE 68

4.4.4.3.4 Line 1: Change -15° to $+15^{o}$.

PAGE 70

Delete existing Table XXXVI and add: New Table XXXVI shown as page 4 of this amendment.

PAGE 71

Add the following new paragraph:
4.4.4.8 DT + factors table data inspection. The data contained within the DT + factors table on the front disc shall be visually inspected to verify that this data is in accordance with Table XXVIII.

PAGE 73

TABLE XXXVII, first column, first line change: "0' on Pressure" to read "0' on Pressure Altitude Scale Center Disc".

PAGE 76

* Delete Section 5 in its entirety and add:

"5 PACKAGING

5.1 Preservation-packaging. Preservation-packaging shall be level A, C, or Industrial, as specified (see 6.2).

5.1.1 Level A.

5.1.1.1 Cleaning. Computer shall be cleaned in accordance with process C-1 of MIL-P-116.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:49Z
Check the source to verify that this is the current version before use.

5.1.1.2 Drying. Computer shall be dried in accordance with process D-4 of MIL-P-116.

5.1.1.3 Preservation application. Not applicable.

5.1.1.4 Unit packaging. Unless otherwise specified by the contracting activity, each computer shall be packaged in quantity unit packs of one each in accordance with Method 1C1 of MIL-P-116. Overbox completed pack in PPP-B-636 container.

TABLE XXXVI

LEAD DISTANCE WINDOW LEAD DISTANCE SCALE ACCURACY TEST

Lead Distance Scale	Graduation Mark	Targer TAS Indication	
		Minimum	Maximum
90° HCA Single Turn	22 33 44 55 66	1.2290 1.369 1.545 1.813 2.276	1.232 1.372 1.555 1.818 2.284
90° HCA D.T.F.	10 25 40 55 70	.016150 .006690 .004160 .002846 .001947	.016250 .006710 .004173 .002854 .001953
90° HCA FINAL LEAD-40° Turn	22 34 46 58 70	.2560 .2709 .2910 .3220 .3855	.2568 .2717 .2918 .3230 .3865
110° HCA Single Turn	18 26 35 43 52	.904 1.028 1.220 1.482 2.025	.906 1.030 1.224 1.486 2.035
110° HCA D.T.F.	10 25 40 55 70	.012350 .004990 .003036 .002014 .001314	.012450 .005030 .003046 .002020 .001318
110° HCA FINAL LEAD-30° Turn	18 26 35 43 52	.1706 .1880 .2146 .2510 .3266	.1714 .1888 .2154 .2518 .3276

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:49Z
Check the source to verify that this is the current version before use.

Apply sufficient cushioning material between bag and unit container of a type, density, and thickness to insure shock transmission does not exceed peak values in G's established for the computer when completed packs are subjected to the rough handling drop tests of MIL-P-116.

5.1.2 Level C. Each computer shall be clean, dry, and individually packaged in a manner that will afford adequate protection against corrosion, deterioration, and physical damage during shipment from supply source to the first receiving activity.

5.1.3 Industrial. The Industrial preservation of computer shall be in accordance with ASTM D3951.

5.2 Packing. Packing shall be level A, B, C, or Industrial as specified (see 6.2).

5.2.1 Level A. Computer packaged as specified in 5.1.1 shall be packed in shipping containers conforming to PPP-B-601, Styles A or B, Class overseas, unless otherwise specified by the contracting activity. Insofar as practical, exterior shipping container shall be of uniform shape size, minimum tare and cube consistant with the protection required.

5.2.2 Level B. Computer packaged as specified in 5.1.1 shall be packed in shipping containers conforming to PPP-B-636, class weather-resistant, unless otherwise specified by the contracting activity. Other requirements as specified in 5.2.1 apply.

5.2.3 Level C. Packing shall be applied which affords adequate protection during domestic shipment from the supply source to the first receiving activity for immediate use. This level shall conform to applicable carrier rules and regulations.

5.2.4 Industrial. The packaged computer shall be packed in accordance with ASTM D3951.

5.3 Marking. In addition to any other markings required by the contract or order (see 6.2), interior and exterior containers shall be marked in accordance with MIL-STD-129."

The margins of this amendment are marked with an asterisk to indicate where changes (addtions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
AIR FORCE - 99

Preparing Activity:
AIR FORCE - 71

Project Number:
6605 - F358

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:49Z
Check the source to verify that this is the current version before use.