NOTE: The document identifier and heading has been changed on this page to reflect that this is a performance specification. There are no other changes to this document. The document identifier on subsequent pages has not been changed, but will be changed the next time this document is revised.

INCH-POUND


MIL-PRF-83536/18
27 March 1992

PERFORMANCE SPECIFICATION SHEET

RELAYS, ELECTROMAGNETIC, ESTABLISHED RELIABILITY, 4PDT, LOW LEVEL TO 10 AMPERES, MAGNETIC LATCH, HERMETICALLY SEALED, ALL WELDED, DC COILS

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation MIL-PRF-83536.




RAISED VERTICAL FLANGE MOUNT (RVFM) WITH SOLDER HOOKS

FIGURE 1. Dimensions and configurations.

DISTRIBUTION STATEMENT A. Approved for public release, distribution is unlimited.


Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:53Z
Check the source to verify that this is the current version before use.



RAISED VERTICAL FLANGE MOUNT (RVFM) WITH SOCKET PINS

FIGURE 1 Dimensions and configurations - Continued


Source: https://assist.dla.mil -- Downloaded: 202610-23T08:53Z
Check the source to verify that this is the current version before use.




HORIZONTAL FLANGE MOUNT (HFM) WITH SOLDER HOOKS

FIGURE 1 Dimensions and configurations - Continued


Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:53Z
Check the source to verify that this is the current version before use.



CIRCUIT DIAGRAM TERMINAL VIEW



MOUNTING HOLE LAYOUT (RVFM)



MOUNTING HOLE LAYOUT (HFM)

FIGURE 1 Dimensions and configurations - Continued

Source: https://assist.dla.mil -- Downloaded: 202640-23T08:53Z
Check the source to verify that this is the current version before use.

Inches	mm	Inches	mm	Inches	mm
000	0 00	172	4 37	937	23 80
001	0 03	200	5 08	1 010	25 65
002	0 05	270	6 86	1 025	26 04
005	0 13	300	7 62	1 062	26 98
040	1 02	310	7 87	1 396	35 46
050	1 27	312	7 92	1.406	35 71
062	1 58	500	12 70	1 446	36 73
150	3 81	625	15 88	1 718	43.64
156	3 96	810	20 57		

NOTES

1. Dimensions are in inches
2. Metric equivalents are given for general information only
3. Unless otherwise specified, tolerance is ± 010 (0.25 mm).
4. There shall be affixed to the relay a suitable legible circuit diagram that identifies each terminal location specified
5. These relays are polarized monostable
6. This relay shall not operate or be damaged by reverse polarity
7. Applicable to horizontal flange mount only. The circuit diagram, manufacturer's PIN, and the military PIN shall be marked on the near side The remaining portion of the nameplate data shall be marked on the far side
8. Applicable to horizontal flange mount only Relays shall be marked with the manufacturer's name or CAGE code and date code. Marking shall be with the bottom of the print adjacent to the near side
9. Socket pin terminals, except the polarizing pin, shall be gold-plated in accordance with MIL-G-45204, type II, class I The nickel underplating shall be 50 to 150 microinches thick minimum.
10. Silicone rubber gasket, AMS 3332, shore hardness 15 to 35, thickness 050 ± 005 (1 27 ±0 13 mm)
11. Relay is magnetically latched in both positions
12. All hooks shall be tin finished
13. Relays shall have a (+) sign placed on the circuit diagram as shown
14. Coil symbol optional in accordance with MIL-STD-1285
15. Indicated terminals shall be identified by contrasting beads
16. Plane of critical motion for vibration and shock is Y-axis

FIGURE 1 Dimensions and configurations - Continued

Source: https://assist.dla.mil -- Downloaded: 202610-23T08:53Z
Check the source to verify that this is the current version before use.

REQUIREMENTS

Contact data

Load ratings See table I

Low level 10 to 50 mA at 10 to 50 mV dc or peak ac

Intermediate current Applicable

Mixed loads Applicable

TABLE I Rated contact load and cycles (amperes per pole)

Type of load (high level)	Cycles x 10^3	28 V dc	115 V ac 1 phase 400 Hz	115 V ac 1 phase 50/60 Hz 1/	115/200 V ac 3 phase 400 Hz	115/200 V ac 3 phase 50/60 Hz 1/
Resistive	100	10	10	2 5	10	2 5
Inductive	20	8	8	N/A	8	N/A
Inductive	10	N/A	N/A	2 5	N/A	2 5
Motor	100	4	4	2	4	2
Lamp	100	2	2	1	N/A	N/A

1/ For 50/60 Hz rating, rupture and overload are not applicable and life for each load shall be 10,000 cycles

Life 100,000 cycles, unless otherwise specified (see table I)

Contact voltage drop or resistance

Initial contact voltage drop 0 100 volt maximum Rated resistive current at 6 V dc or peak ac Relays shall not make or break this load

Initial contact resistance 0 010 ohm maximum 50 mA max at 6 V dc or peak ac

High level life (contact voltage drop)

During life 10 percent open circuit voltage maximum

After life 0 125 volt maximum

Intermediate current (contact resistance)

During intermediate current 3 ohms maximum

After intermediate current 0 150 ohm maximum

Low level (contact resistance)

During low level 100 ohms maximum

After low level 0 150 ohm maximum at 100 mA and 28 V dc

Contact bounce 1 0 millisecond maximum

Contact stabilization time 2 5 milliseconds maximum

Overload current 40 amperes dc (60 amperes ac)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:53Z
Check the source to verify that this is the current version before use.

Rupture current· 50 amperes dc, 60 amperes ac

Time current relay characteristics See table II

TABLE II Time current relay characteristics 1/

Successive application	Amperes	Time
1	15	1 hour
2	50	5 0 seconds
3	100	1 2 seconds
4	250	0 2 second
5	350	0 1 second

1/ All relays shall withstand overload and fault currents Relays must be able to sustain five applications (make and carry only) of power concurrently on adjacent poles at each of five different current levels in the sequence listed in table II Separate relays shall be tested at 28 V dc and 115/200 V ac, 400 Hz 3-phase Cooling time between successive applications shall be 30 minutes Tests shall be performed on both normally open and normally closed contacts There shall be no failures or evidence of welding or sticking and relays shall pass contact voltage drop at the conclusion

Coil data 1/: See table III

Operate time 15 milliseconds maximum (each coil) with rated coil voltage over the temperature range.

Duty rating Continuous.

Coil transient suppression Not applicable

Neutral screen Applicable

Electrical data

Insulation resistance

Initial. 100 megohms minimum at 500 V dc

After life or environmental tests 50 megohms minimum at 500 V dc

1/ CAUTION Due to possible interaction of relay magnetic fields, the following spacing requirements, as a minimum, shall be considered in dense packaging situations.

a Row to row assisting fields· 125 (3 18 mm)

b. Row to row opposing fields 1875 (4 763 mm)

c Side to side alternating fields 0625 (1 588 mm)

d Side to side like fields 125 (3 18 mm)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:53Z
Check the source to verify that this is the current version before use.

TABLE III Dash numbers and characteristics 1/

Dash number 2/		Mount	Coil data						
			At 25°C				Over temperature range	Maximum pickup voltage	
Solder hook	Socket pin		Coil voltage (V dc) 3/		Coil resistance (ohms) minimum	Specified pickup voltage (V dc) 4/	Specified pickup voltage (V dc) 4/	High temperature test	Continuous current test
			Rated	Max					
001	002	RVFM	6	7 3	25	3 5	4 5	5 0	5 7
003	---	HFM	6	7 3	25	3 5	4 5	5 0	5 7
004	005	RVFM	12	14 5	100	6 5	9 0	9 9	11 25
006	---	HFM	12	14 5	100	6 5	9 0	9 9	11 25
007	008	RVFM	28	29 5/	405	14 5	18 0	19 8	22 5
009	---	HFM	28	29 5/	405	14 5	18 0	19 8	22 5
011	012	RVFM	48	50	1350	24 0	36 0	38 0	42 0
013	---	HFM	48	50	1350	24 0	36 0	38 0	42 0
6/ 7/ 014	---	RVFM	28	29 5/	405	14 5	18 0	19 8	22 5
6/ 7/ 015	---	HFM	28	29 5/	405	14 5	18 0	19 8	22 5

1/ Each relay possesses high level and low level capabilities However, relays previously tested or used above 10 mA resistive at 6 V dc maximum or peak ac open circuits are not recommended for subsequent use in low level applications

2/ The suffix letter L, M, P, or R to designate the applicable failure rate level shall be added to the applicable listed dash number Failure rate level (percent per 10,000 cycles) L, 3 0, M, 1 0, P, 0 1, R, 0 01 Example 001L, 002R

3/ CAUTION The use of any coil voltages less than the rated coil voltage will compromise the operation of the relay

4/ Pickup voltage as shown is for test purposes only and is not to be used for design criteria

5/ When maximum ambient temperature does not exceed +85°C the maximum coil voltage shall be 32 V dc

6/ Appendices A and B of MIL-R-83536 applicable to these dash numbers only

7/ Marking ink, when tested in accordance with ASTM-E 595 shall meet the following outgassing requirements Total Mass Loss (TML) shall not exceed 1 0 percent of the original specimen mass Collected Volatile Condensable Material (CVCM) shall not exceed 0 1 percent of the original specimen mass

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:53Z
Check the source to verify that this is the current version before use.

Dielectric withstanding voltage 3/

	All others	
	Coil to coil Coil to case	All other points
Sea level		
Initial	1000	1250
After life	1000	1000
Altitude		
At 80,000 feet	250	350
At 300,000 feet	500	500

Maximum leakage current 100 microamperes rms in accordance with MIL-R-83536

. Environmental characteristics·

Temperature range -70°C to +125°C

Maximum altitude rating 300,000 feet

Shock (specified pulse) Applicable, MIL-STD-202, method 213, test condition C except peak value shall be 200 g's for 6 ±1 ms Contact chatter shall not exceed 10 microseconds maximum for closed contacts and 1 microsecond maximum closure for open contacts

Vibration (sinusoidal) Applicable, MIL-STD-202, method 204, 30 g's except frequency range shall be 10 to 3,000 Hz Contact chatter shall not exceed 10 microseconds maximum for closed contacts and 1 microsecond maximum closure for open contacts

Vibration (random) Applicable to qualification and group C inspection Test in accordance with MIL-STD-202, method 214, test condition IG (0 4 g^2/Hz, 50 to 2000 Hz), 15 minutes each plane Contact chatter shall not exceed 10 microseconds maximum for closed contacts and 1 microsecond maximum closure for open contacts

Acceleration Applicable, except 15 g's

Physical data

Dimensions and configurations See figure 1

Weight 0 17 pound (77 2 g's)

Terminal strength

Solder hook terminals

Pull force· 10 pounds ±1 0 pound

3/ Dielectric may be improved by suitable insulation of terminals and wiring after installation

Source: https://assist.dla.mil -- Downloaded: 202640-23T08:53Z
Check the source to verify that this is the current version before use.

Bend Applicable

Twist Not applicable

Socket pin terminals

Pull force 10 pounds ±1 ½ pound

Bend Applicable

Twist Not applicable

Terminal solderability Applicable to solder hook terminals only

Seal Hermetic

Marking Applicable

Part or Identifying Number (PIN) M83536/18 (dash number from table III and suffix letter designating failure rate level) PIN is a new term encompassing previous terms used in specifications such as part number, type designator, and identification number

Qualification inspection

Qualification inspection and sample size See table IV

TABLE IV Qualification inspection and sample size 1/

Single submission	Group submission	
18 units plus 1 open unit for level L at C = 0 2/	M83536/18-008	18 units plus 1 open unit for level L at C = 0 2/
33 units plus 1 open unit for level M at C = 0 2/	"	33 units plus 1 open unit for level M at C = 0 2/
Qualification inspection as applicable	"	Qualification inspection as applicable
	M83536/18-007 M83536/18-009	2 units, qualification inspection table, group II, shock, vibration, acceleration, terminal strength, and seal
	M83536/18-002 M83536/18-006 M83536/18-012 M83536/18-014 M83536/18-015	2 units, qualification inspection table, group II 2 units, qualification inspection table, group I and group II

1/ For retention of qualification or extension of qualification to lower failure rate levels, all life test data accumulated on MIL-R-83536/19 may be used in addition to MIL-R-83536/18 data Prior to performance of retention of qualification testing, the relay manufacturer shall preselect the sampling plan

2/ The number of units required for qualification testing shall be increased as required in group V, table II of MIL-R-83536, if the contractor elects to test the number of units permitting one or more failures Prior to performance of qualification testing, the relay manufacturer shall preselect the sampling plan

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:53Z
Check the source to verify that this is the current version before use.

Qualification inspection (reduced testing) (sample size - 2 units each coil voltage and 1 unsealed unit) See table V

If the relays produced for MIL-R-83536/18 are similar in construction and design except for the suppression network to the relays produced for MIL-R-83536/19 then reduced testing for qualification of MIL-R-83536/18 relays may be performed concurrent with or subsequent to successful qualification of MIL-R-83536/19 relays For reduced testing see table V

TABLE V Qualification inspection (reduced testing)

Inspection
2 units each coil voltage Group II of qualification inspection table 1 unsealed sample unit for internal inspection

Supersession data See table VI

TABLE VI Supersession data

Superseded PIN M6106/51-	Replacement PIN M83536/18-
001	007
002	008
003	009

CONCLUDING MATERIAL

Custodians
Army - ER
Navy - EC
Air Force - 85

Review activities
Air Force - 99
DLA - ES

Preparing activity
Air Force - 85

Agent
DLA - ES

(Project 5945-0824-17)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:53Z
Check the source to verify that this is the current version before use.