INCH-POUND
MIL-PRF-83726/18J
18 July 2023
SUPERSEDING
MIL-R-83726/18H
11 January 2016

PERFORMANCE SPECIFICATION SHEET

RELAYS, HYBRID, TIME DELAY (ON RELEASE), TRACK MOUNTED, TYPE IIA, CLASS B, 10 AMPERES, 2PDT, HERMETICALLY SEALED, FIXED TIME, 0.1 TO 300 SECONDS

Inactive for new design after 23 June 1995.
No superseding document.

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification and MIL-PRF-83726.





FIGURE 1. Dimensions and configuration.

AMSC N/A FSC 5945


DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:27Z
Check the source to verify that this is the current version before use.


Inches	mm
.001	0.03
.005	0.13
.015	0.38
.031	0.79
.040	1.02
.046	1.17
.060	1.52
.064	1.63
.078	1.98
.079	2.01
.094	2.39
.140	3.56
.200	5.08
.270	6.86
.313	7.95
.400	10.16
.800	20.32
1.025	26.04
1.250	31.75
2.118	53.80
2.707	68.76



ALTERNATE KNOB ASSEMBLY



VIEW A-A



CIRCUIT DIAGRAM

TERMINAL VIEW

NOTES:

1. Dimensions are in inches.
2. Unless otherwise specified, tolerance is ±.010 (0.25 mm).
3. Metric equivalents are given for general information only.
4. Terminal numbers shall not appear on the relay header. There shall be a legible circuit diagramon the relay which identifies each terminal location specified.
5. For mounting track, see MIL-PRF-12883/49. For bracket and socket assembly, see MIL-PRF-12883/51.
6. Gasket material: Methylvinyl silicone; shore hardness A40.
7. Terminal plating: Shall provide the operational, environmental, and interface characteristics to provide a reliable interconnect to gold plated contacts. Terminals shall be gold plated. One system for gold plating that may be used is ASTM B488, type 3, class 1.25 with a nickel underplate of 50 to 150 microninches thick. The gold plating system shall enable the product to meet the performance requirements of this specification and shall be approved by the qualifying activity.
8. Enclosure finish color: SAE-AMS-STD-595, color 34449.
9. Coil suppression: Back EMF 42 V dc maximum.
10. Knob and post shall be nickel plated (100 microinches thick minimum), 303 stainless steel.

FIGURE 1. Dimensions and configuration - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:27Z
Check the source to verify that this is the current version before use.




FIGURE 1. Dimensions and configuration - Continued.

TABLE I. Dash numbers and time delay characteristics.

Dash number 1/ 2/	Time delay (seconds) ±10% 3/
-1000	0.1
-1001	1.0
-5001	5.0
-1602	16.0
-6002	60.0
-1803	180.0
-3003	300.0

1/ Additional time delay relays within the 0.1- to 300-second delay range are available. To establish Part or Identifying numbers (PIN's) not listed in table I (see "PIN" herein).
2/ PIN's having a suffix letter A following the dash number impose more stringent EMI requirements than PIN's with a suffix letter W. For Government logistical support the suffixed PIN's will be supplied (see "PIN" herein).
3/ Ten percent of the nominal value under all combinations of input voltage and environmental extremes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:27Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Contact data:

Configuration: 2PDT.

Life/load ratings: See table II.

TABLE II. Life load ratings (relay case grounded).

Type of load	Life (cycles)	Amperes	
		28 V dc	115/200 1 and 3 phase 400 Hz
Resistive	100,000	10	10
Inductive	20,000	8	8
Motor	100,000	4	4
Lamp	100,000	2	2
Mechanical life (reduced current)	400,000	2.5	2.5

Contact voltage drop:

Initial: 0.150 volt.

After life tests: 0.175 volt.

Intermediate current: Applicable in accordance with MIL-PRF-83536.

Contact bounce: 1 millisecond (maximum).

Overload:

DC: 40 amperes.

AC: 60 amperes.

Rupture: 1/

DC: 50 amperes.

AC: 80 amperes.

Input data:

Duty rating: Continuous.

Maximum voltage (over temperature range): 30 V dc.

1/ Not applicable if time current relay characteristics at 25°C are required, or if the MIL-PRF-83536/9,/10, /11 being used is qualified to MIL-PRF-83536.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:27Z
Check the source to verify that this is the current version before use.

Rated voltage (over temperature range): 28 V dc.

Minimum voltage (over temperature range): 20 V dc.

Minimum voltage (high-temperature test): 20 V dc.

Minimum voltage (continuous current tests): 20 V dc.

Maximum coil current at 25°C: 0.150 ampere.

Operate time: 10 milliseconds (maximum).

Recycle time: 50 milliseconds maximum (over the total temperature range and with both minimum and maximum input voltages). Relay will recycle if control voltage is removed from and reapplied to the control terminal C1 during the timing cycles.

Electrical data:

Insulation resistance at 500 V dc: 2/

Initial: 100 megohms (minimum).

After life or environmental tests: 100 megohms (minimum).

Dielectric strength (sea level): 2/

	Initial	After life tests
Coil to case. 3/	1,050 V rms	1,050 V rms
All other points. 4/	1,250 V rms	1,250 V rms

Dielectric strength (altitude)
(80,000 feet): 2/ 5/

	Initial	After life tests
Coil to case. 3/	350 V rms	350 V rms
All other points. 4/	350 V rms	350 V rms

Transients (at terminals X1, X2, and C1):

Transient voltage limits (input): In accordance with MIL-STD-461 (methods CS101, CS114, RS101, and RS103) for PIN's with a suffix letter W. For PIN's with a suffix letter A, the same limits apply except that the field intensity limits for RS103 are as specified in table III. Susceptibility testing shall not cause the relay to change state nor affect the timing interval beyond allowable tolerance limits.

2/ Terminals X1, X2 and C1 are connected together during this test.
3/ Leakage current is limited to 50 microamperes.
4/ Leakage current is limited to 25 microamperes.
5/ Relay is not installed in its bracket and socket assembly (MIL-PRF-12883/51-004).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:27Z
Check the source to verify that this is the current version before use.

TABLE III. RS103 levels for suffix letter A PIN's.

Frequency	RS103 level (volt/meter)
14 kHz to 200 MHz	20
200 MHz to 450 MHz	65
450 MHz to 1 GHz	20
1GHz to 12 GHz	100

Transient voltage limits (output): In accordance with MIL-STD-461 (methods CE106 and RE103), voltage spikes generated by time delay relays shall not exceed 42 volts during the following time periods starting at the instant of opening of the relay coil circuit:

PIN's with a suffix letter W: 50 microseconds.

PIN's with a suffix letter A: 500 microseconds.

Monitoring of spike voltages shall be by a device (such as a memory type oscilloscope) that can detect, measure, display, and record 0.25 to 1000 volts over the applicable time durations specified herein. Switches used to control the time delay relays during voltage-spike measurements shall not be EMI suppressed.

Time current relay characteristics at 25°C: 6/ Relays shall sustain five applications (make and carry only) of power concurrently on adjacent poles at each of five different current levels for the time durations shown in table IV. Separate relays shall be tested at 28 V dc and 115/200 V ac, 400 Hz, 3 phase. Cooling time between successive applications shall be 30 minutes. The test shall be performed on both normally open and normally closed contacts of each relay. There shall be no failures or evidence of welding or sticking, and relays shall pass contact voltage drop at conclusion.

TABLE IV. Time-current relay characteristics at 25°C.

1	15 A	1 hour
2	59 A	5.0 seconds
3	100 A	1.2 seconds
4	250 A	0.2 second
5	350 A	0.1 second

CAUTION: Compare with time-current characteristics of associated circuit protective device.

Environmental data (relay installed in bracket and socket assembly M12883/50 and secured in mounting track M12883/49.

Temperature range (operating): -70°C to +125°C.

Maximum altitude rating: 80,000 feet.

6/ Not applicable if the MIL-PRF-83536/9, /10, /11 relay being used is qualified to the time current relay characteristics at 25°C requirements of MIL-PRF-83536.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:27Z
Check the source to verify that this is the current version before use.

Shock G level: 50 g's.

Duration: 10 milliseconds.

Maximum duration contact opening: 10 microseconds.

Maximum duration contact closing: 1 microsecond.

Vibration (sinusoidal):

G level: 30 g's.

Frequency range: 10 Hz to 3,000 Hz.

Vibration (random): Applicable in accordance with MIL-STD-202-214, test condition 1B.

Power spectral density: 0.4 g^2/Hz.

Frequency range: 50 Hz to 2,000 Hz.

Duration: 15 minutes each plane.

Acceleration: 15 g's.

Seal: Applicable to nonhermetically-sealed relays and hermetically-sealed (potted) relays.

Physical data:

Dimensions and configuration: See figure 1.

Weight: 0.34 pound (.153 kilogram) maximum.

Knob strength: The rod to knob junction shall be capable of resisting an axial pull of 35 pounds without degradation.

Marking: See MIL-PRF-83726. In addition, relays shall be marked with the ESDS identifier as specified in MIL-STD-1285.


ESDS protection program: The manufacturer shall establish and maintain an ESD control program in accordance with ANSI/ESD-S20.20 for mission critical equipment. Evidence of such compliance shall be verified by the qualifying activity of this specification as a prerequisite for qualification and continued qualification. This program shall be documented by an ESD control plan that must be under document control. As a minimum, this plan must address the identification of ESDS sub-components and preservation, packaging, and quality assurance. A model ESD control program is available from the qualifying activity and may be used as a guideline. Further guidance for ESD control is available from the EDS/ESD Association and the Electronics Industry Association (EIA). This requirement is applicable to all manufacturers who handle ESDS component parts and materials in the relay manufacturing or testing process. This requirement is not limited to manufacturers qualifying ESDS end items.

ESDS verification: As a part of qualification or qualification after redesign, ESD testing shall be done in accordance with method 3015 of MIL-STD-883 modified to test at 16,000 volts. Testing at lower voltage levels is not required. This testing shall be accomplished as part of the group III for qualification inspection and as part of the group C inspection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:27Z
Check the source to verify that this is the current version before use.

ESDS preservation and packaging: Relays shall be preserved and packaged in such a manner as to ensure that the integrity of ESD sensitive relays is not diminished. ESD sensitive relays shall be preserved and packaged in accordance with the requirements of ANSI/ESD-S20.20.

PIN: Consists of the prefix M83726/18-, a four-digit dash number (expressed in milliseconds), and a suffix letter (indicating the extent of EMI requirements) as follows:



Examples:

M83726/18-1000W-100 millisecond time delay, with less stringent EMI requirements.

M83726/18-1001A-1 second time delay, with more stringent EMI requirements.

Quality assurance provisions: Group B and group C testing are not required. The manufacturer shall notify the qualifying activity in the event of any design or construction changes, and shall impose additional testing requirements as necessary.

The Qualified Products List (QPL) associated with this inactive for new design specification will be maintained until acquisition of the product is no longer required, whereupon the specification and the QPL will be canceled.

7/ Any relays numbered prior to the date of this specification with a suffix indication shall be considered interchangeable (store and issue) with the W for relays with less stringent EMI requirements (Y,X) or A for relays with more stringent EMI requirements (B,C).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:27Z
Check the source to verify that this is the current version before use.

NOTE: As of 15 June 1999, MIL-PRF-83726 no longer specifies Quality Levels, but existing order configurations may still include them. Relays with a "W" quality level indicator at the end are interchangeable with relays without a quality level letter.

Changes from previous issue. The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the previous issue.

Referenced documents. In addition to MIL-PRF-83726, this document references the following:

SAE-AMS-STD-595	MIL-STD-202-214	MIL-STD-461	MIL-STD-883
MIL-STD-1285	MIL-PRF-12883/49	MIL-PRF-12883/51	
ANSI/ESD-S20.20	MIL-PRF-83536	MIL-PRF-83536/9	
MIL-PRF-83536/10	MIL-PRF-83536/11	ASTM B488	

Custodians:
Navy - EC
Air Force - 85
DLA - CC

Preparing activity:
DLA - CC

(Project 5945-2023-046)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:27Z
Check the source to verify that this is the current version before use.