MIL-F-51069C(EA)
27 March 1979
SUPERSEDING
MIL-F-51069B(MU)
1 September 1967

MILITARY SPECIFICATION

FILTER UNIT, GAS-PARTICULATE, FOUR MAN, 12 CFM, M8A3

This specification is approved for use by US Army Armament Research and Development Command, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers a gas-particulate filter unit.

2. APPLICABLE DOCUMENTS

2.1 Issues of documents. The following documents, of the issue in effect on date of invitation for bids, or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

QQ-S-781 - Strapping, Steel, and Seals.
PPP-B-621 - Boxes, Wood, Nailed and Lock-Corner.
PPP-B-636 - Boxes, Shipping, Fiberboard.
PPP-T-76 - Tape, Pressure-Sensitive Adhesive, Paper.

FSC 4240

: Beneficial comments (recommendations, additions, delet-ons) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Command, Attn: DRDAR-TSC-S, Aberdeen Proving Ground, MD 21010 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter,

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:49Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-P-116 - Preservation-Packaging, Methods of.
MIL-B-121 - Barrier Material, Greaseproofed, Waterproofed, Flexible.
MIL-I-51072 - Installation Kit, Gas-Particulate Filter Unit, Armored Vehicle, M20A1.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.
MIL-STD-1188 - Commercial Packaging of Supplies and Equipment.

DRAWINGS AND TECHNICAL DATA PACKAGE LIST (TDPL)

US ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND

CHEMICAL SYSTEMS LABORATORY

TDPL 5-19-1779 - Filter Unit, Gas-Particulate, Four-Man, 12 CFM, M8A3.

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Materials and components.

3.1.1 Materials. All materials cited on TDPL 5-19-1779 or on the subsidiary drawings shall conform to the specifications listed thereon, or to the specific characteristics set forth on the drawings.

3.1.2 Components. All components of the filter unit shall conform to the specifications and drawings listed on TDPL 5-19-1779 and subsidiary drawings.

3.2 Workmanship. The filter unit shall be free of damage such as bent, chipped, or burred metal parts and cracked, kinked, or torn rubber parts, and foreign matter (dirt, grease, oil, or viscous material).

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:49Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.

4.1.1 Contractor's responsibility. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specifications where such inspections are deemed necessary to assure supplies and services conform to specified requirements.

4.1.2 Objective evidence. The contractor shall provide objective evidence acceptable to the contracting officer that the requirements of 3.1 and section 5 for which specific inspection has not been provided in this specification have been satisfied.

4.2 Quality conformance inspection.

4.2.1 Lotting. A lot shall consist of the filter units produced by one manufacturer, at one plant, from the same materials, under essentially the same manufacturing conditions. However, no more than one lot of air purifiers shall be represented in any one lot of finished filter units.

4.2.2 Sampling for examination. Sampling shall be conducted in accordance with MIL-STD-105.

4.2.3 Inspection procedure.

4.2.3.1 Examination. Filter units shall be examined and tested in accordance with the classification of defects and MIL-STD-105.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:49Z
Check the source to verify that this is the current version before use.

4.2.3.2 Classification of defects.

(a) Filter unit, gas-particulate, four man, 12 cfm, M8A3 (TDPL 5-19-1779).

Categories	Defects
Critical:	None defined
Major:	AQL 1.0 percent defective
101	Component missing
102	Component incorrectly assembled
103	Workmanship (3.2)

5. PACKAGING

5.1 Preservation (level A).

5.1.1 Cleaning and drying. The components which comprise the filter unit shall be cleaned method C-1 of MIL-P-116 and dried by any of the drying methods listed therein which will not be harmful to the item.

5.1.2 Unit packing.

5.1.2.1 Hoses. All fittings on hoses shall be wrapped with MIL-B-121 greaseproof barrier material, type II, grade A, class 2, size 8 inches by 8 inches and secured with PPP-T-76 tape, size 2 inches by 6 inches. The hoses shall be coiled loosely and placed in a PPP-B-636 fiberboard box, style RSC, grade W5c, size 14-1/2 inches by 14-1/2 inches by 5-1/2 inches inside dimensions. Closure shall be in accordance with PPP-B-636, appendix.

5.1.2.2 Installation kit. The kit shall be preserved and packaged in accordance with the level A requirements of MIL-I-51072.

5.1.2.3 Air purifier. The air purifier shall be preserved and packaged in accordance with the level A requirements of its Packaging Data Sheet which is identified by its National Stock Number.

5.2 Packing (level A, B or commerical) (see 6.2).

5.2.1 Level A. The components of the kit, unit packed as specified in 5.1.2, shall be packed in a PPP-B-621 nailed wood box, style 4-1/2, class 2, grade A. Interior dimensions shall be 15 inches by 15 inches by 15-3/4 inches. Closure shall be in accordance with PPP-B-621, appendix. Strapping shall be minimum 3/8 inch galvanized, conforming to QQ-S-781.

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:49Z
Check the source to verify that this is the currenversion before use.

5.2.2 Level B. The components of the kit, unit packed as specified in 5.1.2, shall be packed in a PPP-B-636 fiberboard box, style RSC, grade V3c, size 15 inches by 15 inches by 15-3/4 inches inside dimensions. Closure shall be in accordance with PPP-B-636, appendix.

5.2.3 Commercial. Commercial packing shall be in accordance with MIL-STD-1188.

5.3 Marking (level A, B or commercial) (see 6.2).

5.3.1 Levels A and B. In addition to any special markings required by the contract or order, unit packages, intermediate packages, and shipping containers shall be marked in accordance with MIL-STD-129. A packing list shall be provided as specified in MIL-STD-129.

5.3.2 Commercial. Commercial marking shall be in accordance with MIL-STD-1188.

6. NOTES

6.1 Intended use. The filter unit covered by this specification is intended to remove toxic aerosols and gases from air supplied to crews of military vehicles (tanks, personnel carriers, etc).

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Level of packing required.
(c) Level of marking required.

6.3 Component specifications. The component specifications for the M8A3 Filter Unit are as follows:

Title	Number
Filter, Gas, 12 CFM, M12A1	MIL-F-14512
Filter, Particulate, 12 CFM, M13	MIL-F-52011
Hose: For Filter Units	MIL-H-14506
Installation Kit, Gas-Particulate Filter Unit, Armored Vehicle, M20A1	MIL-I-51072
Centrifugal Fan and Motor, Assembly, 12 CFM	MIL-C-50084
Precleaner, Air Purifier, M1A1	MIL-P-50085
Purifier, Air, M2A2	MIL-P-51070
Separator, Dust	MIL-S-50087
Coupling, Half, Quick Disconnect	MIL-C-51073

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:49Z
Check the source to verify that this is the current version before use.

Custodian:

Army - EA

Preparing activity:

Army - EA

Project No. 4240-A513

Source: https://assist.dla.mil -- Downloaded: 202640-22T20:49Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 202640-22T20:49Z
Check the source to verify that this is the current version before use.