NOTE: The document identifier and heading has been changed on this page to reflect that this is a performance specification. There are no other changes to this document. The document identifier on subsequent pages has not been changed, but will be changed the next time this document is revised.

INCH-POUND

MIL-PRF-83536/16A
13 May 1994
SUPERSEDING
MIL-R-83536/16
27 March 1992

PERFORMANCE SPECIFICATION SHEET

RELAYS, ELECTROMAGNETIC, ESTABLISHED RELIABILITY, 4PDT, LOW LEVEL TO 10 AMPERES, PERMANENT MAGNET DRIVE, HERMETICALLY SEALED, ALL WELDED, DC COILS

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation MIL-PRF-83536.





FIGURE 1. Dimensions and configurations.

DISTRIBUTION STATEMENT A. Approved for public release, distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:53Z
Check the source to verify that this is the current version before use.



RAISED VERTICAL FLANGE MOUNT (RVFM)

FIGURE 1. Dimensions and configurations - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:53Z
Check the source to verify that this is the current version before use.




FIGURE 1. Dimensions and configurations - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:53Z
Check the source to verify that this is the current version before use.






FIGURE 1. Dimensions and configurations - Continued.


Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:53Z
Check the source to verify that this is the current version before use.



TERMINAL LAYOUT



CIRCUIT DIAGRAM (NO MOUNT, RVFM, AND HFM)



CIRCUIT DIAGRAM (OPTIONAL INTERNAL DIODE CONFIGURATION)

FIGURE 1. Dimensions and configurations - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:53Z
Check the source to verify that this is the current version before use.

Inches	mm	Inches	mm	Inches	mm
.001	0.03	.172	4.37	.937	23.80
.002	0.05	.200	5.08	1.010	25.65
.005	0.13	.218	5.54	1.025	26.04
.040	1.02	.270	6.86	1.062	26.97
.050	1.27	.310	7.87	1.396	35.46
.062	1.57	.312	7.92	1.406	35.71
.150	3.81	.625	15.88	1.446	36.73
.156	3.96	.810	20.57	1.718	43.64

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Unless otherwise specified, tolerance is ±.010 (0.25 mm).
4. There shall be affixed to the relay a legible circuit diagram that identifies each terminal location specified.
5. These relays are polarized monostable.
6. This relay shall not operate or be damaged by reverse polarity.
7. Permanent magnet drive consists of a permanent magnet with its flux path switched and combined with the electro-magnet flux.
8. Applicable to horizontal flange mount only. The circuit diagram, manufacturer's PIN, and the military PIN shall be marked on the near side. The remaining portion of the nameplate data shall be marked on the far side.
9. Applicable to horizontal flange mount only. Relays shall be marked with the manufacturer's name or CAGE code and date code. Marking shall be with the bottom of the print adjacent to the near side.
10. Socket pin terminals shall be gold-plated in accordance with MIL-G-45204, type II, class I. The nickel underplating shall be 50 to 150 microinches thick minimum.
11. Silicone rubber gasket, AMS 3332, shore hardness 15 to 35, thickness .050 ±.005 (1.27 ±0.13 mm).
12. Back EMF (transient voltage): 42 V dc maximum.
13. JANTX or equivalent screened semiconductors or hybrid devices shall be used for internal coil suppression. Relays using suppression devices shall continue to operate should the suppression circuit be in a failure mode. Diodes shall have a peak inverse voltage of 600 V dc minimum.
14. Indicated terminals shall be identified by contrasting beads.
15. Plane of critical motion for vibration and shock is Y-axis.

FIGURE 1. Dimensions and configurations - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:53Z
Check the source to verify that this is the current version before use.





FIGURE 2. Outline dimensions and configuration, track mount (see notes 9 and 10).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:53Z
Check the source to verify that this is the current version before use.



CIRCUIT DIAGRAM (TRACK MOUNT)

Inches	mm	Inches	mm
.001	0.03	.094	2.39
.005	0.13	.140	3.56
.010	0.25	.200	5.08
.015	0.38	.270	6.86
.020	0.51	.313	7.95
.040	1.02	.500	12.70
.046	1.17	1.025	26.04
.062	1.57	1.250	31.75
.078	1.98	1.310	33.27
.079	2.01	1.910	48.51

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Unless otherwise specified, tolerance is ±.010 (0.25 mm).
4. This relay shall not operate or be damaged by reverse polarity. Semiconductors shall not be used for this purpose.
5. Permanent magnet drive consists of a permanent magnet with its flux path switched and combined with the electromagnetic flux.
6. Terminal numbers shall not appear on the header. There shall be affixed to the relay a legible circuit diagram that identifies each terminal location specified.
7. Back EMF suppression circuit: JANTX or equivalent screened semiconductors shall be used. Back EMF shall be 42 V dc maximum. Relays using suppression devices shall continue to operate should the suppression circuit be in a failure mode.
8. All terminals shall be gold plated in accordance with MIL-G-45204, type II, class I; underplating shall be nickel, 50 to 150 microinches thick.
9. Track mount knob, post, and base shall be 303 Cres nickel plated in accordance with McAir P.S. 13112 or equivalent, 100 microinches thick minimum. The latching pin shall be 303 Cres passivated or nickel plated in accordance with McAir P.S. 13112 or equivalent, 100 microinches thick minimum.
10. Track mount relay shall be capable of mating with M6106/5 "Bracket and Socket Assembly", configuration I. The latching pin shall be capable of withstanding an axial pull of 35 pounds, in a direction away from the knob, without any degradation. The rotation of the knob mechanism shall be restricted such that the latching pins cannot be placed on the side opposite the M6106/4 bracket cutouts.
11. Indicated terminals shall be identified by contrasting beads.

FIGURE 2. Outline dimensions and configuration, track mount (see notes 9 and 10) - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:53Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Contact data:

Load ratings: See table I.

Low level: 10 to 50 μA at 10 to 50 mV dc or peak ac.

Intermediate current: Applicable.

Mixed loads: Applicable.

TABLE I. Rated contact load and cycles (amperes per pole).

Type of load (high level)	Cycles x 10^3	28 V dc	2/ 115 V ac 1 phase 400 Hz	2/ 115 V ac 1 phase 50/60 Hz 1/	2/ 115/200 V ac 3 phase 400 Hz	2/ 115/200 V ac 3 phase 50/60 Hz 1/
Resistive	100	10	10	2.5	10	2.5
Inductive	20	8	8	N/A	8	N/A
Inductive	10	N/A	N/A	2.5	N/A	2.5
Motor	100	4	4	2	4	2
Lamp	100	2	2	1	N/A	N/A

1/ For 50/60 Hz rating, rupture and overload are not applicable and life for each load shall be 10,000 cycles.
2/ AC load ratings are not applicable to -034.

Life: 100,000 cycles, unless otherwise specified (see table I).

Contact voltage drop or resistance:

Initial contact voltage drop: 0.100 volt maximum. Rated resistive current at 6 V dc or peak ac. Relays shall not make or break this load.

Initial contact resistance: 0.010 ohm maximum. 50 mA maximum at 6 V dc or peak ac.

High level life (contact voltage drop):

During life: 10 percent open circuit voltage maximum.

After life: 0.125 volt maximum.

Intermediate current (contact resistance):

During intermediate current: 3 ohms maximum.

After intermediate current: 0.150 ohm maximum.

Low level (contact resistance):

During low level: 100 ohms maximum.

After low level: 0.150 ohm maximum at 100 mA and 28 V dc.

Contact bounce: 1.0 millisecond maximum.

Contact stabilization time: 2.5 milliseconds maximum.

Break bounce (normally open contacts): 0.1 millisecond maximum.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:53Z
Check the source to verify that this is the current version before use.

Overload current: 40 amperes dc, 60 amperes ac.

Rupture current: 50 amperes dc, 80 amperes ac.

Time current relay characteristics: See table II.

TABLE II. Time current relay characteristics. 1/

Successive application	Amperes	Time
1	15	1 hour
2	50	5.0 seconds
3	100	1.2 seconds
4	250	0.2 second
5	350	0.1 second

1/ All relays shall withstand overload and fault currents. Relays must be able to sustain five applications (make and carry only) of power concurrently on adjacent poles at each of five different current levels in the sequence listed in table II. Separate relays shall be tested at 28 V dc and 115/200 V ac, 400 Hz 3-phase. Cooling time between successive applications shall be 30 minutes. Tests shall be performed on both normally open and normally closed contacts. There shall be no failures or evidence of welding or sticking and relays shall pass contact voltage drop at the conclusion.

Coil data: See table III. 1/ 2/

Operate time: 15 milliseconds maximum with rated coil voltage over the temperature range.

Release time: 15 milliseconds maximum, 20 milliseconds maximum (track mount) from rated coil voltage over the temperature range.

Duty rating: Continuous.

Coil transient suppression: Applicable; 42 vdc maximum.

Neutral screen: Not applicable.

Electrical data:

Insulation resistance:

Initial: 100 megohms minimum at 500 V dc.

After life or environmental tests: 100 megohms minimum at 500 V dc (track mount), 50 megohms minimum at 500 V dc (all others).

1/ CAUTION: Due to possible interaction of relay magnetic fields, the following spacing requirements, as a minimum, shall be considered in dense packaging situations:

a. Row to row assisting fields: .125 (3.18 mm).

b. Row to row opposing fields: .1875 (4.763 mm).

c. Side to side alternating fields: .0625 (1.588 mm).

d. Side to side like fields: .125 (3.18 mm).

2/ Track mount relays shall have the pickup, hold, and dropout voltage, and timing tests, performed with an M6106/5 bracket placed around the relay housing.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:53Z
Check the source to verify that this is the current version before use.

TABLE III. Dash numbers and characteristics. 1/

Dash number 2/			Mount	Coil data										
				At 25°C						Over temperature range			Maximum pickup voltage	
Solder pin	Solder hook	Socket pin		Coil voltage (V dc) 3/		Coil resistance (ohms) minimum	Specified pickup voltage (V dc) 4/	Specified hold voltage (V dc) 4/	Specified dropout voltage (V dc) 4/	Specified pickup voltage (V dc) 4/	Specified hold voltage (V dc) 4/	Specified dropout voltage (V dc) 4/	High temperature test	Continuous current test
				Rated	Max									
001	002	003	No mount	6	7.3	16	3.2	1.6	0.4	4.5	2.3	0.25	5.0	5.7
004	005	006	RVFM	6	7.3	16	3.2	1.6	0.4	4.5	2.3	0.25	5.0	5.7
007	008	---	HFM	6	7.3	16	3.2	1.6	0.4	4.5	2.3	0.25	5.0	5.7
009	010	011	No mount	12	14.5	63	6.5	3.3	0.75	9.0	4.5	0.5	9.9	11.25
012	013	014	RVFM	12	14.5	63	6.5	3.3	0.75	9.0	4.5	0.5	9.9	11.25
015	016	---	HFM	12	14.5	63	6.5	3.3	0.75	9.0	4.5	0.5	9.9	11.25
017	018	019	No mount	28	5/ 29	260	13.5	5.5	2.3	18.0	7.0	1.5	19.8	22.5
020	021	022	RVFM	28	5/ 29	260	13.5	5.5	2.3	18.0	7.0	1.5	19.8	22.5
---	---	6/ 034												
023	024	---	HFM	28	5/ 29	260	13.5	5.5	2.3	18.0	7.0	1.5	19.8	22.5
---	---	025	Track	28	5/ 29	260	13.5	5.5	2.3	18.0	7.0	1.5	19.8	22.5
026	027	028	No mount	48	50	800	24.0	12.0	3.0	36.0	14.0	2.0	38.0	42.0
029	030	031	RVFM	48	50	800	24.0	12.0	3.0	36.0	14.0	2.0	38.0	42.0
032	033	---	HFM	48	50	800	24.0	12.0	3.0	36.0	14.0	2.0	38.0	42.0

1/ Each relay possesses high level and low level capabilities. However, relays previously tested or used above 10 mA resistive at 6 V dc maximum or peak ac open circuits are not recommended for subsequent use in low level applications.
2/ The suffix letter L, M, P, or R to designate the applicable failure rate level shall be added to the applicable listed dash number. Failure rate level (percent per 10,000 cycles): L, 3.0; M, 1.0; P, 0.1; R, 0.01. Example: 001L, 002R.
3/ CAUTION: The use of any coil voltages less than the rated coil voltage will compromise the operation of the relay.
4/ Pickup, hold, and dropout voltages are for test purposes only and are not to be used for design criteria.
5/ When maximum ambient temperature does not exceed +85°C, the maximum coil voltage shall be 32 V dc.
6/ Dash number -034 is supplied without internal arc barriers. This relay is not rated for ac loads.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:53Z
Check the source to verify that this is the current version before use.

Dielectric withstanding voltage: 3/

	Track mount		All others	
	Coil to case	All other points	Coil to case	All other points
Sea level:				
Initial:	1050	1500	1000	1250
After life:	1050	1250	1000	1000
Altitude:				
At 80,000 feet:	350	350	350	350
At 300,000 feet:	---	---	500	500

Maximum leakage current: 100 microamperes rms in accordance with MIL-R-83536.

Environmental characteristics:

Temperature range: -70°C to +125°C.

Maximum altitude rating: 300,000 feet, 80,000 feet for track mount.

Shock (specified pulse): Applicable, MIL-STD-202, method 213, test condition C, 200 grams for 6 ±1 ms, except horizontal flange mount peak g value shall be 100 grams for 6 ±1 ms. Contact chatter shall not exceed 10 microseconds maximum for closed contacts and 1 microsecond maximum closure for open contacts.

Vibration (sinusoidal): Applicable, MIL-STD-202, method 204, 30 grams except frequency range shall be 10 to 3,000 Hz. Horizontal flange mount shall be 20 grams, 57 to 3,000 Hz. Contact chatter shall not exceed 10 microseconds maximum for closed contacts and 1 microsecond maximum closure for open contacts.

Vibration (random): Applicable to qualification and group C inspection. Test in accordance with MIL-STD-202, method 214, test condition IG (0.4 g^2/Hz, 50 to 2000 Hz), 15 minutes each plane; for horizontal flange mount test condition IE (0.2 g^2/Hz). Contact chatter shall not exceed 10 microseconds maximum for closed contacts and 1 microsecond maximum closure for open contacts.

Vibration (random): Applicable to track mount only. Applicable to qualification only. Test in accordance with MIL-STD-202, method 214, test condition IJ, 1.5 hours per axis. Contact chatter shall not exceed 10 microseconds maximum for closed contacts and 1 microsecond maximum closure for open contacts.

Acceleration: Applicable, except 15 grams.

Physical data:

Dimensions and configurations: See figure 1.

Weight: 0.17 pound (77 grams), 0.2 pound (90.6 grams) for track mount.

Terminal strength:

Solder hook terminals:

Pull force: 10 pounds ±1.0 pound.

3/ Dielectric may be improved by suitable insulation of terminals and wiring after installation.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:53Z
Check the source to verify that this is the current version before use.

Bend: Not applicable to leads .047 (1.19 mm) and larger.

Twist: Not applicable.

Solder pin terminals:

Pull force: For .062 diameter terminals: 10 pounds ±1.0 pound.

Bend: Not applicable to leads .047 (1.19 mm) and larger.

Twist: Not applicable.

Socket pin terminals:

Pull force: For .062 diameter terminals: 10 pounds ±1.0 pound.

Bend: Not applicable to leads .047 (1.19 mm) and larger.

Twist: Not applicable.

Terminal solderability: Applicable to solder pin and solder hook terminals only.

Seal: Hermetic.

Marking: Applicable.

Part or Identifying Number (PIN): M83536/16 (dash number from table III and suffix letter designating failure rate level). PIN is a new term encompassing previous terms used in specifications such as part number, type designator, and identification number.

Qualification inspection:

Qualification inspection and sample size: See table IV.

TABLE IV. Qualification inspection and sample size. 1/

Single submission	Group submission	
18 units plus 1 open unit for level L at C = 0 2/	M83536/16-022	18 units plus 1 open unit for level L at C = 0 2/
33 units plus 1 open unit for level M at C = 0 2/	"	33 units plus 1 open unit for level M at C = 0 2/
Qualification inspection as applicable	"	Qualification inspection as applicable
	M83536/16-018 M83536/16-023 M83536/16-025 M83536/16-028 M83536/16-034	2 units, qualification inspection table, group II, shock, vibration, acceleration, terminal strength, and seal
	M83536/16-002 M83536/16-014 M83536/16-032	2 units, qualification inspection table, group II

1/ For retention of qualification or extension of qualification to lower failure rate levels, all life test data accumulated on MIL-R-83536/15 may be used in addition to MIL-R-83536/16 data. Prior to performance of retention of qualification testing, the relay manufacturer shall preselect the sampling plan.

2/ The number of units required for qualification testing shall be increased as required in group V, table II of MIL-R-83536, if the contractor elects to test the number of units permitting one or more failures. Prior to performance of qualification testing, the relay manufacturer shall preselect the sampling plan.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:53Z
Check the source to verify that this is the current version before use.

Supersession data: See table V.

TABLE V. Supersession data.

Superseded PIN	Replacement PIN M83536/16-
MS27400- 17	022
18	031
23	021
24	024
29	021
30	024
31	022
37	020
38	020
42	018
43	017
46	018
47	017
M6106/2- 001	025
003	025

Revision letters are not used to denote changes due to the extensiveness of the changes.

CONCLUDING MATERIAL

Custodians:
Army - ER
Navy - EC
Air Force - 85

Review activities:
Air Force - 99
DLA - ES

Preparing activity:
Air Force - 85

Agent:
DLA - ES

(Project 5945-0944-01)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:53Z
Check the source to verify that this is the current version before use.