MILITARY SPECIFICATION

TRANSPARENCY, ANIMATED, 106-MM RECOILLESS RIFLE BREECH MECHANISM

This specification has been approved by the Naval Training Device Center, Department of the Navy. The technical requirements for procuring the animated transparency described herein shall consist of this document and the issue in effect of Specification MIL-T-82391.

1. SCOPE

1.1 This specification covers the requirements for an animated transparency depicting the breech mechanism of the 106-MM recoilless rifle.

1.1.1 This item has been designated by the Naval Training Device Center as Device 3E33 for Navy procurement.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on the date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

Federal

QQ-C-320	Chromium Plating (Electrodeposited)

Military

MIL-A-8625	Anodic Coatings, for Aluminum and Aluminum Alloys
MIL-T-82391	Transparencies, Animated: Design and Development of, General Specification for

PUBLICATIONS

Department of the Army

Technical Manual No. TM9-1000-205-12	Operation and Organizational Maintenance, Cal. .50 Spotting Rifle M8C on Mount M79 or M92 with Tripod M27; and 106-MM Recoilless Rifle M40A1C used on Multiple 106-MM FT SP Rifle M50.

FSC 6910

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:04Z
Check the source to verify that this is the current version before use.

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the Contracting Officer.)

3. REQUIREMENTS

3.1 Material.- Except as specified in 3.1.1, materials used shall be in accordance with the material requirements of MIL-T-82391.

3.1.1 Metals.- All metal parts and fastenings, excluding springs, shall be of corrosion resistant steel, class 2 chromium plated metal in accordance with QQ-C-320 or Type II anodized aluminum in accordance with MIL-A-8625.

3.2 Design.- The animated transparency shall be designed to simulate, in detail, the operation of the breech mechanism of the 106-MM recoilless rifle. The design shall be in accordance with the design requirements of MIL-T-82391 and as specified in paragraph 3.2.1 of this specification.

3.2.1 Design details.- The animated transparency shall be designed for use in demonstrating the operation of the breech mechanism of the 106-MM recoilless rifle in performing the functions of unlocking, cocking, extracting, positioning of the extractor, locking and positioning of the firing mechanism as described in the Government-furnished Technical Manual (TM9-1000-205-12).

3.2.1.1 The following major projectable components shall be depicted:

(a) Operating lever assembly

(b) Breechblock operating lever cam and dog

(c) Cocking cam plate

(d) Breechblock hinge block

(e) Coupling ring bearing rollers

(f) Breechblock

(g) Vent bushing

(h) Firing pin and firing pin housing assembly

(i) Sear

(j) Extractor assembly

(k) Cartridge case detent assembly

(l) Cartridge (partial).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:04Z
Check the source to verify that this is the current version before use.

3.2.1.2 All operative and stationary parts of all components necessary to demonstrate the operation of the unlocking, cocking, extracting, positioning of the extractor, locking and positioning of the firing mechanism functions of the 106-MM recoilless rifle shall be depicted.

3.2.1.3 Means shall be provided for depicting a rear view of the rifle which shall show the rotation of the breechblock within the vent bushing by the operating lever assembly in both the locking and unlocking sequences. The rear view shall be provided with an opaque flap for use when a top view of the rifle is being demonstrated.

3.2.1.4 Means shall be provided for depicting the closed breech in the safe position by the counterclockwise movement of the operating lever.

3.2.1.5 Means shall be provided for indicating the delayed opening of the breechblock due to the elongated recesses of the coupling ring bearing rollers.

3.2.1.6 Means shall be provided for indicating the cartridge being extracted by the actions of the cocking cam plate, extractor assembly and the cartridge case detent assembly as the breechblock and hinge group swings to the rear.

3.2.1.7 The top view and the flap-covered rear view shall be depicted in the same scale and shall be in the same vertical alinement.

3.3 Reliability.- The animated transparency shall meet the reliability requirements of MIL-T-82391.

3.4 Details of components.- Except as specified in 3.4.1 and 3.4.2, the details of components of the animated transparency shall be in accordance with the details of components requirements of MIL-T-82391.

3.4.1 Baseplate.- The baseplate shall have no flaps, levers, slides or other controls that extend beyond the limits of the top and right sides.

3.4.1.1 Baseplate markings.- Information for orientation of the animated transparency, identification of controls or for warning notes shall be engraved with .250 inch high letters and filled with a color (black or white) contrasting with the background, by application of dry transfer lettering, by silk screening or by fluid lettering devices. Markings not engraved shall be protected by transparent sheet plastic.

3.4.2 Static transparency.- An 8 inch x 10 inch static transparency shall be provided depicting the entire recoilless rifle. The transparency shall be mounted within cardboard mounts and shall have the following projectable title:

"106-MM RECOILLESS RIFLE"

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:04Z
Check the source to verify that this is the current version before use.

3.4.2.1 The pictorial view of the recoilless rifle, depicted in the static transparency, shall be rendered in shades of gray and shall have the following areas and components accented with the following colors and be labeled:

(a) Breech mechanism - Amber

(b) Firing system (including the lanyard rod) - Red

(c) Area containing the Planetary Gear System(s) - Yellow

(d) Spotting rifle adjustment cams - Medium Green.

3.4.3 Storage/carrying case.- The storage/carrying case for the animated transparency shall be in accordance with the storage/carrying case requirements of MIL-T-82391 except that the material for the top and bottom of the case shall be 1/4 inch exterior grade plywood and provision shall be made for storage of the static transparency of 3.4.2.

3.5 Construction.- Construction shall be in accordance with the construction requirements of MIL-T-82391.

3.6 Performance.- Performance shall be in accordance with the performance requirements of MIL-T-82391.

3.7 Finish and color.- Finish and color shall be in accordance with the finish and color requirements of MIL-T-82391.

3.8 Nameplates or product markings.- Nameplates or product markings shall be in accordance with the nameplates or product markings of MIL-T-82391.

3.9 Workmanship.- Workmanship shall be in accordance with the workmanship requirements of MIL-T-82391.

4. QUALITY ASSURANCE PROVISIONS

4.1 Inspections, examinations and tests.- Inspections, examinations and tests shall be in accordance with the quality assurance provisions of MIL-T-82391.

5. PREPARATION FOR DELIVERY

5.1 Preservation, packaging, packing and marking.- Preservation, packaging, packing and marking shall be in accordance with the preparation for delivery requirements of MIL-T-82391.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:04Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 The notes of MIL-T-82391 are applicable.

CUSTODIAN:
Navy-TD

PROCURING ACTIVITY:
Navy-TD
Project No. 6910-N301

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:04Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:04Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity *(as indicated on reverse hereof)*.

SPECIFICATION

ORGANIZATION *(Of submitter)* | CITY AND STATE

CONTRACT NO. | QUANTITY OF ITEMS PROCURED | DOLLAR AMOUNT $

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES.

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)* | DATE

DD FORM 1 APR 63 1426 REPLACES NAVSHIPS FORM 4863, WHICH IS OBSOLETE

Source: https://assist.dla.mil -- Downloaded: 202610-23T07:04Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE NAVY

POSTAGE AND FEES PAID
NAVY DEPARTMENT

OFFICIAL BUSINESS

Commanding Officer
Naval Training Device Center
Specifications Control OFFICE. CODE 301
Orlando, Florida 32813

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:04Z
Check the source to verify that this is the current version before use.