INCH-POUND

A-A-58015
27 May 93

COMMERCIAL ITEM DESCRIPTION

TRAILER, FIRE FIGHTING
(FOAM, 1,000 GALLON CAPACITY)

General Services Administration has authorized
the use of this commercial item description (CID).

1. Abstract:

1.1 This Commercial Item Description (CID) describes a commercial 1,000 gallon foam trailer with a 100 gpm transfer pump. The quantities and types shall be specified by the purchaser. The trailer shall be certified legal for over the public road use.

2. Salient Characteristics:

2.1 Failure of the trailer to meet the following salient characteristics will require rejection of the offer. The trailer shall be an assembly of new materials (used or rebuilt products shall not be used) and shall be free from faulty construction or any defect which affects appearance, serviceability or durability. All components and accessories shall be represented in the manufacturer's sales data as standard or optional. The trailer shall be representative of the quality and workmanship found in foam trailers offered for new commercial sale.

2.2 The trailer shall be capable of being pulled on paved or graded gravel roads and cross country terrain. The trailer shall consist of a trailer unit, a pump unit and a tank.

2.3 Trailer Unit

2.3.1 The trailer unit shall have tandem 8000 lb rated axles.

2.3.2 The trailer shall have a steel frame.

2.3.3 The trailer shall have standard ICC brake lights and directional signals.

Beneficial comments, recommendations, additions, deletions, clarifications, etc., and any data which may improve this document should be sent to: WR-ALC/LZMD, Robins AFB GA. 31098-5609

AMSC N/A FSC 4210

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:58Z
Check the source to verify that this is the current version before use.

2.3.4 A three position adjustable pintle hook hitch shall be provided.

2.3.5 The trailer unit shall have a surge brake system. When specified, each wheel shall be provided with an electric brake in lieu of the surge brake system. When an electric brake system is specified, a manual controller kit for mounting on the dash of the towing vehicle and a controller kit for synchronizing the trailer electric brakes with the brakes of the towing vehicle shall be provided.

2.3.6 The trailer unit shall have a crankdown stand located to the rear of the pintle hook.

2.4 Pump Unit

2.4.1 The pump shall be a diesel powered electric starting centrifugal pump capable of transferring 100 gpm through 100 feet of 1/2-inch hose. When specified, a 250 gpm pump shall be provided.

2.4.2 Suction piping shall be constructed to allow the pump to draft from the tank or a separate external source (5 gallon cans or 55 gallon drums).

2.4.3 Piping shall be valved to allow for tank fill or transfer line discharge.

2.5 Tank

2.5.1 A 1,000 gallon polypropylene foam tank shall be provided and meet all the minimum standards and testing of NFPA 1901 for a tank.

2.5.2 The tank shall be baffled to meet the standards of NFPA 1901.

2.5.3 One fill tower shall be provided with two 5 gallon cans capacity. The tower shall have a removable polypropylene screen and a hinged cover.

2.5.4 A pressure vacuum vent shall be provided.

2.6 Two hose beds shall be provided to hold at least 100 feet of preconnected 1 3/4-inch hose each.

2.7 All materials and components of the foam trailer that come in contact with the foam shall be compatible and non-corrossive with the types of foams defined in NFPA 412.

2.8 The exterior surfaces of the trailer shall be primed and top-coated with a commercial polyurethane Lime Yellow (high gloss) or Olive Drab (semi-gloss) paint as specified at time of purchase. The Lime Yellow trailer shall be provided with a 4-inch red reflective stripe. The Olive Drab trailer shall be provided with a 4-inch black reflective stripe. All standard chrome or polished metal parts, hinges, and tread plates shall be painted Olive Drab.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:58Z
Check the source to verify that this is the current version before use.

3. Regulatory Requirements:

3.1 The offerer/contractor is encouraged to use recovered materials in accordance with Public Law 94-580 to the maximum extent possible.

3.1 For the purpose of this requirement, recovered materials are those materials which have been collected from solid waste and reprocessed to become a source of raw materials as distinguished from virgin raw materials. The components, pieces and parts incorporated in the trailer may be newly fabricated from recovered materials to the maximum extent practicable, provided the trailer(s) produced meets all other requirements of this CID. Used, rebuilt or remanufactured components, pieces and parts shall not be incorporated.

4. Contractor Certification:

The contractor shall certify and maintain substantiating evidence that the product offered meets the salient characteristics of this commercial item description, and that the product conforms to the producer's own drawings, specifications, standards, and quality assurance practices. The government reserves the right to require proof of such conformance prior to the delivery and thereafter as may be otherwise provided for under the provisions of the contract.

5. Packaging, Packing and Marking:

Unless otherwise provided in the contract, the trailer shall be prepared for delivery by common carrier and shall provide for protection against loss or damage while in transit. An identification plate permanently marked, shall be securely mounted on the trailer. The identification plate shall contain the following information:

NOMENCLATURE
MANUFACTURER'S MODEL NUMBER
MANUFACTURER'S SERIAL NUMBER
MANUFACTURER'S NAME
MANUFACTURER'S ADDRESS
MANUFACTURER'S SERVICE PHONE NUMBER
DATE OF MANUFACTURE
CONTRACT NUMBER
NATIONAL STOCK NUMBER
REGISTRATION NUMBER

6. NOTES. The purchaser shall specify the following at time of purchase:

a. If a 250 gpm pumping system is required..

b. If electric brakes are required.

c. Color of the trailer.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:58Z
Check the source to verify that this is the current version before use.

7. Market Acceptability:

7.1 Commercial. The trailer furnished must be the latest model as of the date of award (with minor modifications, as that term is defined in DoD FAR Supplement 252.211-7012, Paragraph K-85 of the solicitation) of an established product previously produced and sold in substantial commercial quantities (exceeding the criteria at FAR 15.804-3 (f) (2) (ii) (A)) for at least 2 years immediately preceding the issuance date of the solicitation. The trailer furnished, or earlier models of it, absent minor modifications, shall have routinely been supported with spares/repair parts which were produced or sold in the normal course of business. At the time delivery, the contractor shall furnish the Administrative Contracting Officer with verification of compliance with these requirements. Offerors shall provide, as part of their proposals, the following information on the trailer (or its earlier models) being offered as a commercial item:

(1) Total sales to the U.S. Government or to contractors for U.S. Government use during the 2 years immediately preceding the issuance date of the solicitation.

(2) Total sale of the item to the general public during the 2 years immediately preceding the issuance date of the solicitation.

(3) Length of time the item has been sold in the commercial market place.

(4) Points of contact and phone numbers of customers to which the item has been sold in the commercial market place.

(5) Other pertinent information necessary to determine that the item is an established commercial item.

CUSTODIAN:
AIR FORCE - 99

PREPARING ACTIVITY
AIR FORCE - 84

Project Number: 4210-0478

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:58Z
Check the source to verify that this is the current version before use.