METRIC

A-A-59003/6
31 May 1995
SUPERSEDING
MIL-A-21577/6
28 September 1962

COMMERCIAL ITEM DESCRIPTION

AMPLIFIER ASSEMBLY AM-2316/SIA

The General Services Administration has authorized the use of this commercial item description as a replacement for MIL-A-21577/6A which is canceled.

1. **Scope**. This specification covers the detailed requirements for an audio amplifier control assembly AM-2316/SIA.

2. **Salient characteristics**.

2.1 **General**. Amplifier assembly AM-2316/SIA shall be in accordance with applicable paragraphs of A-A-59003 and as specified herein. Whenever a requirement of A-A-59003 conflicts with a requirement of this specification, the requirement of this specification shall govern.

2.2 **Equipment**. Equipment complement shall consist of two power amplifiers in a common deck mounted enclosure. Maximum dimensions shall not exceed the following: height 1524 mm; width 813 mm; and depth 508 mm.

2.3 **Forced air cooling**. In addition to the requirements of A-A-59003, facilities for forced air cooling will be required for power amplifiers. Blower motors shall be individually fused. Temperature requirements of the amplifier assembly shall be met with blowers in nonoperating condition.

2.4 **Test facilities**. A test meter and switching facilities shall be included in each power amplifier, and shall provide a ready means for indicating the operating conditions of each electronic stage, and the output signal level. The meter calibration and circuit component values shall be such that the operating condition of the amplifiers can be determined directly from the meter without reference to tables or charts.

2.5 **Output power**. The rated output power for each of the two power amplifier assemblies shall be 500 watts, minimum rating.

2.6 **Interstage input facilities**. Interstage input circuit, input impedance, and input level will not be required.

2.7 **Oscillator and preamplifier**. Oscillator assemblies and preamplifier assemblies are not required.

2.8 **Input facilities**. Amplifier assembly AM-2316/SIA shall have the following input facilities.

AMSC N/A

FSC 6320

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:01Z
Check the source to verify that this is the current version before use.

2.8.1 **Preamplifier terminals**. Terminals shall be provided for input from preamplifier assembly to each power amplifier.

2.8.2 **Amplifier terminals**. Terminals shall be provided for input controls from Amplifier-control assembly AN/SIA-114, AN/SIA-117, or AN/SIA-118.

2.9 **Input impedance**. The input impedance of the power amplifier assembly shall be 8000 ohms (bridging).

2.10 **Output facilities**. Amplifier assembly AM-2316/SIA shall have the following output facilities.

2.10.1 **Output voltage**. Each amplifier assembly shall have facilities which will provide either 70 ± 4 volts root mean square (rms) at rated output power, or 95 ± 5 volts rms at rated output power.

2.10.2 **Terminals**. Terminals shall be provided for 70-volt, 95-volt, and low output from each power amplifier.

3. **Quality assurance**. Sampling, examination, and tests shall be in accordance with A-A-59003.

4. **Packaging**. Packaging shall be in accordance with A-A-59003.

5. **Notes**.

5.1 **Intended use**. Amplifier assembly AM-2316/SIA is intended for use in general purpose shipboard announcing systems.

5.2 **Notes**. The notes specified in A-A-59003 are applicable to this specification.

Preparing activity:
Navy - SH
(Project 6320-N052)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:01Z
Check the source to verify that this is the current version before use.