LLL-A-00650C(GSA-FSS)
August 29, 1969
INTERIM REVISION OF
Fed. Spec. LLL-A-650b
May 20, 1959

INTERIM FEDERAL SPECIFICATION

ARCH AND CLIP BOARD FILES, COMPOSITION

HARDBOARD BACK

This Interim Federal Specification was developed by the Standardization Division, Federal Supply Service, General Services Administration, Washington, D.C. 20406, based upon currently available technical information. It is recommended that Federal agencies use it in procurement and forward recommendations for changes to the preparing activity at the address shown above.

The General Services Administration has authorized the use of this Interim Federal Specification as a valid exception to Federal Specification LLL-A-650b, dated May 20, 1959.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers arch and clip board files for holding papers.

1.2 Classification.

1.2.1 Types. The arch and clip board files covered by this specification shall be of the following types and sizes, as specified in the invitation for bid (see 6.2).

Type I. Arch board file with or without paper perforator, or indexes and cover, as specified in the invitation for bid (see 3.3 and 6.2).

Type II. Clip board (see 3.3 and 6.2).

1.2.2 Sizes. The arch and clip board files shall be of the sizes as specified in 3.3.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of the specification to the extent specified herein.

Federal Specifications:

UU-P-121 - Paper, Bond and Writing, White and Colored.
UU-P-701 - Pressboard; Colored.
LLL-B-810 - Building Board (Hardboard) Hard Pressed, Vegetable Fiber.
PPP-B-585 - Boxes, Wood, Wirebound.
PPP-B-591 - Boxes, Fiberboard, Wood-Cleated.
PPP-B-601 - Boxes, Wood, Cleated-Plywood.
PPP-B-621 - Boxes, Wood, Nailed and Lock-Corner.
PPP-B-636 - Box, Fiberboard.

Federal Standard:

Fed. Std. No. 123 - Marking for Domestics Shipment (Civilian Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20402.

(Single copies of this specification and other product specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Service Centers at the General Services Administration Regional Offices in Boston, New York, Washington, D.C., Atlanta, Chicago, Kansas City, Mo., Fort Worth, Denver, San Francisco, Los Angeles, and Seattle Washington.

FSC 7520

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:47Z
Check the source to verify that this is the current version before use.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Specifications:

MIL-B-10377 - Box, Wood, Cleated, Veneer, Paper Overlaid.
MIL-L-10547 - Liners, Case, Waterproof.

Military Standards:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

(Copies of Military Specifications and Standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Material. The material shall be as specified. Where material is not definitely defined, it shall be of the quality and composition best suited for the intended purpose. When the dimension(s) of the material is not specified, it shall be at the discretion of the manufacturer.

3.1.1 Composition Hardboard. Composition hardboard used in the manufacture of arch and clip board files shall conform to LLL-B-810: Type I, or II - Standard or tempered; Surface 2 - Smooth both sides; Finish A - Surface unfinished; Design a - Board plain.

3.1.2 Sheet Steel. The sheet steel shall be plain carbon steel, hot or cold rolled at the manufacturer's option. The sheet steel shall be finished as specified in 3.4.

3.1.3 Steel wire. The steel wire shall be plain carbon steel, and shall be finished as specified in 3.4.

3.2 Design and construction.

3.2.1 Board. The board for the arch and clip board files shall be made of composition hardboard (see 3.1.1). The board shall be not less than 0.115 inch, and not more than 0.155 inch thick. The board shall be smooth on both sides (see 3.1.1), and all corners and edges shall be rounded and smooth.

3.2.2 Type I, arch board file. The boards for the arch board files shall conform to the requirements stated in 3.1.1 and 3.2.1. An arch paper holder shall be securely fastened and centered to the upper part of the board (see 3.2.2.1). When specified, a paper perforator shall be firmly attached to the lower part of the board (see 3.2.2.2 and 6.2). An alphabetical index with a cover and metal compressor shall be furnished, when specified (see 3.2.2.3 and 6.2).

3.2.2.1 Arch paper holder. The arch paper holder shall have a base with two metal arches. Each arch shall have a fixed and movable portion spaced on 2-3/4 inch centers. The fixed portion of the arch shall have a useable filing height of 2-1/2 inches, plus or minus 1/4 inch.

The base of the arch paper holder shall be made of 22 gage, minimum (.0299 inch) sheet steel, as specified in 3.1.2. A concealed spring locking device within the base, or a single-action lever type locking device, shall firmly hold the movable portion of each arch when in either an open or closed position. The bottom of the base shall have, as an integral part, an extension with a 3/8 ± 1/8 inch diameter eye or cutout, extending sufficiently beyond the upper edge of the board to permit the board to be suspended from a flat vertical surface.

The movable portion of each arch shall be J-shaped and shall be made of 9 gage, minimum (.1495 inch) steel wire, as specified in 3.1.3. The fixed portion of each arch shall be made of steel, and shall be either solid or hollow construction. The fixed portion of the arch shall be so designed to provide a suitable stop for the movable J-shaped wire arch when in closed position. When tested as specified in 4.4.2.1, the arches shall open and close easily and be in alignment when closed.

3.2.2.2 Perforator. When specified (see 3.2.2 and 6.2) the arch board file shall be equipped with a metal perforator having an overall height not greater than 1-1/4 inch above the face of the board. The perforator mechanism shall punch two 1/4 inch holes, 2-3/4 inches center-to-center. The punches shall not stick to the dies and perforations shall be free from torn or ragged edges and entirely punched out. A tolerance of plus 1/32 inch will be permitted in size of hole after punching. The perforator shall perform satisfactorily when tested in accordance with 4.4.2.2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:47Z
Check the source to verify that this is the current version before use.

3.2.2.3 Index cards and cover. When specified (see 3.2.2 and 6.2), index cards and cover shall be furnished with the arch board file.

The index cards shall consist of at least 20 manila cards of graduated length, lettered, and arranged to form an alphabetical index along the right-hand margin of the file. The index cards shall be perforated so as to pass readily over any portion of the arch.

The cover shall be made of 0.030 inch pressboard conforming to the requirements for type I of UU-P-701. Unless otherwise specified, the cover shall not be wider than the width of the board, and not more than 1/2 inch less than the width of the board specified. The cover for size 9 by 14-1/2 inch board shall not be less than 11 inches long, and for size 9 by 17 inch board, not less than 13 inches long. Unless otherwise specified, length of cover for other size boards shall be in accordance with standard commercial practice. The cover shall be perforated so as to pass readily over any portion of the arch. Each cover shall be equipped with an adjustable metal compressor designed with a locking device to hold the cover at any point on the fixed portion of the arch.

3.2.3 Type II, clip board. The board for the clip boards shall conform to the requirements specified in 3.1.1 and 3.2.1. A metal spring clip shall be securely attached and centered at the upper part of the board (see 3.2.3.1).

3.2.3.1 Metal spring clip. The clamp of the clip shall not be less than 5-1/2 inches wide, and shall open a minimum of 1 inch. The clip shall be capable of holding securely any number of sheets of paper from one sheet to full capacity (one inch), when tested as specified in 4.4.2.3.

The base and clamp of the clip shall be made of 22 gage, minimum (.0299 inch) sheet steel, as specified in 3.1.2. The spring, base and clamp shall be firmly held in place by a rivet or an appropriate pin. The clamp shall be fabricated with a concavity having an eye or cutout 3/8 ± 1/8 inch diameter. The clamp shall not flex when pressure is exerted to open the clip, and tested as specified in 4.4.2.3. The base of the clip shall have, as an integral part, an extension with a 3/8 ± 1/8 inch diameter eye or cutout, extending sufficiently beyond the upper edge of the board to permit board to be suspended from a flat vertical surface. The exposed surfaces of the clip shall be smooth, and all corners and edges shall be rounded and smooth.

3.3 Boards dimensions. The dimensions for type I arch board files, and type II clip board files shall be as specified in table I. A plus or minus tolerance of 1/8 inch will be permitted in the overall length and width of the boards.

TABLE I. Board dimensions (in inches)

Type I - Sizes	Type II - Sizes
7 x 12	9 x 12-1/2
9 x 14-1/2	9 x 15-1/2
9 x 17	9-1/4 x 11-3/4
	9 x 17
	13-1/4 x 11-1/4

3.4 Finish. All metal components shall be uniformly nickel, cadmium or zinc plated or coated, and having a bright finish (see 4.4.1).

3.5 Identification marking. Unless otherwise specified, each arch and clip board shall be permanently and legibly marked with the name or trademark of the manufacturer.

3.6 Workmanship. The arch and clip boards shall be free from defects or imperfections which may affect appearance, or may impair serviceability. All components shall be devoid of sharp corners, edges, or other imperfections that may be hazardous to the user.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specifications where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Sampling.

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:47Z
Check the source to verify that this is the current version before use.

4.2.1 Size of lot. All arch and clip board files of the same type, size, and components presented for inspection at one time shall be considered a lot for the purpose of examination and test.

4.2.2 Sampling for inspection. Sampling for inspection shall be performed in accordance with MIL-STD-105, except where otherwise specified.

4.2.3 Sampling for visual and dimensional examination. Random samples of arch or clip board files shall be taken from each lot in accordance with MIL-STD-105. A sample unit shall be one board file. The arch and clip board files shall be examined for defects listed in table II. The Inspection Level shall be S-3, and the Acceptable Quality Level (AQL) shall be 4.0 percent defective for major defects, and 6.0 percent defective for minor defects.

4.2.4 Sampling for preparation for delivery. Sampling shall be in accordance with MIL-STD-105. The lot size shall be the number of shipping containers in the end item inspection lot. For examination of interior packaging, the sample unit shall be one shipping container fully prepared for delivery and selected at random just prior to closing operations. The inspection level shall be S-4, and the AQL shall be 4.0 defects per hundred units.

4.2.5 Sampling for coating or plating test. One sample unit shall be taken from each lot, and each metal component shall be tested as specified in 4.4.1.

4.2.6 Sampling for performance test. Random samples of arch or clip board files for each test shall be taken from each lot in accordance with MIL-STD-105. A sample unit shall be one board file. The arch and clip board files shall be tested as specified in 4.4.2. The inspection level shall be S-2 and the AQL shall be 4.0 percent defective.

4.3 Examination.

4.3.1 Visual and dimensional examination for end items. Samples taken in accordance with 4.2.3 shall be examined for defects listed in table II. Any sample having one or more defects shall be rejected. If the number of defective units in the sample exceeds the acceptance number for that sample, the entire lot represented by the sample shall be rejected.

TABLE II. Classification of defects

Examine	Defects	Major	Minor
Material	Board material not as specified.	X	
	Metal components material not as specified.	X	
Arch paper holder	Arch paper holder not centered on board.	X	
	Arch paper holder missing.	X	
	Not firmly attached to board.	X	
	Arches not spaced 2-3/4 inch centers.	X	
	Locking device absent.	X	
	Arch J-wires not of proper diameter.	X	
	Fixed posts do not have suitable stops for J-shaped wire.	X	
	Fixed post length not within tolerance.	X	
	Eye or cutout not as specified or missing.	X	
Perforator (when specified)	Perforator missing.	X	
	Not securely attached to board.	X	
	Overall height more than 1-1/4 inches.	X	
	Perforator mechanism not as specified.	X	
Index and cover (when specified)	Index cards or cover missing.	X	
	Index cards or cover not as specified.	X	
Metal Clip	Metal clip missing.	X	
	Not firmly attached to board.	X	
	Clamp less than 5-1/2 inches wide.	X	
	Clamp does not have concavity.	X	
	Concavity does not have a 3/8 ± 1/8 inch eye or cutout.	X	
	Base does not have an extension with an eye or cutout as specified.	X	
Dimension	Width or length of board not within tolerance specified.	X	
	Board thickness less than 0.115 inch, or more than 0.155 inch.	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:47Z
Check the source to verify that this is the current version before use.

TABLE II. Classification of defects (con)

Examine	Defects	Major	Minor
Finish	Metal components do not have a bright coating or plating as specified.	X	
Identification marking	Not as specified.		X
Workmanship	Board contains scratches or blisters.	X	
	Board not free from rough edges and corners.		X
	Surface of board not smooth.		X
	Metal components not free from rough edges or corners.		X

4.3.2 Examination of preparation for delivery. Samples selected in accordance with 4.2.4 shall be examined for defects listed in table III to determine that packaging, packing and marking comply with the requirements of section 5. Defects of closure listed below shall be examined on shipping containers fully prepared for delivery.

TABLE III. Examination of preparation for delivery

Examine	Defects
Markings (exterior and interior)	Omitted; incorrect; illegible; improper size, location, sequence, or method of application.
Materials	Any component missing or damaged.
Workmanship	Boxes: Inadequate stapling and application of components such as incomplete closure of container flaps and loose strapping. Case liner missing, damaged, or incorrectly constructed. Distortion of container.

4.4 Tests.

4.4.1 Tests for coating or plating. Samples taken in accordance with 4.2.5 shall be subjected to one of the following tests applicable to the finish of the end product. Failure to identify an authorized plating or coating of 3.4 shall be cause for rejection of the entire lot.

4.4.1.1 Identification for presence of nickel. Using a medicine dropper, apply several drops of nitric acid (HNO_3), Sp. gr. 1.42 to the metal surface. At the end of one minute observe acid drop; a clear pale green color indicates presence of nickel.

4.4.1.2 Identification for presence of zinc and cadmium. Place part or the entire metal component in a beaker of nitric acid (HNO_3), Sp. gr. 1.42. At the end of 1 minute observe the reaction. A vigorous reaction and no precipitate identifies zinc. A slight reaction and a yellow-colored solution identifies cadmium.

4.4.2 Performance tests. Samples selected in accordance with 4.2.6 shall be subjected to the following tests. Any arch or clip board file in the sample failing one or more tests shall be considered defective. If the number of defective units in the sample exceeds the acceptance number for that sample, the entire lot represented by the sample shall be rejected.

4.4.2.1 Arch paper holder. Open and close the movable J-shaped arch 25 times to assure compliance with the requirement stated in 3.2.2.1.

4.4.2.2 Perforator. Six sheets of white bond paper, conforming to UU-P-121, type I, 32 pounds, shall be perforated one at a time. Then, all six sheets of paper shall be assembled as one unit and perforated at different locations at least three times. The tests shall assure compliance with the requirements specified in 3.3.2.2.

4.4.2.3 Metal clip board. Open and close metal clip 25 times. Then, fill clip board with paper 8 x 10-1/2, or 8-1/2 x 11-1/2 inches to full capacity (one inch), and hang clip board against a wall for thirty minutes. The tests shall assure compliance with the requirements stated in 3.2.3.1.

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A, B, or C as specified (see 6.2).

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:47Z
Check the source to verify that this is the current version before use.

5.1.1 Level A, B, or C. Unless otherwise specified, arch and clip boards shall be packaged in accordance with the suppliers commercial practice.

5.2 Packing. Packing shall be level A, B, or C as specified (see 6.2).

5.2.1 Level A. Arch and clip boards of one type, class, and size packaged as specified in 5.1.1 shall be packed in a close fitting box conforming to PPP-B-636, grade V3c or V3s. The box shall be closed, waterproofed and strapped in accordance with the appendix to PPP-B-636. Alternatively one of the following specifications may be used. PPP-B-591, PPP-B-601; PPP-B-621, PPP-B-585 or MIL-B-10377. Each box shall be provided with a sealed case liner conforming to MIL-L-10547, type I or II, grade B or C, class 2. Gross weight of wood boxes shall not exceed 200 pounds.

5.2.2 Level B.

5.2.2.1 Type I, arch board. Six (6) type I, arch boards with perforator or 12 type I, arch boards without perforator shall be packed in a close-fitting box conforming to PPP-B-636, class domestic. The box shall be closed in accordance with the appendix to the box specification.

5.2.2.2 Type II, clip board. Twenty-four (24) type II, clip boards of like description shall be packed in a close-fitting box conforming to PPP-B-636, class domestics. Bursting strength of the box shall be not less than 275 pounds p.s.i. The box shall be closed in accordance with the appendix to the box specification.

5.2.3 Level C. Arch and clip boards shall be packed to insure carrier acceptance and safe delivery at destination at the lowest rates, in containers complying with the rules and regulations applicable to the mode of transportation.

5.3 Marking. In addition to markings required by the contract or order the unit and shipping container shall be marked in accordance with Fed. Std. No. 123 or MIL-STD-129 as applicable.

6. NOTES

6.1 Intended use.

6.1.1 Clip board file. The clip board files are intended as a writing board, and enable the operator to readily add or remove sheet(s) of paper.

6.1.2 Archboard. The arch board files are intended to hold perforated sheets of paper, and serve as a writing board.

6.2 Ordering data. Purchasers should exercise any desired option offered herein and include the following information in procurement documents.

(a) Title, number, and date of this specification.
(b) Type and size of board files required.
(c) Type I board files with paper perforator, indexes and cover, if required.
(d) Levels of packaging and packing.
(e) Any special marking, if required.

GSA DC 70-4136

Source: https://assist.dla.mil -- Downloaded: 2026l0-26T12:47Z
Check the source to verify that this is the current version before use.

GENERAL SERVICES ADMINISTRATION - FEDERAL SUPPLY SERVICE

SPECIFICATION COMMENT SHEET

BUDGET BUREAU NO. 29-R0175

INSTRUCTIONS

This form provides a way for users of this specification to inform the originator of problems encountered in its use. It is not to be used to request changes to accommodate proprietary features. All comments will be considered and appreciated, but please do not expect a reply. To comment: detach, complete, fold, staple, and mail.

NOTE: Comments on this form do not constitute or imply authorization to waive any part of the document or serve to amend contractual requirements.

1. SPECIFICATION

LLL-A-00650C(GSA-FSS) Arch and Clip Board Files, Composition Hardboard Back

2. CONTRACT NO. *(If any)*	3. QUANTITY ON CONTRACT *(Optional)*	4. DOLLAR VALUE *(Optional)*

5. GENERAL NATURE OF PROBLEM *(e.g., inspection difficulties, manufacturers unable to meet tolerances, containers collapse under normal warehousing conditions, etc.)*

6. SPECIFIC REQUIREMENTS AFFECTED *(Include paragraph number and lines of wording)*

7. SPECIFIC PROBLEMS *(e.g. tests in 4.2.2 will not assure that the battery will last required time; temperature ranges in table 2 do not conform to commercially available items.)*

8. RECOMMENDATIONS

9. NAME OF MANUFACTURER, ASSOCIATION, GOVT., AGENCY, ETC.	10. ADDRESS *(Number, Street, City, State and Zip Code)*

11. NAME AND TITLE OF SUBMITTER	12. DATE

FORM GSA FEB 69 2200

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:47Z
Check the source to verify that this is the current version before use.