LLL-C-00110A(GSA-FSS)
November 15, 1968
SUPERSEDING
Int. Fed. Spec. LLL-C-00110(GSA-FSS)
June 5, 1959

INTERIM FEDERAL SPECIFICATION

CASE, FILING, TRANSFER, WOOD OR FIBER

This Interim Federal Specification was developed by the Standardization Division, Federal Supply Service, General Services Administration, Washington, D.C., 20405, based upon currently available technical information. It is recommended that Federal agencies use it in procurement and forward recommendations for changes to the preparing activity at the address shown above.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers transfer filing cases with detachable cover and follower (compressor), to be used for maintenance, transfer or storage of Index cards.

1.2 Classification.

1.2.1 Type and sizes. The cases shall be of one type and of the dimension indicated herein, for the following card sizes as specified (see 3.4 and 6.2):

Size I - For 3 x 5 inch cards
Size II - For 4 x 6 inch cards
Size III- For 5 x 8 inch cards

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issues in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

Federal Specification:

PPP-B-636 - Box Fiberboard.
PPP-T- 97 - Tape, Pressure-Sensitive Adhesive, Filament Reinforcement.

Federal Standards:

Fed. Std. No. 123 - Marking for Domestic Shipment (Civilian Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20402.

(Single copies of this specification and other product specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Service Centers at the General Services Administration Regional Offices in Boston, New York, Washington, D.C., Atlanta, Chicago, Kansas City, Mo., Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, Washington.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Standards:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

Source: https://assist.dla.mil -- Downloaded: 202640-26T12:46Z
Check the source to verify that this is the current version before use.

(Copies of Military Specifications and Standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Material.

3.1.1 Tray and cover. The basic material of which the tray and cover is fabricated shall be binders' board, solid wood, plywood, hard pressed fiberboard, or a suitable combination thereof. The side and bottom material of the tray shall be not less than 0.10 inch thick, and the front and back material shall be not less than 0.20 inch thick. The material of the cover shall be not less than 0.10 inch thick.

3.1.2 Covering and lining. The exterior covering material of the sides of the tray and the entire cover shall be agate marblelized paper. The bottom outside shall be covered with black or dark blue paper. The interior lining material shall be suitable blue or matching dark blue paper.

3.1.3 Follower assembly. The follower and rod or track shall be made of cold-rolled steel with a corrosion resistant finish. The follower shall be not less than 24 United States gage, and the rod shall be not less than 1/8 inch in diameter.

3.1.4 Label holder and pull. The label holder and pull shall be made of steel, and shall be brass plated and coated with lacquer.

3.2 Design. The cases shall be designed for maintenance, transfer, or storage of index cards, and shall permit easy removal and replacement of cards without damage. Each case shall have a removable cover. The tray and cover shall be covered, and the interior shall be lined as specified in 3.3.3. Each case shall have a follower (compressors) as specified in 3.3.4, and a label holder and pull as specified in 3.3.5.

3.3 Construction

3.3.1 Tray. All trays shall be made of wood, plywood, hard-pressed fiberboard, or a suitable combination thereof. The construction shall be such so that the tray shall not crack or deform when tested as specified in 4.4.2. The cutout on each side of the tray shall be not less than 1-1/2 inch from the corners, and the length shall be a minimum of 5-3/4 inches. The inside height of the cutout sides shall be 3 inches for size I; 4 inches for size II; and 5 inches for size III. The inside bottom of the tray shall be reinforced full length with two strips of wood, binders' board, or hard-pressed fiberboard that will form a channel for the follower rod. Each reinforcing strip for size I shall be not less than 1-1/4 inch wide; and for size II not less than 1-1/2 inch wide; and for size III not less than 2 inches wide. The strips shall be of sufficient thickness to permit index cards to rest on the strips, not on the follower rod. All strips shall be glued or otherwise secured to the bottom adjacent to the sides. All outside corners of the tray shall be reinforced with appropriate metal or equivalent staples, and with cloth tape or a suitable fabric properly cemented. The reinforcing fabric shall extend approximately one half inch on each side of the corners.

3.3.2 Cover. The cover shall be made of binder's board. All outside corners of the cover shall be reinforced with appropriate metal or equivalent staples, and with cloth tape, or filament tape, conforming to PPP-T-97. The tape shall cover the entire outside corners, and shall extend a minimum of one half inch on each side of the corners. All sides of the cover shall extend down over the tray approximately one inch.

3.3.3 Covering. The exterior of the sides of the tray and the entire cover shall be covered with agate marblelized paper. The paper shall extend a minimum of 1/4 inch over the edges into the sides and over the bottoms of the tray. The inside of the tray and cover shall be lined with suitable blue or matching dark blue paper. The outside bottom of the tray shall be covered with black or dark blue paper.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:46Z
Check the source to verify that this is the current version before use.

3.3.4 Follower assembly. The follower assembly shall consist of a follower plate mounted on a rod or track. For size I the follower plate shall be not less than 2-1/2 inches high and 3 inches wide; for size II not less than 3-1/4 inches high and 3-3/4 inches wide; and for size III not less than 4 inches high and 5-1/4 inches wide. Corners and edges of the follower plate shall be smooth. The rod or track shall be centered at the bottom of the tray between the reinforcing strips and shall extend the entire length of the tray. The follower plate shall move easily along the rod or track when released by light manual pressure, and shall hold firmly in position by friction at any point along the rod or track when tested as specified in 4.4.3.

3.3.5 Label holder and pull. The label holder and pull shall be made from one piece of material as specified in 3.1.4. All corners and edges shall be rounded and smooth. The label holder and pull shall be securely attached to the tray front, and shall be secured in such manner as to prevent the label card from sliding out through the lower part of the label holder.

3.4 Tray inside dimensions. The tray inside dimensions shall be as specified in table I. A plus tolerance of 1/4 inch, or a minus tolerance of 1/8 inch will be permitted in all dimensions.

Table I - Tray inside dimension (in inches)

Card sizes	Height	Width	Depth
3 x 5	3-1/2	5-1/4	10-3/4
4 x 6	4-1/2	6-1/4	10-3/4
5 x 8	5-1/2	8-1/4	10-3/4

3.5 Identification marking. Each transfer filing case shall be permanently and legibly marked with the name or trademark of the manufacturer.

3.6 Workmanship. All cases shall be free from any defects and imperfections which affect appearance or may impair the serviceability. The bottom, corners, strips, follower, and label holder shall be properly secured. The covering and lining materials shall be neatly cemented to present a smooth and uniform appearance. The cover shall fit properly, and shall open and close smoothly.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2 Sampling.

4.2.1 Size of lot. All cases of one size presented for delivery at one time shall be considered a lot for the purpose of inspection and tests.

4.2.2 Sampling and inspection for acceptance. Sampling and inspection shall be performed in accordance with MIL-STD-105.

4.2.3 Sampling for visual inspection. Random sample of cases shall be taken from each lot in accordance with MIL-STD-105. A sample unit shall be one case. The cases shall be examined for defects listed in table II. The inspection level shall be S-3, and the Acceptable Quality Level (AQL) shall be 4.0 defect per hundred units.

4.2.4 Sampling for end-item tests. Sampling for end-item tests. Random sample of cases shall be taken from each lot in accordance with MIL-STD-105. A sample unit shall be one case. The cases shall be tested as specified in 4.4.2 and 4.4.3. The inspection level shall be S-2, and the AQL 4.0 per hundred.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:46Z
Check the source to verify that this is the current version before use.

4.2.5 Sampling for preparation for delivery. Sampling shall be in accordance with MIL-STD-105. The sample unit shall be one shipping container fully prepared for delivery with the exception that it need not be sealed. The lot size shall be the number of shipping container in the end-item inspection lot. The inspection level shall be S-2 and the AQL shall be 2.5 defects per hundred units.

4.3 Examination

4.3.1 Visual and dimensional examination of end-item. Samples taken in accordance with 4.2.3 shall be examined for defects listed in table II. Any case having one or more defects shall be rejected. If the number of defective units in the sample exceeds the acceptance number for that sample, the entire lot represented by the sample shall be rejected.

Table II. - Visual and dimensional defects

Examine	Defects
Material	Material not as specified.
	Material thickness not as specified.
Construction	Corner of tray and cover not reinforced as specified.
	Width of bottom reinforcement strips not as specified.
	Bottom reinforcement not properly secured.
	Follower not properly installed.
	Label holder and pull not as specified.
	Tray, and cover not fully covered outside, or fully lined inside.
	Covering paper does not overlap as specified.
Dimensions	Inside dimensions of tray not as specified.
Color	Color of covering and lining material not as specified.
Workmanship	Covering and lining material not smoothly applied, nor devoid of wrinkles, bubbles and ragged edges.
	Corners not completely covered.
Identification marking	Identification marking missing, incomplete or illegible.

4.3.2 Examination of preparation for delivery. Samples selected in accordance with 4.2.5 shall be examined for defect listed in Table III, to determine that packaging, and marking requirements of section 5 of this specification are complied with. Defects of closure listed below shall be examined on shipping containers fully prepared for delivery.

Table III. - Classification of preparation for delivery defects

Examine	Defect
Marking (exterior and interior)	Omitted, incorrect, illegible, or improper size, location, sequence, or method application.
Materials	Any component missing, or not as specified.
	Any component damaged, affecting serviceability.
Workmanship	Inadequate application of components, such as: incomplete closure of container flaps, loose strapping, improper taping, inadequate stapling.
	Bulging or distortion of containers.
Content	Number per bundle and container is more, or less than required.
Weight	Weight exceeds requirements.

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:46Z
Check the source to verify that this is the current version before use.

4.4 Tests

4.4.1 Tests for end-item. Samples selected in accordance with 4.2.4 shall be subjected to the following tests. Any case in the sample failing one, or more test shall be considered defective. If the number of defective cases exceeds the acceptance number for the sample, the lot represented by the sample shall be rejected.

4.4.2 Operational test. Move follower plate to the extreme end of the tray and fill tray with cards of the proper size or equivalent weight. Tilt tray forward 55 degrees so that follower plate will be in the upward position. Leave tray in this position for 60 minutes. Reverse follower plate to the other end of the tray and repeat the same procedure. The test shall assure compliance with the requirements stated in 3.3.1.

4.4.3 Operational test for follower. Move follower ten (10) times along the entire length of the rod or track back and forth stopping periodically and applying pressure at the upper part of the follower plate to assure compliance with the requirements specified in 3.3.4.

5. PREPARATION FOR DELIVERY

5.1 Packing. Packing shall be level A, B, or C as specified (see 6.2).

5.1.1 Level A. Twelve cases, of one stock number, shall be packed in a box conforming to PPP-B-636, class-weather resistant. The box shall be closed in accordance with the appendix to the box specification.

5.1.2 Level B. Twelve cases, of one stock number, shall be packed in a box conforming to PPP-B-636, class domestic. The box shall be closed in accordance with the appendix to the box specification.

5.1.3 Level C. Cases shall be packed to insure carrier acceptance and safe delivery at destination at the lowest rates, in containers complying with the rules and regulations applicable to the mode of transportation.

5.2 Marking.

5.2.1 Civil agencies. In addition to markings required by the contract or order, the shipping containers shall be marked in accordance with Fed. Std. 123.

5.2.2 Military activities. In addition to markings required by the contract or order, the shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. The transfer, filing cases are intended to be used as file cases for the maintenance, transfer or storage of index cards without damaging them, and to readily permit their removal and replacement.

6.2 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in procurement document:

(a) Title, number, and date of this specification.
(b) Sizes (see 1.2.1 and 3.4
(c) Level of packaging and packing (see 5)
(d) Marking requirements (see 5.2)

GSA DC 69-6904

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:46Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:46Z
Check the source to verify that this is the current version before use.