LLL-H-1142A
May 8, 1973
SUPERSEDING
Int. Fed. Spec. LLL-H-001142(GSA-FSS)
April 25, 1966

FEDERAL SPECIFICATION

HANGER, TROUSER

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1 SCOPE

1.1 This specification covers a clamp type trouser hanger with a locking device.

2. APPLICABLE DOCUMENTS

2.1 The following specifications and standards, of the issues in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

Federal Specifications:

PPP-B-566 - Boxes, Folding, Paperboard.
PPP-B-636 - Box, Fiberboard.
PPP-B-665 - Boxes, Paperboard, Metal Stayed (Including Stay Material).
PPP-B-676 - Boxes, Set-Up, Paperboard.

Federal Standard:

Fed. Std. No. 123 - Marking for Domestic Shipment (Civil Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U. S. Government Printing Office, Washington, DC 20402.)

(Single copies of this specification and other Federal Specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Service Centers at the General Services Administration Regional Offices in Boston, New York, Washington, DC, Atlanta, Chicago, Kansas City, MO, Fort Worth, Denver, San Francisco Los Angeles, and Seattle WA.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Specification:

MIL-W-6110 - Wood; Determination of Moisture Content of.

Military Standards:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

(Copies of Military Specifications and Standards required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

FSC 7290

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:47Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Materials.

3.1.1 Wood. Wood used in the fabrication of the hanger jaws shall be any of the following species: Red alder, beech, birch, cherry, gum or maple. Wood shall be dried to a moisture content not exceeding 12 percent (see 4.4.2) and shall be free of knots, splits, splinters, holes or other defects which may affect appearance or serviceability.

3.1.2 Felt. Felt shall be of good commerical quality suitable for the intended use.

3.1.3 Wire, steel. Wire used for the hook and locking device shall be 0.135 ± .002 inch diameter 10 (gage) minimum to 0.162 ± .002 inch diameter (8 gage) maximum cold drawn low carbon steel.

3.2 Construction. Trouser hangers shall consist of two parallel wood jaws held in position by a steel wire locking device and suspended by means of a steel wire hook.

3.2.1 Jaws. Jaws shall not be less than 9 inches long by 7/8 inch wide by 5/16 inch thick and shall be smoothly finished with all sharp edges removed. Each jaw shall be made with a concave area in the inside center, sufficient to provide clearance for trouser seams, allowing a positive clamping action on the garment. The contact surfaces of each jaw shall be lined with felt, securly glued to the jaws or shall be constructed with grooves in the surface to prevent garment slippage, at the manufacturer's option.

3.2.2 Felt lining. The width of each felt strip shall be equal to the width of the jaws and the length of each felt strip shall extend the full length of the actual contact surfaces.

3.2.3 Grooves. Grooves shall extend the full length of the actual contact surfaces, and shall not be less than 1/2 inch in width.

3.2.4 Hook and locking device. The locking device shall be of such design as to be readily and conveniently operated. It shall be positive in action and incapable of releasing without manual operation. When in the loaded position, the hook and locking device shall not in any way interfere with the suspended trousers. When locked, the jaws shall press firmly together and the hook shall be in an upright position.

3.3 Finish.

3.3.1 Wood. Wood jaws shall be evenly coated with a standard commercial lacquer or varnish on all surfaces.

3.3.2 Wire. Wire shall be galvanized (zinc coated) or nickel plated, at the option of the manufacturer.

3.4 Workmanship. Trouser hangers shall be free from sharp edges, projections, slivers and defects which might impair its serviceability or appearance. Surfaces shall be free from flaws and cracked or peeling plating, varnish or lacquer.

4.2 Sampling.

4.2.1 Lot. Unless otherwise specified (see 6.2), a lot shall consist of all trouser hangers submitted for inspection at the same time.

4.2.2 Visual examination of end item. Sampling for visual examination shall be in accordance with level S-3 in MIL-STD-105.

4.2.3 Sampling for tests. Samples for tests shall be in accordance with level S-2 in MIL-STD-105.

4.3 Inspection.

4.3.1 End item. Hangers selected in accordance with 4.2.2 shall be examined for defects listed in table I. The Acceptable Quality Levels (AQL's) for defects shall be 2.5 percent defective for major defects and 4.0 percent defective for minor defects in accordance with MIL-STD-105.

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:47Z
Check the source to verify that this is the current version before use.

TABLE I. Classification of defects, end item

Examine	Defect	Major	Minor
Wood jaws	Not smoothly finished.		X
	Species of wood not as specified.		X
	Cracked, warped, fractured or split.	X	
	Knots, holes, sharp edge or splinters	X	
	Projection or sliver that may cause injury to clothing.	X	
	Warped out of shape.	X	
Construction and workmanship	Wood jaws not parallel or held in position by a steel wire locking device.	X	
	Not suspended by means of a steel wire hook.		X
	Contact surface of each jaw not lined with felt.	X	
	Felt not securely glued to jaws.		X
	Felt strip not full width of jaws.		X
	Felt strip length less than 1 inch.		X
	Width of grooves not as specified.	X	
	Grooves not cut full length of contact surfaces.	X	
Hook and locking device	Hook and locking device not of material specified.		X
	Locking device not readily and conveniently operated.	X	
	Locking device not positive in action.	X	
	Locking device releases without manual operation.	X	
	When locked, jaws do not press firmly together with the hook in an upright position.		X
	In a loaded position, hook and locking device interfere with suspended trousers.	X	
Finish	Wood jaws not laquered or varnished.		X
	Finish tacky, blistered, peeled, scratched, wrinkled, stained or uneven.		X
	Wire finish not as specified.	X	
	Plating uneven, peeling or scratched.		X

4.3.2 Inspection of preparation for delivery requirements. An inspection shall be made to determine that the packaging, packing and marking comply with the requirements in section 5 of this specification. Defects shall be scored in accordance with table II. For examination of interior packaging the sample unit shall be one shipping container fully prepared for delivery, selected at random just prior to the closing operations. Sampling shall be in accordance with MIL-STD-105. Defects of closure listed shall be examined on shipping containers fully prepared for delivery. The lot size shall be the number of shipping containers in the end item inspection lot. The inspection level shall be S-2 with an acceptable quality level (AQL) of 4.0 defects per hundred units.

TABLE II. Classification of preparation for delivery defects

Examine	Defects
Markings (exterior and interior)	Omitted; incorrect; illegible; improper size, location, sequence, or method of application.
Materials	Any component missing or damaged.
Workmanship	Inadequate application of components such as incomplete closure of container flaps, loose strapping, distortion of container.
Contents (exterior and interior container)	Number per container is more or less than required. Nev weight exceeds requirements.

4.4 Tests.

Source: https://assist.dla.mil -- Downloaded: 202640-26T12:47Z
Check the source to verify that this is the current version before use.

4.4.1 Acceptance. The AQL for tests shall be 6.5 on the basis of percent defective.

4.4.2 Moisture. The moisture content shall be determined by the oven drying or electrical moisture meter method in accordance with MIL-W-6110 (see 3.1.1).

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A, B, or C as specified (see 6.2).

5.1.1 Level A. Twenty-four (24) hangers shall be packaged in a close fitting box conforming to PPP-B-566, PPP-B-665, or PPP-B-676.

5.1.2 Level B. The hangers shall be packaged as specified in 5.1.1.

5.1.3 Level C. The hangers shall be packaged in accordance with the suppliers commercial practice.

5.2 Packing. Packing shall be level A, B, or C as specified (see 6.2).

5.2.1 Level A. Six (6) unit packages of hangers shall be packed in a close fitting box conforming to PPP-B-636, class weather resistant. The box shall be closed and strapped in accordance with the appendix to the box specification.

5.2.2 Level B. Six (6) unit packages of hangers shall be packed in a close fitting box conforming to PPP-B-636, class domestic. The box shall be closed in accordance with the appendix to the box specification.

5.2.3 Level C. The hangers shall be packed to insure carrier acceptance and safe delivery at destination in containers at the lowest rates complying with the rules and regulations applicable to the mode of transportation.

5.3 Marking.

5.3.1 Civil agencies. In addition to markings required by the contract or order, the interior packages and shipping containers shall be marked in accordance with Fed. Std. No. 123.

5.3.2 Military activities. In addition to markings required by the contract or order, the interior packages and shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. Hangers covered by this specification are to be used to suspend trousers, by the cuff end, in a full length position.

6.2 Ordering data. Purchasers should select the preferred options permitted herein and include the following in procurement documents:

(a) Title, number and date of this specification.
(b) Size of lot, if different from 4.2.1.
(c) Selection of applicable level of packaging and packing required (see 5.1 and 5.2).

6.3 Samples. If, for any particular purpose, samples with bids are necessary, they should be specifically asked for in the invitation for bids and the particular purpose to be served by the bid sample shall be definitely stated, the specification to apply to all other respects.

MILITARY INTERESTS:

DOD has waived coordinating on revisions and amendments to this Federal Specification until further notice.

Preparing activity:

GSA-FSS

User interest:

Army-GL

Orders for this publication are to be placed with the General Services Administration, acting as an agent for the Superintendent of Documents. See section 2 of this specification to obtain extra copies and other documents referenced herein. Price 10 cents each.

Source: https://assist.dla.mil -- Downloaded: 202640-26T12:47Z
Check the source to verify that this is the current version before use.