LLL-R-530b
July 13, 1967
SUPERSEDING
Fed. Spec. LLL-R-530a
January 28, 1963

FEDERAL SPECIFICATION

ROLLING PINS (WOOD)

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers wooden rolling pins.

1.2 Classification. Rolling pins shall be one of the following types, as specified (see 6.2 and 6.3).

Type I - With stationary handles, 3-3/4 inch minimum diameter, 22 to 24 inches overall length.
Type III - Without handles, (pie rolling) 1-1/2 inch minimum diameter, 11-1/2 to 12-1/2 inch overall length.

2. APPLICABLE DOCUMENTS

2.1 The following specifications and standards, of the issues in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

Federal Specifications:

L-P-378 - Plastic Sheet and Strip (Polyolefin).
PPP-B-601 - Boxes, Wood, Cleated-Plywood.
PPP-B-621 - Boxes, Wood, Nailed and Lock-Corner.
PPP-B-636 - Box, Fiberboard.
PPP-B-640 - Boxes, Fiberboard, Corrugated, Triple-Wall.
PPP-F-320 - Fiberboard; Corrugated and Solid, Sheet Stock (Container Grade), and Cut Shapes.

Federal Standard:

Fed. Std. No. 123 - Marking for Domestic Shipment (Civilian Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U. S. Government Printing Office, Washington, D. C., 20402.

(Single copies of this specification and other product specifications required by activities outside the Federal Government for bidding purposes are available without charge at the General Services Administration Regional Offices in Boston, New York, Washington, D. C., Atlanta, Chicago, Kansas City,Mo., Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, Wash.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Specification:

MIL-W-6110 - Wood; Determination of Moisture Content of.

Military Standards:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.
MIL-STD-130 - Identification Marking of U. S. Military Property.

(Copies of Military Specifications and Standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

FSC 7330

Source: https://assist.dla.mil -- Downloaded: 202640-26T12:47Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Preproduction sample. When specified (see 6.2), before production is commenced, a sample rolling pin covered by this specification shall be submitted or made available to the contracting officer or his authorized representative for approval in accordance with 4.2. The approval of the preproduction sample authorizes the commencement of production, but does not relieve the supplier of responsibility for compliance with all applicable provisions of this specification. The preproduction sample shall be manufactured in the same facilities to be used for the manufacture of the production items.

3.2 Standard product. The rolling pins delivered under this specification shall be the manufacturer's commercially current standard product except for any changes necessary to comply with the requirements specified herein.

3.3 Materials. Materials not definitely specified shall be of the quality used by the manufacturer in his currently available commercial rolling pins.

3.3.1 Wood. Wood shall be birch, beech, maple, or sycamore.

3.4 Design and construction. The rolling pins shall be fabricated from the wood specified in 3.3.1. Wood shall be free of shakes, splits, wormhole, decay and knots. Mineral streaks shall be not greater than 1/8 inch in width. Slope of grain shall not exceed 1 in 10 inches. Visible areas of dark heartwood shall not exceed 10 percent of the surface area of the finished rolling pin. The moisture content at the time of fabrication, shall be not greater than 8 percent when tested as specified in 4.3.1.1. The roller body shall be cylindrical with an out of roundness not exceeding 1/16 of an inch when tested as specified 4.4.1, and shall be straight within 1/16 inch when tested as specified in 4.4.2. All edges shall be beveled.

3.4.1 Type I. The type I rolling pin shall consist of a roller body with a stationary handle fixed at the center of each end. The roller body shall be not less than 3-3/4 inches in diameter. The handles shall be 4 ± 1/8 inch in length measured from the end of the roller body. The overall length shall be 23 ± 1 inch. The handles shall be fastened to the roller body with commercial glue in accordance with the manufacturer's standard practice and shall not break, crack, permanently deform, or separate from the roller when tested as specified in 4.4.3.

3.4.2 Type III. The type III rolling pin shall consist of a roller body without handles. The roller body shall be not less than 1-1/2 inches in diameter and shall be 12 ± 1/2 inch in length. The ends of the roller body shall be hemisperical in shape.

3.5 Marking.

3.5.1 Military agencies. The letters "U. S." in characters 3/16 inch high shall appear on each rolling pin. Marking shall be in accordance with MIL-STD-130.

3.5.2 Civil agencies. The manufacturer shall permanently and legibly indent his name or trademark of such known character easily identifiable with said manufacturer on each rolling pin.

3.6 Finish. All surfaces of the rolling pins shall be finished in accordance with the manufacturer's standard practice.

3.7 Workmanship. The rolling pins shall be clean and free of dents, cracks, slivers, splinters, loose grain, loose knots, bark, and unnatural discoloration or surface bruises.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2 Preproduction sample inspection. When a preproduction sample is required, it shall be examined for defects in table I and specified dimensions and tested in accordance with 4.4.1 through 4.4.3.

4.3 Sampling for inspection. Sampling for inspection shall be made in accordance with provisions set forth in MIL-STD-105, unless otherwise indicated hereinafter.

Source: https://assist.dla.mil -- Downloaded: 20260-26T12:47Z
Check the source to verify that this is the current version before use.

4.3.1 Components and material inspection. In accordance with 4.1, components and material shall be inspected and tested with all the requirements specified in referenced specifications, drawings, and standards unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

4.3.1.1 Wood, moisture content. The moisture content of the wood shall be determined at the time of fabrication in accordance with MIL-W-6110, for conformance with the requirements of 3.4. The determination of moisture content shall be performed on each lot of wood at time of fabrication. The lot shall be the amount of wood offered for inspection at one time. The sample unit shall be one piece of wood. Three determinations shall be taken on each sample unit and results shall be the average of the 3 determinations. The inspection level shall be S-4 with an acceptable quality level (AQL) of 2.5 defects, expressed in terms of defects per hundred units.

4.3.2 Inspection of the end products. The inspection lot shall consist of all rolling pins of one type offered for inspection at one time. The sample unit shall be one rolling pin.

4.3.2.1 Visual examination. Examination of the rolling pins shall be in accordance with the classification of defects listed in table I. The inspection level shall be level II with AQL's of 2.5 for major defects and 6.5 for total defects, expressed in terms of defects per hundred units.

TABLE I. Classification of defects

Examine	Defect	Classification	
		Major	Minor
Finish	Not in accordance with manufacturer's standard practice	X	
Design, construction, and workmanship	Grain slopes more than 1 in 10 inches		X
	Mineral streaks not over 1/8 inch wide		X
	More than 10 percent of all exterior surfaces dark hardwood		X
	Splits or shakes	X	
	Splinters	X	
	Surface bruised		X
	Evidence of bark dry rot or decay	X	
	Any knots (including pin knots)		X
	Wormholes on roller surface	X	
	Wormholes on end of roller or handle surface		X
	Unnatural discoloration		X
	Edge not beveled		X
	Not correct species of wood	X	
	Broken handle (type I)	X	
	Handle missing (type I)	X	
	Handle not stationary (type I)		X
	Ends of rollers not hemisperical (type III)		X
Marking	Not glued where required	X	
	Missing, not as specified, illegible		X

4.3.2.2 Dimensional examination. Examination shall be made of the end item to determine conformance to dimensional requirements of the specification. Any nonconformance to the specified requirements shall be classified as a defect. The inspection level shall be S-2 with an AQL of 4.0 defects, expressed in terms of defects per hundred units.

4.3.2.3 Testing of the end item. The end item shall be tested as specified in 4.4.1 thru 4.4.3. The inspection level shall be level S-2 with an AQL of 4.0, expressed in terms of defects per hundred units.

4.3.3 Examination of preparation for delivery. An examination shall be made to determine that packaging, packing, and marking as required by section 5 are complied with. Defects shall be scored as specified in table II. The sample unit shall be one shipping container fully prepared for delivery. The lot shall be the number of containers in the inspection lot. The inspection level shall be S-4 with an AQL of 6.5 defects, expressed in terms of defects per hundred units.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:47Z
Check the source to verify that this is the current version before use.

TABLE II. Examination of preparation for delivery

Examination	Defect
Marking	Omitted; missing; incorrect; illegible; of improper size, location, sequence, or method of application.
Materials	Component missing, damaged, or otherwise defective.
Workmanship	Inadequate application of components such as incomplete closure of polyethylene bag or container flaps, loose strapping, bulging or distortion of containers.
Contents	Contents per container are more or less than required.

4.4 Tests.

4.4.1 Roundness. The body diameter of the rolling pin shall be measured around the circumference at each end and at the center to determine compliance with 3.4.

4.4.2 Straightness. Lay the rolling pin on a level surface. Attempt to insert a 1/16-inch feeler gage between the roller body and the level surface at each end and at the center of the body to determine compliance with 3.4.

4.4.3 Handle strength. Clamp the rolling pin in a horizontal position and suspend a 75 pound weight from the center of each handle for 3 minutes. Remove the weights and examine the rolling pin for strength requirements specified in 3.4.1.

5. PREPARATION FOR DELIVERY

5.1 Packaging shall be level A or C, as specified (see 6.2).

5.1.1 Level A. Each rolling pin shall be placed in a close-fitting polyethylene bag. The polyethylene film shall be minimum 0.002-inch thick conforming to type II, grade A, B, or C, finish 1 or 2 of L-P-378. All seams shall be heatsealed abd shall conform to the heatseal strength requirements of L-P-378. The mouth end of the bag, when prepared for closure, shall extend a minimum of 6 inches beyond the packaged item. Closure of the bag shall be accomplished by double-folding the plastic material at the mouth and taping it to the bag body with pressure sensitive tape (see 6.4).

5.1.2 Level C. Rolling pins shall be packed to afford adequate protection against damage during shipment from the supply source to the first receiving activity. The supplier may use his standard practice when it meets this requirement.

5.2 Packing. Packing shall be level A, B, or C, as specified (see 6.2).

5.2.1 Level A. Fifteen type I or fifty type III rolling pins, packaged as specified in 5.1, shall be packed in the most compact manner in a snug-fitting cleated-plywood or nailed wood shipping container conforming to overseas type, type 3 load of PPP-B-601; or class 2, style 2 or 4, type 3 load of PPP-B-621. Shipping containers containing type I rolling pins, packaged as specified in 5.1.1, shall be provided with fiberboard pads conforming to grades W5c or W5s of PPP-F-320, placed within the shipping container at both ends or sides, wherever applicable, to protect the polyethylene from puncture by the rolling pin handles. Closure and strapping shall be in accordance with the appendix of the applicable container specification.

5.2.2 Level B. Fifteen type I or fifty type III rolling pins, packaged as specified in 5.1, shall be packed as specified in 5.2.1 except that shipping containers shall conform to PPP-B-636, class domestic; domestic type, style A or B of PPP-B-601; class 1, style 2 or 4, type 3 load of PPP-B-621; or PPP-B-640, class 1; and fiberboard pads shall conform to type CF or SF, class domestic, grade 200 of PPP-F-320.

5.2.3 Level C. Rolling pins, packaged as specified in 5.1, shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies. Containers shall be in accordance with rules or regulations of carriers applicable to the mode of transportation.

5.3 Marking.

Source: https://assist.dla.mil -- Downloaded: 202640-26T12:47Z
Check the source to verify that this is the current version before use.

5.3.1 Civil agencies. In addition to any special marking required by the contract or order, shipping containers shall be marked in accordance with Fed. Std. No. 123.

5.3.2 Military agencies. In addition to any special marking required by the contract or order, shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. The rolling pins covered by this specification are intended for use in the preparation of food in kitchens and bakeries.

6.2 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in procurement documents:

(a) Title, number, and date of this specification.
(b) Type required (see 1.2).
(c) Whether preproduction sample is required (see 3.1).
(d) Selection of applicable levels of packaging and packing (see 5.1 and 5.2).

6.3 Supersession data. The type I, sizes 1 and 2, and all type II rolling pins specified in LLL-R-530a have been deleted. The types I and III rolling pins covered by this specification are the same as the type I, size 3, and type III, size 1, respectively, of LLL-R-530a.

6.4 Packaging. The method of packaging referred to in 5.1.1 is similar to method III of MIL-P-116.

MILITARY CUSTODIANS:

Army - GL
Navy - SA
Air Force - 84

Review activities:

Navy - SA
Air Force - 84, 85, 41

User activities:

Army - MD
Navy - MC, CG

Preparing activity:

Army - GL

CIVIL AGENCIES INTEREST:

GSA
HEW
VA

5

Orders for this publication are to be placed with dministration, acting as an agent for the Superintendent of Documents. See section 2 of this specification to obtain extra copies of documents referenced herein. Price of this specification

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:47Z
Check the source to verify that this is the current version before use.