INCH-POUND

MMM-A-1058A
INTERIM AMENDMENT 2
June 30, 1995
SUPERSEDING
INTERIM AMENDMENT 1
January 26, 1978

INTERIM AMENDMENT

TO

FEDERAL SPECIFICATION

ADHESIVE, RUBBER, (IN PRESSURIZED DISPENSERS)

This interim amendment was developed by the General Services Administration, Federal Supply Service, based upon currently available technical information.

The General Services Administration has authorized the use of this interim amendment, which forms a part of MMM-A-1058A, dated January 16, 1975, by all federal agencies.

PAGE 1

Paragraph 1.1, line 1, delete "two types" and substitute "one type".

Paragraph 1.2, line 1, for "types" read "type" and line 3, delete "Type II - Non-flammable (Low Solids)".

Paragraph 2.1, under "Federal Specifications", delete references to "PPP-B-585, PPP-B-591, PPP-B-640, and PPP-F-320".

Under "Federal Standards", delete "Fed. Std. No. 123".

Under "Military Standards", delete "MIL-STD-129".

PAGE 2

Paragraph 2.2, under "National Motor Freight Classification", line 2, delete "Tariff Order Section" and substitute "Traffic Department".

Paragraph 3.1.2, delete entire paragraph.

DISTRIBUTION STATEMENT A Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:48Z
Check the source to verify that this is the current version before use.

PAGE 2 (Continued)

* Paragraph 3 1.3 1, add new sentence at the end of the paragraph "There shall be no vinyl chloride in the aerosol propellant when tested as specified in 4.4.8."

Paragraph 3 1 3 2, delete entire paragraph.

Paragraph 3.2.1, line 5, delete "Each container ... in 5.3", and substitute "Each aerosol dispenser shall be labeled with the following information:

(a) Net weight in ounces.
(b) Name of material.
(c) Manufacturer's name and address.
(d) Precautions for use and storage.
(e) Directions for use including surface preparation.
(f) Date of manufacture by month and year.
(g) Date of first reinspection (12 months after date of manufacture)
(h) Store below 80°F.
(i) Name of the propellant or propellants."

PAGE 3

Paragraph 3.2.2, line 5, delete "--not elongate and touch the bottom of the can and shall--." At the end of the paragraph, add the following sentence: "It shall be possible to remove and replace the dispensing valve without releasing any ingredients of the container."

* Paragraph 3.2.3, line 2, delete "plastic".

Paragraph 3.4.1.1, line 2, delete "for type I and not less than 8 percent for type II".

Paragraph 3.4.2.1, lines 5-10, delete the column titled type II.

* Paragraph 3.4.2.2, delete and substitute:

"3.4.2.2 Internal pressure. When tested as specified in 4.4.1, the internal pressure, in pounds per square inch gage (p.s.i.g.), shall be 25 to 70 at 73 4°F (23°C) and not more than 140 at 130°F (54.4°C)."

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:48Z
Check the source to verify that this is the current version before use.

PAGE 4

* Paragraph 3.4.2.3, delete and substitute:

"3 4 2.3 Delivery rate. When tested as specified in 4.4.5, the dispenser shall spray the adhesive at a rate of not less than 20 and not moran 70 grams per minute (g per min)."

Paragraph 3.4.2,4, line 2, delete "for type I and three inches wide for type II"

Paragraph 3.4.2.5, delete entire paragraph.

Paragraph 4.3.1, delete in its entirety, including Table I, and substitute the following:

"4.3.1 Inspection of preparation for delivery. An inspection shall be made to determine whether the packaging, packing and marking comply with the requirements of Section 5. The sample unit shall be one shipping container fully prepared for delivery and selected at random. Sampling shall be in accordance with MIL-STD-105. The inspection level shall be S-2 with an AQL of 4.0 expressed as percent defective."

PAGE 6

Paragraph 4.4.7, delete entire paragraph.

Add new paragraph 4.4.8 as follows:

* "4.4.8 Analysis of propellant gas for vinyl chloride.

4.4.8.1 Special apparatus and materials. The chemical analysis described herein requires the following apparatus and materials:

a) The can-piercing, pressure-measuring device recommended in the CSMA Aerosol Guide for determining the internal pressure of aerosol products. The device is available as Model CBA-6 from Builders Sheet Metal Works, Inc., 110 Wester Street, New York, New York 10012.

b) A temperature-programmable gas chromatograph (Hewlett-Packard Model 5750 gas chromatograph, or equivalent) equipped with 0.5 ml gas sampling valve and thermal conductivity detector.

c) Two stainless steel gas chromatography columns, 1.83 m long by 3 mm outside diameter, packed with 60-200 mesh silica gel.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:48Z
Check the source to verify that this is the current version before use.

d) Standard propellant gas in lecture bottles (available from Matheson Gas Products or another supplier): vinyl chloride.

e) Lecture bottle control valves, Matheson Model 58, or equivalent.

4.4.8.2 Gas chromatographic analysis. Condition the chromatographic columns at 200°C with helium as the carrier gas at a flow rate of 75-100 ml/min for one hour. Remove the actuator and cap of an unused aerosol container Puncture the can using the pressure measuring device, and connect the device to the gas chromatograph. Triplicate chromatographic analyses shall be done on the aerosol propellant sample and on mixtures of the aerosol propellant with each of the five standard propellant gases. For mixing each standard propellant with the aerosol propellant sample, use a "T" connect (Swagelock or equivalent) The "T" connection shall be removed entirely when the aerosol propellant sample alone is to be analyzed.

Bubble each gas sample through the sampling valve at a moderate rate for two minutes before each run is made to purge the valve of any other gases. Analyze the samples using a temperature program from 100 to 200°C at 6°C per minute, with a 2 minute post injection hold at 100°C and a 5 minute upper limit hold at 200°C. There shall be no material in the aerosol propellant sample having the same retention time as any of the five standard propellant gases."

Delete section 5 and substitute·

"5. PREPARATION FOR DELIVERY

5.1 Packing. Packing shall be level A or commercial, as specified (see 6.2).

5.1.1 Level A.

5.1.1.1 Intermediate pack. Unless otherwise specified (see 6.2), 12 filled aerosol dispensers of adhesive of like description, shall be packed in a box conforming to PPP-B-636, type CF or SF, weather-resistant, style optional. Interior fiberboard partition separators shall be used as required to prevent shifting of cans. The box shall be closed in accordance with the appendix to the box specification.

5.1.1 2 Shipping container. Intermediate packs (5.1.1.1) of like description shall be packed in a close fitting box conforming to PPP-B-636, grade V3c, style RSC or FOL The box shall be closed in accordance with the appendix to the box specification. Alternatively, cleated

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:48Z
Check the source to verify that this is the current version before use.

PAGE 6 (Continued)

plywood, wire bound or nailed wood boxes shall be acceptable shipping containers when lined with a waterproof barrier material. The edges of the barrier material shall be sealed with waterproof tape or adhesive

5.1.2 Commercial. The aerosol cans of adhesive shall be packaged in accordance with normal commercial practice and packed in fiberboard boxes that will assure acceptance by common carrier and provide product protection against loss and damage during multiple shipments, handling and storage. The shipping container shall be in compliance with National Motor Freight Classification or Uniform Freight Classification.

5.2 Unitization. When shipments to Government depots are full car or truckload, the shipping containers shall be unitized to facilitate handling, in accordance with normal commercial practice. The unitized load shall not exceed 2,500 pounds in weight, 63 inches in height, 56 inches in length, and 45 inches in width.

5.3 Marking Marking shall be as specified in the contract or order "

PAGE 7

Paragraph 6.1.1, delete entire paragraph.

Paragraph 6.2(d), delete "packaging and" and reference to "and 5.2".

Paragraph 6 2(f), delete.

The margins of this interim amendment are marked with asterisks (or vertical lines) to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only, and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

CIVIL AGENCY
COORDINATING ACTIVITY:

GSA-FSS

Preparing Activity:
Navy - AS
(Project No. 8040-N191)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:48Z
Check the source to verify that this is the current version before use.