NOT MEASUREMENT SENSITIVE

MIL-DTL-3628/69C
15 November 1996
SUPERSEDING
MIL-B-3628/69B
30 July 1993

DETAIL SPECIFICATION SHEET

BADGE, QUALIFICATION, COMBAT AND SPECIAL SKILL, RIGGER, ARMY

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-3628 listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation.

MATERIAL: Red Brass or Nickel Silver

DASH NO.
-1: Regular Size
-2: Miniature Size
-3: Regular Size, Subdued

FINISH:
-1, -2: Nickel Plated (Red Brass only), Silver Plated, Oxidized, Relieved, Matte Finish and shall match TIOH Metal Finish Chip Number 14.
-3: Dull, Flat Black Enamel Finish.

DIMENSIONS:
HEIGHT (Overall):
-1, -3: 11/16 inch (1.75 cm) (REF)
-2: 3/8 inch (0.98 cm) (REF)
WIDTH (Overall):
-1, -3: 1-3/4 inches (4.45 cm) (REF)
-2: 1 inch (2.54 cm) (REF)

AMSC N/A FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T19:18Z
Check the source to verify that this is the current version before use.

THICKNESS (Minimum Forced Area): 0.035 inch ± 0.005 inch (0.088 cm ± 0.012 cm)
OVERALL DEPTH (Including Forced Area):
-1, -3: 0.095 inch ± 0.005 inch (0.241 cm ± 0.012 cm)
-2: 0.070 inch ± 0.005 inch (0.177 cm ± 0.012 cm)

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. The dull, flat black enamel for Dash No. -3 shall match FED-STD-595 Number 37038.

3. A full forcer shall be used to bring up the canopy and ridge line of the wings.

4. The attaching device shall be prong and clutch type. The prongs shall be located on the horizontal center line equidistant from each end and 1-1/4 inch + 0 - 1/8 inch (3.18 cm + 0 - 0.32 cm) apart for regular size badges and 3/4 inch + 0 - 1/8 inch (1.91 cm + 0 - 0.32 cm) apart for dress miniature size badges.

5. Dash No. -1 and -2 may be nickel or rhodium plated with a mirror-like polished finish which shall match TIOH Metal Finish Chip Number 16 for commercial sale only. For nickel or rhodium plated items, the silver plating requirements shall not apply.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodian:
Army - IH

Preparing activity:
Army - IH

Review activities:
DLA - CT

(Project No. 8455-0864)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T19:18Z
Check the source to verify that this is the current version before use.