MILITARY SPECIFICATION SHEET

BADGE, QUALIFICATION, COMBAT AND SPECIAL SKILL, TACTICAL AIR CONTROL PARTY

This specification is approved for use by all Departments and Agencies of the Department of Defense. The complete requirements for procuring the item(s) described herein shall consist of this document and the issue in effect of Specification MIL-B-3628.

MATERIAL: Red Brass or Nickel Silver

DIMENSIONS (INCHES): (Ref)
Width (overall): 1 5/8
Thickness (at wing): .120 ± .010

FINISH:
Nickel Plated (red brass only), silver plated, oxidized relieved matte finish.

NOTES:

1. Piercing shall be as shown.

2. A mock forcer may be used to bring up the detail on the wings.

3. The attaching device shall be the prong and clutch type. The prongs shall be located on the horizontal center line and centered on each wing. The prongs shall be hard soldered or fused to the reverse of the badge.

Custodian:
Army - IH
Air Force - 11
Review activities:
Air Force - 82,99
DLA - CT
User activities:
Air Force - 45

Preparing activity:
Army - IH

(Project No. 8455 - 0325)

AMSC NA 1 of 1 FSC 8455
DISTRIBUTION STATEMENT A. Approved for public release, distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T19:19Z
Check the source to verify that this is the current version before use.