MILITARY SPECIFICATION

EYEPIECE ASSEMBLY FOR AN/PAS-7

This specification is approved for use by USA Electronics Command, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the eyepiece assembly for Viewer, Infrared AN/PAS-7 (see 6.1).

2. APPLICABLE DOCUMENTS

2.1 Issues of documents. The following documents of the issue in effect on the date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

NN-P-71	- Pallet, Materials Handling, Wood Stringer Construction 2-Way and 4-Way (Partial)
QQ-S-781	- Strapping, Steel, Flat and Seals
PPP-B-585	- Boxes, Wood, Wirebound
PPP-B-601	- Boxes, Wood, Cleated-Plywood
PPP-B-621	- Boxes, Wood, Nailed and Lock Corner
PPP-B-636	- Boxes, Shipping, Fiberboard
PPP-B-640	- Boxes, Fiberboard, Corrugated, Triple Wall
PPP-C-843	- Cushioning Material, Cellulosic
PPP-F-320	- Fiberboard, Corrugated and Solid, Sheet Stock (Container Grade), and Cut Shapes
PPP-S-760	- Strapping, Nonmetallic, (and Connectors)
PPP-T-97	- Tape, Pressure-Sensitive Adhesive, Filament Reinforced

MILITARY

MIL-P-116	- Preservation-Packaging Methods of
MIL-B-121	- Barrier Material, Greaseproofed, Waterproofed, Flexible

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:58Z
Check the source to verify that this is the current version before use.

MIL-B-131	- Barrier Materials, Water Vaporproof, Flexible, Heat-Sealable
MIL-P-11268	- Parts, Materials, and Processes Used in Electronic Equipment
MIL-M-13231	- Marking of Electronic Items

STANDARDS

FEDERAL

FED-STD-356	- Commercial Packaging of Supplies and Equipment

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	- Marking for Shipment and Storage
MIL-STD-147	- Palletized and Containerized Unit Loads 40 Inch x 48 Inch Pallets, Skids, Runners, or Pallet Type Base
MIL-STD-171	- Finishing of Metal and Wood Surfaces
MIL-STD-252	- Classification of Visual and Mechanical Defects for Equipment, Electronic, Wired and Other Devices
MIL-STD-454	- Standard General Requirements for Electronic Equipment
MIL-STD-810	- Environmental Test Methods

DRAWINGS

ELECTRONICS COMMAND

DL-SM-B-774008	- Eyepiece Assembly

(Copies of specifications, standards, drawings and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Item definition. The eyepiece assembly, one of the components comprising the Viewer, Infrared AN/PAS-7, presents a magnified image of the cathode-ray tube display. The eyepiece assembly mounts on Viewer, Infrared SU-85/PAS-7, the handheld viewer portion of the Viewer, Infrared AN/PAS-7, and incorporates a provision for adjusting the focus of the eyepiece and an eyeshield with an automatic, internal light security shutter.

3.2 First article. When specified in the contract or purchase order, the contractor shall furnish first article units in accordance with 4.3, (see 6.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:58Z
Check the source to verify that this is the current version before use.

3.3 Construction. The eyepiece assembly shall be constructed in accordance with the drawings, parts list and other documents listed on USAECOM Drawing DL-SM-B-774008.

3.4 Material. Material shall be as specified herein and as shown on the applicable drawings. Material not specified, shall be selected by the contractor, shall be subject to all provisions of this specification and shall conform to MIL-P-11268.

3.5 Operational and environmental.

3.5.1 Eyepiece focus control. The manual eyepiece focus control shall adjust the focus to plus or minus 4 diopters minimum within 360° of rotation and shall have positive stops at each extreme of travel.

3.5.2 Index reference marker. Direction of focus shall be indicated by an index reference marker consisting of zero (0), plus (+), and minus (-) marks.

3.5.3 Visible light. No light shall be visible from the eyepiece assembly to a dark adapted observer in any direction from the eyepiece assembly.

3.5.4 Temperature.

3.5.4.1 Operating. Minus 32°C to plus 49°C.

3.5.4.2 Non-operating. Minus 62°C to plus 68°C.

3.5.5 Temperature shock. Minus 57°C plus 0°C, minus 1.5°C to plus 68°C, plus 1.5°C, minus 0°C within five minutes.

3.5.6 Vibration. The eyepiece assembly shall withstand vibratory displacement of 0.030 inch peak to peak minimum over a frequency range of 10 to 55 hertz (Hz).

3.5.7 Humidity. The eyepiece assembly shall experience no damage (see 6.3) or degradation of performance in an atmosphere with a minimum relative humidity of 93 percent.

3.5.8 Fungus. The eyepiece assembly shall show no more than six minute unrelated spots, each not greater than 0.015 square inch in an area of sparse microbial growth (see 6.3.2) as evidenced by growth colonization (see 6.3.3) which include branching (see 6.3.4) and sporulation (see 6.3.5) on or within each cubic foot, or fraction thereof, or equipment assembly volume. Isolated instances of partial tubular germination (see 6.3.6) shall be included in this evaluation.

3.6 Government furnished equipment. Unless otherwise specified in the contract or purchase order, there shall be no Government furnished equipment provided.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:58Z
Check the source to verify that this is the current version before use.

3.7 Treatment and painting. Unless otherwise specified, the metallic parts of the eyepiece assembly shall be given a treatment and painting per MIL-STD-171.

3.8 Marking. Unless otherwise specified, the eyepiece assembly and all components shall be marked per MIL-M-13231.

3.9 Workmanship. Unless otherwise specified workmanship of the eyepiece assembly shall conform to Requirement 9, MIL-STD-454.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Classification of inspection. The inspections specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).
c. Inspection of preparation for delivery (see 4.7).

4.3 First article inspection.

4.3.1 Inprocess inspection prescribed by a specification or drawing. Each lot of components and subassemblies shall have all parameters examined for defects in conformance with the inspection plan in the applicable specification or on the drawing. Defects not listed as major shall be classified as minor.

4.3.2 Examination. Each assembled eyepiece assembly shall be examined for defects in accordance with Table I. One or more defects shall be cause for rejection of that eyepiece assembly.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:58Z
Check the source to verify that this is the current version before use.

TABLE I. Examination.

Inspection	Requirement paragraph	Inspection criteria
Any part or component missing or damaged	3.3, 3.4	MIL-STD-252
Treatment and painting not as specified	3.7	MIL-STD-171
Markings not as specified or illegible	3.8	MIL-M-13231
Workmanship not as specifed	3.9	MIL-STD-454

4.3.3 Tests. Upon successful completion of the inprocess inspections and assembled examination specified in 4.3 the first article eyepiece assembly shall be subjected to the tests in Table II. Prior to start of tests, the eyepiece assembly shall be identified as to their applicable subgroups (see 6.2). Tests shall be conducted in the order listed. Failure of any test shall constitute first article failure.

TABLE II. First article inspection.

Inspection	Requirement paragraph	Test paragraph	Subgroup 1	Subgroup 2
Eyepiece focus control	3.5.1	4.6.1	X	
Index reference marker	3.5.2	4.6.2	X	
Visible light	3.5.3	4.6.3	X	
Temperature operating	3.5.4.1	4.6.4	X	
Temperature non-operating	3.5.4.2	4.6.4	X	
Temperature shock	3.5.5	4.6.5	X	
Vibration	3.5.6	4.6.6	X	
Humidity	3.5.7	4.6.7	X	
Fungus	3.5.8	4.6.8		X

4.4 Quality conformance inspection.

4.4.1 Inprocess inspection. Inprocess inspection on the eyepiece assembly shall be as specified in 4.3.1.

4.4.2 Examination. Each assembled eyepiece assembly shall be examined as specified in Table I. Presence of one or more defects shall be cause for rejection of that eyepiece assembly.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:58Z
Check the source to verify that this is the current version before use.

4.4.3 Tests.

4.4.3.1 Group A inspection. Following successful completion of the inprocess inspection and assembled examination of 4.4.1 and 4.4.2, each eyepiece assembly shall be tested in accordance with Table III in the order listed. Failure of any test shall be cause for rejection of that unit.

TABLE III. Group A inspection.

Inspection	Requirement paragraph	Test paragraph
Eyepiece focus control	3.5.1	4.6.1
Index reference marker	3.5.2	4.6.2

4.4.3.2 Group B inspection. Group B inspection shall be conducted on eyepiece assembly selected from units which have passed the tests in 4.4.3.1. Sampling of lots shall be in accordance with MIL-STD-105, AQL 2.5 percent defective, inspection level S-3 combined. Tests shall be conducted in accordance with Table IV.

TABLE IV. Group B inspection.

Inspection	Requirement paragraph	Test paragraph
Visible light	3.5.3	4.6.3

4.4.3.3 Group C inspection. Group C inspection shall be conducted on eyepiece assembly selected from units which have passed the tests in 4.4.3.1. The sample(s) shall be subjected to the inspections specified in Table V. Samples shall be selected in accordance with 4.4.3.3.1. Tests shall be performed in the order listed.

4.4.3.3.1 Sampling for Group C inspection.

4.4.3.3.1.1 Subgroup 1. For this subgroup 1 eyepiece assembly shall be selected from the first quality conformance inspection production lot. For subsequent Group C inspection 1 eyepiece assembly shall be selected every month from the monthly specified quantity (see 6.2).

4.4.3.3.1.2 Subgroup 2. For this subgroup 1 eyepiece assembly shall be selected from every sixth quality conformance inspection lot (see 6.2).

Source: https://assist.dla.mil -- Downloaded: 202610-26T03:58Z
Check the source to verify that this is the current version before use.

TABLE V. Group C Inspection.

Inspection	Requirement paragraph	Test paragraph
Subgroup 1		
Temperature operating	3.5.4.1	4.6.4
Temperature non-operating	3.5.4.2	4.6.4
Temperature shock	3.5.5	4.6.5
Vibration	3.5.6	4.6.6
Humidity	3.5.7	4.6.7
Subgroup 2		
Fungus	3.5.8	4.6.8

4.4.3.3.2 Group C failures. Actions required relative to Group C failures shall be as specified in the contract or order (see 6.2).

4.4.3.4 Reinspection of Group B and C sample units. Unless otherwise specified, sample units which have been subjected to and passed Group B and C inspection may be accepted on contract or order provided all damage is repaired and the units are resubjected to and pass Group A inspection.

4.5 Test methods. Tests required to determine compliance with the requirements of this specification shall be conducted in accordance with the test procedures specified herein. Unless otherwise specified all tests shall be run at +23°C, ± 3°C. (See 6.3)

4.6 Operational and environmental.

4.6.1 Eyepiece focus control. With the eyepiece assembly mated to a test fixture which simulates an image provided by the cathode-ray tube display, the eyepiece focus control shall be rotated to the + position, as indicated by the index reference marker, and the true diopter setting shall be measured with a diopter tester. The eyepiece focus control shall then be rotated to the - position, and the true diopter setting shall be measured. The range of rotation of the focus control, in degrees, from the + position to the - position shall be observed. Failure to comply with the requirements of 3.5.1 shall constitute a failure of this test.

4.6.2 Index reference marker. This test shall be performed during the performance of the eyepiece focus control test (see 4.6.1). It shall be observed whether the direction of focus is indicated correctly by the index reference marker. Failure to comply with the requirement of 3.5.2 shall constitute a failure of this test.

Source: https://assist.dla.mil -- Downloaded: 202610-26T03:58Z
Check the source to verify that this is the current version before use.

4.6.3 Visible light. The visible light test shall be conducted under a moonless nighttime condition (not more than 10^{-3} footcandles). An observer shall have 20/20 vision (vision corrected to 20/20 shall be acceptable), normal color vision, and shall undergo dark adaption for not less than 10 minutes prior to making the observation. With the eyepiece assembly mated to a test fixture which simulates the light output of the cathode-ray tube display, the eyepiece assembly shall be observed in all directions for visible light. With an observer's eye placed against a compressed eyeshield, it shall be observed in all directions whether light is visible from the eyepiece assembly. Failure to comply with the requirement of 3.5.3 shall constitute a failure of this test.

4.6.4 Temperature.

4.6.4.1 High temperature. The eyepiece assembly shall be subjected to test in accordance with Method 501, Procedure I of MIL-STD-810. Temperature for Step 2 shall be plus 68°C. Temperature for Step 4 shall be plus 49°C. Failure to operate or pass inspection of MIL-STD-810 shall constitute a failure of this test.

4.6.4.2 Low temperature. The eyepiece assembly shall be subjected to test in accordance with Method 502, Procedure I of MIL-STD-810. The temperature for Step 2 shall be minus 62°C and shall be maintained until temperature stabilization of the test item is reached. The temperature for Step 4 shall be minus 32°C. Failure to operate or pass inspection of MIL-STD-810 shall constitute a failure of this test.

4.6.5 Temperature shock. The eyepiece assembly shall be subjected to test in accordance with Method 503, Procedure I of MIL-STD-810. The maximum temperature for Steps 1 and 4 shall be plus 68°C. Failure to operate or pass inspection of MIL-STD-810 shall constitute a failure of this test.

4.6.6 Vibration. The eyepiece assembly shall be operated under standard conditions and a record made of all data necessary to determine compliance with required performance. These data shall provide the criteria for checking operational requirements of the eyepiece assembly at the conclusion of the vibration test. The eyepiece assembly shall be subjected to a simple harmonic motion having a vibratory displacement of 0.030 inch minimum peak to peak, with the frequency being changed in discrete steps of 1 Hz and maintained at least 10 seconds at each frequency over the frequency range of 10 to 55 hertz. Failure to operate shall constitute failure of this test.

4.6.7 Humidity. The eyepiece assembly shall be subjected to test in accordance with Method 507, Procedure II of MIL-STD-810. Failure to operate or pass inspection of MIL-STD-810 shall constitute failure of this test.

4.6.8 Fungus. The eyepiece assembly shall be subjected to test in accordance with Method 508, Procedure I of MIL-STD-810. Failure to comply with the requirement of 3.5.8 shall constitute a failure of this test.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:58Z
Check the source to verify that this is the current version before use.

4.7 Inspection of preparation for delivery. Preparation for delivery shall be inspected in accordance with MIL-P-116 to determine compliance to requirements of Section 5.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging. Preservation and packaging shall be level A, B or Commercial as specified (see 6.2).

5.1.1 Level A, maximum military protection.

5.1.1.1 Cleaning. Eyepiece assembly - Part of Viewer, Infrared, AN/PAS-7 shall be cleaned in accordance with process C-1 of MIL-P-116.

5.1.1.2 Drying. Eyepiece assembly - Part of Viewer, Infrared AN/PAS-7 shall be dried in accordance with the applicable procedure of MIL-P-116.

5.1.1.3 Preservation application. None required.

5.1.1.4 Unit packaging. Unit packaging shall be in accordance with the methods prescribed in MIL-P-116 as specified herein.

5.1.1.4.1 Technical literature. Each technical literature shall be packaged method IC-1.

5.1.1.4.2 Eyepiece Assembly - Part of Viewer, Infrared AN/PAS-7. Each unit shall be individually packaged method IA-8 as follows: Cushion each unit with material conforming to PPP-C-843, type II, 1/4 inch in thickness. Place the cushioned item within a barrier bag fabricated of material conforming to MIL-B-131, Class 2. Heat seal the closure, leaving a small opening for exhausting air. Exhaust the entrapped air and complete the seal. Place the sealed bag with contents within a close-fitting fiberboard box conforming to PPP-B-636, W5c. Place the technical literature, packaged as specified in 5.1.1.4.1, on top of the contents, directly under the lid of the box. Close the box in accordance with the appendix of the box specification.

5.1.2 Level B, minimum military protection.

5.1.2.1 Cleaning, drying and preservation application. Each eyepiece assembly - Part of Viewer, Infrared, AN/PAS-7 shall be cleaned, dried, preserved as specified in 5.1.1.1 through 5.1.1.3.

5.1.2.2 Unit packaging. Each eyepiece assembly - Part of Viewer, Infrared, AN/PAS-7 shall be individually packaged method IC-1 as follows: Cushion each unit with material conforming to PPP-C-843, type II, 1/4 inch in thickness. Place the cushioned item within a barrier bag fabricated of material conforming to MIL-B-121, type II. Heat seal the closure, leaving a small opening for exhausting air. Exhaust the entrapped air and complete the seal. Place the sealed bag with contents within a

Source: https://assist.dla.mil -- Downloaded: 202610-26T03:58Z
Check the source to verify that this is the current version before use.

close-fitting fiberboard box conforming to PPP-B-636, W5c. Place the technical literature, packaged as specified in 5.1.1.4.1, on top of the contents, directly under the lid of the box. Close the box in accordance with the appendix of the box specification.

5.1.3 Commercial packaging. Commercial packaging shall be in accordance with FED-STD-356.

5.2 Packing. Packing shall be level A, B or Commercial as specified (see 6.2). Shipping containers for level A and B shall be capable of stacking and supporting superimposed loads during shipment and storage without damaging the container(s) or its contents.

5.2.1 Level A, maximum military protection. A quantity of eyepiece assembly - Part of Viewer, Infrared, AN/PAS-7, packaged as specified in 5.1, shall be packed within a close-fitting fiberboard box conforming to PPP-B-636, type CF, class weather-resistant. Box closure shall be as specified in the appendix of the box specification. A quantity of the containers shall be packed within a close-fitting box conforming to PPP-B-601, overseas type; PPP-B-621, style 4, class 2; or PPP-B-585, style 2 or 3, class 3. When the gross weight exceeds 200 pounds, or the container length and width is 48 x 24 inches or more and the weight exceeds 100 pounds, 3 x 4 inch skids, laid flat shall be applied in accordance with the requirements of the container specification, or if not specified in the specification, in a manner which will adequately support the item and facilitate the use of material handling equipment. Closure and strapping shall be in accordance with the applicable container specification or appendix thereto except that metal strapping shall conform to QQ-S-781, type I, finish A.

5.2.1.1 Palletization. Palletization shall be required when: containers specified in 5.2.1 do not require skids; quantities per destination comprise a pallet load; and container size permits use of one of the pallet patterns of MIL-STD-147. A quantity of containers packed as specified in 5.2.1, except that container strapping may be omitted, shall be placed on a pallet, load type I, conforming to MIL-STD-147. The pallet shall be softwood conforming to NN-P-71, type IV, size 2. The load shall be "bonded" to the pallet by strapping conforming to QQ-S-781, type I finish A or shrink film.

5.2.2 Level B, minimum military protection. A quantity of eyepiece assembly - Part of Viewer, Infrared AN/PAS-7, packaged as specified in 5.1, shall be packed within a close-fitting fiberboard box conforming to PPP-B-636, type CF, class weather-resistant. Box closure shall be as specified in the appendix of the box specification. A quantity of the containers shall be packed within a close-fitting fiberboard box conforming to PPP-B-640, class 2, style E, or PPP-B-636, type CF, class weather-resistant, variety DW. The gross weight of boxes conforming to

Source: https://assist.dla.mil -- Downloaded: 202610-26T03:58Z
Check the source to verify that this is the current version before use.

PPP-B-640, shall not exceed 250 pounds. When the gross weight exceeds 200 pounds, or the container length and width is 48 x 24 inches or more and the weight exceeds 100 pounds, containers will be pallet-mounted on pallets conforming to NN-P-71, type IV. Closure shall be in accordance with the appendix of the applicable box specification. Reinforcing shall be by pressure-sensitive filament tape banding or nonmetallic strapping conforming to PPP-T-97 and PPP-S-760, respectively; selection of the material and application shall be in accordance with the appendix of the applicable box specification.

5.2.2.1 Palletization. Palletization shall be required when: containers specified in 5.2.2 do not require pallet mounting; quantities per destination comprise a pallet load; and container size permits use of one of the pallet patterns of MIL-STD-147. A quantity of containers packed as specified in 5.2.2, shall be placed on a pallet, load type I, conforming to MIL-STD-147. The pallet shall be softwood conforming to NN-P-71, type IV, size 2. A fiberboard cap shall be employed over the load having two sides extending down the stacked load at least 12 inches to accommodate marking requirements. The cap shall be fabricated of fiberboard conforming to PPP-F-320, class weather-resistant, W5s or V3c. The load shall be "bonded" to the pallet by strapping conforming to QQ-S-781, type I, finish A or shrink film.

5.2.3 Commercial packing. Commercial packing shall be in accordance with FED-STD-356.

5.3 Marking.

5.3.1 Military marking. In addition to any special marking required by the contract or order, interior packages and exterior shipping containers shall be marked in accordance with MIL-STD-129.

5.3.2 Commercial marking. In addition to any special marking required by the contract or order, interior packages and exterior shipping containers shall be marked in accordance with FED-STD-356.

6. NOTES

6.1 Intended use. The eyepiece assembly, when mated to Viewer, Infrared, SU-85/PAS-7, shall present to the operator a magnified image of the image displayed on the cathode-ray tube screen. The eyepiece assembly is designed specifically for use as part of Viewer, Infrared, AN/PAS-7.

6.2 Ordering data. Procurement documents should specify the following:

a. Title, number, and date of this specification.
b. Levels of preservation-packaging and packing required (see 5.1 and 5.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:58Z
Check the source to verify that this is the current version before use.

c. The necessary tests to verify compliance with the prohibition of radioactivity in optical elements.
d. When first article tests are to be conducted and the number of eyepiece assemblies in each subgroup (see 3.2, 4.3 and Table I). Time frame required for submission of first article test reports and time frame required for approval of first article test reports by the contracting officer.
e. Actions required related to Group C failures.

6.3 Definitions.

6.3.1 Damage. Breakage, loosening, shifting, evidence of corrosion, or failure of any finish, hardware, connection or component; leakage or condensation of moisture within the eyepiece; any degradation in input or output characteristics, and any failure of the focus control to perform its function.

6.3.2 Microbial growth. Microbial growth of very minute organisms. Such organisms when present in large numbers may provide a colony visible to the naked eye.

6.3.3 Growth colonization. Growth colonization is a mass of individual plants, generally of one species, living together; or a group of hyphae which is formed from one spore or cell and may be one individual plant. Colonization which completely covers the surface of the nutrient material constitutes abundant growth.

6.3.4 Branching. Branching is a connected arrangement of filaments (hyphae) formed by shoots on secondary stems growing from the main stem or filament (hypha).

6.3.5 Sporulation. Sporulation is the formation of minute unicellular reproductive or dormant bodies, called spores.

6.3.6 Tubular germination. Tubular germination is partial growth by the production of hyphae, which are tubular shaped fungal filaments. Tubular germination constitutes restricted individual spore growth not proceeding to colonization.

6.3.7 Room temperature. Room temperature is defined as +23°C, ± 3°C.

Custodian;
Army - EL

User activity:
Army - MU

Preparing activity:
Army - EL

Project No. 5855-A112

Source: https://assist.dla.mil -- Downloaded: 202610-26T03:58Z
Check the source to verify that this is the current version before use.

To detach this form, cut along this line

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION MIL-E-49084 EYEPIECE ASSEMBLY FOR AN/PAS-7

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1 JAN 66 1426

REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

ESC-FM 1068-68

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:58Z
Check the source to verify that this is the current version before use.

FOLD

Department of the Army
Headquarters
U.S.Army Electronics Command
Fort Monmouth, New Jersey 07703

POSTAGE AND FEES PAID

OFFICIAL BUSINESS

Commanding General
U.S.Army Electronics Command
ATTN: ~~XXXXXXX~~ DRSEL-RD-TS
Fort Monmouth, New Jersey 07703

FOLD

To detach this form, cut along this line

Source: https://assist.dla.mil -- Downloaded: 202610-26T03:58Z
Check the source to verify that this is the current version before use.