MILITARY SPECIFICATION

NAVIGATION SET, POSITION FIXING, LORAN AN/PSN-6( ) AND (UNITS OF)

This specification is approved for use by the Electronics Command, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense

1. SCOPE

1.1 This specification covers the following units of one type of LORAN Field Navigation Set which provides LORAN C/D navigation and position fixing in the field and is designated AN/PSN-6( ) (see 6.1 and 6.5):

Receiver, LORAN R-1897( )/PSN-6
Control-Indicator C-9547( )/PSN-6
Cable Assembly, Special Purpose, Electrical CX-12984( )/PSN-6
Antenna, AT-892( )/PRC-25 (See 6.2c)

1.2 This specification also covers the following AN/PSN-6( ) accessory unit: Cable Assembly, Special Purpose, Electrical CX-12985( )/PSN-6.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on the date of invitation for bids, or request for proposal form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

NN-P-71	Pallet, Material Handling, Wood, Stringer Construction, 2 Way and 4 Way (Partial)
QQ-S-781	Strapping, Steel, Flat and Seals
PPP-B-585	Box, Wood, Wirebound
PPP-B-601	Box, Wood, Cleated Plywood
PPP-B-621	Box, Wood, Nailed and Lock Corner
PPP-B-636	Box, Shipping, Fiberboard
PPP-B-640	Box, Fiberboard, Corrugated, Triple-wall
PPP-F-320	Fiberboard, Corrugated and Solid, Sheet Stock (Container Grade), and Cut Shapes
PPP-S-760	Strapping, Nonmetallic, (And Connectors)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:58Z
Check the source to verify that this is the current version before use.

PPP-T-97	Tape, Pressure-sensitive Adhesive, Filament Reinforced

MILITARY

MIL-P-116	Preservation packaging, Methods of
MIL-T-713	Twine, Impregnated, Lacing and Tying
MIL-S-901	Shock Tests, H.i. (High-impact); Shipboard Machinery, Equipment and Systems, Requirements for
MIL-P-11268	Parts, Materials and Processes Used in Electronic Equipment
MIL-M-13231	Marking of Electronic Items
MIL-F-14072	Finishes for Ground Signal Equipment
MIL-S-19500	Semiconductor Device, General Specification for
MIL-P-19644	Plastic Molding Material (Polystyrene Foam, Expanded Bead)
MIL-P-26514	Polyurethane Foam, Rigid or Plastic, for Packaging
MIL-P-55110	Printed Wiring Boards
MIL-C-55442	Cable Assemblies and Cord Assemblies, Packaging of
MIL-P-55640	Printed Wiring Boards, Multilayer (Plated-through Holes)

STANDARDS

FEDERAL

FED-STD-356	Commercial Packaging of Supplies and Equipment
FED-STD-595	Colors

MILITARY

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	Marking for Shipment and Storage
MIL-STD-147	Palletized and Containerized Unit Loads 40 inch x 48 inch Pallets, Skids, Runners or Pallet Type Base
MIL-STD-252	Classification of Visual and Mechanical Defects for Equipment, Electronic, Wired, and Other Devices

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:58Z
Check the source to verify that this is the current version before use.

MIL-STD-275	Printed Wiring for Electronic Equipment
MIL-STD-454	Standard General Requirements for Electronic Equipment
MIL-STD-461	Electromagnetic Interference Characteristics Requirements for Equipment
MIL-STD-462	Electromagnetic Interference Characteristics, Measurement of
MIL-STD-781	Reliability Tests, Exponential Distribution
MIL-STD-810	Environmental Test Methods

DRAWINGS

U. S. ARMY ELECTRONICS COMMAND

SC-DL-135893	Drawing and Data List for Antenna AT-892( )/PRC-25

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Description. - Navigation Set, Position Fixing, LORAN AN/PSN-6( ) is a man-portable unit which provides display of LORAN time differences (TD's) to a resolution of one-hundredth of a microsecond and position information in Universal Transverse Mercator (UTM) coordinates by automatically acquiring and tracking LORAN C and LORAN D radio frequency signals provided by ground transmitters. The AN/PSN-6( ) may be installed in a vehicle by securing it to Mount, Navigation Set MT-4717( )/PSN-6, which is part of Vehicle Mount Adapter Group OF-34( )/PSN-6.

3.2 Government-loaned property. - The Government will loan the contractor the following property to be used in testing:

a. One LORAN C (SS0) PROM pair.
b. One LORAN C (SS7) PROM pair - (Fort Benning coverage area).
c. One LORAN D (L-3) coverage area PROM pair.
d. One Packboard (NSN 8465-00-935-4732).
e. One Mod Kit, Packboard (NSN 8465-00-935-4737).

3.3 Construction. - The equipment shall be constructed in accordance with and be capable of meeting the requirements of this specification. Parts, materials and processes shall conform with specification MIL-P-11268.

Source: https://assist.dla.mil -- Downloaded: 2026\10-26T03:58Z
Check the source to verify that this is the current version before use.

3.4 First article samples. - The contractor shall furnish the specified number of First Article samples on order, as required by the invitation for bids and contract. (See 4.3 and 6.2).

3.5 Cleaning. - Cleaning shall comply with the requirements of MIL-P-11268 and requirement 9 of MIL-STD-454.

3.5.1 Parts. - Prior to the application of conformal coating, on those parts affected, and after fabrication, parts shall be cleaned in accordance with good commercial practice. Cleaning processes shall have no deleterious effect. Post cleaning assembly processes shall minimize handling by bare hands to prevent contamination by fungus nutrients. Corrosive material shall be removed completely prior to mounting the parts on chassis, panels and other parts.

3.5.2 Units. - After assembly, units shall be cleaned thoroughly and shall be free from particles of solder, flux and other foreign material. In addition, when necessary, such cleaning shall also be performed before final assembly of the units.

3.6 Weight and size.

3.6.1 Weight (See 4.17.1). - The total weight of the AN/PSN-6( ) shall not exceed 8.1 pounds. The weight of each unit comprising the AN/PSN-6( ) shall not exceed the following: 6.2 pounds for Receiver, LORAN R-1897( )/PSN-6; 1.1 pounds for Control Indicator C-9547( )/PSN-6; 0.4 pounds for Cable Assembly, Special Purpose, Electrical CX-12984( )/PSN-6; and 0.5 pounds for Antenna AT-892( )/PRC-25. The weight of accessory unit Cable Assembly, Special Purpose, Electrical CX-12985( )/PSN-6( ) shall be less than 1.2 pounds.

3.6.2 Size (See 4.17.2). - The dimensions of each of the units shall be as follows:

a. Receiver, LORAN R-1897( )/PSN-6:

Height - 6.32 $\pm$ 0.015 inches
Depth - 4.00 $\pm$ 0.015 inches
Width -10.12 $\pm$ 0.015 inches

b. Control-Indicator C-9547( )/PSN-6:

Height - 3.60 $\pm$ 0.015 inches
Depth - 2.38 $\pm$ 0.015 inches
Width - 4.94 $\pm$ 0.015 inches

Source: https://assist.dla.mil -- Downloaded: 202610-26T03:58Z
Check the source to verify that this is the current version before use.

c. Cable Assembly, Special Purpose, Electrical CX-12984( )/PSN-6 shall be 38.5 $\pm \frac{2}{0}$ inches in length.

d. Cable Assembly, Special Purpose, Electical CX-12985( )/PSN-6 shall be 60.8 $\pm \frac{2}{0}$ inches in length.

3.7 Controls (See 4.14). - All movable controls shall operate properly without binding or other undue restriction. Controls shall not be assembled in a misaligned condition.

3.8 Finish, protective (See 4.4). - The equipment shall be finished in accordance with MIL-F-14072. The final paint film on type I surfaces shall be semigloss olive drab enamel, Color No. X24087 of FED-STD-595.

3.9 Securing of parts (See 4.14).

3.9.1 General. - Brackets, lugs, inserts, bolts and others mounting arrangements shall retain items securely when subjected to specified service conditions.

3.9.2 Securing of parts by threaded fasteners. - Nylok or other screws and nuts with plastic devices and loctite or similar sealants shall not be subjected to temperatures in excess of 250°F (as during baking of paint). Loctite or similar sealants shall be applied in accordance with the manufacturer's instructions.

3.10 Marking (See 4.4).

3.10.1 General. - Marking shall conform to MIL-M-13231. Markings on exterior of case shall be in accordance with Group I of that specification.

3.10.2 Visibility. - Whenever practicable, parts, subassemblies and assemblies shall be so mounted that their identification markings will be readily visible with minimum disassembly of the unit(s).

3.10.3 Serial numbers. - The unit(s) listed in 1.1 with the exception of the antenna shall be serial numbered by means of nameplates or cable markers as applicable.

3.11 Soldering (See 4.14).

3.11.1 Soldering. - Soldering shall conform to Requirement 5 of MIL-STD-454.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:58Z
Check the source to verify that this is the current version before use.

3.11.2 Rosin-base residues. - Flux residues shall be removed. Mechanical means such as agitation, brushing, etc. may be used in conjunction with solvents. The cleaning solvents, and methods used, shall not have any deleterious effect on the parts, materials and assemblies being cleaned.

3.11.3 Process. - There shall be no sharp points or rough surfaces resulting from insufficient heating. The solder shall feather out to a thin edge, indicating proper flowing and wetting actions, and shall not be crystallized, overheated or underheated. The minimum necessary amount of flux and solder shall be used for electrical connections. Any means employed to remove an unavoidable excess of flux shall not incur the risk of loose particles of flux, brush bristles or other foreign material remaining in the unit(s), flux being spread over a larger area or damage to the unit. Insulation material that has been subjected to heating during the soldering operation shall be undamaged and parts fastened thereto shall not have become loosened.

3.12 Wiring, cabling, bonds and grounds (See 4.14).

3.12.1 Internal cabling. - Insulated wires shall be formed into cables, except where operation of the unit(s) would be adversely affected thereby or where it is physically impracticable as in the case where the resulting cables would be excessively large and would interfere with operation of maintenance. The cabling of wires shall be effected by tape or twine, conforming to MIL-T-713. Individual conductors thus secured shall lie essentially parallel; however, this does not prohibit the use of twisted pairs.

3.12.2 Slack. - Wires and cables shall be as short as practical, except that sufficient slack shall be provided for the following purposes:

a. To prevent undue stress on cable forms, wires and connections, including connections to resiliently supported parts.

b. To enable parts to be removed and replaced during servicing without disconnecting other parts.

c. To provide for at least two (2) replacements of the part to which the wire or cable is connected, except where uninsulated wires are used.

3.12.3 Protection. - Wires and cables shall be so placed and protected as to avoid contact, under specified service conditions, with rough or irregular surfaces or sharp edges.

Source: https://assist.dla.mil -- Downloaded: 202640-26T03:58Z
Check the source to verify that this is the currentversion before use.

3.12.4 Support. - Wire and cable shall be properly supported and secured to prevent undue stress on the conductors and terminals and undue change in position of the wire or cable:

a. During and after subjection of the unit(s) to specified service conditions, or

b. After service or repair of the unit(s) in the normal manner.

3.12.5 Clearance. - Clearance betweeen solder connections or bare conductors, on terminal boards, relays or other parts, shall be such that no accidental contact can occur between adjacent connections when subjected to specified service conditions.

3.12.6 Splicing. - Wires in a continuous run between two (2) terminals shall not be spliced during the wiring operation.

3.12.7 Connections, general. - Before being soldered to terminal lugs or fixed terminals, wires shall be mechanically secured so that the connections are not dependent for strength on solder alone. Where practicable, wires soldered to fixed terminals shall be looped at least one-half turn but not more than three-quarters turn around the terminal before soldering. Bared ends of wire leads to be terminated in solder-type terminal lugs shall be tinned, silver plated, or lead-alloy coated. No varnish, lacquer, inspection permit, or other coating shall be applied to completed electrical connections.

3.12.8 Bonds and grounds. - Mating surfaces requiring bonding for equipment current path returns and shock hazards shall be free of all anodic film, grease, paint, lacquer or other high resistance coatings from the immediate areas of contact. The D.C. resistance of bonds and grounds shall not exceed 2.5 milliohms. All panel mounted connectors and components and the panel mating surfaces shall be free of non-conductive finishes and provide positive bonding and grounding with mating connectors and equipment ground plane. The bonding D.C. resistance for all connectors and panel mounted components shall not exceed 2.5 milliohms.

3.13 Semiconductors (Transistors & Diodes) (See 4.4). - These electronic devices (semiconductors and diodes) shall conform to MIL-S-19500.

3.14 Service Conditions (See 4.8). - The unit(s) on order shall be capable of meeting the service conditions as specified herein.

Source: https://assist.dla.mil -- Downloaded: 202610-26T03:58Z
Check the source to verify that this is the currentversion before use.

3.14.1 Low temperature (See 4.8.1). - The equipment shall operate without degradation in specified performance at ambient temperature as low as -50°F and shall withstand prolonged storage at -70°F.

3.14.2 High temperature (See 4.8.2). - The equipment shall operate without degradation in specified performance at ambient temperature as high as 125°F plus the effects of solar radiation at a rate of 360 BTU/ft^2/hr., and shall withstand prolonged storage at 160°F.

3.14.3 Altitude (See 4.8.3). - The equipment shall operate without degradation in specified performance at altitudes to 10,000 feet above sea level, and shall withstand air transport at altitudes to 50,000 feet.

3.14.4 Humidity (See 4.8.4). - The equipment shall have the capability of operating without degradation in specified performance and shall sustain no physical damage during and after prolonged exposure to extreme high humidity levels as encountered in tropical areas.

3.14.5 Dust (See 4.8.5). - The equipment, in the operating mode, but not energized, shall withstand exposure to fine sand and dust particles with wind speeds of up to 20 knots.

3.14.6 Immersion (See 4.8.6). - The equipment shall be immersion proof to a covering depth of 3 feet of water for a period of not less than 2 hours.

3.14.7 Vibration (See 4.8.7).

3.14.7.1 Resonance, part I (See 4.8.7.1). - The equipment shall be free of damaging resonances at frequencies below 55 Hz.

3.14.7.2 Resonance, part II (See 4.8.7.2). - The equipment shall be free of damaging resonances at frequencies below 55 Hz while normally secured to Mount, Navigation Set MT-4717( )/PSN-6.

3.14.7.3 Vehicular transport (See 4.8.7.3). - The equipment shall be capable of withstanding the type of shock encountered during field transport, and shall show no evidence of physical or electrical degradation.

3.14.7.4 Vehicular bounce (See 4.8.7.4). - The equipment, while normally secured to Mount, Navigation Set MT-4717( )/PSN-6, shall be capable of withstanding the type of shock encountered in a vehicle

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:58Z
Check the source to verify that this is the current version before use.

moving across rough terrain and shall suffer no physical or electrical degradation.

3.14.8 Shock (See 4.8.8).

3.14.8.1 Bench handling (See 4.8.8.1). - The unit(s) shall be capable of withstanding bench handling as encountered in servicing.

3.14.8.2 Shock drop (See 4.8.8.2). - The equipment in the manpack configuration shall be capable of withstanding shocks normally encountered during the unloading and loading of equipment.

3.14.8.3 Ballistic shock (See 4.8.8.3). - The equipment installed within or upon armored vehicles shall be resistant to high level shock caused by ballistic impact, air explosions and similar field conditions.

3.14.9 Fungus (See 4.8.9). - The equipment, in the operating mode, but not energized, shall withstand exposure to fungus growth as encountered in tropical climates.

3.14.10 Salt fog (See 4.8.10). - The equipment, in the operating mode, but not energized, shall be capable of withstanding exposure to salt-sea atmosphere and shall show no evidence of corrosion as evidenced by any visible degradation that can be attributed to flaky, pitted, blistered or otherwise loosened finish or clogging or binding of moving parts. The unit(s) shall not be required to operate electrically.

3.14.11 Explosive atmosphere (See 4.8.11). - The equipment shall not cause ignition of an ambient explosive - gaseous mixture with air when operating in such an atmosphere.

3.14.12 Rain (See 4.8.12). - The equipment shall be capable of operating without degradation in specified performance and show no evidence of physical damage, during precipitation at variable rate to a total of 9.5 inches over a 12 hour period with intermittent wind speed to 35 knots.

3.14.13 Orientation (See 4.8.13). - The equipment shall operate satisfactorily at any orientation up to 90 degrees from normal operating position (forward, backward, left, or right).

3.15 Reliability (see 4.9). - The equipment shall have a specified MTBF (θo) of 1000 hours.

Source: https://assist.dla.mil -- Downloaded: 202640-26T03:58Z
Check the source to verify that this is the current version before use.

3.16 Electromagnetic interference (See 4.10). - The AN/PSN-6( ) with Mount, Navigation Set MT-4717( )/PSN-6 shall meet the following emission and susceptibility requirements of MIL-STD-461A, Notice 4:

CE 01		CS 01	RE02	RS02
CE 03		CS 02	RE02.1	(b) RS03
CE 04	(a)	CS 03		
CE 05	(a)	CS 04		
CE 06		CS 06		

(a) The frequency range for requirements CS03 and CS04 shall be 10 kHz to 20 MHz excluding the band of 80 kHz to 120 kHz. There shall be no degradation of performance or malfunction.

(b) The frequency range for requirement RS03 shall be 10 kHz to 1 GHz with the following field intensity levels:

.010 to 1.9 MHz	1 volt/meter
2 to 29.99 MHz	5 volt/meter
30 to 1000 MHz	10 volt/meter

3.17 Electrical, Receiver, LORAN R-1897( )/PSN-6 (See 4.11). - Unless otherwise specified, the receiver shall meet the requirements specified in 3.17.1 through 3.17.12 under standard test conditions with the equipment oriented in any direction.

3.17.1 Sensitivity (See 4.11.1). - The receiver shall automatically search, settle, track and readout the LORAN C/D time difference when the LORAN signal is 12 microvolts rms at the space coupling node and standard reference sampling point for both LORAN C and LORAN D.

3.17.1.1 Reaction time (See 4.11.1.1). - The reaction time for the receiver to go into track shall be as indicated in TABLE I.

3.17.1.2 Time Difference accuracy (See 4.11.1.2). - The time difference error of the receiver shall not exceed the values indicated in TABLE I for the 90% upper confidence limit (UCL) for both the mean time difference error and the standard deviation.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:58Z
Check the source to verify that this is the current version before use.

TABLE I. 12 uv Sensitivity.

LORAN Signal	S/N	Max. React Time	Max. UCL Mean Error	Max. UCL Std. Dev.
C	0dB	4.5 min	50 nsec	50 nsec
C	-14dB	12.0 min	80 nsec	170 nsec
D	-14dB	4.8 min	50 nsec	80 nsec
D	0dB	2.0 min	40 nsec	40 nsec

3.17.2 Sensitivity at minimum signal (See 4.11.2).

3.17.2.1 Reaction time (See 4.11.2.1). - The reaction time for the receiver to search, lock-on and track a 5 microvolt LORAN C signal without noise at the space coupling node and standard reference sampling point shall not exceed 12.0 minutes.

3.17.2.2 Time Difference accuracy (See 4.11.2.2). - The time difference error of the receiver when tracking at minimum signal shall not exceed 170 nanoseconds for the 90% upper confidence limit of the standard deviation time difference error or 80 nanoseconds for the 90% upper confidence limit of the mean time difference error.

3.17.3 Interference rejection (See 4.11.3). - The receiver shall be capable of operation when up to three non-synchronous signals and one synchronous interfering signal of up to +30dB and +10dB, respectively, above the desired LORAN signal are being received with the LORAN signal.

3.17.3.1 LORAN C interference rejection (See 4.11.3.1). - The receiver's reaction time to go into track shall not exceed 12 minutes. The 90% upper confidence limits for the mean and the standard deviation of the time difference error shall not exceed 80 nanoseconds and 240 nanoseconds respectively.

3.17.3.2 LORAN D interference rejection (See 4.11.3.2). - The receiver's reaction time to go into track shall not exceed 4.8 minutes. The 90% upper confidence limits for the mean and the standard deviation of the time difference error shall not exceed 50 nanoseconds and 70 nanoseconds respectively.

3.17.4 Differential signal amplitude (See 4.11.4). - The receiver shall be capable of specified performance when the differential signal amplitude between any two LORAN signals is 60dB.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:58Z
Check the source to verify that this is the current version before use.

3.17.5 Input signal range (See 4.11.5). - The receiver shall be capable of specified performance over an input signal range of 12 microvolts to 50 millivolts when the differential signal amplitude between any two LORAN signals does not exceed 60dB.

3.17.6 Input transient voltage (See 4.11.6). - The receiver shall not be damaged by transient voltages of 30 volts or less at the antenna terminal with individual transients not to exceed one millivolt second.

3.17.7 Constant velocity (See 4.11.7). - The receiver shall stay in track when subjected to constant velocities up to 140 Km/hr in the LORAN signal area.

3.17.8 Acceleration step response (See 4.11.8). - The receiver shall be capable of maintaining track when subjected to accelerations up to 0.7g for durations of at least 10 seconds. Within one minute after completion of the acceleration the receiver shall provide time differences to an accuracy of $\pm$0.3 microseconds.

3.17.9 Crossing rate signal (See 4.11.9). - The receiver's reaction time to go into track on a LORAN signal shall not exceed 5.0 minutes when one crossing rate signal of the same amplitude as the desired LORAN signal is present. The 90% upper confidence limit for the mean time difference error shall not exceed 50 nanoseconds.

3.17.10 Skywave signals.

3.17.10.1 LORAN C skywaves (See 4.11.10.1). - In the presence of skywaves having a minimum delay of 75 microseconds and an amplitude of up to 30dB over that of a desired LORAN C signal, the receiver shall go into track within 5 minutes and the 90% upper confidence limit of the mean time difference error shall not exceed 50 nanoseconds.

3.17.10.2 LORAN D skywaves (See 4.11.10.2). - In the presence of skywaves having a minimum delay of 65 microseconds and an amplitude equal to that of a desired LORAN D signal, the receiver shall go into track within 5 minutes and the 90% upper confidence limit of the mean time difference error shall not exceed 40 nanoseconds.

3.17.11 Reprogrammable memory (See 4.11.11). - The receiver shall have two replaceable PROMS containing, as a minimum, the LORAN chain constants and the program constants used in the tranformation from time differences to UTM coordinates. The PROMS shall be reprogrammable (non-destruct) type.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:58Z
Check the source to verify that this is the current version before use.

3.17.12 Time difference to UTM transformation (See 4.11.12). - The receiver shall automatically provide for transformation of LORAN time difference parameters to Universal Transverse Mercator coordinates over an area consisting of 16 UTM grid squares in a four by four array. The UTM output shall be updated at least once every 2.0 seconds and have a maximum error of 20 meters in the Northing and Easting components. The rms values for Northing and Easting errors for UTM in any four by four grid square array shall be less than 15 meters.

3.18 Electrical, Control-Indicator C-9547( )/PSN-6 (See 4.12). - Unless otherwise specified, the control-indicator shall meet the requirements specified under standard test conditions with the unit(s) oriented in any direction.

3.18.1 Display (See 4.12.1). - The control-indicator shall be compatible with the receiver and when connected to the receiver shall provide for the display of the data listed below by way of 3 alpha readouts and 8 numeric readouts.

a. TST (Alpha-Numeric Display Test).

b. SCH (Displays that the receiver is searching for the LORAN signal).

c. STL (Displays that the receiver is in the process of locking on the LORAN signal).

d. TRK (Displays that the receiver has locked on the LORAN signal).

e. U (Displays that the LORAN signal being displayed is unreliable or that TD's are outside the coverage area of the PROM's).

f. TDA (Displays the TDA of receiver position to a resolution of 0.01 microsecond).

g. TBA (Displays the TDB of receiver position to a resolution of 0.01 microsecond).

h. UTM (Displays the UTM coordinates of the receiver position to a resolution of 10 meters).

3.18.2 Dim control (See 4.12.2). - The control indicator shall contain a continuously adjustable dim control to provide a means of

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:58Z
Check the source to verify that this is the current version before use.

dimming the display increases from no light output to conserve battery power. At maximum brightness the display shall be readable in sunlight.

3.19 Input power (See 4.20).

3.19.1 Primary power. - The unit(s) shall perform as specified over a voltage range of 10 to 15 volts when operated from either one battery BA-4386( )/PRC-25 or the Vehicle Mount Adapter Group OF-34( )/PSN-6.

3.19.2 Power consumption. - The maximum power consumption for any AN/PSN-6( ) Navigation Set in the track mode with readout at maximum intensity shall not exceed 16 watts at 12.5 VDC at 70°F.

3.20 Burn-In (See 4.6). - Each unit on order shall be burned-in for a minimum of 48 hours (on-time), the last 24 hours (on-time) of which shall be failure free.

3.21 Antenna AT-892( )/PRC-25 (See 4.13). - Antenna AT-892( )/PRC-25 shall be constructed in accordance with SC-DL-135893, and shall meet the following requirements.

3.21.1 Leaf material temper (See 4.13.1). - The leaf material shall show no fracture and shall withstand straightening without breaking or fracturing of any leaf.

3.21.2 Antenna Base Flexure (See 4.13.2). - The base of the tape antenna shall withstand flexing without damage.

3.21.3 Antenna base support (See 4.13.3). - The end of the ferrule shall not drop more than 1/2 inch when a 1/2 pound downward pressure is applied.

3.22 Interchangeability (See 4.15). - Like units, assemblies, subassemblies, and replaceable parts shall conform to requirement 7 of MIL-STD-454 and shall be physically and functionally interchangeable. Items which are covered by specified electrical performance requirements shall meet specified performance requirements prior to installation into the unit(s). After installation of these items prior to submission of unit(s) for the quality performance tests, adjustments shall be made, if required to permit the unit(s) to meet full equipment specification requirements. Alteration of any items, or the unit(s), shall not be permitted.

3.23 Operational inspection (See 4.16). - Immediately prior to packaging and after applicable processes, inspections, and tests are

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:58Z
Check the source to verify that this is the current version before use.

completed each unit(s) shall be subjected to the operational inspection as specified herein.

3.24 Workmanship (See 4.14). - The equipment shall be manufactured and assembled in accordance with the following requirements and paragraphs herein:

MIL-STD-454	
Soldering	Requirement 5
Workmanship	Requirement 9
Paragraphs herein:	
Cleaning	3.5
Controls	3.7
Securing of parts	3.9
Soldering	3.11
Wiring, Cabling Bonds, and Grounds	3.12

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. - Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2 Classification of inspection. - Inspection shall be classified as follows:

a. First Article Inspection (does not include preparation for delivery). (See 4.3)

b. Inspection covered by subsidiary documents. (See 4.4)

Source: https://assist.dla.mil -- Downloaded: 202610-26T03:58Z
Check the source to verify that this is the current version before use.

c. Quality conformance inspection:

(1) Quality conformance inspection of equipment before preparation for delivery (See 4.5).

(2) Quality conformance inspection of preparation for delivery. (See 4.18 and 4.19)

4.3 First article inspection. - This inspection shall be performed by the contractor unless otherwise specified in the contract. It shall consist of the inspection specified in the subsidiary documents covering the items listed in 4.4, and the inspection specified for Groups A, B, C, and D (See Tables III, IV, V and VI respectively). The First Article inspection will normally be performed in the order indicated in Table II.

TABLE II. First Article Tests.

Requirement/ Paragraph	Test Paragraph	Sample Size 1 ea	1 ea	1 ea	1 ea	*
Subsidiary Documents, 3.8, 3.10, 3.13	4.4	1	1	1	1	1
Visual/Mechanical, 3.24	4.14	2	2	2	2	2
Burn-In, 3.20	4.6	3	3	3	3	3
Electrical Test, 3.17, 3.18	4.11, 4.12	4	4	4	4	4
Mechanical Interchangeability, 3.22	4.15	5	5			
Electrical Interchangeability, 3.22	4.15	6	6			
Weight, 3.6.1	4.17.1	7				
Size, 3.6.2	4.17.2	8				
Input Power, 3.19	4.20	9	7	5	5	5
Low Temperature, 3.14.1	4.8.1	10				
High Temperature, 3.14.2	4.8.2	11				

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:58Z
Check the source to verify that this is the current version before use.

TABLE II. - First Article Tests (Continued)

Requirement/ Paragraph	Test Paragraph	Sample, Size 1 ea	1 ea	1 ea	1 ea	*
Altitude, 3.14.3	4.8.3	12				
Resonance, Part I, 3.14.7.1	4.8.7.1	13				
Vehicular Transport, 3.14.7.3	4.8.7.3	14				
Ballistic Shock, 3.14.8.3	4.8.8.3	15				
Rain, 3.14.12	4.8.12	16				
Salt Fog, 3.14.10	4.8.10	17				
Orientation, 3.14.13	4.8.13		8			
Resonance, Part II, 3.14.7.2	4.8.7.2		9			
Bench Handling, 3.14.8.1	4.8.8.1		10			
Shock Drop, 3.14.8.2	4.8.8.2		11			
Immersion, 3.14.6	4.8.6		12			
Vehicular Bounce, 3.14.7.4	4.8.7.4		13			
Dust, 3.14.5	4.8.5		14			
Explosive Atmosphere,3.14.11	4.8.11		15			
Humidity, 3.14.4	4.8.4	18				
Fungus, 3.14.9	4.8.9				6	
EMI, 3.16	4.10			6		
Reliability, 3.15	4.9					6

*See Paragraph 4.9.1 and 4.9.2 for sample size.

Other First Article inspections may precede, follow, or be interspersed among the foregoing.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:58Z
Check the source to verify that this is the current version before use.

4.4 Inspection covered by subsidiary documents. - The following shall be inspected under the applicable subsidiary documents, as part of the inspection before preparation for delivery:

ITEM	WHERE REQUIRED
Finish, protective	3.8
Marking	3.10
Semiconductors (Transistors & Diodes)	3.13

4.5 Quality conformance inspection of equipment before preparation for delivery. - Each unit on order shall be subjected to Burn-In (See 3.20) prior to conformance inspection. The contractor shall perform the inspection specified in 4.4 and 4.5.1 thru 4.5.5. This does not relieve the contractor of his responsibility for performing any additional inspection which is necessary to control the quality of the product and to assure compliance with all specification requirements. Failure to meet any requirement as a result of Burn-In shall be classified as a defect and recorded as such. The Government, at its discretion, may perform all or any part of the specified inspection, to verify the contractor's compliance with specified requirements (See 6.6). Test equipment for Government verification inspection shall be made available by the contractor.

4.5.1 Group A inspection. - Each unit on order shall be inspected for conformance to all the inspection and test requirements of Table III. Each lot shall be subject to verification utilizing the procedures of MIL-STD-105, using the general inspection levels and the AQL's indicated in Table III. Group A inspection shall be performed in any order which is satisfactory to the Government, except that the operational inspection in 4.16 shall be last (See 6.4).

TABLE III. Group A Inspection.

Inspection	Req. Para.	Insp. Para.	AQL Major	AQL Minor
Visual and Mechanical				
Assemblies and Modules	3.24	4.14		
Analog Module Assy			1.0%	2.5%
Digital Circuit Timing Circuit Card Assy			1.0%	2.5%
Digital I/O Module Assy			1.0%	2.5%
Digital Processor Assy			1.0%	2.5%

Source: https://assist.dla.mil -- Downloaded: 202640-26T03:58Z
Check the source to verify that this is the current version before use.

TABLE III. Group A Inspection (Continued)

Inspection	Req. Para.	Insp. Para.	AQL Major	AQL Minor
Visual and Mechanical				
Preamp Circuit Card			1.0%	2.5%
Interconnect Circuit Card			1.0%	2.5%
Power Supply			1.0%	2.5%
Logic Module Assy			1.0%	2.5%
Diode Matrix and Display Assy			1.0%	2.5%
Decoder/Driver Assy			1.0%	2.5%
Control and Output Circuit Card Assy			1.0%	2.5%
Panel Assy			0.65%	2.5%
Receiver, LORAN R-1897( )/PSN-6 (less cover and modules)	3.24	4.14	0.65%	4.0%
Receiver, LORAN R-1897( )/PSN-6 (assembled)	3.24	4.14	1.0%	4.0%
Control-Indicator C-9547( )/PSN-6 (less panel)	3.24	4.14	0.65%	2.5%
Control-Indicator C-9547( )/PSN-6 (assembled)	3.24	4.14	1.0%	4.0%
Antenna AT-892( )/PRC-25	3.21.1 3.24	4.13.1 4.14	1.0%	4.0%
Cable Assy, Sp. Purpose Electrical CX-12984( )/PSN-6	3.24	4.14	1.0%	4.0%
Cable Assy, Sp. Purpose, Electrical CX-12985( )/PSN-6	3.24	4.14	1.0%	4.0%
Electrical				
Navigation Set, Position Fixing LORAN AN/PSN-6( ):			*1.0% for combined Group	
Power consumption	3.19.2	4.20.2		
Receiver, LORAN R-1897( )/PSN-6:			*1.0% for combined Group	
Sensitivity	3.17.1	4.11.1 (Test 1 only)		
Interference rejection	3.17.3.1	4.11.3.1		
Input signal range	3.17.5	4.11.5		
Time difference to UTM transformation	3.17.12	4.11.12		

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:58Z
Check the source to verify that this is the current version before use.

TABLE III. Group A Inspection (Continued)

Inspection	Req. Para.	Insp. Para.	AQL Major	AQL Minor
Control-Indicator C-9547( )/PSN-6:			*1.0% for combined Group	
Display	3.18.1	4.12.1		
Dim Control	3.18.2	4.12.2		
Operational Inspection:	3.23	4.16	0.1%	

*All electrical defects are considered major.

4.5.2 Group B inspection. - This inspection, including sampling, shall conform to Table IV and to the procedures for small sampling inspection of MIL-STD-105 using the special inspection levels. The AQL shall be 6.5 percent defective and the inspection level shall be SI for normal, tightened and reduced inspection. Group B inspection shall normally be performed on samples selected from units that have been subjected to and passed the Group A inspection.

4.5.2.1 Order of inspection within Group B. - Group B inspection shall be performed in any order which is satisfactory to the Government.

TABLE IV. Group B Inspection.

Inspection	Req. Para.	Insp. Para.	AQL
Mechanical Interchangeability	3.22	4.15	6.5%
Electrical Interchangeability	3.22	4.15	6.5%

4.5.3 Group C Inspection. - This inspection shall be as listed in Table V and shall be performed on sample unit(s) that have been subjected to and met Group A and B inspections. No defects shall be allowed. Sample unit(s) shall be selected in accordance with 4.5.3.1.

Source: https://assist.dla.mil -- Downloaded: 202610-26T03:58Z
Check the source to verify that this is the current version before use.

TABLE V. Group C Inspection.

Inspection	Req. Para.	Insp. Para.
Sub Group I		
Electrical, Receiver	3.17	4.11
Input Power	3.19	4.20
Sub Group II		
Weight	3.6.1	4.17.1
Size	3.6.2	4.17.2
Low Temperature	3.14.1	4.8.1
High Temperature	3.14.2	4.8.2
Altitude	3.14.3	4.8.3
Resonance, Part I	3.14.7.1	4.8.7.1
Vehicular Transport	3.14.7.3	4.8.7.3
Ballistic Shock	3.14.8.3	4.8.8.3
Rain	3.14.12	4.8.12
Salt Fog	3.14.10	4.8.10
Humidity	3.14.4	4.8.4
Sub Group III		
Orientation	3.14.13	4.8.13
Resonance, Part II	3.14.7.2	4.8.7.2
Bench Handling	3.14.8.1	4.8.8.1
Shock Drop	3.14.8.2	4.8.8.2
Immersion	3.14.6	4.8.6
Vehicular Bounce	3.14.7.4	4.8.7.4
Dust	3.14.5	4.8.5
Explosive Atmosphere	3.14.11	4.8.11
Antenna Base Flexure	3.21.2	4.13.2
Antenna Base Support	3.21.3	4.13.3
Fungus	3.14.9	4.8.9
Sub Group IV		
Electromagnetic Interference	3.16	4.10

4.5.3.1 Sampling for Group C inspection. - Units shall be selected at random for each group of inspections in Table V as specified in 4.5.1.1 thru 4.5.3.1.5. The first samples selected shall be at the start of the contract from the first quality conformance inspection production

Source: https://assist.dla.mil -- Downloaded: 202610-26T03:58Z
Check the source to verify that this is the current version before use.

lot(s). Selection of samples shall be as specified. Within 60 calendar days after selection, the samples shall have been subjected to and completed the Group C inspections. (See 6.3)

4.5.3.1.1 Subgroup I. - For this subgroup, two units from the first production units (up to 50 units) shall be selected for the first Group C inspection. For subsequent inspection, two units every 12 months shall be selected.

4.5.3.1.2 Subgroup II. - For this subgroup, one unit (this unit may be the unit selected for above Subgroup I), from the first production units (up to 50 units) shall be selected for the first Group C inspection. For subsequent Group C inspection, one unit every 12 months shall be selected.

4.5.3.1.3 Subgroup III. - For this subgroup, one unit from the first production units (up to 50 units) shall be selected for the first Group C inspection. For subsequent Group C inspection, one unit every 12 months shall be selected.

4.5.3.1.4 Subgroup IV. - For this subgroup, one (1) unit from the first fifty (50) production units shall be selected for the first Group C inspection. For subsequent Group C inspections, one (1) unit shall be selected from each 100 units produced. This unit shall not have been subjected to 4.5.3.1.1 to 4.5.3.1.3.

4.5.3.2 Non-compliance. - In case of Group C failure occurrence, procedures and requirements specified in the contract shall be followed.

4.5.4 Group D inspection. - Group D inspection shall consist of the Reliability tests specified in 4.9 and shall be performed on units from lots which have been subjected to and passed Group A and Group B inspection.

TABLE VI. Group D Inspection.

Inspection	Req. Para.	Insp. Para.
Reliability	3.15	4.9

4.5.4.1 Sampling for Group D inspection. - A maximum of five equipments shall be selected at random from the first production lot. For subsequent Group D inspection, a maximum of five equipments shall be selected at random from each production lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:58Z
Check the source to verify that this is the current version before use.

4.5.4.2 Non-compliance. - In case of Group D failure occurrence, procedures and requirements specified in the contract shall be followed.

4.5.5 Reinspection of conforming Group C and Group D sample units .- Unless otherwise specified, sample units which have been subjected to and passed Group C and Group D inspection may be accepted on the contract or purchase order, provided all damage is repaired and the units are cleaned of all foreign matter and are resubjected to and pass Group A inspection.

4.6 Burn-in (See 3.20). - Each unit shall be subjected to a minimum 48-hour (on time) burn-in period, the last 24 hours (on time) of which shall be failure free. This test shall consist of a two-hour "OFF" period and a six-hour "ON" period. The burn-in shall be accomplished in accordance with Test Level E of MIL-STD-781B except that the temperature limits shall be -50°F and +155°F and input voltage cycling shall be in accordance with paragraph 5.2.4 thereof. Failures shall be recorded and analyzed, but shall not be considered relevant for computation of equipment MTBF. A failure shall be as defined in 4.9.4 herein.

4.7 Standard test conditions. - Unless otherwise specified, inspections shall be performed at room temperature and humidity.

4.7.1 Standard test signal. - The standard LORAN C/D test signal necessary for test of the AN/PSN-6( ) shall be the signal generated by the LORAN C/D Simulator as approved by the contracting officer.

4.8 Service conditions (See 3.14). . - Unless otherwise specified, the service condition tests shall be conducted in accordance with MIL-STD-810. No defects shall be allowed. Visual and electrical performance tests are required before, during and after each environmental condition test as indicated in TABLE VII and TABLE VIII.

4.8.1 Low temperature. - The unit(s) shall be tested in accordance with Method 502, Procedure I. The storage temperature (Step 2) shall be -70°F and shall be maintained for a period of not less than 2 hours following stabilization of the test item. Low operating temperature (Step 4) shall be -46°C (-50°F). Power to the equipment shall be provided as necessary to check operation. (Note: The battery is not required to withstand the same test environment as the equipment). This is for the purpose of determining compliance with 3.14.1.

4.8.2 High temperature. - The unit(s) shall be subjected to a temperature extreme of 160°F, both operating and non-operating. This test shall be performed in accordance with Method 501, Procedure II to determine compliance with 3.14.2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:58Z
Check the source to verify that this is the current version before use.

4.8.3 Altitude. - The unit(s) shall be subjected to an altitude of 50,000 feet above sea level non-operating, and 10,000 feet above sea level operating. This test shall be performed in accordance with Method 500, Procedure I to determine compliance with 3.14.3.

4.8.4 Humidity. - The unit(s) shall be subjected to the test of Method 507, Procedure III. In Step 7 of Procedure III, the chassis shall be removed from its enclosure or the test item shall be otherwise opened so as to expose the normally sealed areas to the chamber environment. In Step 6, measurements shall be taken during the last 5 hours of the last cycle. This test will be performed to determine compliance with 3.14.4.

4.8.5 Dust. - The unit(s) shall be subjected to the test of Method 510, Procedure I. This test shall be performed to determine compliance with 3.14.5.

4.8.6 Immersion. - The unit(s) shall be subjected to the test of Method 512, Procedure I. This test shall be performed in order to determine compliance with 3.14.6.

4.8.7 Vibration.

4.8.7.1 Resonance, part I. - The unit(s) shall be subjected to the test of Method 514, Procedure XI, Part 1. This test shall be performed in order to determine compliance with 3.14.7.1.

4.8.7.2 Resonance, part II. - The unit(s), mounted to the MT-4717( )/PSN-6, shall be subjected to the test of Method 514, Procedure IX, Part 1. This test shall be performed in order to determine compliance with 3.14.7.2.

4.8.7.3 Vehicular transport. - The unit(s) shall be subjected to the test of Method 514, Procedure XI, Part 2. This test shall be performed in order to determine compliance with 3.14.7.3.

4.8.7.4 Vehicular bounce. - The unit(s), mounted to the MT-4717( )/PSN-6, shall be subjected to the test of Method 514, Procedure IX, Part 2. This test shall be performed in order to determine compliance with 3.14.7.4.

4.8.8 Shock.

4.8.8.1 Bench handling. - The unit(s) shall be subjected to the test of Method 516, Procedure V. This test shall be performed in order to determine compliance with 3.14.8.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:58Z
Check the source to verify that this is the current version before use.

4.8.8.2 Shock drop. - The equipment mounted on the backpack harness (comprised of Packboard, NSN 8465-00-935-4732, and Mod Kit, Packboard, NSN 8465-00-935-4737) shall be subjected to the test of Method 516.1, Procedure II. This test shall be performed to determine compliance with 3.14.8.2.

4.8.8.3 Ballistic shock. - The unit(s), mounted to the MT-4717( )/PSN-6, shall be subjected to the test of MIL-S-901, for Type A, lightweight equipment in order to determine compliance with 3.14.8.3.

4.8.9 Fungus. - The unit(s) shall be subjected to the test of Method 508, Procedure I. Operation of the unit(s) is not required, but examination at the conclusion of the exposure period shall reveal no evidence of viable fungus on any surface. This test shall be performed in order to determine compliance with 3.14.9.

4.8.10 Salt fog. - The unit(s), mounted to the MT-4717( )/PSN-6, shall be subjected to the test of Method 509, Procedure I. The unit(s) shall not be required to operate electrically. All external moveable controls, access covers, and the test buttons shall be operable mechanically. Failure criteria will also include corrosion of finishes and metals, which shall be defined as any visible degradation of the equipment surface that can be attributed to flakey, pitted, blistered, or otherwise loosened finish, or metal surface. This test shall be performed to determine compliance with 3.14.10.

4.8.11 Explosive atmosphere. - The unit(s) either taken one at a time or in any combination thereof, shall be tested in accordance with Method 511, Procedure I in order to determine compliance with 3.14.11.

4.8.12 Rain. - The unit(s) shall be subjected to the test of Method 506, Procedure I. During each 30 minute rain period, the wind shall be maintained for 15 minutes, commencing 5 minutes after the start of the period, as specified in the procedure. The unit(s) need only be operated during the last 10 minutes of the 30 minute period. This test shall be performed to determine compliance with 3.14.12.

4.8.13 Orientation. - The unit(s) shall be inclined for a minimum of 5 minutes in each plane (forward, backward, left, and right) to an angle of 90 $\pm$ 3 degrees. During inclination in each plane, the unit(s) shall meet the operational performance requirements of 3.17.1. This test shall be performed to determine compliance with 3.14.13.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:58Z
Check the source to verify that this is the current version before use.

TABLE VII. Electrical Test Parameters Applicable to Service Condition Inspections.

Type of Test	Parameters to be Measured	Insp. Para.
Type I	Reaction time	4.11.1.1(Test II only)
	Interference rejection	4.11.3.1(Test II only)
Type II	Reaction time	4.11.1.1(Test II only)
	Time difference to UTM transformation	4.11.12
	Power consumption	4.20.2

TABLE VIII. Electrical and Visual Tests Applicable to Service Condition Inspections.

Service Condition		Applicable Electrical/Visual Tests		
Description	Insp. para.	Before	During	After
Low temperature	4.8.1	I	II	I/Visual
High temperature	4.8.2	I	II	I/Visual
Altitude	4.8.3	I	II	I/Visual
Humidity	4.8.4	I	II	I/Visual
Dust	4.8.5	I	--	I/Visual
Immersion	4.8.6	Visual	--	Visual
Vibration	4.8.7.1	I	Visual	I/Visual
	4.8.7.2	I	Visual	I/Visual
	4.8.7.3	I	--	I/Visual
	4.8.7.4	I	--	I/Visual
Shock	4.8.8.1	I/Visual	--	I/Visual
	4.8.8.2	I/Visual	--	I/Visual
	4.8.8.3	I	--	I/Visual
Fungus	4.8.9	Visual	Visual	Visual
Salt Fog	4.8.10	Visual	--	Visual
Explosive Atmosphere	4.8.11	I	Move Controls/ Switches	--
Rain	4.8.12	I	II	I/Visual
Orientation	4.8.13	I	II	--

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:58Z
Check the source to verify that this is the current version before use.

4.9 Reliability (See 3.15).

4.9.1 First article reliability test. - The contractor shall perform a reliability qualification test in accordance with Test Plan IV of MIL-STD-781. The specified MTBF (θo) shall be met when tested under conditions of Test Level C of MIL-STD-781 while the equipment is operated in the UTM mode. A maximum of five equipments shall be randomly selected for reliability testing from the First Article lot.

4.9.2 Reliability production test. - The contractor shall perform a reliability production test on each lot in accordance with Test Plan IVa of MIL-STD-781. The specified MTBF (θo) shall be met when tested under conditions of Test Level C of MIL-STD-781 while the equipment is operated in the UTM mode. The maximum number of equipments used for this test shall be five. For reliability production tests, a lot is defined as three months production or fifty units, whichever comes first.

4.9.3 Thermal survey. - Prior to burn-in and reliability testing, a thermal survey, in accordance with paragraph 5.1.5 of MIL-STD-781 shall be performed.

4.9.4 Failure definition. - A failure is defined as the inability of the equipment to perform its required function. This includes any event which causes departure from performance as required by this specification, or the contractor's approved test procedures. Paragraphs 5.5 through 5.10 inclusive of MIL-STD-781 shall apply. The types failures and required actions shall be in accordance with paragraph 5.5.1 of MIL-STD-781. Determination of compliance shall be in accordance with paragraph 5.4.8 of MIL-STD-781.

4.9.5 Parameters to be measured. - The following parameters are to be measured and recorded daily in accordance with paragraph 5.4.6 of MIL-STD-781: TDA accuracy, TDB accuracy, UTM accuracy and power consumption.

4.9.6 Rework and retest provisions. - Once a reject decision has been reached, no rerun can be made of that test on the same or a new sample from the same lot, unless positive action, consisting of design change, modification, or rework actually relating to observed failures, has been applied to the lot. Any subsequent rerun must start at zero hours operating time.

4.10 Electromagnetic interference. - The AN/PSN-6( ), as mounted with Mount Navigation Set MT-4719( )/PSN-6 shall be tested for compliance with the requirements of 3.16 using the measurement techniques of MIL-STD-462, Notice 3. To demonstrate compliance with requirement RS03 the equipment shall be tested as an unsheltered unit. Test Methods CS03 and

Source: https://assist.dla.mil -- Downloaded: 202640-26T03:58Z
Check the source to verify that this is the currentversion before use.

CS04 shall be performed over the 10 KHz to 20 MHz frequency range excluding the band of 80 KHz to 120 KHz. For Method CS04 a signal level of -13 DBMW, 80 DB above system sensitivity (-93 DBMW) shall be used. Degradation of performance or malfunction for all susceptability testing shall be defined as follows:

a. The 90% upper confidence limits (UCL's) of the mean time difference (TD) error and the standard deviation of the TD error shall not exceed $\pm$ .050 microseconds during any susceptibility test. Twenty-five readings shall be taken to demonstrate that the 90% UCL of the performance of the equipment is within specification requirements.

b. Time in excess of 4.5 minutes for the equipment to go into track shall be considered a susceptible condition.

4.11 Electrical, Receiver, LORAN R-1897( )/PSN-6 (See 3.17).

4.11.1 Sensitivity (See 3.17.1). - The sensitivity shall be measured in terms of lock-on reaction time and the accuracy of the readout of the Slave A signal with a LORAN simulator set up as indicated in TABLE IX.

4.11.1.1 Reaction time (See 3.17.1.1). - Reaction time is the time for the receiver to attain track after power turn on. Three reaction time tests as indicated in TABLE VII shall be conducted during which search and settle shall be recorded. Not less than 8 out of ten reaction times with limits not to exceed those specified shall be obtained for each of the three tests.

4.11.1.2 Time difference accuracy (See 3.17.1.2). - Three tests as indicated in TABLE VII shall be performed to demonstrate the receiver's time difference accuracy. Five minutes after the receiver goes into track, TDA readings shall be taken every 75 seconds for 25 readings. The calculated 90% upper confidence limits for both the mean and standard deviation time difference error shall not exceed the specified limits.

TABLE IX. 12 uv Sensitivity Tests.

	Test I	Test II	Test III	Test IV
LORAN Signal				
LORAN	C	C	D	D
PRI	100,000 usec	100,000 usec	39,700 usec	39,700 usec
TDA	40,125 usec	40,125 usec	12,125 usec	12,125 usec

Source: https://assist.dla.mil -- Downloaded: 202610-26T03:58Z
Check the source to verify that this is the current version before use.

TABLE IX. 12 uv Sensitivity Tests (Continued)

	Test I	Test II	Test III	Test IV
LORAN Signal				
TDB	60,125 us	60,125 usec	24,125 usec	24,125 usec
Slave A	12 uv	12 uv	12 uv	12 uv
Slave B	120 uv	120 uv	120 uv	120 uv
Master	120 uv	120 uv	120 uv	120 uv
S/N	0 dB	-14 dB	-14 dB	0 dB
Performance				
Max Reaction Time	4.5 min	12.0 min	4.8 min	2.0 min
Max UCL Mean Error	50 nsec	80 nsec	50 nsec	40 nsec
Max UCL Std. Dev.	50 nsec	170 nsec	80 nsec	40 nsec

NOTE: The PROM's to be used for the tests in TABLE IX are to be Government loaned equipment. The PROM's to be used for the LORAN C test are identified as the LORAN C (SSO) PROM pair. The PROM to be used for the LORAN D tests is identified as the LORAN D (L-3) PROM pair.

4.11.2 Sensitivity at minimum signal (See 3.17.2). - The sensitivity for minimum LORAN C signal shall be measured in terms of lock-on reaction time and the accuracy of TDA with the LORAN simulator set up as for Test I of TABLE IX except that there shall be no noise and the Slave A signal shall be 5 microvolts and the Master and Slave B signals shall be 50 microvolts.

4.11.2.1 Reaction time (See 3.17.2.1). - The reaction time under minimum signal conditions shall be tested ten times. Eight reaction times shall not exceed 12.0 minutes.

4.11.2.2 Time difference accuracy (See 3.17.2.2). - TDA readings shall be taken every 75 seconds starting 5 minutes after going into track. Twenty-five readings shall be taken. The calculated 90% upper confidence limit of the standard deviation of the TDA error shall not exceed 170 nanoseconds and the 90% upper confidence limit of the mean time difference error shall not exceed 80 nanoseconds.

Source: https://assist.dla.mil -- Downloaded: 202610-26T03:58Z
Check the source to verify that this is the current version before use.

4.11.3 Interference rejection (See 3.17.3). - Three interfering non-synchronous signals and one interfering synchronous signal of +30dB and +10dB, respectively, above the desired LORAN signal shall be applied to the input of the receiver with the LORAN signal.

4.11.3.1 LORAN C interference rejection (See 3.17.3.1). - The LORAN signal of Test II of TABLE IX shall be used. The receiver reaction time to go into track shall not exceed 12 minutes. Five minutes after the receiver goes into track, TDA readings shall be taken every 75 seconds for 25 readings. The calculated 90% upper confidence limits of the mean and the standard deviation of the time difference error shall not exceed 80 nanoseconds and 240 nanoseconds respectively.

4.11.3.2 LORAN D interference rejection (See 3.17.3.2). - The signal of Test III of TABLE IX shall be used, except that the amplitude of the Master and Slave B shall be 500 microvolts and the amplitude of Slave A shall be 50 microvolts. The receiver time to go into track shall not exceed 4.8 minutes. Five minutes after the receiver goes into track, TDA readings shall be taken every 75 seconds for 25 readings. The calculated 90% upper confidence limits for the mean and the standard deviation of the time difference error shall not exceed 50 nanoseconds and 70 nanoseconds respectively.

4.11.4 Differential signal amplitude (See 3.17.4). - A LORAN signal as given by Test I of TABLE IX shall be used except that the amplitude of the Master and Slave B signals shall be 12 millivolts. The receiver shall go into track within 4.5 minutes. Five minutes after the receiver is in track, TDA readings shall be taken every 75 seconds for 25 readings. The calculated 90% upper confidence limit of the mean time difference error shall not exceed 50 nanoseconds.

4.11.5 Input signal range (See 3.17.5). - A LORAN signal as given by Test I of TABLE IX shall be used except that the amplitude of the Master and Slave B signals shall be 50 millivolts and the amplitude of the Slave A signal shall be 50 microvolts. The receiver shall go into track within 4.5 minutes. Five minutes after the receiver goes into track, TDA readings shall be taken every 75 seconds for 25 readings. The calculated 90% upper confidence limit of the mean confidence limit of the mean time difference error shall not exceed 50 nanoseconds.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:58Z
Check the source to verify that this is the current version before use.

4.11.6 Input transient voltage (See 3.17.6). - Four consecutive one millivolt second transient pulses shall be applied to the receiver antenna terminal. The applied voltages shall be 1, 10, 20, and 30 volts. The time between the pulses is not critical, and the receiver shall be off. After the 4 pulses have been applied, the set shall be operated, with the applied LORAN C signal as depicted in Table IX, Test I, except that there shall be no noise. For not less than 8 out of 10 tests, the reaction time to go into track shall not exceed 4.5 minutes.

4.11.7 Constant velocity (See 3.17.7). - The capability to stay in track during constant velocity shall be demonstrated using a LORAN C signal as given by Test I of TABLE IX, except that the signal to noise ratio shall be -6dB. TDA's shall be increased in 0.5 microsecond steps at approximate 3 second intervals for 45 seconds. (15 Steps) The receiver shall remain locked and in track and shall indicate a TDA of 40,132.5 $\pm$ 0.3 us within one minute after completion of the last step.

4.11.8 Acceleration step response (See 3.18.8). - The capability of the receiver to maintain track during a 0.7g acceleration shall be demonstrated using a LORAN C signal as given by Test I of TABLE IX, except that the signal to noise ratio shall be -8dB and the Slave A signal shall be 50 microvolts. At end of each of 5 successive two second intervals during a 10 second period, the TDA shall be increased by 0.1, 0.3, 0.7, 1.2, and 2.1 microsecond steps respectively. The receiver shall remain locked and provide a TDA output of 40,129.4 $\pm$ 0.3 microseconds within one minute after completion of the last step.

4.11.9 Crossing rate signal (See 3.17.9). - A LORAN C signal as given in Test I of TABLE IX and a similar crossing signal with a PRI of 99,900 microseconds and Slave A amplitude of 120 microvolts shall be simultaneously applied to the input of the receiver. The receiver shall go into track within 5 minutes. Five minutes after the receiver goes into track, TDA readings shall be taken every 75 seconds for 25 readings. The calculated 90% upper confidence limit for mean time difference error shall not exceed 50 nanoseconds.

4.11.10 Skywave signals (See 3.17.10). - The conditions given in TABLE X shall be used to simulate a skywave environment.

Source: https://assist.dla.mil -- Downloaded: 202640-26T03:58Z
Check the source to verify that this is the current version before use.

TABLE X. Skywave Signals Tests.

	Test I	Test II	Test III
LORAN	C	C	D
PRI	100,000 usec	100,000 usec	39,700 usec
TDA	40,125 usec	40,125 usec	12,125 usec
TDB	60,125 usec	60,125 usec	24,125 usec
Master	50 uv	50 uv	50 uv
Slave A	50 uv	50 uv	50 uv
Slave B	50 uv	75 uv	50 uv
Skywave A	160 uv (+10 dB)	1600 uv (+30 dB)	50 uv
Skywave A Delay	50 usec	75 usec	65 usec

4.11.10.1 LORAN C skywaves (See 3.17.10.1). - The signals of tests I and II of TABLE X shall be applied to the antenna terminal of the receiver to demonstrate that the receiver operates in the presence of LORAN C skywaves. The receiver shall go into track within 5 minutes. Five minutes after the receiver goes into track, TDA readings shall be taken every 75 seconds for 25 readings. The calculated 90% upper confidence limit for the mean time difference error shall not exceed 50 nanoseconds.

4.11.10.2 LORAN D skywaves (See 3.17.10.2). - The signals of Test III of TABLE X shall be applied to the antenna terminal of the receiver to demonstrate that the receiver operates in the presence of LORAN D skywaves. The receiver shall go into track within 5 minutes. Five minutes after the receiver goes into track, TDA readings shall be taken every 75 seconds for 25 readings. The calculated 90% upper confidence limit for the mean time difference error shall not exceed 40 nanoseconds.

4.11.11 Reprogrammable Memory (See 3.17.11). - A PROM programmer (e.g., MX-9643/PSN-6 or equivalent) shall be used to demonstrate that the PROM's are reprogrammable by erasing the program in the PROM and then reprogramming and verifying the PROM's for a different grid location.

4.11.12 Time difference to UTM transformation (See 3.17.12). - Using a simulated LORAN C signal with 1 millivolt signals for Master and Slaves A and B, a PRI of 99,300 microseconds, and no noise, the

Source: https://assist.dla.mil -- Downloaded: 202640-26T03:58Z
Check the source to verify that this is the current version before use.

TDA's and TDB's of TABLE XI shall be sequentially provided to the receiver in UTM mode and containing Government loaned PROM's indentified as the Fort Benning, Georgia coverage area PROM's (SS7). The receiver shall provide the theoretical UTM coordinates with a maximum error of 20 meters in the Northing and Easting components. The calculated rms values of the error of the Northing and Easting components shall be less than 15 meters.

TABLE XI. Time difference to UTM transformation.

GRIDS	TDA	TDB	THEORETICAL UTM
1	13,676	69,020	FL2490:2483
2	13,899	69,586	GL7991:4983
3	13,337	69,386	FK7481:2501
4	14,068	68,995	FM7483:2480
5	14,398	68,738	FN7472:2491
6	13,311	69,794	GK7986:0989
7	14,169	69,355	GM5983:2487
8	14,399	69,932	GN0983:0988
9	13,318	69,846	KE1972:0995
10	14,125	69,702	KF5991:8992
11	13,514	70,279	LE4101:3121
12	14,118	70,207	LF5982:5079
13	14,591	70,012	LG5910:5962
14	14,799	69,910	LH6216:1180
15	14,235	69,811	KG9136:0434
16	14,643	69,556	KH8969:1223

4.12 Electrical, Control-Indicator C-9547( )/PSN-6.

4.12.1 Display (See 3.18.1). - The control-indicator shall be cycled through the following modes to verify that all functions are displayed: TST, TDA, TDB and UTM. The SCH, STL and TRK displays shall be verified by immediately switching to the TDA mode after the control-indicator is energized. The U display shall be verified by removing the LORAN signal. The following shall be indicated for each display:

a. TST shall display eleven "⊟"'s.

b. SCH shall display "SCH".

c. STL shall display "STL".

Source: https://assist.dla.mil -- Downloaded: 202640-26T03:58Z
Check the source to verify that this is the current version before use.

d. TRK shall display "TRK" for at least the first 5 seconds after entering the track mode.

e. TDA shall display "bbAb" followed by seven digits, where "b" is a blank.

f. TDB shall display "bbBb" followed by seven digits, where "b" is a blank.

g. UTM shall display a blank followed by two alpha and eight numeric characters.

h. U shall display "U" in the first readout position, followed by the information applicable to the mode of operation.

4.12.2 Dim control (See 3.18.2). - The operation of the dim control shall be verified with the control-indicator in the test mode by observing that the brightness of the display increases from no light output as the control is rotated in a clockwise direction. At maximum brightness all of the display elements shall be readable and of the same brightness to the eye when observed from a distance of 3 feet in a test area with an illuminance of no less than 100 foot candles.

4.13 Antenna AT-892( )/PRC-25.

4.13.1 Leaf material temper (See 3.21.1). - A section containing three leaves shall be bent 180° with the aid of a vise. The jaws shall then be reduced to 1/8 inch. The leaf material shall be examined for fracture. The requirements of 3.21.1 shall be met.

4.13.2 Antenna base flexure (See 3.21.2). - The antenna base shall be flexed for 3000 cycles. Each cycle shall consist of a bend of 90° from a vertical position so that the ferrule end is horizontal, back to the vertical, then 90° in the opposite direction in the same vertical plane and then back to the vertical. The rate of flexure shall be at a rate not exceeding 30 cycles per minute.

4.13.3 Antenna base support (See 3.21.3). - The finished antenna base shall be mounted in an inverted position about a vertical axis, and the flexible part of the antenna bent completely to a 2-3/4 inch inside radius. This should result in a arc of greater than 90°. The ferrule shall then be lowered until the cylindrical surface of the ferrule is horizontal. The requirements of 3.22.3 shall then be met when 1/2 pound downward pressure is applied to the end of the ferrule.

4.14 Visual and mechanical. - Prior to assembly into the unit(s), printed circuit boards shall be examined for compliance with MIL-P-

Source: https://assist.dla.mil -- Downloaded: 202640-26T03:58Z
Check the source to verify that this is the current version before use.

55110, MIL-R-55640, and MIL-STD-275. Assemblies, modules and sections shall be examined for compliance with MIL-STD-454. All external, movable controls, access covers and test buttons shall be operated mechanically. Assembled unit(s) shall be examined for defects listed in MIL-STD-252. This inspection shall be performed in order to determine compliance with 3.24.

4.15 Interchangeability. - The mechanical dimensions and electrical performance of parts shall be physically and electrically interchangeable among the units as required by requirement 7 of MIL-STD-454. When a listed dimension or performance requirement is not within specified limits, it shall be considered a major defect. Mechanical dimensions and electrical performance shall be measured during manufacturing and test to determine conformance with physical and functional interchangeability requirements of 3.22. When a listed dimension or performance requirement is not within specified limits, it shall be considered a major defect. Verification of electrical and mechanical interchangeability shall be further demonstrated as follows:

a. Mechanical (dimensions). - Subassemblies from 2 sample units shall be interchanged and mechanical conformance verified.

b. Electrical (performance). - The 2 sample units with some, but not all, subassemblies interchanged shall be tested to determine compliance with the performance requirements of 3.17 and 3.18.

4.16 Operational inspection. - The final adjustment of each unit on order shall be verified. Each unit shall be operated to determine compliance with 3.23 by using Fort Benning coverage area PROM's. The RF output of the LORAN simulator shall be applied at the antenna input of the AN/PSN-6( ), which shall provide Time Difference A and Time Difference B outputs within $\pm$ 1 microsecond of the simulator settings, and UTM outputs within $\pm$20 meters of the theoretical coordinates. Any two grid values from TABLE XI chosen at random may be used.

4.17 Weight and size.

4.17.1 Weight. - The units shall be weighed to determine compliance with 3.6.1.

4.17.2 Size. - The dimensions of the unit(s) shall be measured to determine compliance with 3.6.2.

4.18 Quality conformance inspection of preparation for delivery. - Preparation for delivery shall be inspected in accordance with Specification MIL-P-116, to determine conformance with the packaging requirements of Section 5.

Source: https://assist.dla.mil -- Downloaded: 202610-26T03:58Z
Check the source to verify that this is the currenversion before use.

4.19 Rough handling test (preparation for delivery). - When rough handling tests in accordance with Specification MIL-P-116 are required by contract, the operational inspection test of 4.16 shall be conducted to determine freedom from operational malfunction caused by rough handling.

4.20 Input power.

4.20.1 Primary power (See 3.19.1). - With the units operated from either one battery BA-4386( )/PRC-25 or the Vehicle Mount Adapter Group OF-34( )/PSN-6 verify that the sensitivity requirements of 3.18.1 are met over the voltage range of 10 to 15 volts.

4.20.2 Power consumption (See 3.19.2). - The input power shall be measured to determine compliance with 3.19.2.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging. - Preservation and packaging shall be level A, B or Commercial as specified (See 6.2d).

5.1.1 Level A, maximum military protection.

5.1.1.1 Cleaning. - Navigation Set, Position Fixing, LORAN AN/PSN-6( ) shall be cleaned in accordance with process C-1 of MIL-P-116.

5.1.1.2 Drying. - Navigation Set, Position Fixing, LORAN AN/PSN-6( ) shall be dried in accordance with the applicable procedure of MIL-P-116.

5.1.1.3 Preservation application. - None required.

5.1.1.4 Unit packaging. - Unit packaging shall be in accordance with the methods prescribed in MIL-P-116 as specifed herein.

5.1.1.4.1 Technical literature. - Each technical literature shall be packaged method IC-1.

5.1.1.4.2 Cable assemblies. - Each cable assembly shall be packaged in accordance with specification MIL-C-55442.

5.1.1.4.3 Navigation Set, Position Fixing, LORAN AN/PSN-6( ). - Each individual component shall be packaged method III as follows: Cushion each unit on all surfaces with cells or pads, or both, fabricated conforming to PPP-F-320, type CF, class weather resistant, variety SW, grade W5c, designed to protect all projections and absorb

Source: https://assist.dla.mil -- Downloaded: 202640-26T03:58Z
Check the source to verify that this is the currentversion before use.

the shock of impact in handling and transit. As an alternate, cushioning material conforming to MIL-P-19644 or polyurethane foam conforming to MIL-P-26514. Place each cushioned unit within a close-fitting fiberboard box conforming to PPP-B-636, W5c.

5.1.1.4.4 Consolidation. - Place the items packaged as specified in 5.1.1.4.2 and 5.1.1.4.3 within a close-fitting fiberboard box conforming to PPP-B-636, type CF, class weather-resistant. Place the technical literature, packaged as specified in 5.1.1.4.1, on top of the contents, directly under the lid of the box. Close the box in accordance with the appendix of the box specification.

5.1.2 Level B, minimum military protection.

5.1.2.1 Cleaning, drying, and preservation application. - Each individual component shall be cleaned, dried, and preserved as specified in 5.1.1.1 through 5.1.1.3.

5.1.2.2 Unit packaging. - Each individual component shall be unit packaged as specified in 5.1.1.4.2 through 5.1.1.4.4 except that cable assemblies and technical literature shall be packaged method III. All other requirements remain the same.

5.1.3 Commercial packaging. - Commercial packaging shall be in accordance with FED-STD-356.

5.2 Packing. - Packing shall be level A, B or Commercial, as specified. Shipping containers for level A and B shall be capable of stacking and supporting superimposed loads during shipment and storage without damaging the container(s) or its contents (see 6.2d).

5.2.1 Level A, maximum military protection. - A quantity of Navigation Set, Position Fixing, LORAN AN/PSN-6( ), packaged as specified in 5.1, shall be packed within a close-fitting box conforming to PPP-B-601, overseas type; PPP-B-621, style 4, class 2; or PPP-B-585, style 2 or 3, class 3. When the gross weight exceeds 200 pounds, or the container length and width is 48 x 24 inches or more and the weight exceeds 100 pounds, 3 x 4 inch skids, laid flat, shall be applied in accordance with the requirements of the container specification, or if not specified in the specification, in a manner which will adequately support the item and facilitate the use of material handling equipment. Closure and strapping shall be in accordance with the applicable container specification or appendix thereto except that metal strapping shall conform to QQ-S-781, type I, finish A.

Source: https://assist.dla.mil -- Downloaded: 202610-26T03:58Z
Check the source to verify that this is the current version before use.

5.2.1.1 Palletization. - Palletization shall be required when containers specified in 5.2.1 do not require skids, quantities per destination comprise a pallet load, and container size permits use of one of the pallet patterns of MIL-STD-147. A quantity of containers packed as specified in 5.2.1, except that container strapping may be omitted, shall be placed on a pallet, load type I, conforming to MIL-STD-147. The pallet shall be softwood conforming to NN-P-71, type IV, size 2. The load shall be "bonded" to the pallet by strapping conforming to QQ-S-781, type I, finish A, or shrink film.

5.2.2 Level B, minimum military protection. - A quantity of Navigation Set, Position Fixing, LORAN AN/PSN-6( ), packaged as specified in 5.1, shall be packed within a close-fitting fiberboard box conforming to PPP-B-640, class 2, style E, or PPP-B-636, type CF, class weather resistant, variety DW. The gross weight of boxes conforming to PPP-B-640, shall not exceed 250 pounds. When the gross weight exceeds 200 pounds, or the container length and width is 48 x 24 inches or more and the weight exceeds 100 pounds, containers will be pallet-mounted on pallets conforming to NN-P-71, type IV. Closure shall be in accordance with the appendix of the applicable box specification. Reinforcing shall be by pressure-sensitive filament tape banding or nonmetallic strapping conforming to PPP-T-97 and PPP-S-760, respectively; selection of the material and application shall be in accordance with the appendix of the applicable box specification. When a single unit is shipped to a single destination no packing is required; the unit container shall serve as the shipping container. Reinforcing shall be as specified above.

5.2.3 Commercial packing. - Commercial packing shall be in accordance with FED-STD-356.

5.3 Marking.

5.3.1 Military marking. - In addition to any special marking required by the contract or order, interior packages and exterior shipping containers shall be marked in accordance with MIL-STD-129.

5.3.2 Commercial marking. - In addition to any special marking required by the contract or order, interior packages and exterior shipping containers shall be marked in accordance with FED-STD-356.

6. NOTES

6.1 Intended use. - Navigation Set, Position Fixing, LORAN AN/PSN-6( ) provides position in both LORAN time differences and UTM

Source: https://assist.dla.mil -- Downloaded: 202640-26T03:58Z
Check the source to verify that this is the current version before use.

coordinates. The set is intended to be a portable, field unit, carried by one man either as a single unit or mechanically attached to Radio Set AN/PRC-25 or AN/PRC-77. In addition, the unit(s) shall also provide for vehicle adaptation via the Vehicle Mount Adapter Group OF-34( )/PSN-6.

6.2 Ordering data. - Procurement documents should specify the following:

a. Title, number, and date of this specification and any amendment thereto.

b. Accessory units (see 1.2), if any, to be procured.

c. Whether Antenna AT-892( )/PRC-25 is to be Government furnished. Groups A, B, C, and D testing for Government furnished equipment is not required unless specified by the procurement document.

d. Levels of preservation and packaging and packing (see Section 5).

e. When rough handling and functional tests are required.

f. First Article Inspection. - Several samples of each item cited in Section 1 are generally required so that lengthy environmental and reliability tests can be completed on specified sample units while complete performance measurements can be made on other sample units. (See 3.4).

6.3 Group C inspection. - Approval to accept units on order may be withheld, at the discretion of the Government, pending decisions from the procuring activity, until compliance with 4.5.3 is complete.

6.4 Location of operational inspection. - It is desirable that the operational inspection (4.16) be performed at a location that will minimize handling (which might cause damage to the units) after this inspection. It is recommended that the entire lot (including the sample units) be inspected at the packaging site immediately prior to packaging.

6.5 Nomenclature. - The parenthesis in the nomenclature will be deleted or replaced by a letter identifying the particular design; for example, AN/PSN-6A. The contractor shall apply for nomenclature in accordance with the applicable clause in the contract. (See 1.1)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:58Z
Check the source to verify that this is the current version before use.

6.6 Verification inspection. - Verification by the Government will be limited to the amount deemed necessary to determine compliance with the contract and will be limited in severity to the definitive quality assurance provisions established in this specification and the contract. The amount of verification by the Government will be adjusted to make maximum utilization of the contractor's quality control system and the quality history of the product.

6.7 Government-loaned property. - The contracting officer should arrange to loan the property listed in 3.2.

Custodian
Army EL

Preparing Activity
Army EL
Project No. 5825-A009

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:58Z
Check the source to verify that this is the current version before use.