INCH-POUND

MIL-S-48686 (AR)
AMENDMENT 2
16 March 1994
SUPERSEDING
AMENDMENT 1
16 February 1990

MILITARY SPECIFICATION

SAFETY AND ARMING DEVICE, GUIDED MISSILE: M143E1
MECHANICAL PARTS AND ASSEMBLY FOR

This Amendment forms a part of Military Specification MIL-S-48686 (AR), dated 4 February 1987, and is approved for use by the US Army Armament, Munitions and Chemical Command and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

2.1.1, under FEDERAL, Add: "A-A-113 - Tape, Pressure Sensitive Adhesive."

2.2, under AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM):

Add the following:

"ASTM-B209 - Standard Specification for Aluminum-Alloy Sheet and Plate

ASTM-B211 - Standard Specification for Aluminum-Alloy Bars, Rod and Wires

ASTM-B221 - Standard Specification for Aluminum-Alloy, Extruded Bars, Rods, Wire, Shapes and Tubes"

PAGE 3

2.3, Next to last line: Delete "uspersede" and substitute "supersede".

PAGE 4

TABLE I, Solenoid (Left) and Solenoid (Right) under Safe & Locked: Delete "12.3 to 14.9" and substitute "11.8-14.1".

PAGE 7

* 3.3.4, Line 6: Delete "± 300" and substitute "within ± 500"

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

PAGE 13

4.3.1, Drawing 9390604: Delete in its entirety.

PAGE 17

4.4.2.1, Sheet 1 of 1, Delete in its entirety and replace with included sheet.

PAGE 18

4.4.2.2, Sheet 1 of 1, Delete in its entirety and replace with included sheet.

PAGE 19

4.4.2.3, Sheet 1 of 1, Major 101, under requirement para: Delete "3.2.3" and substitute "3.2.2.4".

PAGE 20

4.4.2.4, Sheet 1 of 1, Delete in its entirety and replace with included sheet.

PAGE 21

4.4.2.5, Sheet 1 of 1: Delete in its entirety and replace with included sheet.

PAGE 22

4.4.2.6, Sheet 1 of 1, Major 101, under requirement para: Delete "3.2.3" and substitute "3.2.2.4".

PAGE 23

4.4.2.7, Sheet 1 of 1, Delete in its entirety and replace with included sheet.

PAGE 24

4.4.2.8, Sheet 1 of 1, Delete in its entirety and replace with included sheet.

PAGE 25

4.4.2.9, Sheet 1 of 1, Major 101, under requirement para: Delete "3.2.3" and substitute "3.2.2.4".

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

with included sheet.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.1	Pinion, Number 2		12630890
			NEXT HIGHER ASSEMBLY 12630888

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Pivot diameter (2 places)		0.40%	3.2	Gage
102	Pivot surface finish (2 places)		0.40%	3.2	Gage
103	Shoulder-to-shoulder length		0.40%	3.2	Gage
104	Shoulder finish (2 places)		0.40%	3.2	Gage
105	Coating, thickness (min)	4	1/	3.1.2	Gage/4.5.6.3
106	Coating, adhesion	4	1/	3.1.2	Test/4.5.6.4
Minor					
201	Pinion profile		0.65%	3.4	Visual
202	Coating missing, incomplete or improper		0.65%	3.4	Visual
203	Evidence of poor workmanship		1.0%	3.4	Visual

NOTES:

1/ Requires four piece parts and one coupon from plated lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.2	Gear, Number 2				12630889
					NEXT HIGHER ASSEMBLY 12630888
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Gear profile		0.40%	3.2	Gage
102	Coating, thickness (min)	4	1/	3.1.2	Gage/4.5.6.3
103	Coating, adhesion	4	1/	3.1.2	Test/4.5.6.4
Minor					
201	Coating missing, incomplete or improper		0.65%	3.4	Visual
202	Evidence of poor workmanship		1.0%	3.4	Visual

NOTE

1/ Requires four piece parts and one coupon from plated lot.

Source: https://assist.dla.mil -- Downloaded: 2026-02-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.4	Pinion, Escapement		12630893
			NEXT HIGHER ASSEMBLY 12630891

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Pivot diameter (2 places)		0.40%	3.2	Gage
102	Pivot surface finish (2 places)		0.40%	3.2	Gage
103	Shoulder-to-shoulder length		0.40%	3.2	Gage
104	Shoulder finish (2 places)		0.40%	3.2	Gage
105	Coating, thickness (min)	4	1/	3.1.2	Gage/4.5.6.3
106	Coating, adhesion	4	1/	3.1.2	Test/4.5.6.4
Minor					
201	Pinion profile		0.65%	3.4	Visual
202	Coating missing, incomplete or improper		0.65%	3.4	Visual
203	Evidence of poor workmanship		1.0%	3.4	Visual

NOTES:

1/ Requires four piece parts and one coupon from plated lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.5	Gear, Escapement				12630892
					NEXT HIGHER ASSEMBLY 12630891
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	True position of tooth to tooth length (.2159)		0.40%	3.2	Gage
102	Gear profile		0.40%	3.2	Gage
103	Coating, thickness (min)	4	1/	3.1.2	Gage/4.5.6.3
104	Coating, adhesion	4	1/	3.1.2	Test/4.5.6.4
Minor					
201	Coating missing, incomplete or improper		0.65%	3.4	Visual
202	Evidence of poor workmanship		1.0%	3.4	Visual

NOTE

Requires four piece parts and one co[illegible]n from plated lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.7	Pinion, Number 1		12630887
			NEXT HIGHER ASSEMBLY 12630885

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Pivot diameter (2 places)		0.40%	3.2	Gage
102	Pivot surface finish (2 places)		0.40%	3.2	Gage
103	Shoulder to shoulder length		0.40%	3.2	Gage
104	Shoulder finish (2 places)		0.40%	3.2	Gage
105	Coating Thickness (min)	4	1/	3.1.2	Gage/4.5.6.3
106	Coating adhesion	4	1/	3.1.2	Test/4.5.6.4
Minor					
201	Pinion profile		0.65%	3.4	Visual
202	Coating missing, incomplete or improper		0.65%	3.4	Visual
203	Evidence of poor workmanship		1.0%	3.4	Visual

NOTES: Requires four piece parts and one coupon from plated lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.8	Gear, Number 1				12630886
					NEXT HIGHER ASSEMBLY 12630885
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Gear profile		0.40%	3.2	Gage
102	Coating Thickness (min)	4	1/	3.1.2	Gage/4.5.6.3
103	Coating adhesion	4	1/	3.1.2	Test/4.5.6.4
Minor					
201	Coating missing, incomplete or improper		0.65%	3.4	Visual
202	Evidence of poor workmanship		1.0%	3.4	Visual

NOTES:

Requires four piece parts and one coupon from plated lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

PAGE 26

4.4.2.10, Sheet 1 of 1, Delete in its entirety and replace with included sheet.

PAGE 27

4.4.2.11, Sheet 1 of 1, Delete in its entirety and replace with included sheet.

PAGE 30

4.4.2.14, Sheet 1 of 1: Delete in its entirety and replace with included sheet.

PAGE 32

4.4.2.16, Sheet 1 of 1, Delete in its entirety and replace with included sheet.

PAGE 33

4.4.2.17, Sheet 1 of 1: Delete in its entirety and replace with included sheet.

PAGE 34

4.4.2.18, Sheet 1 of 1: Delete in its entirety and replace with included sheet.

PAGE 37

4.4.2.21, Sheet 1 of 1: Delete in its entirety and replace with included sheet.

PAGE 38

4.4.2.22, Sheet 1 of 2: Delete in its entirety and replace with included sheet.

PAGE 39

4.4.2.22, Sheet 2 of 2: Delete in its entirety and replace with included sheet.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE			SHEET 1 OF 1	DRAWING NUMBER
4.4.2.10	Shaft, Lever				12630897
					NEXT HIGHER ASSEMBLY 12630894
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Pivot diameter (2 places)		0.40%	3.2	Gage
102	Pivot finish (2 places)		0.40%	3.2	Gage
103	Shoulder-to-shoulder length		0.40%	3.2	Gage
104	Shoulder finish (2 places)		0.40%	3.2	Gage
105	Taper diameter runout		0.40%	3.2	Gage
106	Coating Thickness (min)	4	1/	3.1.2	Gage/4.5.6.3
107	Coating adhesion	4	1/	3.1.2	Test/4.5.6.4
Minor					
201	Coating missing, incomplete or improper		0.65%	3.4	Visual
202	Evidence of poor workmanship		1.0%	3.4	Visual

NOTES: Requires four piece parts and one coup[illegible] from plated lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.11	Pallet, Lever				12630896
					NEXT HIGHER ASSEMBLY 12630894
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Diameter, large		0.40%	3.2	Gag
102	Finish, large diameter		0.40%	3.2	Gage
103	Coating Thickness (min)	4	1/	3.1.2	Gage/4.5.6.3
104	Coating adhesion	4	1/	3.1.2	Test/4.5.6.4
Minor					
201	Coating missing, incomplete or improper		0.65%	3.4	Visual
202	Evidence of poor workmanship		1.0%	3.4	Visual
203	Length		1.0%	3.4	Visual

NOTES:
Requires four piece parts and one coupon from plated lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.14	Plate, Bottom		12630881
			NEXT HIGHER ASSEMBLY 12630880

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Diameter of #2 Gear & Pinion (G&P) hole		0.40%	3.2	Gage
102	Location of #2 (G&P) hole		0.40%	3.2	Gage
103	Diameter of pivot holes (.0319) 3 places		0.40%	3.2	Gage
104	Location of pivot holes (.0319) 3 places		0.40%	3.2	Gage
105	Location of pillar holes (3 places)				
106	Coating, thickness (min)	4	0.40%	3.2	Gage/4.5.6.3
107	Coating adhension	4	0.40%	3.2	Test/4.5.6.3
Minor					
201	Diameter of pillar holes (3 places)		0.65%	3.4	Visual
202	Coating, missing, incomplete or improper		0.65%	3.4	Visual
203	Evidence of poor workmanship		1.0%	3.4	Visual

NOTES:

Requires four piece parts and one coupon from plated lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.16	Pillar, Number 1				12630883
					NEXT HIGHER ASSEMBLY 12630880
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Length determining endshake		0.40%	3.2	Gage
Minor					
201	Diameter, top plate end		0.65%	3.4	Visual
202	Diameter, bottom plate end		0.65%	3.4	Visual
203	Evidence of poor workmanship		1.0%	3.4	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

MIL-S-48686 (AR)
AMENDMENT 2

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.17	Pillar, Number 2				12630884
					NEXT HIGHER ASSEMBLY 12630880
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major 101	length determining endshake		0.40%	3.2	Gage
Minor 201	Diameter, top plate end		0.65%	3.4	Visual
202	Diameter, bottom plate end		0.65%	3.4	Visual
203	Evidence of poor workmanship		1.0%	3.4	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.18	Escapement Assembly				12630880
					NEXT HIGHER ASSEMBLY 9390600
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Stake missing, pillar above flush, Pillar #1 (bottom plate)		0.40%	3.2	Visual
102	Stake missing, pillar #2 (2 places, top plate)		0.40%	3.2	Visual
103	Stake missing, pillar #2 (2 places, bottom plate)		0.40%	3.2	Visual
104	Push-off, partial assembly, top plate (Nondestructive)		0.40%	3.2.2.1	Test
105	Push-off, partial assembly, bottom plate (Nondestructive)		0.40%	3.2.2.2	Test
Minor					
201	Evidence of poor workmanship		1.0%	3.4	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.21	Switch Board Assembly				12630822
					NEXT HIGHER ASSEMBLY 9390600
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Location of contact in operating position (6 places)		0.40%	3.2	Gage
102	Contact force at operating position (6 places)		0.40%	3.2	Gage/Test
Minor					
201	Improper copper wire		0.65%	3.2	Visual
202	Evidence of solder bridging prior to adhesive application		0.65%	3.2	Visual
203	Adhesive in area of contact bend or operating area		0.65%	3.2	Visual
204	Evidence of poor workmanship		1.0%	3.4	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026/10-26T03:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 2		DRAWING NUMBER
4.4.2.22	Plate, Center				9390601
					NEXT HIGHER ASSEMBLY 9390600
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Diameter of pivot hole (4 places)		0.40%	3.2	Gage
102	Location of pivot hole (4 places)		0.40%	3.2	Gage
103	Diameter of base dowel hole (2 places)		0.40%	3.2	Gage
104	Location of base dowel hole (2 places)		0.40%	3.2	Gage
105	Diameter of tee spacer dowel hole (4 places)		0.40%	3.2	Gage
106	Location of tee spacer dowel hole (4 places)		0.40%	3.2	Gage
107	Pitch diameter of switch board assy. hole (4 places)		0.40%	3.2	Gage
108	Location of switch board assy. threaded hole (4 places)		0.40%	3.2	Gage
109	Diameter of switch Board (pin) hole (4 places)		0.40%	3.2	Gage
110	Location of switch Board (pin) (4 places)		0.40%	3.2	Gage
111	Diameter of escapement hole (2 places)		0.40%	3.2	Gage
112	Width of escapement slot (2 places)		0.40%	3.2	Gage
113	Location of escapement hole (2 places)		0.40%	3.2	Gage
114	Length of escapement slot (2 places)		0.40%	3.2	Gage

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER
4.4.2.22	Plate, Center				9390601
					NEXT HIGHER ASSEMBLY 9390600
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
115	Diameter of tee spacer mtg. hole (6 places)		0.40%	3.2	Gage
116	Location of tee spacer mtg. hole (6 spaces)		0.40%	3.2	Gage
117	Pitch diameter of base mtg. hole (2 places)		0.40%	3.2	Gage
118	Location of base mtg. hole (2 places)		0.40%	3.2	Gage
119	Diameter of top plate dowel pin hole (2 places)		0.40%	3.2	Gage
120	Location of top plate dowel pin hole (2 places)		0.40%	3.2	Gage
Minor					
201	Protective finish improper, incomplete or missing		0.65%	3.2	Visual
202	Evidence of poor workmanship		1.0%	3.4	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

PAGE 40

4.4.2.23, Sheet 1 of 1, Major 101 and 102, under EXAMINATION OR TEST: Add "(2 places)". Delete minor 202 in its entirety.

PAGE 41

4.4.2.24, Sheet 1 of 1: Delete in its entirety and replace with included sheet.

PAGE 42

4.4.2.25, Sheet 1 of 1: Delete in its entirety and replace with included sheet.

PAGE 43

4.4.2.26, Sheet 1 of 1: Delete in its entirety and replace with included sheet.

PAGE 46

4.4.2.29, Sheet 1 of 1, Delete in its entirety and replace with included sheet.

PAGE 47

4.4.2.30, Sheet 1 of 1, Delete in its entirety and replace with included sheet.

PAGE 48

4.4.2.31, Sheet 1 of 1, Delete in its entirety and replace with included sheet.

PAGE 49

4.4.2.32, Sheet 1 of 1, Delete in its entirety and replace with included sheet.

PAGE 50

4.4.2.33, Sheet 1 of 1: Delete in its entirety and replace with included sheet.

PAGE 52

4.4.2.35, Sheet 1 of 1: Delete in its entirety and replace with included sheet.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.24	Housing, "G" Weight Latch				9390612
					NEXT HIGHER ASSEMBLY 9390813
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Location of latch hole		0.40%	3.2	Gage
102	Diameter oflatch hole		0.40%	3.2	Gage
103	Diameter of locating hole		0.40%	3.2	Gage
104	Location of locating hole		0.40%	3.2	Gage
105	Width of locating slot		0.40%	3.2	Gage
106	Location of locating slot		0.40%	3.2	Gage
107	Location of slot for latch pin		0.40%	3.2	Gage
108	Width of slot		0.40%	3.2	Gage
109	Surface finish in slot and large hole		0.40%	3.2	Visual
110	Coating, thickness (min)	1	1/	3.1.2	Gage/4.5.6.3
111	Coating, adhesion	1	1/	3.1.2	Test/4.5.6.4
Minor					
201	Radius around edge of slot missing (intersection with latch hole)		0.65%	3.2	Visual
202	Evidence of foreign material in large diameter hole		0.65%	3.4	Visual
203	Evidence of poor plating adhesion in large diameter hole		0.65%	3.4	Visual
204	Evidence of poor workmanship		1.0%	3.4	Visual

NOTES:

Requires one piece part and coupon f[illegible] plated lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.25	Latch, "G" Weight		12630814
			NEXT HIGHER ASSEMBLY 12630813

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Inside diameter, min		0.40%	3.2	Gage
102	Outside diameter (max)		0.40%	3.2	Gage
103	Location of g weight latch pin hole		0.40%	3.2	Gage
104	Coating, thickness (min)	4	1/	3.1.2	Gage/4.5.6.3
105	Coating, adhesion	4	1/	3.1.2	Test/4.5.6.4
Minor					
201	Radius missing on solid end		0.65%	3.2	Visual
202	Coating missing, incomplete or improper		0.65%	3.4	Visual
203	Surface finish, outside diameter		0.65%	3.4	Visual
204	Evidence of poor workmanship		1.0%	3.4	Visual

NOTES:

Requires one piece part and coupon from plated lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-S-48686 (AR)
AMENDMENT 2

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.26	Pin, "G" Weight Latch				12630815
					NEXT HIGHER ASSEMBLY 12630813
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Large outside diameter, max.		0.40%	3.2	Gage
102	Coating, thickness (min)	4	1/	3.1.2	Gage/4.5.6.3
113	Coating, adhesion	4	1/	3.1.2	Test/4.5.6.4
Minor					
201	Coating missing, incomplete or improper		0.65%	3.2	Visual
202	Pitch diameter, min.		0.65%	3.4	Visual
203	Length, end to end		0.65%	3.4	Visual
204	Undercut missing		0.65%	3.4	Visual
205	Evidence of poor workmanship		1.0%	3.4	Visual

NOTES:

Requires one piece part and coupon f[illegible] plated lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.29	Plate, Shorting, Detonator				12630806
					NEXT HIGHER ASSEMBLY 12630802
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Perpendicularity of hole # 1		0.40%	3.2	Gage
102	Location of hole #2		0.40%	3.2	Gage
103	Traces not within profile tolerance		0.40%	3.2	Gage
Minor					
201	Gold plating improper		0.65%	3.2	Visual
202	Nickel plating improper		0.65%	3.4	Visual
203	Thickness of board		0.65%	3.4	Visual
204	Hole diameter (4 places)		0.65%	3.4	Visual
205	Evidence of poor workmanship		1.0%	3.4	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.30	Pin, Terminal				12630805
					NEXT HIGHER ASSEMBLY 12630802
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	Large diameter (swage end)		0.65%	3.2	Visual
202	Length (swage end)		0.65%	3.4	Visual
203	Finish messing, incomplete or improper		0.65%	3.4	Visual
204	Evidence of poor workmanship		1.0%	3.4	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.31	Shorting Plate, Detonator Assembly				12630804
					NEXT HIGHER ASSEMBLY 12630802
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Solder not in accordance with MIL-STD-2000 (2 places)		0.40%	3.2	Gage
Minor					
201	Pin not swaged (2 places)		0.65%	3.2	Visual
202	Evidence of poor workmanship		1.0%	3.4	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.32	Resistor Shorting Plate Detonator Assembly				12630803
					NEXT HIGHER ASSEMBLY 12630802
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Soldering not in accordance with MIL-STD-2000		0.40%	3.2	Gage
Minor					
201	Incorrect resistor		0.65%	3.2	Visual
202	Evidence of poor workmanship		1.0%	3.4	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-04-02T10:40:26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.33	Housing, Detonator				12630807
					NEXT HIGHER ASSEMBLY 12630802
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Diameter of hole for detonator		0.40%	3.2	Gage
102	Depth of hole for detonator		0.40%	3.2	Gage
103	Location of hole for detonator		0.40%	3.2	Gage
104	Diameter of mounting hole (2 places)		0.40%	3.2	Gage
105	Location of mounting hole (2 places)		0.40%	3.2	Gage
106	Location of shorting plate mounting holes (2 places)		0.40%	3.2	Gage
107	Diameter of shorting plate mounting holes (2 places)		0.40%	3.2	Gage
Minor					
201	Sharp edges at intersection of detonator hole and wire feed through hole		0.65%	3.4	Visual
202	White "S" missing from green field		0.65%	3.2	Visual
203	Paint incorrect or improperly located		0.65%	3.2	Visual
204	Protective finish missing, incomplete or improper		0.65%	3.2	Visual
205	Evidence of poor workmanship		1.0%	3.4	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: (2020-10-26T03:57Z)
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.35	Spring, "G" Weight				9390589
					NEXT HIGHER ASSEMBLY 9390590
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Load at 1.300 in.		0.40%	3.2	Gage
102	Load at .575 in.		0.40%	3.2	Gage
Minor					
201	End open		0.65%	3.2	Visual
202	Inside diameter		0.65%	3.2	Gage
203	Evidence of poor workmanship		1.0%	3.4	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-01-26T03:57Z
Check the source to verify that this is the current version before use.

PAGE 55

4.4.2.38, Sheet 1 of 1, Major 103, under requirement para: Delete "3.2.3" and substitute "3.2.1".

PAGE 56

4.4.2.39, Sheet 1 of 1, Minor 201: Delete in its entirety.

PAGE 58

4.4.2.41, Sheet 1 of 2: Delete in its entirety and replace with included sheet.

PAGE 59

4.4.2.41, Sheet 2 of 2: Delete in its entirety and replace with included sheet.

PAGE 61

4.4.2.43, Sheet 1 of 1, Major 103: Delete in its entirety.

PAGE 62

4.4.2.44, Sheet 1 of 2: Delete in its entirety and replace with included sheet.

PAGE 64

4.4.2.45, Sheet 1 of 1, Delete "Location of dowel holes" and substitute "Location of dowel hole"

PAGE 66

4.4.2.47, Sheet 1 of 1, next higher assembly: Delete "9390692" and substitute "9390602".

PAGE 68

4.4.2.49, Sheet 1 of 1: Delete in its entirety.

PAGE 69

4.4.2.50, Sheet 1 of 1: Delete in its entirety and replace with included sheet.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 2		DRAWING NUMBER
4.4.2.41	Rotor, Detonator				9392415
					NEXT HIGHER ASSEMBLY 12630810
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Diameter of pivots (2 places)		0.40%	3.2	Gage
102	Shoulder to shoulder distance of mid-diameter shaft and pivot shaft		0.40%	3.2	Gage
103	Tooth-to-tooth composite tolerance		0.40%	3.2	Gage
104	Total composite tolerance		0.40%	3.2	Gage
105	Surface finish on pivot diameters (2 places)		0.40%	3.2	Gage
106	Location of holes for detonator housing		0.40%	3.2	Gage
107	Pitch diameter of threads for detonator		0.40%	3.2	Gage
108	Surface finish on shoulder (2 places)		0.40%	3.2	Gage
109	Coating, thickness	1	Coupon	3.1.2	Gage/4.5.6.3
110	Coating, adhesion	1	Coupon	3.1.2	Visual/4.5.6.4
Minor					
201	Location of screw thread hole in side (2 places)		0.65%	3.2	Gage
202	Pitch diameter (max) of screw threads		0.65%	3.2	Gage
203	Location of hole for pin		0.65%	3.2	Gage
204	Diameter of hole for pin (max)		0.65%	3.2	Gage

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-26T03:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER
4.4.2.41	Rotor, Detonator				9392415
					NEXT HIGHER ASSEMBLY 12630810
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Minor					
205	End of gear teeth to centerline (2 places)		0.65%	3.2	Gage
206	Width of slots (2 places)		0.65%	3.2	Gage
207	Location of slots (2 places)		0.65%	3.2	Gage
208	Presence of timing mark		0.65%	3.2	Visual
209	Location of hole for lead weight		0.65%	3.2	Gage
210	Coating missing, incomplete or improper		0.65%	3.4	Visual
211	Improper color or location of paint		0.65%	3.4	Visual
212	Black "A" missing on red field		0.65%	3.4	Visual
213	Evidence of poor paint adhesion		0.65%	3.2	Test/4.5.8
214	Evidence of poor workmanship		1.0%	3.4	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2024-10-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 2		DRAWING NUMBER
4.4.2.44	Latch Actuator Solenoid Assembly Solenoid, Rotary				12630826/9390608
					NEXT HIGHER ASSEMBLY 9390606
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Distance to latch actuator assembly from bottom of solenoid		0.40%	3.2	Gage
102	Location of latch actuator assembly with mounting studs		0.40%	3.2	Gage
103	Spring pin missing		0.40%	3.2	Visual
104	Dimple missing (4 places)		0.40%	3.2	Visual
	SEQUENCE REQUIRED (105, 106, 107)				
105	Output torque with 5 oz. weight @ -40 F		0.40%	3.2	Test
106	Output torque with 5 oz. weight @ 70 F	1/	100%	3.2	Test
107	Output torque with 5 oz. weight @ 150 F		0.40%	3.2	Test
108	Diameter of rotating shaft		0.40%	3.2	Gage
109	Spring torque @ 2 degrees rotation		0.40%	3.2	Test
110	Spring torque @ 43 degrees rotation, max.		0.40%	3.2	Test
111	Rotation		0.40%	3.2	Gage
112	Stroke direction		0.40%	3.2	Manual
113	Resistance @ 70 degrees F		0.40%	3.2	Test
114	Axial shaft movement, max.		0.40%	3.2	Gage

NOTES:
1/ Input current shall be limited to 1.65 ADC MAX.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.50	Rail				9390605
					NEXT HIGHER ASSEMBLY 9390590
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Diameter		0.40%	3.2	Gage
102	Length		0.40%	3.2	Gage
103	Surface finish		0.40%	3.2	Gage
104	Straightness		0.40%	3.2	Gage
Minor					
201	Protective finish missing, incomplete or improper		0.65%	3.2	Visual
202	Evidence of poor workmanship		1.0%	3.4	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-26T03:57Z
Check the source to verify that this is the current version before use.

PAGE 71

4.4.2.52, Sheet 1 of 1, Major 101: Delete "MIL-STD-1460" and substitute "MIL-STD-2000".

PAGE 72

4.4.2.53, Sheet 1 of 1: Delete in its entirety and replace with included sheet.

PAGE 73

4.4.2.54, Sheet 1 of 1: Delete in its entirety and replace with included sheet.

PAGE 74

4.4.2.55, Sheet 1 of 1, Major 101, under EXAMINATION OR TEST: Delete in its entirety and substitute "maximum gap between latch and pin". Delete minor 201

PAGE 75

4.4.2.56, Sheet 1 of 1: Delete in its entirety and replace with included sheet.

PAGE 76

4.4.2.57, Sheet 1 of 1, Delete in its entirety and replace with included sheet.

PAGE 78

4.4.2.59, Sheet 1 of 1, Delete major 102.

PAGE 80

4.4.2.61, Sheet 1 of 3, under Major: Add "109a Location of Slot for Latch, 0.40%, 3.2, Gage".

PAGE 82

4.4.2.61, Sheet 3 of 3: Delete in its entirety and replace with included sheet.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.53	Pin, Rotor Latch				9390599
					NEXT HIGHER ASSEMBLY 9390597
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Small diameter, min		0.40%	3.2	Gage
102	Surface finish on tapered diameter and spherical radius		0.40%	3.2	Gage
103	Length from shoulder to spherical radius		0.40%	3.2	Gage
104	Coating, thickness (min)	4	1/	3.1.2	Gage/4.5.6.3
105	Coating, adhesion	4	1/	3.1.2	Gage/4.5.6.4
Minor					
201	Coating missing, incomplete or improper		0.65%	3.2	Visual
202	Evidence of poor workmanship		1.0%	3.4	Visual

NOTES:

Requires four piece parts and one coupon from plated lot.

Source: https://assist.dla.mil -- Downloaded: (2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.56	Detent, Rotor Latch		9390593
			NEXT HIGHER ASSEMBLY 9390592

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Diameter of hole		0.40%	3.2	Gage
102	Profile		0.40%	3.2	Gage
103	Finish of step		0.40%	3.2	Visual
104	Coating, thickness (min)	4	1/	3.1.2	Gage/4.5.6.3
105	Coating, adhesion	4	1/	3.1.2	Gage/4.5.6.4
Minor					
201	Thickness		0.65%	3.2	Gage
202	Coating missing, incomplete or improper		0.65%	3.4	Visual
203	Evidence of poor workmanship		1.0%	3.4	Visual

NOTES:

Requires four pieces parts and one coupon from plated lot.

Source: https://assist.dla.mil -- Downloaded: 2026-04-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.57	Bearing, Rotor Latch Detent		12630820
			NEXT HIGHER ASSEMBLY 9390592

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Diameter, of hole		0.40%	3.2	Gage
102	Profile		0.40%	3.2	Gage
103	Finish of step		0.40%	3.2	Visual
104	Coating, thickness (min)	4	1/	3.1.2	Gage/4.5.6.3
105	Coating, adhesion	4	1/	3.1.2	Test/4.5.6.4
Minor					
201	Thickness		0.65%	3.2	Gage
202	Coating missing, incomplete or improper		0.65%	3.4	Visual
203	Evidence of poor workmanship		1.0%	3.4	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-02-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.57	Bearing, Rotor Latch Detent		12630820
			NEXT HIGHER ASSEMBLY 9390592

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Diameter, of hole		0.40%	3.2	Gage
102	Profile		0.40%	3.2	Gage
103	Finish of step		0.40%	3.2	Visual
104	Coating, thickness (min)	4	1/	3.1.2	Gage/4.5.6.3
105	Coating, adhesion	4	1/	3.1.2	Test/4.5.6.4
Minor					
201	Thickness		0.65%	3.2	Gage
202	Coating missing, incomplete or improper		0.65%	3.4	Visual
203	Evidence of poor workmanship		1.0%	3.4	Visual

NOTES:

Requires four pieces parts and one c( )n from plated lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 3 OF 3		DRAWING NUMBER
4.4.2.61	Plate, Outer				9390594
					NEXT HIGHER ASSEMBLY 9390592
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Major					
120	Pitch diameter of "G" wgt. latch mtg. hole		0.40%	3.2	Gage
121	Location of "G" wgt. latch mtg. hole		0.40%	3.2	Gage
122	Pitch diameter of switch mtg. hole		0.40%	3.2	Gage
123	Location of switch mtg. hole		0.40%	3.2	Gage
124	Width of switch mtg. slot		0.40%	3.2	Gage
125	Location of switch mtg. slot		0.40%	3.2	Gage
126	Height of switch mtg. slot		0.40%	3.2	Gage
127	Thickness for lower "G" wgt. surface		0.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		1.0%	3.4	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded at 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

PAGE 84

4.4.2.63, Sheet 1 of 1, Major 103 and 108: Delete in their entirety.

PAGE 86

4.4.2.65, Sheet 1 of 1: Delete in its entirety and replace with included sheet.

PAGE 87

4.4.2.66, Sheet 1 of 1: Delete in its entirety and replace with included sheet.

PAGE 88

4.4.2.67, Sheet 1 of 1: Delete in its entirety and replace with included sheet.

PAGE 89

4.4.2.68, Sheet 1 of 1: Delete in its entirety and replace with included sheet.

PAGE 90

4.4.2.69, Sheet 1 of 1: Delete in its entirety and replace with included sheet.

PAGE 91

4.4.2.70, Sheet 1 of 2, Major 108, Under EXAMINATION OR TEST: Delete "2 places" and substitute "4 places".

PAGE 92

4.4.2.70, Sheet 2 of 2, Major 204 & 205: Delete in their entirety.

PAGE 93

4.4.2.71, Sheet 1 of 1, Major 105, under para reference/ inspection method: Delete "4.5.5" and substitute "4.5.4".

4.4.2.71, Sheet 1 of 1, Major 109, under para reference/ inspection method: Delete "4.5.6" and substitute "4.5.5".

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.65	Board, Stiffener		9390611
			NEXT HIGHER ASSEMBLY 9390590

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Diameter of mounting hole (4 places)		0.40%	3.2	Gage
102	Location of mounting hole (4 places)		0.40%	3.2	Gage
103	Diameter of hole (12 places)		0.40%	3.2	Gage
104	Location of hole (12 places)		0.40%	3.2	Gage
105	Location of solenoid lead cutout (2 places)		0.40%	3.2	Gage
Minor					
201	Diameter of clearance hole (2 places)		0.65%	3.2	Gage
202	Location of clearance hole (2 places)		0.65%	3.2	Gage
203	Edge chamfer missing		0.65%	3.2	Visual
204	Radius missing on corners (8 places)		0.65%	3.2	Visual
205	Profile of cutouts (2 places)		0.65%	3.2	Gage
206	Diameter of solenoid mtg hole (4 places)		0.65%	3.2	Gage
207	Location of solenoid mtg hole (4 places)		0.65%	3.2	Gage
208	Evidence of poor workmanship		1.0%	3.4	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-01-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.66	Plate, Base				9390591
					NEXT HIGHER ASSEMBLY 9390590
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Diameter of four warhead large thru holes		0.40%	3.2	Gage
102	Location of four warhead large thru holes		0.40%	3.2	Gage
103	Location of cover hole (8 places)		0.40%	3.2	Gage
104	Diameter of cover hole (8 places)		0.40%	3.2	Gage
105	Location of warhead orientation notch		0.40%	3.2	Gage
106	Thickness of lead output diaphram (2 places)		0.40%	3.2	Gage
107	Flatness		0.40%	3.2	Gage
108	Outside dimension (2 places)		0.40%	3.2	Gage
109	Diameter of "A" hole (7 places)		0.40%	3.2	Gage
110	Location of "A" hole (7 places)		0.40%	3.2	Gage
111	Lead hole diameter (2 places)		0.40%	3.2	Gage
112	Lead hole location (2 places)		0.40%	3.2	Gage
Minor					
201	Radius missing, outside corners		0.65%	3.2	Visual
202	Counterbore missing, improper side or breaking through		0.65%	3.2	Visual
203	Evidence of poor workmanship		1.0	3.4	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.67	Gear, Escapement	1 OF 1	9390615
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Total tooth profile (not root diameter or top blend radius)		0.40%	3.2	Gage
102	Coating, thickness (min)	4	1/	3.1.2	Gage/4.5.6.3
103	Coating, adhesion	4	1/	3.1.2	Test/4.5.6.4
104	Diameter of large center hole		0.40%	3.2	Gage
Minor					
201	Location of two mounting holes		0.65%	3.2	Gage
202	Diameter of mounting holes		0.65%	3.2	Gage
203	Finish of gear teeth		0.65%	3.2	Visual
204	Coating missing, incomplete or improper		0.65%	3.4	Visual
205	Evidence of poor workmanship		1.0%	3.4	Visual

NOTES:

Requires four piece parts and one coupon from plated lot.

Source: https://assist.dla.mil -- Downloaded: 2026-03-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.68	Rotor, Balance		9390616
			NEXT HIGHER ASSEMBLY 9390416

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Diameter of pivots (2 places)		0.40%	3.2	Gage
102	Shoulder to shoulder distance of mid-diameter		0.40%	3.2	Gage
103	Total composite tolerance		0.40%	3.2	Gage
104	Tooth-to-tooth composite tolerance		0.40%	3.2	Gage
105	Finish of pivot (2 places)		0.40%	3.2	Gage
106	Coating, thickness (min)	1	1/	3.1.2	Gage/4.5.6.3
107	Coating, adhesion	1	1/	3.1.2	Test/4.5.6.4
108	Diameter of gear mount		0.40%	3.2	Gage
Minor					
201	Location of threaded holes (2 places)		0.65%	3.2	Gage
202	Pitch diameter of screw threads, max		0.65%	3.2	Gage
203	Presence of timing mark		0.65%	3.2	Visual
204	Coating missing, incomplete or improper		0.65%	3.2	Visual
205	Evidence of poor workmanship		1.0%	3.4	Visual

NOTES:

Requires one piece part and coupon from each plated lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.69	Balance Rotor Assembly				9392416
					NEXT HIGHER ASSEMBLY 9390590
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major 101	Weight		0.40%	3.2	Scale
Minor 201	Escapement gear not against rotor		0.65%	3.2	Visual/Manual
202	Escapement gear loose		0.65%	3.2	Visual/Manual
203	Pan head screw not seated (2 places)		0.65%	3.2	Visual/Manual
204	Evidence of poor workmanship		1.0%	3.4	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-01-26T03:57Z
Check the source to verify that this is the current version before use.

PAGE 95

4.5.6, line 1: Delete "perform" and substitute "supplement".

4.5.4.2, line 5: Delete "2a" and substitute "3a".

4.5.4.2, line 10: Delete "2b" and substitute "3b".

4.5.5.2, line 3: Delete "2b" and substitute "3b".

PAGE 96

4.4.6.2.1, Under Table IV: Add:

"A1	aluminum alloy, bar or wire, 7075-T6	ASTM B211
A2	aluminum alloy, sheet, 6061-T6	ASTM B209
A3	aluminum alloy, rod 6061-T6	ASTM B221
A4	aluminum alloy, rod 7075-T6	ASTM B221
A5	aluminum alloy, bar or wire, 6061-T6	ASTM B211"

PAGE 97

Add new paragraph 4.5.8 as follows:

"4.5.8. Paint adhesion. A 3/4" wide pressure-sensitive adhesive tape conforming to Federal Specification A-A-113, is to be applied to the entire red field. The tape is to be applied flush to the surface, the inspector is to use manual pressure to remove entrapped air. After waiting 10 seconds to allow return to ambient temperature, the tape is to be sharply pulled in a direction approximately 180 degrees to that which it was applied.

The tape is to be inspected for evidence of paint removed from the component. Paint removed around the perimeter of the red field resulting from overspray of the lacquer beyond the primer shall not constitute rejection. Evidence of removal of paint inside the perimeter of the painted field shall constitute rejection of the painted lot.

Upon rejection of a lot of painted components, the adhesion test may be performed 100% to serve as a screening test. Those components which pass this adhesion test are then to be considered acceptable."

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the previous amendment.

Custodian:
Army - AR

Preparing activity:
Army - AR

Project: 1336-A610)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.