MIL-S-48735A(AR)
31 March 1982
SUPERSEDING
MIL-S-48735(AR)
13 December 1977

MILITARY SPECIFICATION

SAFE AND ARMING DEVICE FOR MINES, M718/M741 SYSTEMS METAL PARTS FOR

This specification is approved for use by the U.S. Army Armament Research and Development Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification contains requirements not normally covered by the drawings, and provides quality assurance provisions for the fabrication of S&A metal parts for the AT/AV Mines used in the M718/M741 System.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. Unless otherwise specified, the following specifications and standards of the issue listed in that issue of the Department of Defense Index of Specifications and Stantards (DoDISS) specified in the solicitation, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-T-10727	-	Tin Plating, Electrodeposited or Hot-dipped, for Ferrous and Non-Ferrous Metals
MIL-A-48078	-	Ammunition, Standard Quality Assurance Provisions, General Specification For

STANDARDS

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-1188	-	Commercial Packaging of Supplies and Equipment

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Command, Attn. DRDAR-QA, Dover, New Jersey 07801 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

2.1.2 Other Government documents, drawings, and publications. The following other Government documents form a part of this specification to the extent herein.

DRAWINGS (See 6.4)

U.S. ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND

9277774 - Cable, Flexible
9277786 - Lock, Centrifugal
9277790 - "G" Weight
9277794 - Holder, Spring
9277808 - Shield Assy
9277809 - Shield, MDF
9277810 - Shield
9277812 - Disc, Closure, Lock
9277832 - Spring, Slider Lock
9277833 - Spring, Slider
9277834 - Spring, Centrifugal Lock
9277835 - Spring, "G" Weight
9277843 - Cup
9277846 - Cup, Closure
9277848 - Cup & Tube Assembly
9277854 - Tubing
9277871 - Lock, "G" Weight
9277978 - Dual MDF Chamber
9277979 - Interrupter
9277991 - Pin (Dual MDF Assembly)
9278001 - Clip, Grounding
9278004 - Holder, Lead
9278008 - Housing
9278010 - Closure, Lock Rear
9278023 - Cup, Booster
9278042 - Retainer, Spring
9278046 - Spring, "G" Weight Lock
9278057 - Lock, Rear
9278060 - Lock, Slider
9278086 - Slider
9278106 - Spacer
9278109 - Spring, Rear Lock
9317584 - Setback Pin
9317585 - Spring, Setback Pin
9317589 - Closure, "G" Weight
9317590 - Closure, Slider
9317591 - Closure, Firing Pin
9317616 - Pin, Stop
9317617 - Setback Pin Assembly
9317647 - MDF Preform, Right Side
9317648 - MDF Preform, Left Side

(Copies of specifications, standards, drawings, and publications, required by suppliers in connection with specific procurement functions, should be obtained from the procuring activity or as directed by the Contracting Officer).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

American Society For Testing And Materials

ASTM E 18-74 - Standard Test Methods For Rockwell Hardness and Rockwell Superficial Hardness of Metallic Materials

(Application for copies should be addressed to: American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

2.1.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENTS

3.1 Materials. Materials shall be in accordance with the applicable drawings, specifications, and standards.

3.2 Parts. The parts shall comply with all requirements specified on applicable drawings, associated drawings, and with all requirements specified in applicable specifications and standards.

3.3 Spring embrittlement. Plated springs shall not break when extended to the point of minimum permanent distortion.

3.4 Continuity resistance of the flexible cable (Drawing 9277774). The continuity resistance, measured from each of the two (2) detonator terminal pads at open end of cable to the ground terminal pad at the open end of cable shall be less than one hundred (100) milliohms. The continuity resistance measured from each of the terminal pads at closed end of cable to the adjacent terminal pad at the closed end of cable shall be less than one hundred (100) milliohms.

3.5 First article inspection. This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

3.6 Workmanship.

3.6.1 Plastic and metal characteristics. All components shall be free from cracks, splits, cold flow, shrinkage, cold shuts, inclusion, porosity, or any similar characteristic.

3.6.2 Burrs. Parts shall be free from burrs.

3.6.3 Foreign matter. Parts shall be free from chips, dirt, grease, rust, corrosion, or any embedded foreign material.

3.6.4 Cleaning. The cleaning method shall not be injurious to any of the parts, nor shall the parts be contaminated by the cleaning agent.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection and standard quality assurance provisions. Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply, and are hereby made a part of this detail specification.

4.2 Classification of inspections. The following type of inspection shall be conducted on this item.

a. First Article Inspection
b. Quality Conformance Inspection

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article sample, as designated by the Contracting Officer, for evaluation in accordance with the provisions of 4.3.2 and 4.3.3. The first article sample shall consist of the following items in the sample quantities indicated.

Part Description	Drawing	Quantity
Cable, Flexible	9277774	10
Lock, Centrifugal	9277786	10
"G" Weight	9277790	10
Lock, "G" Weight	9277871	10
Clip, Grounding	9278001	10
Housing	9278008	10
Slider	9278086	10
Setback Pin	9317584	10

4.3.2 Inspections to be performed. See MIL-A-48078 and also Table I specified herein.

4.3.3 Rejection. See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection

CLASSIFICATION OF DEFECTS & TESTS

MIL-S-48735A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 2		DRAWING NUMBER
	S & A Metals Parts				See Below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Cable, Flexible (Dwg. 9277774)				
	Examination for defects	10		3.2	4.4.2.1
	Continuity resistance	10		3.4	4.5.4
	Lock, Centrifugal (Dwg. 9277786)				
	Examination for defects	10		3.2	4.4.2.2
	"G" Weight (Dwg. 9277790)				
	Examination for defects	10		3.2	4.4.2.3
	Hardness	Note 1		3.2	4.5.1
	Lock, "G" Weight (Dwg. 9277871)				
	Examination for defects	10		3.2	4.4.2.19
	Hardness	Note 1		3.2	4.5.1
	Clip, Grounding (Dwg. 9278001)				
	Examination for defects	10		3.2	4.4.2.23
	Housing (Dwg. 9278008)				
	Examination for defects	10		3.2	4.4.2.25

NOTES:

1. Ten (10) parts shall be selected from each heat treat batch.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection

CLASSIFICATION OF DEFECTS & TESTS

MIL-S-48735A(AR)

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER
	S & A Metals Parts				See Below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Slider (Dwg. 9278086)				
	Examination for defects	10		3.2	4.4.2.29
	Hardness	Note 1		3.2	4.5.1
	Setback Pin (Dwg. 9317584)				
	Examination for defects	10		3.2	4.4.2.34
	Hardness	Note 1		3.2	4.5.1

NOTES:

1. Ten (10) parts shall be selected from each heat treat batch.

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078.

4.4.2 Examination. See MIL-A-48078.

a. Sampling plans. Unless otherwise specified in the classification of defects and test tables, sampling plans and procedures for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.1	Cable, Flexible				9277774
					NEXT HIGHER ASSEMBLY 9277868
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Location of terminal holes		0.40%	3.2	Gage
102	Diameter of terminal holes		0.40%	3.2	Gage
103	Continuity resistance	Note 1	0.40%	3.4	4.5.4
104	Any bridging of copper between conductive path		100%	3.2	Visual
105	Any separation of plastic lamination		0.40%	3.2	Visual
Minor					
201	Profile of cable		0.65%	3.2	Visual
202	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

1. Any cable which fails to comply with the specified resistance shall be classed defective and removed from the lot. (Non-destructive test).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-S-48735A(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.2	Lock, Centrifugal		9277786
			NEXT HIGHER ASSEMBLY
			9278015

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Large outside diameter		0.40%	3.2	Gage
102	Small outside diameter		0.40%	3.2	Gage
103	Overall length		0.40%	3.2	Gage
104	Length to shoulder		0.40%	3.2	Gage
105	Inside diameter (min)		0.40%	3.2	Gage
106	Surface finish improper		0.40%	3.2	Visual
107	Protective finish missing, or improper		0.40%	3.2	Certification
108	Chamfer missing		0.40%	3.2	Visual
109	Length from small diameter end to start of groove (max)		0.40%	3.2	Gage
110	Length from shoulder to start of groove (max)		0.40%	3.2	Gage
111	Depth of groove (min)		0.40%	3.2	Gage
112	Chamfer at open end of lock, missing or improper		0.40%	3.2	Visual/Gage
Minor					
201	Depth of counterbore		0.65%	3.2	Gage
202	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.3	"G" Weight		9277790
			NEXT HIGHER ASSEMBLY 9278015

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Length		0.40%	3.2	Gage
102	Outside diameter		0.40%	3.2	Gage
103	Diameter of counterbore		0.40%	3.2	Gage
104	Surface finish improper		0.40%	3.2	Gage
105	Hardness	4.4.3.1		3.2	4.5.1
106	Chamfer missing or improper		0.40%	3.2	Visual
107	Protective finish missing, or improper		0.40%	3.2	Visual
Minor					
201	Depth of counterbore		0.65%	3.2	Gage
202	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-S-48735A(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.4	Holder, Spring		9277794
			NEXT HIGHER ASSEMBLY 9278015

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Material improper			3.1	Certificate of conformance
102	Outside diameter		0.40%	3.2	Gage
103	Chamfer missing or improper		0.40%	3.2	Visual
104	Height of outside diameter		0.40%	3.2	Gage
105	Overall height		0.40%	3.2	Gage
106	Flatness		0.40%	3.2	Gage
Minor					
201	Protective finish missing or improper		0.65%	3.2	Visual
202	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-S-48735A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9277808
4.4.2.5	Shield Assembly				NEXT HIGHER ASSEMBLY 9278015
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Location of shield (Dwg. 9277810)		0.40%	3.2	Gage
102	Shield (9277810) flush to .01 below flush with shield (9277809) surface "X"		0.40%	3.2	Gage
103	True position of the two shields		0.40%	3.2	Gage
104	Spot weld(s) missing or not secure		0.40%	3.2	Visual/Manual
Minor					
201	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

12

Source: https://assist.dla.mil - Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-S-48735A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9277809
4.4.2.6	Shield, MDF				NEXT HIGHER ASSEMBLY 9277808
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	True position of four equally spaced holes		0.40%	3.2	Gage
102	Diameter of four equally spaced holes (min)		0.40%	3.2	Gage
103	Inside diameter		0.40%	3.2	Gage
104	Thickness		0.40%	3.2	Gage
Minor					
201	Height		0.65%	3.2	Gage
202	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

Source: https://assist.dla.mil - Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-S-48735A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.7	Shield				9277810
					NEXT HIGHER ASSEMBLY
					9277808
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Radius of curvature		0.40%	3.2	Gage
102	Thickness		0.40%	3.2	Gage
103	Arc length		0.40%	3.2	Gage
Minor					
201	Length		0.65%	3.2	Gage
202	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

Source: https://assist.dla.mil - Downloaded: 2020-10-25T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-S-48735A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9277812
4.4.2.8	Disc, Closure, Lock				NEXT HIGHER ASSEMBLY 9278015
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Diameter		0.40%	3.2	Gage
102	Thickness		0.40%	3.2	Gage
103	Flatness		0.40%	3.2	Gage
Minor					
201	Protective finish missing or improper		0.65%	3.2	Visual
202	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-S-48735A(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.9	Closure, "G" Weight		9317589
			NEXT HIGHER ASSEMBLY 9278015

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Outside diameter		0.40%	3.2	Gage
102	Thickness		0.40%	3.2	Gage
103	Radius, max		0.40%	3.2	Gage
104	Diameter, hole		0.40%	3.2	Gage
105	True position of hole		0.40%	3.2	Gage
106	Flatness		0.40%	3.2	Gage
107	Protective finish missing or improper		0.40%	3.2	Visual
Minor					
201	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-S-48735A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9317590
4.4.2.10	Closure, Slider				NEXT HIGHER ASSEMBLY 9278015
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Outside diameter		0.40%	3.2	Gage
102	Thickness		0.40%	3.2	Gage
103	Chamfer missing or improper		0.40%	3.2	Visual
104	Diameter, Hole		0.40%	3.2	Gage
105	True position of hole		0.40%	3.2	Gage
106	Flatness		0.40%	3.2	Gage
107	Protective finish missing or improper		0.40%	3.2	Visual
Minor					
201	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-S-48735A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9277832
4.4.2.11	Spring, Slider, Lock				NEXT HIGHER ASSEMBLY 9278015
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Outside diameter		0.40%	3.2	Gage
102	Load at specified height	4.4.3.4		3.2	Gage/4.5.5
103	Spring rate	4.4.3.2	---	3.2	4.5.2
104	Spring embrittlement	4.4.3.3	---	3.3	4.5.3
Minor					
201	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-S-48735A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9277833
4.4.2.12	Spring, Slider				NEXT HIGHER ASSEMBLY 9278015
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Outside diameter		0.40%	3.2	Gage
102	Load at specified height	4.4.3.4	---	3.2	Gage/4.5.5
103	Spring rate	4.4.3.2	---	3.2	4.5.2
104	Spring embrittlement	4.4.3.3	---	3.3	4.5.3
Minor					
201	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-S-48735A(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.13	Spring, Centrifugal, Lock		9277834
			NEXT HIGHER ASSEMBLY 9278015

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Outside diameter		0.40%	3.2	Gage
102	Load at specified height	4.4.3.4	---	3.2	Gage/4.5.5
103	Spring rate	4.4.3.2	---	3.2	4.5.2
Minor					
201	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-S-48735A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9277835
4.4.2.14	Spring, "G" Weight				NEXT HIGHER ASSEMBLY 9278015
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Outside diameter		0.40%	3.2	Gage
102	Load at specified height	4.4.3.4	---	3.2	Gage/4.5.5
103	Spring rate	4.4.3.2	---	3.2	4.5.2
Minor					
201	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-S-48735A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9277843
4.4.2.15	Cup				NEXT HIGHER ASSEMBLY 9277848
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Length		0.40%	3.2	Gage
102	Width		0.40%	3.2	Gage
103	Radius of ends		0.40%	3.2	Gage
104	Short height		0.40%	3.2	Gage
105	Long height		0.40%	3.2	Gage
106	Location of hole		0.40%	3.2	Gage
107	Diameter or hole		0.40%	3.2	Gage
Minor					
201	Thickness of material		0.65%	3.2	Gage
202	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

Source: https://assist.dla.mil - Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-S-48735A(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.16	Cup, Closure	1 OF 1	9277846
			NEXT HIGHER ASSEMBLY
			9277858

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Length		0.40%	3.2	Gage
102	Width		0.40%	3.2	Gage
103	Short height		0.40%	3.2	Gage
104	Long height		0.40%	3.2	Gage
Minor					
201	Thickness of material		0.65%	3.2	Gage
202	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

Source: https://assist.dla.mil - Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-S-48735A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9277848
4.4.2.17	Cup and Tube Assembly				NEXT HIGHER ASSEMBLY 9277855
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Any part damaged		0.40%	3.2	Visual
102	Length of protrusion of tubing		0.40%	3.2	Gage
103	Weld missing or insecure		0.40%	3.2	Visual/Manual
Minor					
201	Finish missing or improper		0.65%	3.2	Visual
202	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

Source: https://assist.dla.mil - Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-S-48735A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.18	Tubing				9277854
					NEXT HIGHER ASSEMBLY
					9277848
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Length		0.40%	3.2	Gage
102	Outside diameter		0.40%	3.2	Gage
103	Inside diameter		0.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

Source: https://assist.dla.mil - Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-S-48735A(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER 9277871
4.4.2.19	Lock "G" Weight		NEXT HIGHER ASSEMBLY 9278015

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Large diameter (min) both ends		0.40%	3.2	Gage
102	Small diameter (max) both ends		0.40%	3.2	Gage
103	Hardness	4.4.3.1		3.2	Gage
104	Chamfer of large dia. two surfaces at hole end		0.40%	3.2	Visual
105	Overall length (max)		0.40%	3.2	Gage
106	Length to large diameter from hole end		0.40%	3.2	Gage
107	Length to end of large diameter from hole end		0.40%	3.2	Gage
108	Diameter, hole		0.40%	3.2	Gage
109	Depth of hole		0.40%	3.2	Gage
110	Protective finish missing or improper		0.40%	3.2	Visual
Minor					
201	Length of large diameter at closed end		0.65%	3.2	Gage
202	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-S-48735A(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.20	Dual MDF Chamber		9277978
			NEXT HIGHER ASSEMBLY 9277986

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Outside diameter		0.40%	3.2	Gage
102	Length		0.40%	3.2	Gage
103	Length of O.D. to bottom of chamfer		0.40%	3.2	Gage
104	Width of slot		0.40%	3.2	Gage
105	Depth of slot		0.40%	3.2	Gage
106	Diameter of large holes (2)		0.40%	3.2	Gage
107	True position of large holes		0.40%	3.2	Gage
108	Diameter of small hole		0.40%	3.2	Gage
109	True position of small hole		0.40%	3.2	Gage
110	Protective finish missing or improper		0.40%	3.2	Visual
Minor					
201	Width of tang		0.65%	3.2	Gage
202	Diameter of thru holes (2)		0.65%	3.2	Gage
203	Depth from bottom of large hole(s) to bottom of thru hole(s)		0.65%	3.2	Gage
204	Depth of small hole		0.65%	3.2	Gage
205	Chamfer on bottom surface		0.65%	3.2	Gage
206	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-S-48735A(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.21	Interrupter		9277979
			NEXT HIGHER ASSEMBLY 9278015

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Large O.D.		0.40%	3.2	Gage
102	Small O.D.		0.40%	3.2	Gage
103	Length		0.40%	3.2	Gage
104	Length of small O.D.		0.40%	3.2	Gage
105	Undercut missing		0.40%	3.2	Visual
106	Protective finish missing or improper		0.40%	3.2	Visual
Minor					
201	Chamfer of large O.D.		0.65%	3.2	Visual
202	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-S-48735A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9277991
4.4.2.22	Pin, Locating				NEXT HIGHER ASSEMBLY 9277986
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	Length		0.65%	3.2	Gage
202	Protective finish missing or improper		0.65%	3.2	Visual
203	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

Source: https://assist.dla.mil - Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-S-48735A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9278001
4.4.2.23	Clip Grounding				NEXT HIGHER ASSEMBLY 9278015
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Material improper		--	3.1	Certificate of conformance
102	Inside length		0.40%	3.2	Gage
103	Location of tab		0.40%	3.2	Gage
104	Height of tab		0.40%	3.2	Gage
105	Width of tab		0.40%	3.2	Gage
106	Width of legs		0.40%	3.2	Gage
107	Radius of legs		0.40%	3.2	Gage
108	Two spherical indentations missing		0.40%	3.2	Visual
109	Tabs at leg bottoms missing		0.40%	3.2	Visual
110	Any fracturing at bends		0.40%	3.2	Visual
111	Protective finish missing or improper		0.40%	3.2 Note 1	Visual
Minor					
201	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES: 1. Per MIL-T-10727, paragraphs 3.4 and 3.5.

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-S-48735A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.24	Holder, Lead				9278004
					NEXT HIGHER ASSEMBLY
					9278011
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Small outside diameter		0.40%	3.2	Gage
102	Large outside diameter		0.40%	3.2	Gage
103	True position of large O.D. to small O.D.		0.40%	3.2	Gage
104	Diameter of small thru hole (max)		0.40%	3.2	Gage
105	True position of small thru hole		0.40%	3.2	Gage
106	Diameter of large thru hole		0.40%	3.2	Gage
107	True position of large thru hole		0.40%	3.2	Gage
108	Length of slot		0.40%	3.2	Gage
109	Width of slot		0.40%	3.2	Gage
110	True position of slot		0.40%	3.2	Gage
111	Depth of slot		0.40%	3.2	Gage
Minor					
201	Length from solid end to shoulder		0.65%	3.2	Gage
202	Length from shoulder end to chamfer		0.65%	3.2	Gage
203	Protective finish missing or improper		0.65%	3.2	Visual
204	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

Source: https://assist.dla.mil/ Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-S-48735A(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.25	Housing (Rear Lock)	1 OF 5	9278008
			NEXT HIGHER ASSEMBLY 9278015

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Large outside diameter		0.40%	3.2	Gage
102	Small outside diameter		0.40%	3.2	Gage
103	True position of small O.D. to large O.D.		0.40%	3.2	Gage
104	Distance of small O.D. to flat		0.40%	3.2	Gage
105	Overall length		0.40%	3.2	Gage
106	Length from closed end to edge of shoulder		0.40%	3.2	Gage
107	Diameter of large center hole		0.40%	3.2	Gage
108	True position of large center hole		0.40%	3.2	Gage
109	Diameter of small center hole		0.40%	3.2	Gage
110	True position of small diameter center hole		0.40%	3.2	Gage
111	Diameter of counterbore at the small center hole end (Sect A-A)		0.40%	3.2	Gage
112	Depth of counterbore at the small center hole end (Sect B-B)		0.40%	3.2	Gage
113	True position of counterbore at the small center hole end (Sect A-A)		0.40%	3.2	Gage
114	Length from bottom of large diameter center hole to end of small diameter center hole (Sect B-B)		0.40%	3.2	Gage
115	Radius of curvature from large diameter to small diameter center hole		0.40%	3.2	Gage
116	Diameter of long hole parallel to center hole		0.40%	3.2	Gage
117	True position of long hole parallel to center hole		0.40%	3.2	Gage

NOTES:

Source: https://assist.dla.mil - Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-S-48735A(AR)

PARAGRAPH	TITLE	SHEET 2 OF 5	DRAWING NUMBER
4.4.2.25	Housing (Rear Lock)		9278008
			NEXT HIGHER ASSEMBLY 9278015

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
118	True position of hole perpendicular to long hole and center hole (Sect A-A)		0.40%	3.2	Gage
119	Diameter of hole perpendicular to long hole and center hole (Sect A-A)		0.40%	3.2	Gage
120	True position of small diameter hole in detail "F", sht. 2		0.40%	3.2	Gage
121	Diameter of small diameter hole detail F		0.40%	3.2	Gage
122	True position of larger diameter hole, detail F		0.40%	3.2	Gage
123	True position of the four equally spaced holes		0.40%	3.2	Gage
124	Small diameter of the four equally spaced holes		0.40%	3.2	Gage
125	Large diameter of the four equally spaced holes		0.40%	3.2	Gage
126	Depth to shoulder of the four equally spaced holes		0.40%	3.2	Gage
127	Location of the two thru holes in side cutout (View H-H)		0.40%	3.2	Gage
128	Small diameter of the two holes in side cutout (Sect B-B)		0.40%	3.2	Gage
129	Large diameter of the two holes in side cutout (Sect B-B)		0.40%	3.2	Gage
130	Length of the smaller diameter portion of the two thru holes		0.40%	3.2	Gage
131	True position of the two centrifugal lock holes (Sect AA of Sht 2)		0.40%	3.2	Gage
132	Large diameter of the two centrifugal lock holes		0.40%	3.2	Gage
133	Small diameter of the two centrifugal lock holes (Sect K-K)		0.40%	3.2	Gage

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-S-48735A(AR)

PARAGRAPH	TITLE		SHEET 3 OF 5		DRAWING NUMBER 9278008
4.4.2.25	Housing (Rear Lock)				NEXT HIGHER ASSEMBLY 9278015
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
134	Depth of large diameter of centrifigal lock holes (Sect K-K)		0.40%	3.2	Gage
135	Diameter of C bore of centrifugal lock holes		0.40%	3.2	Gage
136	Depth of C bore of centrifugal lock holes		0.40%	3.2	Gage
137	True position of the long transverse hole (2 sides)		0.40%	3.2	Gage
138	Diameter of the transverse hole		0.40%	3.2	Gage
139	Diameter of the counterbore of transverse hole (2 sides)		0.40%	3.2	Gage
140	Depth of the counterbore of transverse hole (2 sides)		0.40%	3.2	Gage
141	True position of large diameter transverse hole in slot		0.40%	3.2	Gage
142	Diameter of large transverse hole in slot		0.40%	3.2	Gage
143	Depth from bottom of transverse hole to O.D. of center hole (sect GG, sht 3)		0.40%	3.2	Gage
144	True position of small diameter hole in bottom of large diameter transverse hole		0.40%	3.2	Gage
145	Diameter of small diameter hole in bottom of large transverse hole		0.40%	3.2	Gage
146	Length of slot in bottom of large diameter transverse hole		0.40%	3.2	Gage
147	Width of slot in bottom of large diameter transverse hole		0.40%	3.2	Gage
148	True position of slot in bottom of diameter transverse hole		0.40%	3.2	Gage

NOTES:

Source: https://assist.dla.mil - Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-S-48735A(AR)

PARAGRAPH	TITLE	SHEET 4 OF 5	DRAWING NUMBER
4.4.2.25	Housing (Rear Lock)		9278008
			NEXT HIGHER ASSEMBLY 9278015

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
149	Diameter of transverse hole, Sect J-J		0.40%	3.2	Gage
150	True position of transverse hole, Sect J-J		0.40%	3.2	Gage
151	Location of hole perpendicular to transverse hole in sect. J-J at edge of small O.D.		0.40%	3.2	Gage
152	Large diameter of hole perpendicular to transverse hole in sect. J-J at edge of small O.D.		0.40%	3.2	Gage
153	True position of above hole		0.40%	3.2	Gage
154	Small diameter of hole perpendicular to transverse hole in sect. J-J at edge of small O.D.		0.40%	3.2	Gage
155	True position of above hole		0.40%	3.2	Gage
156	Length of large diameter section of above hole (sect M-M)		0.40%	3.2	Gage
157	Length of small diameter section of above hole (sect M-M)		0.40%	3.2	Gage
158	Diameter of C bore at end center hole (sect N-N)		0.40%	3.2	Gage
159	Depth of C bore of above hole		0.40%	3.2	Gage
160	Diameter of C bore at end hole parallelling center hole (sect N-N)		0.40%	3.2	Gage
161	Depth of C bore of above hole (sect N-N)		0.40%	3.2	Gage
162	Length of large O.D.		0.40%	3.2	Gage
163	Surface finishes improper		0.40%	3.2	Gage
164	Material improper		0.40%	3.1	Certificate of Conformance

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-S-48735A(AR)

PARAGRAPH	TITLE		SHEET 5 OF 5		DRAWING NUMBER 9278008
4.4.2.25	Housing (Rear Lock)				NEXT HIGHER ASSEMBLY 9278015
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
165	Width Slot "A"		0.40%	3.2	Gage
166	Width Slot "B"		0.40%	3.2	Gage
Minor					
201	Angle of the shoulder between the small O.D. and large O.D.		0.65%	3.2	Gage
202	Angle of the slot		0.65%	3.2	Gage
203	Depth of the long hole parallel to the center hole		0.65%	3.2	Gage
204	Depth to the second shoulder of the detail "F" hole		0.65%	3.2	Gage
205	Depth from small outside diameter to bottom of side cutout containing the two thru holes		0.65%	3.2	Gage
206	Evidence of poor workmanship		0.65%	3.6	Visual
207	Protective finish missing or improper		0.65%	3.2	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-S-48735A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.26	Closure, Lock, Rear				9278010
					NEXT HIGHER ASSEMBLY
					9278015
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Diameter		0.40%	3.2	Gage
102	Thickness		0.40%	3.2	Gage
103	Flatness		0.40%	3.2	Gage
Minor					
201	Protective finish missing or improper		0.65%	3.2	Visual
202	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

Source: https://assist.dla.mil - Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9278057
4.4.2.27	Lock, Rear				NEXT HIGHER ASSEMBLY 9278015
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Large outside diameter		0.40%	3.2	Gage
102	Small outside diameter		0.40%	3.2	Gage
103	Overall length		0.40%	3.2	Gage
104	Length to shoulder		0.40%	3.2	Gage
105	Radius missing or improper		0.40%	3.2	Gage
106	Hardness	4.4.3.1		3.2	Gage
107	Surface finish improper		0.40%	3.2 Note 1	Gage
Minor					
201	Chamfer missing or improper		0.65%	3.2	Visual
202	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

1. Certification of passivation required for alternate material.

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-S-48735A(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.28	Lock, Slider (Maraging Steel)		9278060
			NEXT HIGHER ASSEMBLY 9278015

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Diameter of pin (along length with spherical end)		0.40%	3.2	Gage
102	Diameter of shoulder (max)		0.40%	3.2	Gage
103	True position of shoulder diameter to pin diameter		0.40%	3.2	Gage
104	Hardness	4.4.3.1	--	3.2	4.5.1/Gage
Minor					
201	Length from front face of shoulder to spherical tip		0.65%	3.2	Gage
202	Length from rear face of shoulder to spherical tip		0.65%	3.2	Gage
203	Total length		0.65%	3.2	Gage
204	Diameter of pin (along length with flat end)		0.65%	3.2	Gage
205	Protective finish missing or improper		0.65%	3.2	Visual
206	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-S-48735A(AR)

PARAGRAPH	TITLE	SHEET 1 OF 2	DRAWING NUMBER
4.4.2.29	Slider		9278086
			NEXT HIGHER ASSEMBLY
			9278011

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Large O.D. of body		0.40%	3.2	Gage
102	Small O.D. of body		0.40%	3.2	Gage
103	True position of small O.D. to large O.D.		0.40%	3.2	Gage
104	Small inside diameter (max)		0.40%	3.2	Gage
105	True position of I.D. to O.D.		0.40%	3.2	Gage
106	Large I.D.		0.40%	3.2	Gage
107	True position of large I.D. to small I.D.		0.40%	3.2	Gage
108	Runout of firing pin		0.40%	3.2	Gage
109	O.D. of firing pin shaft		0.40%	3.2	Gage
110	Location of radius from small O.D. to large O.D.		0.40%	3.2	Gage
111	Radius from small O.D. to large O.D.		0.40%	3.2	Gage
112	Length of hole in slot (min)		0.40%	3.2	Gage
113	True position of slot (total)		0.40%	3.2	Gage
114	Depth of slot (min)		0.40%	3.2	Gage
115	Length of firing pin		0.40%	3.2	Gage
116	Location of the four (4) equally spaced holes		0.40%	3.2	Gage
117	True position of the pair of holes adjacent to the open end		0.40%	3.2	Gage
118	True position of the pair of center holes		0.40%	3.2	Gage
119	True position of the single hole adjacent to the closed end		0.40%	3.2	Gage

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-S-48735A(AR)

PARAGRAPH	TITLE	SHEET 2 OF 2	DRAWING NUMBER
4.4.2.29	Slider		9278086
			NEXT HIGHER ASSEMBLY 9278011

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
120	Distance from O.D. to edge of groove at closed end (max) both sides		0.40%	3.2	Gage
121	Width of groove (2)		0.40%	3.2	Gage
122	Depth of groove (2)		0.40%	3.2	Gage
123	Surface finish improper		0.40%	3.2	Gage
124	Hardness	4.4.3.1		3.2	4.5.1/Gage
125	Diameter of firing pin flat		0.40%	3.2	Gage
126	Angle of firing pin		0.40%	3.2	Gage
127	Length from the end of the slot to hole adjacent to closed end of slider		0.40%	3.2	Gage
Minor					
201	Length from open end to base of pin		0.65%	3.2	Gage
202	Depth from open end to bottom		0.65%	3.2	Gage
203	Chamfer missing		0.65%	3.2	Visual
204	Depth of cutout in end of body		0.65%	3.2	Gage
205	Length of cutout in end of body		0.65%	3.2	Gage
206	Protective finish missing or improper		0.65%	3.2	Visual
207	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.30	Spacer, Cable		9278106
			NEXT HIGHER ASSEMBLY 9278015

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Contour of spacer above max.	Note 1	0.40%	3.2	Gage
102	Thickness	Note 1	0.40%	3.2	Gage
Minor					
201	Location of holes	Note 1	0.65%	3.2	Gage
202	Depth of holes	Note 1	0.65%	3.2	Gage
203	Angle of holes	Note 1	0.65%	3.2	Gage
204	Evidence of poor workmanship	Note 1	0.65%	3.6	Visual

NOTES:
1. See 4.5.6 for alternative method of inspection.

Source: https://assist.dla.mil - Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-S-48735A(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.31	Retainer, Spring		9278042
			NEXT HIGHER ASSEMBLY 9278015

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Flatness		0.40%	3.2	Gage
102	Diameter improper (min)		0.40%	3.2	Gage
103	Thickness improper (min)		0.40%	3.2	Gage
Minor					
201	Protective finish missing or improper		0.65%	3.2	Visual
202	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

Source: https://assist.dla.mil - Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-S-48735A(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.32	Spring, "G" Weight Lock		9278046
			NEXT HIGHER ASSEMBLY 9278015

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Outside diameter		0.40%	3.2	Gage
102	Loads at specified heights improper	4.4.3.4	---	3.2	4.5.5/Gage
Minor					
201	Ends not squared		0.65%	3.2	Visual
202	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-S-48735A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9278109
4.4.2.33	Spring, Rear Lock				NEXT HIGHER ASSEMBLY 9278015
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Outside diameter		0.40%	3.2	Gage
102	Load at specified height	4.4.3.4	---	3.2	4.5.5/Gage
103	Spring rate	4.4.3.2	---	3.2	4.5.2
104	Spring embrittlement	4.4.3.3	---	3.2	4.5.3
Minor					
201	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-S-48735A(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.34	Setback Pin		9317584
			NEXT HIGHER ASSEMBLY 9317617

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Overall length		0.40%	3.2	Gage
102	Length from end of short pin to shoulder		0.40%	3.2	Gage
103	Length from end of long pin to shoulder		0.40%	3.2	Gage
104	Large O.D.		0.40%	3.2	Gage
105	O.D. of short pin		0.40%	3.2	Gage
106	O.D. of long pin		0.40%	3.2	Gage
107	True position of short pin		0.40%	3.2	Gage
108	Hardness	4.4.3.1		3.2	4.5.1
109	Hole location		0.40%	3.2	Gage
110	Hole diameter		0.40%	3.2	Gage
111	True position of hole		0.40%	3.2	Gage
Minor					
201	Protective finish missing or improper		0.65%	3.2	Visual
202	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-S-48735A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9317585
4.4.2.35	Spring, Setback Pin				NEXT HIGHER ASSEMBLY 9278015
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Outside diameter		0.40%	3.2	Gage
102	Load at specified height	4.4.3.4		3.2	Gage/4.5.5
103	Spring rate	4.4.3.2		3.2	4.5.2
Minor					
201	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-S-48735A(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER 9317591
4.4.2.36	Closure, Firing Pin		NEXT HIGHER ASSEMBLY 9278015

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Outside diameter		0.40%	3.2	Gage
102	Inside diameter		0.40%	3.2	Gage
103	True position of inside diameter		0.40%	3.2	Gage
104	Thickness		0.40%	3.2	Gage
105	Length and angle of chamfer		0.40%	3.2	Gage
106	Flatness		0.40%	3.2	Gage (1)
107	Protective finish missing or improper		0.65%	3.2	Visual
Minor					
201	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

(1). Applicable only to stamped parts.

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-S-48735A(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.37	Cup, Booster		9278023
			NEXT HIGHER ASSEMBLY
			9278024

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Length		0.40%	3.2	Gage
102	O.D.		0.40%	3.2	Gage
103	I.D.		0.40%	3.2	Gage
104	True position of I.D.		0.40%	3.2	Gage
105	Thickness		0.40%	3.2	Gage
106	Surface finish, I.D.		0.40%	3.2	Gage
107	Radius improper		0.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 which is Obsolete.

Source: https://assist.dla.mil - Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-S-48735A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9317616
4.4.2.38	Pin, Stop				NEXT HIGHER ASSEMBLY 9317617
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Length		0.40%	3.2	Gage
102	Protective finish missing or improper		0.40%	3.2	Visual
Minor					
201	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

Source: https://assist.dla.mil - Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-S-48735A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.39	Setback Pin Assembly				9317617
					NEXT HIGHER ASSEMBLY
					9278015
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major 101	Projected pin length		0.40%	3.2	Gage
Minor 201	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

51

Source: https://assist.dla.mil - Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-S-48735A(AR)

PARAGRAPH	TITLE	SHEET 1 OF 2	DRAWING NUMBER
4.4.2.40	MDF Preform - Right Side		9317647
			NEXT HIGHER ASSEMBLY 9277986

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Material improper		0.40%	3.2	Certification
102	Radius, top, small		0.40%	3.2	Gage
103	Radius, top, large		0.40%	3.2	Gage
104	Length, center line to left edge		0.40%	3.2	Gage
105	Length, center line to right edge		0.40%	3.2	Gage
106	Length from shoulder		0.40%	3.2	Gage
107	Length from shoulder to top of flat		0.40%	3.2	Gage
108	Radius, top, cavity		0.40%	3.2	Gage
109	Radius, middle, cavity		0.40%	3.2	Gage
110	Radius, bottom, cavity		0.40%	3.2	Gage
111	Radius, internal, cavity		0.40%	3.2	Gage
112	Depth from inner surface to right edge Sect A-A		0.40%	3.2	Gage
113	Length from bottom of relief to centerline Sect. A-A		0.40%	3.2	Gage
114	Radius location Sect. A-A		0.40%	3.2	Gage
115	Length from base of preform to bottom of relief Sect. A-A		0.40%	3.2	Gage
116	Length from base of preform to lip. Sect. A-A		0.40%	3.2	Gage
117	Outer radius		0.40%	3.2	Gage
118	Location of large radius		0.40%	3.2	Gage
119	Overall length from base to top of flat		0.40%	3.2	Gage
120	Wall thickness		0.40%	3.2	Gage
121	Large radius, Sect. B-B		0.40%	3.2	Gage

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-S-48735A(AR)

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER 9317647
4.4.2.40 Cont'd	MDF Preform - Right Side				NEXT HIGHER ASSEMBLY 9277986
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
122	Radius of inner wall, Sect. B-B		0.40%	3.2	Gage
123	Flash or sink masks		0.40%	3.6	Gage
Minor					
201	Depth of top		0.65%	3.2	Gage
202	Depth of relief		0.65%	3.2	Gage
203	Depth to inner surface		0.65%	3.2	Gage
204	Location of relief		0.65%	3.2	Gage
205	Angle, outer		0.65%	3.2	Gage
206	Angle, inner		0.65%	3.2	Gage
207	Depth, overall		0.65%	3.2	Gage
208	Chamfer missing or improper		0.65%	3.2	Gage
209	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

1. See 4.5.6 for alternative method of inspection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-S-48735A(AR)

PARAGRAPH	TITLE	SHEET 1 OF 2	DRAWING NUMBER
4.4.2.41	MDF Preform - Left Side		9317648
			NEXT HIGHER ASSEMBLY 9277986

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Material improper			3.2	Certification
102	Radius, top, small		0.40%	3.2	Gage
103	Radius, top, large		0.40%	3.2	Gage
104	Length, certerline to left edge		0.40%	3.2	Gage
105	Length, center line to right edge		0.40%	3.2	Gage
106	Length from shoulder		0.40%	3.2	Gage
107	Radius, top, cavity		0.40%	3.2	Gage
108	Radius, bottom, cavity		0.40%	3.2	Gage
109	Location, centerline, large radius		0.40%	3.2	Gage
110	Radius, internal		0.40%	3.2	Gage
111	Wall thickness		0.40%	3.2	Gage
112	Radius location (.074 ± .001)		0.40%	3.2	Gage
113	Radius (.05-.02), Sect. A-A		0.40%	3.2	Gage
114	Radius location (.070 ± .005), Sect. A-A		0.40%	3.2	Gage
115	Centerline location (0.57 ± .002), Sect. A-A		0.40%	3.2	Gage
116	Radius location (.110 ± .005), Sect A-A		0.40%	3.2	Gage
117	Centerline location (.115 ± .003), Sect. A-A		0.40%	3.2	Gage
118	Length from base to bottom of relief, Sect A-A		0.40%	3.2	Gage
119	Length from base to lip, Sect A-A		0.40%	3.2	Gage
120	Outer radius, Sect. B-B		0.40%	3.2	Gage
121	Inner radius, Sect. B-B		0.40%	3.2	Gage
122	Flash or sink marks		0.40%	3.6	Gage

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-S-48735A(AR)

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER 9317648
4.4.2.41 Cont'd	MDF Preform - Left Side				NEXT HIGHER ASSEMBLY 9277986
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Minor					
201	Depth of top		0.65%	3.2	Gage
202	Depth of relief		0.65%	3.2	Gage
203	Depth to inner surface		0.65%	3.2	Gage
204	Location of relief		0.65%	3.2	Gage
205	Angle, outer		0.65%	3.2	Gage
206	Angle, inner		0.65%	3.2	Gage
207	Depth overall		0.65%	3.2	Gage
208	Chamfer missing or improper		0.65%	3.2	Gage
209	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES: 1. See 4.5.6* for alternative method of inspection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

4.4.3 Testing.

4.4.3.1 Hardness. A sample of five each of the following parts shall be selected from each heat treated lot and tested for hardness; Slider (Dwg. 9278086), "G" Weight (Dwg. 9277790), and Lock "G" Weight (Dwg. 9277871), Lock, Rear (9278057), Lock, Slider (9278060), and Setback Pin (9317584). If any part fails to meet the drawing requirement, the lot represented by the sample shall be rejected.

4.4.3.2 Spring rate. A sample of thirty (30) springs shall be selected from each heat treat batch and tested for specified requirements in accordance with 4.5.2. The heat treat batch shall be rejected if one (1) or more samples are classed defective.

4.4.3.3 Spring embrittlement. Thirty springs shall be selected from each lot and tested for the specified requirements in accordance with 4.5.3. The lot shall be rejected if one (1) or more samples are classed defective.

4.4.3.4 Spring load. Major Defect. Thirty (30) springs shall be selected from each heat treat batch and tested for the specified requirements in accordance with 4.5.5. The heat treat batch shall be rejected if one (1) or more samples are classed defective.

4.4.4 Inspection equipment. The inspection equipment required to perform the inspections and tests prescribed in this specification is identified in the tables of C.D's (commencing with paragraph 4.4.2.1) and in the test method paragraphs (See 4.5). The contractor shall submit inspection equipment designs for approval, in accordance with the terms of the contract. See Section 6 of MIL-A-48078, and Section 6.2 herein.

4.5 Test methods and procedures.

4.5.1 Hardness. Hardness measurements of the parts specified in paragraph 4.4.3.1 shall be performed as specified in ASTM E 18 using a Rockwell "C" hardness tester. Hardness readings of the Slider (Dwg. 9278086), may be obtained by cutting the part and taking a Rockwell "superficial" measurement of the wall. Parts tested shall not be returned to the lot (Destructive test).

4.5.2 Spring rate. The spring shall be tested for the specified spring rate requirement using the specified height requirement on the applicable piece part drawing as one of the computation points. Any spring failing to comply with the specified spring rate requirements shall be classed defective (Non-Destructive Test).

4.5.3 Spring embrittlement. The springs to be tested shall be compressed to their solid height for a minimum of 24 hours. Each spring shall then be stretched until the minimum point of permanent distortion is reached. If any spring breaks when extended to the minimum point of distortion, it shall be classed defective. Springs tested shall not be returned to the lot (Destructive test).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

4.5.4 Continuity resistance. The flexible cables shall be measured for the specified resistance using a milliohmmeter. Any cable exhibiting resistance in excess of the specified resistance shall be classed defective. Accepted units may be returned to the lot (Non-destructive test).

4.5.5 Spring load. The load at the specified height shall abe measured in accordance with the applicable piece part drawing. Any spring failing to comply with the specified load requirements shall be classed defective. (Non-destructive test).

4.5.6 Dimensional control of molded parts. This paragraph applies to the following parts:

Spacer, Cable - 9278106, ref. para. 4.4.2.30
MDF Preform - Right Side, 9317647, ref. para. 4.4.2.40
MDF Preform - Left Side, 9317648, ref. para. 4.4.2.41

In place of the normal sampling associated with the Classification of Defects, a sample of 5 parts, per cavity, per mold shall be consecutively produced and fully inspected for all drawing requirements to qualify a new or reworked cavity for use in production. The molded parts shall carry the individual cavity identification. As a control of each cavity during production, the above quantity of samples from each cavity shall be inspected after continuous production of each 5,000 parts or at the end of each week, whichever occurs first. If any part fails to meet all drawing requirements, production shall be stopped and the mold corrected. Further, that portion of production since the last control check shall be returned to the contractor for inspection of each separate type of defect in accordance with the sampling plan and AQL specified in the referenced paragraphs.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging.

5.1.1 Level C. Preservation and packaging of parts shall be in accordance with MIL-STD-1188.

5.2 Packing.

5.2.1 Level C. Packing shall be in accordance with MIL-STD-1188.

5.3 Marking.

5.3.1 Level C. Marking shall be in accordance with MIL-STD-1188.

6. NOTES

6.1 Ordering data. Procurement documents shall specify the following:

a. Title, number and date of this specification.
b. Provisions for submission of first article samples.
c. Provisions of MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

6.2 Submission of inspection equipment designs for approval. (See MIL-A-48078). Submit equipment designs as required to Commander: ARRADCOM, ATTN: DRDAR-QAT-I, Dover, NJ 07801.

6.3 Distribution of ammunition data cards. Distribution of data cards shall include the following: Commander, ARRADCOM, ATTN: DRDAR-QAT-M, Dover, NJ 07801.

6.4 Drawings. Drawings listed in Section 2 of this specification under the heading US Army Armament Research and Development Command (ARRADCOM) may also include drawings prepared by, and identified as, Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal, or Picatinny Arsenal drawings. Technical data originally prepared by these activities is now under the cognizance of ARRADCOM.

Custodian:
Army-AR

Preparing Activity:
Army-AR

(Project 1345-A180)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.