MIL-W-48757 (PA)
28 March 1975

MILITARY SPECIFICATION

WARHEAD SECTION, GM, HE: XM251

SPARE PARTS FOR

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers the spare parts for one type of Warhead designated as Warhead Section, GM, HE: XM251.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-T-5021	- Tests Aircraft and Missile Welding Operator's Qualifications
MIL-B-6812	- Bolt, Aircraft
MIL-I-6866	- Inspection Process, Magnetic Particle
MIL-S-7742	- Screw Threads, Standard Optimum Selected Series: General Specification For
MIL-W-8604	- Welding of Aluminum Alloys, Process For
MIL-A-48078	- Ammunition, Standard Quality Assurance Provisions, General Specification For

FSC: 1340

2732

s/s

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes (ABC-STD-105)

MIL-STD-453 - Inspection, Radiographic

DRAWINGS

PICATINNY ARSENAL

PRODUCT AND PACKING DRAWINGS

8808362 Packing and Marking for Storage and Shipment
8808932 Packing for Hardware and Related Items
8877425 Pin, Alignment
8877426 Pin, Shear
8883534 Box, Packing for Repair Parts
8883538 Bag, Packing for Repair Parts
9208288 Plunger, Spring
9208329 Lock, "T", Bolt
9208608 Nose Assembly
9237309 Nut, External Wrenching
9237322 Bolt, Tee
9267740 Seal, Aft Section
9281653 Cover, Protective and Flag Assembly, Sta. 100
9295054 Packing and Marking for Box Packing Ammunition, for Ogive, Rocket: Nose Cone Conical: or Nose Cone, Ogival

2.2 Other publications.-The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on the date of invitation for bids or request for proposal shall apply.

AMERICAN SOCIETY FOR TESTING AND MATERIALS

ASTM E 8-69 - Tension Testing of Metallic Material

(Application for copies should be addressed to: American Society for Testing and Materials, 1916 Race Street, Philadelphia, Pa. 19103)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Material.-Materials shall be in accordance with the applicable drawings and specifications.

3.2 Parts.-The parts shall comply with all requirements specified on drawings 8877425, 8877426, 9208288, 9208329, 9208608, 9237309, 9237322, 9267740 and 9281653, all associated drawings, and with all requirements specified in applicable specifications.

3.3 Mechanical properties.-Cold-working or heat-treating (including quenching-and-tempering, normalizing, normalizing-and-tempering, annealing, and stress-relieving) operations, shall be performed in such a manner as to produce the specified properties uniformly through-out the entire lot. The contractor shall determine the detailed procedures to produce parts meeting the required mechanical properties. These procedures shall be documented and submitted with the first article sample to the Contracting Officer. Changes in these procedures shall also be documented and submitted to the Contracting Officer.

3.4 Welding.-All skin welds shall be reasonably smooth and free of craters. They shall exhibit characteristics of good fusion, penetration and soundness of deposit representative of good welding practice. The process shall be such as to prevent warpage beyond dimensional requirements.

3.4.1 Qualification of Welders and Welding Equipment.-Only welders qualified in accordance wtih Specification MIL-T-5021 shall be permitted to weld aluminum components. A complete qualification test for each welder or welding operator in making warhead skins shall consist of making a butt weld qualification test coupon in accordance with Specification MIL-T-5021. The test coupon shall be of the same type and grade of material and the same thickness to be used in making the longitudinal seam of the warhead skins. The test coupons must satisfactorily pass the test specified in Specification MIL-T-5021. Welding equipment shall be qualified in accordance with MIL-W-8604.

3.4.2. Material Sag.-Sag of material in the area adjacent to the weld shall not be more than .010 below the surface of the joined part.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

3.4.3 Penetrant examination.-Cracks and porous areas shall not exceed 1/2 inch in length in each one inch length. The total length of all cracks and porous areas shall not be more than 2 inches in any skin section. Penetrant examination shall be used to inspect for these defects.

3.4.4 Blow-outs.-Blowouts may be repaired by hand welding provided they do not exceed 1/2 inch in width and 1 inch in length. No more than 3 such areas may be repaired in any skin section.

3.4.5 Mechanical properties of welds.-The tensile strength of aluminum welds shall not be less than 30,000 pounds per square inch, the yield strength shall not be less than 25,000 pounds per square inch, and the elongation shall not be more than eight (8) percent.

3.5 Mechanical properties of component parts.-The aluminum used in fabrication of the components shall comply with the minimum requirements specified in the applicable specification for the heat treatment conditions required.

3.6 Functioning of nose assembly.-The nose assembly with the telescope tube held firmly shall be moved forward, rotated and returned to the original position without any motion stoppage due to interference between parts.

3.7 Spring embrittlement.-Springs which have been treated for embrittlement relief shall show no visual evidence of cracks and shall not break when pulled to the minimum point of permanent distortion.

3.8 Submission of results of contractor-conducted examinations and tests.-The contractor shall forward copies of the results of any of his examinations or tests to the designated address as required by the contract. (See 6.4)

3.9 Workmanship.-All parts and assemblies shall be fabricated and finished in a thorough, workmanlike manner. They shall be free of burrs, chips, sharp edges, cracks, unblended radii, surface defects, dirt, grease, rust, corrosion products, and other foreign matter. The cleaning method used shall not be injurious to any parts, nor shall the parts be contaminated by the cleaning agents. All marking and stamping shall be neat and sharply defined.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

3.10 First article testing.-This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspections.-Unless otherwise specified herein or in the contract the provisions of MIL-A-48078 shall apply and are hereby made a part of the detail specification.

4.2 Classification of Inspections.-The following types of inspection shall be conducted on this item:

a. First Article Inspection
b. Quality Conformance Inspection

4.3 First Article Inspection.-

4.3.1 Submission.-The contractor shall submit a first article as designated by the Contracting Officer for evaluation in accordance with the provisions of 4.3.2. The first article sample shall consist of the following items in sample quantities as indicated.

Part Description	Drawings	Quantity
Pin, alignment	8877425	2
Pin, shear	8877426	6
Plunger, spring	9208288	4
Lock, "T" Bolt	9208329	4
Nose assembly	9208608	1
Skin, nose	9208291	1
Rod, telescope	9208304	1
Tube, telescope	9208310	1
Block, telescope	9208327	1
Latch assembly	9208333	2
Spring, latch	8831279	2
Spring, torsion	9208238	1
Spring, pushbutton	9208662-1	1
Spring, pushbutton	9208662-2	1
Nut, external wrenching	9237309	4
Bolt, tee	9237322	4

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

Cover, protective and flag assembly, Sta. 100	9281653	1
Flag, signal	9280820	1
Cover, protective (modified)	9281708	1

4.3.2 Inspections to be Performed.-See MIL-A-48078 (PA) and Table 1 herein.

4.3.3 Rejection.-See MIL-A-48078 (PA)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

TABLE 1 - FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS MIL-W-48757 (PA)

PARAGRAPH	TITLE		SHEET 1 OF 4		DRAWING NUMBER See Below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Pin, Alignment (Dwg. 8877425) Examination for Defects	2		3.2	4.4.2.1
	Pin, Shear (Dwg. 8877426) Examination For Defects	6		3.2	4.4.2.2
	Plunger, spring (Dwg. 9208288) Examination for Defects	4		3.2	4.4.2.3
	Lock, "T" Bolt (Dwg. 9208329) Examination for Defects	4		3.2	4.4.2.4
	Nose Assembly (Dwg. 9208608) Examination for Defects	1		3.2	4.4.2.5
	Skin, Nose (Dwg. 9208291) Examination for Defects	1		3.2	4.4.2.6
	Examination of Mechanical Properties of Skin	2*		3.5	4.5.2
	Examination of Mechanical Properties of Welds	4**		3.4.5	4.5.3

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

TABLE 1 - FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-W-48757 (PA)

PARAGRAPH	TITLE		SHEET 2 OF 4		DRAWING NUMBER See Below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Rod, Telescope (Dwg. 9208304) Examination for Defects	1		3.2	4.4.2.7
	Tube, Telescope (Dwg. 9208310) Examination for Defects	1		3.2	4.4.2.8
	Block, Telescope (Dwg. 9208327) Examination for Defects	1		3.2	4.4.2.9
	Latch Assembly (Dwg. 9208333) Examination for Defects	2		3.2	4.4.2.10
	Spring, Latch (Dwg. 8831279) Examination for Defects	5		3.2	4.4.2.11
	Spring, Torsion (Dwg. 9208238) Examination for Defects	5		3.2	4.4.2.12
	Spring, Pushbutton (Dwg. 9208662-1) Examination for Defects	5		3.2	4.4.2.13

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

TABLE 1 - FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS MIL-W-48757 (PA)

PARAGRAPH	TITLE		SHEET 3 OF 4		DRAWING NUMBER See Below
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	NEXT HIGHER ASSEMBLY / PARAGRAPH REFERENCE / INSPECTION METHOD
	Spring, Pushbutton (Dwg. 9208662-2) Examination for Defects	5		3.2	4.4.2.14
	Nut, External Wrenching (Dwg. 9237309) Examination for Defects	4		3.2	4.4.2.15
	Bolt, Tee (Dwg. 9237332) Examination for Defects	4		3.2	4.4.2.16
	Seal, aft section (Dwg. 9267740) Examination for Defects	1		3.2	4.4.2.17
	Cover, protective and flag assembly Sta. 100 (Dwg. 9281653) Examination for Defects	1		3.2	4.4.2.18
	Flag, signal (Dwg. 9280820) Examination for Defects	1		3.2	4.4.2.19

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

TABLE 1 - FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-W-48757 (PA)

PARAGRAPH	TITLE		SHEET 4 OF 4		DRAWING NUMBER See Below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE INSPECTION METHOD
	Cover, (modified) (Dwg. 9281708) Examination for Defects	1		3.2	4.4.2.20

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

4.4 Quality Conformance Inspection

4.4.1 Inspection Lot Formation.-Inspection lots shall comply with the lot formation provisions of MIL-A-48078 (PA).

4.4.2 Examination.-See MIL-A-48078 (PA).

a. Sampling Plans.-Unless otherwise specified in the Classification of Defects and Test Tables, sampling plans for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

3737

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS MIL-W-48757 (PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.1	Pin, Alignment				8877425
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major A					
101	Length		0.40%	3.2	Gage
102	Distance to shoulder		0.40%	3.2	Gage
103	Outside diameter		0.40%	3.2	Gage
104	True position of threads		0.40%	3.2	Gage
105	Pitch diameter of threads		0.40%	3.2	Gage
106	Major diameter of threads, min.		0.40%	3.2	Gage
107	Length of chamfer		0.40%	3.2	Gage
108	Locking element missing		100%	3.2	Visual
Minor					
201	Evidence of poor workmanship		0.65%	3.9	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-W-48757 (PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.2	Pin, Shear				8877426
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE / INSPECTION METHOD
Critical	None defined				
Major A					
101	Length		0.40%	3.2	Gage
102	Distance from end to shoulder		0.40%	3.2	Gage
103	Outside diameter		0.40%	3.2	Gage
104	True position of threads		0.40%	3.2	Gage
105	Pitch diameter of threads, min		0.40%	3.2	Gage
106	Major diameter of thread, min.		0.40%	3.2	Gage
107	Chamfer missing		0.40%	3.2	Visual
108	Locking element missing		100%	3.2	Visual
Minor					
201	Evidence of poor workmanship		0.65%	3.9	Visual

NOTES:

Source: https://assist.dla.mil - Downloaded: 2026/10 26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS MIL-W-48757 (PA)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.3	Plunger, Spring		9208288
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major A					
101	End pressure (1/2 way)		0.40%	3.2	Test
102	End pressure (final)		0.40%	3.2	Test
Minor					
201	Evidence of poor workmanship		0.65%	3.9	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-W-48757 (PA)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.4	Lock, "T" Bolt		9208329
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major A					
101	Length		0.40%	3.2	Gage
102	Width		0.40%	3.2	Gage
103	Height		0.40%	3.2	Gage
104	Distance from curved side to tee bolt head cutout		0.40%	3.2	Gage
105	Radius of curved side		0.40%	3.2	Gage
106	Radius of corners on side opposite curved side		0.40%	3.2	Gage
107	Depth of tee bolt head cutout		0.40%	3.2	Gage
108	Radius at tee bolt head cutout		0.40%	3.2	Gage
109	Radius of tee bolt shank cutout		0.40%	3.2	Gage
110	Diameter of holes		0.40%	3.2	Gage
111	True position of holes		0.40%	3.2	Gage
Minor					
201	Diameter of counterbore		0.65%	3.2	Gage
202	Evidence of poor workmanship		0.65%	3.9	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2022-10-26T09:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS MIL-W-48757 (PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9208608
4.4.2.5	Nose Assembly				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major A					
101	Protrusion of latch lever when pushbutton is depressed, min.		100%	3.2	Gage
102	Functioning of nose assembly		100%	3.6	Visual/Manual
Minor					
201	Evidence of poor workmanship		0.65%	3.9	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-W-48757 (PA)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.6	Skin, nose		9208291
			NEXT HIGHER ASSEMBLY 9208608

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major A					
101	Penetrant examination of welds		100%	3.4.3	4.5.1
102	Length		0.40%	3.2	Gage
103	Thickness		0.40%	3.2	Gage
104	Thickness at nose		0.40%	3.2	Gage
105	Perpendicularity of end		0.40%	3.2	Gage
106	Small inside diameter at basic		0.40%	3.2	Gage
107	Large inside diameter at basic		0.40%	3.2	Gage
108	Outside contour improper		0.40%	3.2	Gage
109	Chamfer on inside open end missing		0.40%	3.2	Visual
110	Sag		0.40%	3.4.2	Gage
111	Distance from end to self locking screw holes		0.40%	3.2	Gage
112	True position of self locking screw holes		0.40%	3.2	Gage
113	Distance from end to machine screw holes		0.40%	3.2	Gage
114	True position of machine screw holes		0.40%	3.2	Gage
Minor 201	Evidence of poor workmanship		0.65%	3.9	Visual

NOTES:

Source: https://assist.dla.mil - Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS MIL-W-48757 (PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.7	Rod, Telescope				9208304
					NEXT HIGHER ASSEMBLY
					9208608
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major A					
101	Overall length		0.40%	3.2	Gage
102	True position of spring pin holes		0.40%	3.2	Gage
103	Large diameter		0.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		0.65%	3.9	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9208310
4.4.2.8	Tube, Telescope				NEXT HIGHER ASSEMBLY 9208608
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major A					
101	Overall length		0.40%	3.2	Gage
102	Distance from end to start of groove		0.40%	3.2	Gage
103	Distance from end to center of groove		0.40%	3.2	Gage
104	Outside diameter		0.40%	3.2	Gage
105	Inside diameter		0.40%	3.2	Gage
106	Distance from end to start of telescope tube screw slot		0.40%	3.2	Gage
107	Length of telescope tube screw slot		0.40%	3.2	Gage
108	Width of telescope tube screw slot		0.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		0.65%	3.9	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS MIL-W-48757 (PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9208327
4.4.2.9	Block, Telescope				NEXT HIGHER ASSEMBLY 9208608
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major A					
101	Distance from end to self locking screw holes		0.40%	3.2	Gage
102	Diameter of telescope rod hole		0.40%	3.2	Gage
103	True position of telescope rod hole		0.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		0.65%	3.9	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2020-10-26T05:37Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-W-48757 (PA)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.10	Latch assembly		9208333
			NEXT HIGHER ASSEMBLY 9208608

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major A 101	Any part missing or improperly assembled		100%	3.2	Visual
Minor 201	Evidence of poor workmanship		0.65%	3.9	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS MIL-W-48757 (PA)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.11	Spring. Latch		8831279
			NEXT HIGHER ASSEMBLY 9208333

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major A 101	Spring embrittlement	5	Acc. 0 Rej. 1	3.7	4.5.8
Minor 201	Evidence of poor workmanship		0.65%	3.9	Visual

NOTES:

Source: https://assist.dla.mil - Downloaded: 2020-10-20T03:37Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-W-48757 (PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9208238
4.4.2.12	Spring, Torsion				NEXT HIGHER ASSEMBLY 9208333
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major A 101	Spring embrittlement	5	Acc. 0 Rej. 1	3.7	4.5.8
Minor 201	Evidence of poor workmanship		0.65%	3.9	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-W-48757 (PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9208662-1
4.4.2.13	Spring, Pushbutton				NEXT HIGHER ASSEMBLY 9208333
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major A 101	Spring embrittlement	5	Acc. 0 Rej. 1	3.7	4.5.8
Minor 201	Evidence of poor workmanship		0.65%	3.9	Visual

NOTES:

Source: http://assist.dla.mil - Downloaded: 2020-10-20T05:37Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-W-48757 (PA)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.14	Spring, Pushbutton		9208662-2
			NEXT HIGHER ASSEMBLY 9208333

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major A 101	Spring embrittlement	5	Acc. 0 Rej. 1	3.7	4.5.8
Minor 201	Evidence of poor workmanship		0.65%	3.9	Visual

NOTES:

Source: https://assist.dla.mil - Downloaded: 2026-10-26T02:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS MIL-W-48757 (PA)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.15	Nut, External Wrenching		9237309
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major A					
101	Magnetic particle inspection		100%	3.2	4.5.5
102	Pitch diameter		0.40%	3.2	4.5.6
103	Minor diameter		0.40%	3.2	4.5.6
Minor					
201	Distance across flats of double hex		0.65%	3.2	Gage
202	Largest distance across double hex, min.		0.65%	3.2	Gage
203	Length of double hex, min.		0.65%	3.2	Gage
204	Diameter of bearing surface, min.		0.65%	3.2	Gage
205	Largest outside diameter, max.		0.65%	3.2	Gage
206	Length of largest outside diameter, min.		0.65%	3.2	Gage
207	Overall length, max.		0.65%	3.2	Gage
208	Evidence of poor workmanship		0.65%	3.9	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-W-48757 (PA)

27

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.16	Bolt, Tee		9237322
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major A					
101	Internal defects inspection		100%	3.2	4.5.4
102	Magnetic particle inspection		100%	3.2	4.5.5
103	Pitch diameter		0.40%	3.2	4.5.6
104	Major diameter		0.40%	3.2	4.5.6
105	Hardness	25*	Acc. 0 Rej. 1	3.2	4.5.7
Minor					
201	Symmetry of bolt shank to "A" and "B"		0.65%	3.2	Gage
202	Overall dimension handle, max		0.65%	3.2	Gage
203	Dimension handle, bearing surface, min		0.65%	3.2	Gage
204	Evidence of poor workmanship		0.65%	3.9	Visual

NOTES:
*or five (5) percent of lot, whichever is greater

Source: https://assist.dla.mil - Downloaded: 2026-10-26T03:52Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS MIL-W-48757 (PA)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.17	Seal, aft section		9267740
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major A					
101	Direction of wires		0.40%	3.2	Visual
102	Width		0.40%	3.2	Gage
103	Height		0.40%	3.2	Gage
104	Length		0.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		0.65%	3.9	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2020-10-26T05:37Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS MIL-W-48757 (PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.18	Cover, Protective and Flag Assembly, Sta. 100				9281653
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major B					
101	Marking missing, incomplete or illegible		100%	3.2	Visual
102	Any component incomplete or missing		100%	3.2	Visual
Minor					
201	Evidence of poor workmanship		0.65%	3.9	Visual

NOTES:

Source: https://assist.dla.mil - Downloaded: 2026/10 26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-W-48757 (PA)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.19	Flag, signal		9280820
			NEXT HIGHER ASSEMBLY
			9281653

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major B					
101	Diameter of solid rivot hole, max.		0.40%	3.2	Gage
Minor					
201	Length		0.65%	3.2	Gage
202	Width		0.65%	3.2	Gage
203	Evidence of poor workmanship		0.65%	3.9	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2020-10-26T05:37Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-W-48757 (PA)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.20	Cover, (modified)		9281708
			NEXT HIGHER ASSEMBLY 9281653

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major B 101	Diameter of solid revot hole		0.40%	3.2	Gage
Mjnor 201	Evidence of poor workmanship		0.65%	3.9	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.21	Bag, Packing for Repair Parts	1 OF 1	8883538-2
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major B					
101	Length of bag		0.40%	3.2	Gage
102	Width of bag		0.40%	3.2	Gage
103	Part improperly installed in bag		0.40%	3.2	Visual
104	Bag damaged or improperly sealed		0.40%	3.2	Visual
105	Marking illegible, missing or incorrect		0.40%	3.2	Visual
Minor	None defined				

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-W-48757 (PA)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.22	Bag, Packing for Repair Parts		8883538-3
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major B					
101	Length of bag		0.40%	3.2	Gage
102	Width of bag		0.40%	3.2	Gage
103	Part improperly installed in bag		0.40%	3.2	Gage
104	Bag damaged, or improperly sealed		0.40%	3.2	Visual
105	Marking illegible, missing or incorrect		0.40%	3.2	Visual
Minor	None defined				

NOTES:

Source: https://assist.dla.mil - Downloaded: 2026Jan 26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-W-48757 (PA)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.23	Packing and Marking for Box Packing Ammunition, for Ogive, Rocket: Nose Cone Conical: Or Nose Cone, Ogival	1 OF 1	9295054
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major B					
101	Pads missing or improperly installed		0.40%	3.2	Visual
102	Fiberboard box damaged or improperly sealed		0.40%	3.2	Visual
103	Case liner damaged or improperly sealed		0.40%	3.2	Visual
104	Fiberboard box loose in wood box		0.40%	3.2	Visual/Manual
105	Wood box damaged or improperly strapped		0.40%	3.2	Visual
106	Marking illegible, missing or incorrect		0.40%	3.2	Visual
Minor	None defined				

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-W-48757 (PA)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.24	Bag, Packing, For Repair Parts		8883534-4
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major B					
101	Length of bag		0.40%	3.2	Gage
102	Width of bag		0.40%	3.2	Gage
103	Wrapper missing		0.40%	3.2	Visual
104	Part improperly installed in bag		0.40%	3.2	Gage
105	Bag damaged or improperly sealed		0.40%	3.2	Visual
106	Marking illegible, missing or incorrect		0.40%	3.2	Visual
Minor	None defined				

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2023-10-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-W-48757 (PA)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.25	Packing and Marking for Storage and Shipping	1 OF 1	8808362
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major B					
101	Bags or boxes in container loose		0.40%	3.2	Visual/Manual
102	Container damaged or improperly sealed		0.40%	3.2	Visual
103	Marking illegible, missing or incorrect		0.40%	3.2	Visual
Minor	None defined				

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-26T03:57Z
Check the source to verify that this is the current version before use.

4.4.3 Testing.-Testing is described in the First Article and Quality Conformance Inspection Tables.

4.4.4 Inspection Equipment.-The inspection equipment required to perform the examinations and tests prescribed herein is described in the Paragraph Reference/Inspection Method column in the tables starting with Paragraph 4.4.2.1. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078 and 6.3 herein.

4.5 Test methods and procedures.-

4.5.1 Penetrant examination.-The part shall be subjected to penetrant inspection in accordance with MIL-I-6866. Parts so tested, if acceptable, shall be returned to the lot.

4.5.2 Mechanical properties of skin sections.-Samples of material from the nose skin shall be subjected to the tension test in accordance with ASTM E-8-69 (Part 31) to determine tensile strength, yield strength and percentage of elongation. This is a destructive test. Parts so tested shall not be returned to the lot.

4.5.3 Mechanical properties of welds.-Samples of the welds from the nose skin shall be subjected to the tension test in accordance with STM E-8-69 (Part 31) to determine tensile strength, yield strength and percentage of elongation. This is a destructive test. Parts so tested shall not be returned to the lot.

4.5.4 Internal defects inspection of tee bolt .-The tee bolt shall be inspected for internal defects in accordance with MIL-STD-453, Q.L. 2-2T. Parts so tested if acceptable, shall be returned to the lot.

4.5.5 Magnetic particle inspection of tee bolt and external wrenching nut.-The tee bolt and external wrenching nut shall be inspected for defects in accordance with MIL-I-6868 and MIL-B-6812. Parts so tested, if acceptable, shall be returned to the lot.

4.5.6 Inspection of tee bolt and external wrenching nut threads.-The threads of the tee bolt and external wrenching nut shall be inspected in accordance with MIL-S-7742. Parts so tested, if acceptable, shall be returned to the lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

4.5.7 Hardness of tee bolt.-The tee bolt shall be subjected to the hardness test in accordance with ASTM E-18-67 (Part 31) This is a non-destructive test. Parts so tested if acceptable shall be returned to the lot.

4.5.8 Spring embrittlement.-The spring shall be gripped at both ends and extended to the point of minimum permanent distortion. Failure in meeting the requirement shall class the spring defective. Springs so tested shall not be returned to the lot.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging.-

5.1.1 Level A.-The alignment pin, shear pin, spring plunger, external wrenching nut and tee bolt shall be preserved and packaged in accordance with Dwg. 8808932. The "T" bolt lock shall be preserved and packaged in accordance with Dwg. 8883538-2. The protective and flag assembly cover, sta. 100, shall be preserved and packaged in accordance with Dwg. 8883538-3. The nose assembly shall be preserved and packaged in accordance with Dwg. 9295054. The aft section seal shall be preserved and packaged in accordance with Dwg. 8883534-4.

5.2 Packing.-

5.2.1 Level A.-The alignment pin, shear pin, spring plunger, external wrenching nut, tee bolt, "T" bolt lock, protective and flag assembly cover, sta. 100 and aft section seal preserved and packaged as specified in 5.1.1, shall be packed in accordance with Dwg. 8808362. The nose assembly, preserved and packaged as specified in 5.1.1, shall be packed in accordance with Dwg. 9295054.

5.3 Marking .-Marking shall be in accordance with Drawings 8883534, 8883538, 8808362, 8808932 and 9295054.

5.4 Shipping.-When components from more than one lot are shipped as a carload, each lot shall be kept separate, and the division between lots clearly indicated to prevent mixing of the lots in transit.

6. NOTES

6.1 Intended use.-Spare parts for Warhead Section, GM, HE, XM251.

6.2 Ordering Data.-See MIL-A-48078 (PA).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

6.3 Submission of Inspection Equipment Designs for Approval.-See MIL-A-48078 (PA). Submit equipment designs as required to Commander, Attn: SARPA-QA-T, Picatinny Arsenal, Dover, NJ 07801.

6.4 Submission of results of contractor-conducted examinations and tests.-Unless otherwise specified by the Contracting Officer, the contractor shall forward requested records of examinations or tests to Commander, Picatinny Arsenal, Attn: SARPA-QA-A-S.

6.5 Submission of test data.-In addition to the normal distribution of records, when the spare parts for the XM251 warhead is procured by the U.S. Army Munitions Command, one (1) copy of ammunition data cards shall be forwarded to: Commander, Picatinny Arsenal, Attn: SARPA-QA-A-S.

Custodian:
Army-PA

Preparing Activity:
Army-PA

Project Number: 1340-A477

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/ vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426

REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 202610-26T03:57Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD – 314



OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

COMMANDER
Picatinny Arsenal
ATTN: SARPA-QA-A
Dover, New Jersey 07801

FOLD

2727

90 ?

Source: https://assist.dla.mil -- Downloaded: 202610-26T03:57Z
Check the source to verify that this is the current version before use.