MIL-W-48866A (AR)
28 October 1980
SUPERSEDING
MIL-W-48866 (PA)
15 August 1975

MILITARY SPECIFICATION

WARHEAD SECTION, GM, PRACTICE LIGHTWEIGHT, M252 AND SHIPPING AND STORAGE CONTAINER, XM612, SPARE PARTS FOR

This specification is approved for use by the U.S. Army Armament Research and Development Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification contains requirements not normally covered by the drawings and provides quality assurance provisions for the fabrication of spare parts for the Warhead Section, GM, Practice, Lightweight, M252, and Shipping and Storage Container, XM612.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on the date of invitation for bids, or request for proposals, form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

PPP-B-636	-Boxes, Shipping, Fiberboard

MILITARY

MIL-B-6812	-Bolt, Aircraft
MIL-I-6866	-Inspection Penetrant Method of
MIL-I-6868	-Inspection Process Magnetic Particle
MIL-S-7742	-Screw Threads, Standard Optimum Selected Series: General Specification For
MIL-P-14232	-Parts, Equipment and Tools for Army Material, Packaging and Packing of

FSC: 1336

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Command, Attn. DRDAR-QA, Dover, New Jersey 07801 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

★U.S. GOVERNMENT PRINTING OFFICE: 1980—703-023/165

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

* MIL-B-45887 - Bolt, Tee
MIL-A-48078 - Ammunition, Standard Quality Assurance Provisions, General Specification For
* MIL-E-52798 - Enamel, Alkyd, Camouflage

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
* MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-453 - Inspection, Radiographic
MIL-STD-1168- Lot Numbering of Ammunition
MIL-STD-1595- Aerospace Welder Performance Qualification

DRAWINGS (See 6.6)

U.S. ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND

8808362 - Packing and Marking for Storage and Shipment
* 8808932 - Packing for Hardware and Related Items
8877425 - Pin, Alignment
8877426 - Pin, Shear
8878938 - Cover, Tee Bolt
8879955 - Cover, Electrical Connector, PAL
8883534 - Box, Packing, for Repair Parts
8883538 - Bag, Packing, for Repair Parts
9237309 - Nut, External Wrenching
9237322 - Bolt, Tee
9267740 - Seal, Aft Section
9281653 - Cover, Protective and Flag Assy., Sta 100
* 9288555 - Spacer Assembly, XM612 Container
9295054 - Packing and Marking for Box Packing Ammunition for Ogive Rocket: Nose Cone Conical: or Nose Cone Ogival
10246033 - Nose Cone Assembly, Welded
10246034 - Nose Cone Tip
10246038 - Nose Cone Skin
10293155 - Receptable, Turnlock Fastner
10293157 - Stud, Turnlock Fastener

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the Contracting Officer.)

Source: https://assist.dla.mil -- Downloaded: 202610-26T03:57Z
Check the source to verify that this is the current version before use.

S. Remove stirrer, washing off any residue additional minute

2.2 Other publications. The following documents form a part of this specification herein. Unless otherwise indicated, the issue in effect on the date of invitation for bids or request for proposals shall apply.

American Society for Testing Materials
ASTM-E-8-69 - Tension Testing of Metallic Material
* ASTM E 18-67 - Rockwell Hardness and Rockwell Superficial Hardness of Metallic Materials, Tests for

(Application for copies should be addressed to: American Society for Testing and Materials, 1016 Race Street, Phila., Pa 19103).

3. REQUIREMENTS

3.1 Material. Materials shall be in accordance with the applicable drawings and specifications.

* 3.1.1 Camouflage paint. The camouflage paint shall comply with all requirements specified in MIL-E-52798. (See 4.5.4).

* 3.2 Parts. The parts shall comply with all requirements specified on drawings 8877425, 8877426, 8878938, 8879955, 9237309, 9237322, 9267740, 9281653, 9288555, 10246033, 10293155 and 10293157, all associated drawings and with all requirements specified in applicable specifications.

3.2.1 Tee bolt. (dwg. 9237322). The tee bolt shall comply with all requirements specified in MIL-B-45887. However, First Article requirements specified herein shall apply.

3.3 Mechanical properties. Cold-working or heat-treating (including quenching-and-tempering, normalizing), shall be performed in such a manner as to produce the specified properties uniformly through-out the entire lot. The contractor shall determine the detailed procedures to produce parts meeting the required mechanical properties. These procedures shall be documented and submitted with the First Article sample to the Contracting Officer. Changes in these procedures shall also be documented and submitted to the Contracting Officer.

3.4 Welding. All skin welds shall be reasonably smooth and free of craters. They shall exhibit characteristics of good fusion, penetration, and soundness of deposit representative of good welding practice. The process shall be such as to prevent warpage beyond dimensional requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

3.4.1 Qualification of welders. Only welders qualified in accordance with MIL-STD-1595 shall be permitted to weld steel components. A complete qualification test for each welder or welding operator making warhead skins shall be conducted using butt weld qualification test coupons.

3.4.2 Material sag. Sag of material in the area adjacent to the weld shall not be more than .010 below the surface of the joined part.

3.5 First article testing. This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

3.6 Workmanship. All parts and assemblies shall be fabricated and furnished in a thorough, workmanlike manner. They shall be free of burrs, chips, sharp edges, cracks, unblended radii, surface defects, dirt, grease, rust, corrosion products, and other foreign matter. The cleaning method used shall not be injurious to any parts, nor shall the parts be contaminated by the cleaning agents. All marking and stamping shall be neat and sharply defined.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection and standard quality assurance provisions. Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

4.2 Classification of inspection. The following types of inspection shall be conducted on this item:

a. First article inspection

b. Quality conformance inspection

4.3 First article inspection

4.3.1 Submission. The contractor shall submit a first article sample as designated by the contracting officer for evaluation in accordance with the provisions of 4.3.2. The first article sample shall consist of the following items in sample quantities as indicated:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

Part Description	Drawing No.	Quantity
Pin, Alignment	8877425	2
Pin, Shear	8877426	6
Cover, Tee Bolt	8878938	4
Cover, Electrical Connector, PAL	8879955	1
Nut, External Wrenching	9237309	4
Seal, Aft Section	9267740	1
Cover, Protective and Flag Assembly, Sta. 100	9281653	1
Nose Cone Assembly, Welded	10246033	1
Nose Cone Tip	10246034	1
Nose Cone Skin	10246038	1
Receptacle, Turnlock Fastener	10293155	8
Stud, Turnlock Fastener	10293157	8
* Spacer Assembly	9288555	1
* Bolt, Tee (plated)	9237322	13
* Bolt, Tee (unplated)	9237322	10

4.3.1.1 The first article shall comply with the homogeneity criteria of MIL-A-48078, Paragraph 4.4.1.

4.3.2 Inspections to be performed.-See MIL-A-48078 and Table I specified herein. All inspections listed in Table I shall be classified as Major unless otherwise specified.

4.3.3 Rejection.-See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection

4.4.1 Inspection lot formation.-Inspection lots shall comply with the lot formation provisions of MIL-A-48078.

4.4.2 Examination.-See MIL-A-48078.

a. Sampling plans.-Unless otherwise specified in the Classification of Defects and Test Tables, sampling plans for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

TABLE I - FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 3		DRAWING NUMBER
	Spare Parts for M252 Practice Warhead Section and XM612 Shipping and Storage Container				See Below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Pin, Alignment (Dwg. 8877425) Examination for Defects	2		3.2	4.4.2.1
	Pin, Shear (Dwg. 8877426) Examination for Defects	6		3.2	4.4.2.2
	Cover, Tee Bolt (Dwg. 8878938) Examination for Defects	4		3.2	4.4.2.3
	Cover, Electrical Connector, PAL (Dwg. 8879955) Examination for Defects	1		3.2	4.4.2.4
	Nut, External Wrenching (Dwg. 9237309) Examination for Defects	4		3.2	4.4.2.5

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2020-10-20 10:53:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 2 OF 3		DRAWING NUMBER
	Spare Parts for M252 Practice Warhead Section and XM612 Shipping and Storage Container				See Below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Seal, Aft, Section (Dwg. 9267740) Examination for Defects	1		3.2	4.4.2.6
	Cover, Protrusion and Flag Assembly, Sta. 100 (Dwg. 9281653) Examination for Defects	1		3.2	4.4.2.7
	Nose Cone Assembled, Welded (Dwg. 10246033) Examination for Defects	1		3.2	4.4.2.8
	Nose Cone Tip (Dwg. 10246034) Examination for Defects	1		3.2	4.4.2.9
	Nose Cone Skin (Dwg. 10246038) Examination for Defects	1		3.2	4.4.2.10
	Receptable, Turnlock Fastener (Dwg. 10293155) Examination for Defects	8		3.2	4.4.2.11
	Stud, Turnlock Fastener (Dwg. 10203157)	8		3.2	4.4.2.12
NOTES:	Examination for Defects				

Source: https://assist.dla.mil -- Downloaded: 2026-02-26 10:35:37Z
Check the source to verify that this is the current version before use.

TABLE I - FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-W-48866A (AR)

PARAGRAPH	TITLE	SHEET 3 OF 3	DRAWING NUMBER
	Spare Parts for M252 Practice Warhead Section and XM612 Shipping and Storage Container		See Below
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
*	Spacer Assembly (Dwg. 9288555) Examination for Defects	1		3.2	4.4.2.18
*	Bolt, Tee (Dwg. 9237322), plated Examination for Defects	10[1]		3.2.1	MIL-B-45887
	Continuous Grain Flow Lines	3		3.2.1	MIL-B-45887
	Plating	10[1]		3.2.1	MIL-B- 45887
*	Bolt, Tee (Dwg. 9237322), unplated Hardness Test [3]	10[2]		3.2.1	MIL-B-45887
	Tensile Load Test	10[2]		3.2.1	MIL-B-45887

NOTES:
1. This quantity may be added to the production lot after acceptance.
2. These tests may be performed on the same sample.
3. Hardness shall be checked on the shaft (above the threads and on the end) and on the cross tee, but not on bearing surface. Test per ASTM E 18-67. (Non-Destructive)

Source: https://assist.dla.mil -- Downloaded: 2026/10-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-W-48866A (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.1	Pin, Alignment		8877425
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Length		0.40%	3.2	Gage
102	Distance to shoulder		0.40%	3.2	Gage
103	Outside diameter		0.40%	3.2	Gage
104	True position of threads		0.40%	3.2	Gage
105	Pitch diameter of threads		0.40%	3.2	Gage
106	Major diameter of threads, min.		0.40%	3.2	Gage
107	Length of chamfer		0.40%	3.2	Gage
108	Locking element missing		100%	3.2	Visual
Minor					
201	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

Source: https://assist.dla.mil - Downloaded: 2026-02-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-W-48866A (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 8877426
4.4.2.2	Pin, Shear				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Length		0.40%	3.2	Gage
102	Distance from end to shoulder		0.40%	3.2	Gage
103	Outside diameter		0.40%	3.2	Gage
104	True position of threads		0.40%	3.2	Gage
105	Pitch diameter of threads, min.		0.40%	3.2	Gage
106	Major diameter of thread, min.		0.40%	3.2	Gage
107	Chamfer missing		0.40%	3.2	Visual
108	Locking Element missing		100%	3.2	Visual
Minor					
201	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

MIL-W-48866A (AR)

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.3	Cover, Tee Bolt				8878938
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Diameter mounting holes, min.		0.40%	3.2	Gage
102	Location mounting holes		0.40%	3.2	Gage
103	Width slot, min.		0.40%	3.2	Ggge
104	Alignment slot with mounting holes		0.40%	3.2	Gage
105	Total width		0.40%	3.2	Gage
106	Alignment total width with mounting holes		0.40%	3.2	Gage
107	Length of slot, min.		0.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil - Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

MIL-W-48866A (AR)

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 8879955
4.4.2.4	Cover, Electrical Connector, PAL				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Largest outside diameter		0.40%	3.2	Gage
102	Second largest outside diameter		0.40%	3.2	Gage
103	Smallest outside diameter		0.40%	3.2	Gage
104	Concentricity second largest outside diameter with smallest outside diameter		0.40%	3.2	Gage
105	Concentricity of largest outside diameter with smallest outside diameter		0.40%	3.2	Gage
106	Thickness flanges		0.40%	3.2	Gage
107	Length second largest outside diameter		0.40%	3.2	Gage
108	Total length		0.40%	3.2	Visual
109	Disc missing		0.40%	3.2	Visual
110	Packing missing		0.40%	3.2	Visual
111	Wrench hole missing		0.40%	3.2	Visual
112	Cap does not mate into connector, receptacle MS-20029-15-18		0.40%	3.2	Manual
Minor					
201	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-W-48866A (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9237309
4.4.2.5	Nut, External Wrenching				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Magnetic particle inspection		100%	3.2	4.5.2
102	Pitch diameter		0.40%	3.2	4.5.3
103	Minor diameter		0.40%	3.2	4.5.3
Minor					
201	Distance across flats of double hex.		0.65%	3.2	Gage
202	Largest distance across double hex, min.		0.65%	3.2	Gage
203	Length of double hex, min.		0.65%	3.2	Gage
204	Diameter of bearing surface, min.		0.65%	3.2	Gage
205	Largest outside diameter, max.		0.65%	3.2	Gage
206	Length of largest outside diameter, min.		0.65%	3.2	Gage
207	Overall length, max.		0.65%	3.2	Gage
208	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil - Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

MIL-W-48866A (AR)

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.6	Seal, aft section				9267740
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Direction of wires		0.40%	3.2	Visual
102	Width		0.40%	3.2	Gage
103	Height		0.40%	3.2	Gage
104	Length		0.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9281653
4.4.2.7	Cover, Protective and Flag Assembly, Sta. 100				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Marking missing, incomplete or illegible		100%	3.2	Visual
102	Any component incomplete or missing		100%	3.2	Visual
Minor					
201	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil/ - Downloaded: 2026-02-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

MIL-W-48866A (AR)

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET		DRAWING NUMBER
4.4.2.8	Nose Cone assembly, welded		1 OF 1		10246033
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Penetrant examination of weld		100%	3.2	4.5.1
102	Thickness of Camouflage Paint		100%	3.2	4.5.4
103	Sag		100%	3.4.2	Gage
Minor					
201	Finish improper		100%	3.2	Visual
202	Evidence of poor workmanship		100%	3.6	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

MIL-W-48866A (AR)

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 10246034
4.4.2.9	Nose cone tip				NEXT HIGHER ASSEMBLY 10246033
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
Major					
101	Angle improper		100%	3.2	Gage
102	Length tip to shoulder		100%	3.2	Gage
103	Largest diameter		100%	3.2	Gage
104	Smallest diameter		100%	3.2	Gage
105	Concentricity of largest diameter to smallest diameter		100%	3.2	Gage
106	Length, base to shoulder		100%	3.2	Gage
107	Improper spherical radius		100%	3.2	Gage
Minor					
201	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil/ - Downloaded: 2026-02-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-W-48866A (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.10	Nose cone skin		10246038
			NEXT HIGHER ASSEMBLY
			10246033

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Penetrant examination of weld		100%	3.2	4.5.1
102	Thickness		100%	3.2	Gage
103	Diameter large end		100%	3.2	Gage
104	Diameter small end		100%	3.2	Gage
105	Outside contour improper		100%	3.2	Gage
106	Length		100%	3.2	Gage
107	Concentricity of smallest diameter to largest diameter		100%	3.2	Gage
108	Perpendicularity of large end with largest and smallest diameters		100%	3.2	Gage
109	Parallelism of small end with large end		100%	3.2	Gage
110	Location of mounting holes		100%	3.2	Gage
111	Diameter of mounting holes		100%	3.2	Gage
112	Chamfer on inside of mounting holes		100%	3.2	Gage
113	Sag		0.40%	3.4.2	Gage
* 114	Improper inside weld finish (if applicable)		100%	3.2	Visual
Minor					
201	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-26T03:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.11	Receptacle, Turnlock fastener				10293155
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Location of mounting holes		0.40%	3.2	Gage
102	Diameter of mounting holes, min.		0.40%	3.2	Gage
103	Thickness flange, min.		0.40%	3.2	Gage
104	Total height		0.40%	3.2	Gage
105	Spring not present		0.65%	3.2	Visual
Minor					
201	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

Source: https://assist.dla.mil - Downloaded: 2026-02-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

MIL-W-48866A (AR)

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.12	Stud, Turnlock fastener				10293157
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Pitch diameter of thread		0.40%	3.2	Gage
102	Diameter of shank		0.40%	3.2	Gage
103	Length to thread		0.40%	3.2	Gage
104	Total length		0.40%	3.2	Gage
105	Diameter of head		0.65%	3.2	Gage
106	Slot missing		0.65%	3.2	Gage
Minor					
201	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assistdocs.com - Downloaded: 2026-02-20T05:37Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.13	Bag, Packing for Repair Parts				8883538-2
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Length of bag		0.40%	3.2	Gage
102	Width of bag		0.40%	3.2	Gage
103	Part improperly installed in bag		0.40%	3.2	Visual
104	Bag damaged or improperly sealed		0.40%	3.2	Visual
105	Marking illegible, missing or incorrect		0.40%	3.2	Visual
Minor	None defined				

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil - Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

MIL-W-48866A (AR)

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 8883538-3
4.4.2.14	Bag, Packing for Repair Parts				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Length of bag		0.40%	3.2	Gage
102	Width of bag		0.40%	3.2	Gage
103	Part improperly installed in bag		0.40%	3.2	Gage
104	Bag damaged, or improperly sealed		0.40%	3.2	Gage
105	Marking illegible, missing or incorrect		0.40%	3.2	Visual
Minor	None defined				

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.15	P Packing and Marking for Box Packing Ammunition, for Ogive, Rocket: Nose Cone Conical: Or Nose Cone, Ogival	1 OF 1	9295054
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Pads missing or improperly installed		0.40%	3.2	Visual
102	Fiberboard box damaged or improperly sealed		0.40%	3.2	Visual
103	Case liner damaged or improperly sealed		0.40%	3.2	Visual
104	Fiberboard box loose in wood box		0.40%	3.2	Visual/Manual
105	Wood box damaged or improperly strapped		0.40%	3.2	Visual
106	Marking illegible, missing or incorrect		0.40%	3.2	Visual
Minor	None defined				

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION MIL-W-48866A (AR)

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.16	Bag, Packing, For Repair Parts	1 OF 1	8883534-4
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Length of bag		0.40%	3.2	Gage
102	Width of bag		0.40%	3.2	Gage
103	Wrapper missing		0.40%	3.2	Visual
104	Part improperly installed in bag		0.40%	3.2	Gage
105	Bag damaged or improperly sealed		0.40%	3.2	Visual
106	Marking illegible, missing or incorrect		0.40%	3.2	Visual
Minor	None defined				

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-02-26 10:53:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.17	Packing and Marking for Storage and Shipping				8808362
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Bags or boxes in container loose		0.40%	3.2	Visual/Manual
102	Container damaged or improperly sealed		0.40%	3.2	Visual
103	Marking illegible, missing or incorrect		0.40%	3.2	Visual
Minor	None defined				

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-02-26 10:35:22Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION MIL-W-48866A (AR)

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9288555
* 4.4.2.18	Spacer assembly				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Any component missing, improperly assembled or damaged		100%	3.2	Visual
102	Height		100%	3.2	Gage
103	Width		100%	3.2	Gage
104	Overall thickness of spacer assembly		100%	3.2	Gage
105	Thickness of side pad		0.40%	3.2	Gage
106	Thickness of top pad		0.40%	3.2	Gage
107	Thickness of bottom pad		0.40%	3.2	Gage
108	Diameter of recess for warhead		0.40%	3.2	Gage
109	Distance from center to T-bolt cutout radius centerline		0.40%	3.2	Gage
110	Distance from T-bolt cutout radius centerline to outside edge		0.40%	3.2	Gage
111	Radius of T-bolt cutout		100%	3.2	Gage
112	Radius of warhead washer cutout		0.40%	3.2	Gage
113	Depth of holes, min		0.40%	3.2	Gage
114	Diameter of holes, min		0.40%	3.2	Gage
115	Stencil missing, incomplete or illegible		100%	3.2	Visual
Minor					
201	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-02-26 10:03:37Z
Check the source to verify that this is the current version before use.

4.4.3 Testing.-Testing is described in the First Article and Quality Conformance Inspection Tables.

4.4.4 Inspection Equipment.-The inspection equipment required to perform the examinations and tests prescribed in this specification is identified either directly or by reference in the "Paragraph Reference/Inspection Method" column of the First Article Inspection and Quality Conformance Inspection Tables herein. The contractor shall submit inspection equipment designs to the Government for approval in accordance with the terms of the contract. See Section 6 of MIL-A-48078 and 6.3 herein.

4.5 Test methods and procedures

4.5.1 Penetrant examination.-The part shall be subjected to penetrant inspection in accordance with MIL-I-6866. Parts so tested, if acceptable, shall be returned to the lot.

* 4.5.2 Magnetic particle inspection of external wrenching nut.-The external wrenching nut shall be inspected for defects in accordance with MIL-I-6868. Parts so tested, if acceptable, shall be returned to the lot.

* 4.5.3 Inspection of external wrenching nut threads.-The threads of the external wrenching nut shall be inspected in accordance with MIL-S-7742. Parts so tested, if acceptable, shall be returned to the lot.

* 4.5.4 Camouflage paint thickness on the nose cone assembly.-The camouflage paint thickness shall be tested using a dry film type meter. The primer thickness shall be measured prior to applying the camouflage paint. These measurement locations shall be noted dimensionally and recorded, so subsequent camouflage paint thickness measurements are in the same area. Camouglage paint thickness shall be measured at a minimum of three (3), randomly selected points on the exterior.

5. Packaging

5.1 Preservation and packaging

* 5.1.1 Level A.-The alignment pin, shear pin, external wrenching nut and tee bolt shall be preserved and packaged in accordance with Dwg. 8808932. The "T" bolt lock shall be preserved and packaged in accordance with Dwg. 8883538-2. The protective and flag assembly cover, sta. 100, shall be preserved and packaged in accordance with Dwg. 8883538-3. The nose cone assembly welded, shall be preserved and packaged in accordance

Source: https://assist.dla.mil -- Downloaded: 202610-26T03:57Z
Check the source to verify that this is the currentversion before use.

with Dwg. 9295054. The aft section seal shall be preserved and packaged in accordance with Dwg. 8883534-4. The spacer assembly shall be preserved and packaged in a Type CF, grade W5C fiberboard box in accordance with PPP-B-636.

5.2 Packing

5.2.1 Level A.-The alignment pin, shear pin, external wrenching nut, tee bolt, "T" bolt lock, protective and flag assembly cover, sta. 100 and aft section seal preserved and packaged as specified in 5.1.1, shall be packed in accordance with Dwg. 8808362. The nose cone assembly welded, preserved and packaged as specified in 5.1.1, shall be packed in accordance with Dwg. 9295054.

* 5.2.2 Level B.-The spacer assembly, preserved and packaged as specified in 5.1.1, shall be packed in accordance with MIL-P-14232.

* 5.3 Marking.-In addition to any special marking required by the contract (see 6.2), each intermediate and exterior container shall be marked in accordance with the following: The alignment pin, external wrenching nut and "T" bolt, per 8808932; the "T" bolt lock and the protective and flag assembly cover - sta 100, per 8883538; the nose cone assembly welded per 9295054, the aft section seal per 8883524 and the spacer assembly per MIL-STD-129.

5.4 Shipping.-When components from more than one lot are shipped as a carload, each lot shall be kept separate, and the division between lots clearly indicated to prevent mixing of the lots in transit.

6. NOTES

* 6.1 Intended use.-Spare parts for Warhead Section, GM, Practice, Lightweight, M252, and Shipping and Storage Container, XM612.

6.2 Ordering data.-See MIL-A-48078.

* 6.3 Submission of inspection equipment designs for approval.-See MIL-A-48078. Submit equipment designs as required to Commander, U.S. Army Armament Research and Development Command, ATTN: DRDAR-QAR-I, Dover, N.J. 07801.

* 6.4 Submission of results of contractor-conducted examinations and tests.-Unless otherwise specified by the Contracting

Source: https://assist.dla.mil -- Downloaded: 202640-26T03:57Z
Check the source to verify that this is the currentversion before use.

Officer, the contractor shall forward requested records of examinations or tests to Commander, U.S. Army Armament Research and Development Command, ATTN: DRDAR-QAR-R, Dover, N.J. 07801.

* 6.5 Changes from previous issue.-The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

* 6.6 Drawings.-Drawings listed in Section 2 of this specification under the heading US Army Armament Research and Development Command (ARRADCOM) may also include drawings prepared by, and identified as, Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal or Picatinny Arsenal drawings. Technical data originally prepared by these activities is now under the cognizance of ARRADCOM.

Custodian:
Army-AR

Preparing Activity:
Army-AR

Project Number: 1336-A301

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

test voltage shall be ... The

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-W-48866A Warhead section, GM, Practice Lightweight, M252

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*	TELEPHONE NO.
	DATE

DD FORM 1 OCT 76 1426 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY CARD

FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Armament R & D Command
ATTN: DRDAR-QAR
Dover, New Jersey 07801

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T03:57Z
Check the source to verify that this is the current version before use.