MILITARY SPECIFICATION

CARRIAGE, HOWITZER, 105MM, M2A2 (w/REpAIR PARTS AND W/O EQUIPMENT OR ACCESSORIES)

This interim amendment is issued for use by the Department of the Army with MIL-C-2015B dated 18 September 1958.

PAGE 2

Paragraph 3.2.3: Delete in its entirety and substitute:

"3.2.3 Handwheel loads. With a complete round of dummy ammunition, or equivalent distributed weight, in the chamber of the howitzer and mounted with the recoil mechanism to the carriage, the torque *or* force required at the handwheel center (nut) to elevate or traverse the weapon shall not exceed the following in any position or direction of traverse.

a. For elevation handwheel torque or force, the values shall not exceed limits presented in the table below:

Torque (max.) (inch-pounds)	Handwheel Force (max.) (pounds)	Howitzer Angle of Elevation (Mils)
130	29	Less than 200 mils or' more than 1000 mils.
90	20	Equal to or more than 200 mils or equal to or less than 1000 mils.

b. For traversing handwheel torque, the torque shall not exceed 52 inch-pounds or a force required at the, rim of the handwheel shall not exceed" 13 pounds.':

PAGE 3

Add the following new paragraph:

"3.2.5 Completed carriage storage. Completed carriages shall not be with stored the cannon at elevations lower than 300 mils."

Custodian:
Army-AR
Navy-MC

Preparing *Activity:
Army-AR

Project Number: 1015-A277

U.S.GOVERNMENT PRINTING OFFICE: 1981-703-023/7259

FSC: 1015 .

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:58Z
Check the source to verify that this is the current version before use.