MIL-I-2002C(SHIPS)
30 June 1964
SUPERSEDING
MIL-I-2002B(SHIPS)
6 August 1959
(See 6.2)

MILITARY SPECIFICATION

INDICATORS, BOILER SMOKE, NAVAL SHIPBOARD

1. SCOPE

1.1 This specification covers boiler smoke indicators for shipboard use.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of the specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

W-L-101 - Lamps; Electric, Incandescent, Large, Tungsten-Filament.
FF-S-92 - Screws, Machine, Slotted or Cross-Recessed.
QQ-A-601 - Aluminum Alloy Sand Castings.

MILITARY

MIL-P-116 - Preservation, Methods of.
MIL-D-963 - Drawings, Electrical, Hull and Mechanical Equipment for Naval Shipboard Use.
MIL-C-5541 - Chemical Films for Aluminum and Aluminum Alloys.
MIL-A-8625 - Anodic Coatings, for Aluminum and Aluminum Alloys.
MIL-P-14276 - Paint, Heat Resisting, Silicone, Aluminum.
MIL-P-15328 - Primer, Pretreatment (Formula No. 117 for Metals).
MIL-L-16221 - Lenses, Light; and Globes, Light.
MIL-C-17277 - Clamps, Electric Cable (for Lighting Fixtures, Fittings and Enclosures Except Watertight) (Shipboard Use).

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MS 16752 - Lampholder, Medium Screw, Plastic, 250 Volt, 660 Watt, 2 Contact, 3 Contact.

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications.- The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

OFFICIAL CLASSIFICATION COMMITTEE
Uniform Freight Classification Rules.

(Application for copies should be addressed to the Official Classification Committee, 1 Park Avenue at 33rd Street, New York 16, N.Y.)

NATIONAL BUREAU OF STANDARDS
Handbook H28 - Screw-Thread Standards for Federal Services.

(Application for copies should be addressed to the Superintendent of Documents, Government Printing Office, Washington 25, D.C.)

FSC 6320

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:58Z
Check the source to verify that this is the current version before use.

ASSOCIATION OF AMERICAN RAILROADS
Pamphlet 69-49 - Signal Glasses (Exclusive of Kerosene Hand Lantern Globes).

(Copies may be obtained from Association of American Railroads, 17th and H Streets, N.W., Washington, D.C.)

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

3. REQUIREMENTS

3.1 Material.- Material shall be as hereinafter specified. Material not definitely specified shall be of the quality best suited for the purpose intended.

3.2 General requirements.-

3.2.1 The smoke indicators shall consist of a light unit, a reflecting unit, and a vision unit suitably threaded for attachment to 4-inch pipes or 4-1/2 inch outside diameter tubing. These pipes or tubing intended as connections between the light unit and uptake casing, the reflecting unit and uptake casing and as extensions between the reflecting and vision units shall be furnished with the smoke indicators when specified (see 6.1). Where extension tubes are not to be installed, a reflecting unit only shall be furnished and the light outlet end of the reflecting unit shall be similar in design to that of the vision unit.

3.2.2 The smoke indicator shall clearly and unmistakably indicate the difference between no smoke and smoke of a density which appears as a trace at the top of the boiler smoke pipe.

3.2.3 Boxes and cover plates.- The boxes and cover plates of the light unit, reflecting unit and vision unit shall be made of aluminum alloy conforming to QQ-A-601, zinc-coated malleable iron, cast bronze, or other material satisfactory to the bureau or agency concerned. All metallic fittings on the boxes and cover plates shall be made of steel, protected by a corrosion-resisting finish.

3.2.4 Thumb screws for securing doors or covers shall be not less than 5/16-inch in diameter. All other screws shall be round or fillister headed, conforming to FF-S-92.

3.3 Protective coating.- All surfaces of aluminum or aluminum-alloy shall be protected against corrosion. One of the following methods is to be used:

(a) Method I.- Pretreatment in accordance with MIL-C-5541 or MIL-P-15328, followed by two coats of heat resisting paint in accordance with MIL-P-14276.
(b) Method II.- Anodic coating in accordance with MIL-A-8625.

3.3.1 If method I is used, the pretreatment shall be applied after all machining, heat treatment and fabrication have been completed and after the surfaces have been thoroughly cleaned and dried. After the pretreatment has dried, the paint shall be applied, allowing sufficient time between coats for thorough drying. Method II treatment requirements are fully outlined in MIL-A-8625.

3.4 Light unit.- The light unit shall project a beam of light from an incandescent lamp mounted therein, through the pipe into the uptake, across the uptake through the gases of combustion, through a pipe on the opposite side of the boiler and through a clear polished heat-resisting glass, to a mirror mounted in the reflecting unit. The mirror shall reflect the beam of the light through an angle, as specified in 3.5.1.1, through an extension tube to the vision unit so as to make the beam visible to an operator standing on the floor plates of the boiler room.

3.4.1 The light unit shall consist of the following parts:

Light unit box.
60-watt, 125-volt incandescent lamp.
Lamp socket.
Optical lens.

Source: https://assist.dla.mil -- Downloaded: 202610-16T13:58Z
Check the source to verify that this is the current version before use.

3.4.1.1 The light unit box shall be so constructed as to provide ready access for replacing the incandescent lamp and the electrical connection between the box and lamp base, as well as for cleaning and replacing the optical lens. It shall be threaded with straight pipe thread for attachment to a 4-inch iron pipe size(i.p.s.) pipe passing through the uptake casing. The threads shall conform to Handbook H28.

3.4.1.2 A 60-watt, 125-volt, incandescent lamp shall provide the source of light. Lamp description shall be: tungsten-filament, bulb shape A-21, finish clear, length overall 4-7/16-inches, light center length 2-7/16-inches, life 2000 hours, base type medium screw, light intensity, 665 lumens, in accordance with W-L-101.

3.4.1.3 The lamp socket for mounting the incandescent lamp shall be type A as shown on MS16752.

3.4.1.4 The optical lens shall be so designed as to project the light beam from the incandescent lamp in parallel rays. The lens shall be secured in place by a retaining ring or other satisfactory method, with asbestos gaskets coated with a thin layer of plastic packing between the joint faces of the lens and the light unit and retaining ring. The space around the periphery of the lens shall be filled with the plastic packing to insure a gastight joint when the lens is pressed in place. The optical lens shall be circular and shall conform to the requirements for lunar white (kerosene) lenses specified in Pamphlet No. 69-49, Association of American Railroads.

3.4.1.5 The incandescent lamp shall be mounted with its axis horizontal and be located in proper focus with the optical lens. A cable clamp, conforming to MIL-C-17277, without retaining lips, shall be provided to secure the cable where it enters the light unit.

3.4.1.6 Provision shall be made to permit the replacement of incandescent lamps without removal of the optical lens. The method of attachment to the case shall be by wing nuts to permit easy removal for repair.

3.5 Reflecting unit.-

3.5.1 The reflecting unit shall consist of the following parts:

(a) Reflecting unit box.
(b) Circular glass seal.
(c) Reflecting mirror.

3.5.1.1 The reflecting unit box shall have a 4-inch light inlet and outlet at 90 degrees to each other. It shall be so designed that light entering the inlet will be reflected by the reflecting mirror to the light outlet. Both ends of the reflecting unit shall be threaded with straight pipe threads for attachment to 4-inch pipes i.p.s. or 4-1/2-inch outside diameter tubing. The threads shall conform to Handbook H28. Two lock nuts shall be provided for locking the unit to the extension tubing. A hinged cover plate shall be provided as a side of the box, on which shall be mounted the adjustable frame carrying the reflecting mirror. In mounting the mirror, it shall be protected from direct contact with the frame by felt. The adjustable frame shall be so mounted as to cause the mirror to reflect the beam of light over a minimum range of from 85 degrees to 95 degrees, for example, at least 5 degrees either side of a 90-degree angle.

3.5.1.2 The circular glass seal shall be of substantial thickness conforming to grade E of MIL-L-16221. It shall be fitted in the light inlet end of the reflecting unit and shall effectively seal the reflecting unit against the entrance of air into the boiler uptake through the reflecting unit. The glass shall be so mounted as to be readily accessible for cleaning and replacement without the removal of the reflecting unit from the 4-inch pipe piercing the uptake casing.

3.5.1.3 Reflecting mirror.- The reflecting mirror shall conform to the requirements specified in 3.5.1.3.1, 3.5.1.3.2 and 3.5.1.3.3.

3.5.1.3.1 The glass of the mirror shall be made of the finest grade, be clear without perceptible tint, be free from flaws, bubbles and other defects and shall be ground to a true surface highly polished, front and back.

3.5.1.3.2 The reflective backing of the mirror shall consist of a heavy coating of metallic silver. The metallic silver shall be homogeneous, so that it may be evenly applied to the surface of the glass, and shall form an airtight joint with the glass.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:58Z
Check the source to verify that this is the current version before use.

3.5.1.3.3 There shall be placed over the reflective backing of the mirror, protective backing consisting of one heavy coat of metallic copper and over this copper plate, a coating of heavy enamel which shall so seal the backing as to render it absolutely waterproof and airtight.

3.6 The light unit and reflecting unit shall be made airtight. Provision shall be made for admission of air on the uptake gas side of the lens of the light unit, and of the clear glass sealing the reflecting unit. Admission air to the uptake gas side of the units shall be through six slots or ports at least 1/8 inch in width, 60 degrees apart; angle of admission shall be such as to direct the purging air to keep clean the lens or sealing glass as applicable; slots or ports shall be sized for maximum assistance in providing adequate air pressure to prevent soot particles from drifting toward and obscuring the lens and glass. Two 3/8 inch i.p.s. tapped connections, 180 degrees apart, leading to the air ports on the uptake gas side of the lens or glass shall be provided in or affixed to the units.

3.7 Vision unit.- The vision unit shall be of similar construction to that of the reflecting unit, except that the sealing glass and the draft holes (see 3.6) shall be omitted and straight pipe threads for attachment to 4-1/2-inch outside diameter tubing shall be provided in the light inlet end only. The light outlet end of the vision unit shall have a flared opening to permit as wide a range of visibility as practicable. The opening may be rectangular or circular. Unless otherwise approved, the viewing dimension of the opening shall be not less than 5-1/2 inches. A lock nut for locking the vision unit on the extension tube shall be provided. The mirror frame of the vision unit shall be adjustable and shall reflect a beam of light as specified in 3.5.1.1.

3.8 Drawings.- Drawings shall be in accordance with MIL-D-963.

3.9 Identification plates.-

3.9.1 Identification plates and other designating markings shall be mounted on and furnished as part of the equipment. They shall be attached to the part of the equipment which will not ordinarily be renewed during its normal service life and be located in a readily accessible position so that they can be read at all times without danger to personnel.

3.9.2 Where identification plates or designating plates are mounted on aluminum-alloy, care shall be taken to protect the aluminum-alloy against corrosion (see 3.3) before mounting the plates.

3.9.3 Marking.- The data marked on identification plates shall include the following:

(a) Manufacturer's name.
(b) Identification symbols.
(c) Serial number.
(d) Contract or order number.
(e) Date of manufacture.
(f) Blank space for inspector's official stamp.

3.10 Repair parts.-

3.10.1 The following repair parts shall be furnished:

(a) Optical lens.
(b) Sealing glass.
(c) Reflecting mirror.

3.10.2 Repair parts shall be furnished in quantities as specified (see 6.1). Quantities shall be based upon 10 percent of the total number of each item installed for each ship, fractions to be taken as the next whole number.

3.11 Workmanship.- Workmanship shall be first class in every respect.

3.12 Service life.- For record purposes, the service life of smoke indicators is 30 to 40 years or 120,000 to 160,000 operating hours, whichever comes first.

Source: https://assist.dla.mil -- Downloaded: 202640-16T13:58Z
Check the source to verify that this is the currentversion before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.- Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Sampling for inspection.-

4.2.1 Lot.- All indicators offered for delivery at one time shall be considered a lot for purposes of inspection.

4.2.2 Sampling for examination.- A random sample of indicators shall be selected from each lot in accordance with MIL-STD-105 at special inspection level S-1. The Acceptable Quality Level shall be 1.5 percent defective.

4.2.3 Sampling for test.- A random sample of indicators shall be selected from each lot in accordance with MIL-STD-105 at special inspection level S-3.

4.3 Examination.- Each of the sample indicators selected in accordance with 4.2.2 shall be examined to verify compliance with this specification. Examination shall be conducted as specified in table I. Any indicator in the sample containing one or more defects shall not be offered for delivery. If the number of defective indicators in any sample exceeds the acceptance number for that sample, this shall be cause for rejection of the lot represented by that sample.

Table I - Classification of defects in accordance with MIL-STD-105.

Categories	Defects
Critical:	
1	None defined.
Major:	
101	Indicator not complete: component parts missing.
102	Component parts not new: evidence of reclaimed, used or salvaged components.
103	Evidence of use of unauthorized material and repairs.
104	Indicators do not consist of units specified; not threaded for attachment to pipes or tubing specified.
105	Pipes and tubing for use with smoke indicators not furnished (if required).
106	Light outlet of reflecting unit not similar to outlet of vision unit (if required).
107	Boxes and cover plates of units not made of aluminum-alloy (if specified).
108	Metallic fittings on boxes and cover plates not made of steel, protected by corrosion-resisting finish.
109	Thumb screws for securing doors and covers not proper diameter.
110	Other screws not round or fillister headed.
111	All aluminum and aluminum-alloy surfaces not protected from corrosion.
112	Light unit not complete: component parts missing.
113	Light unit not provided with access to incandescent lamp, electrical connection between lamp and box base and for cleaning and replacing optical lens.
114	Access not threaded with straight pipe thread for attachment to 4-inch iron pipe; threads nonconforming.
115	Incandescent light not provided.
116	Lamp socket not provided.
117	Optical lens not secured in place by retaining ring; no asbestos gaskets between joint faces of lens in light unit and retaining ring.
118	Evidence that plastic packing around lens does not make lens gas-tight.
119	Optical lens not circular; nonconforming to approved standard.
120	Incandescent lamp not mounted with its axis horizontal; not located in proper focus with lens.
121	Cable clamp not provided.
122	Lamps cannot be replaced without removal of lens.

Source: https://assist.dla.mil -- Downloaded: 202610-16T13:58Z
Check the source to verify that this is the current version before use.

Table I - Classification of defects in accordance with MIL-STD-105. (Cont'd.)

Categories	Defects
123	Reflecting unit not complete; component parts missing.
124	Light inlet and outlet not provided in reflecting unit box; inlet and outlet not in specified angular relationship.
125	Ends of reflecting unit not threaded.
126	Threads nonconforming.
127	No hinge cover plate provided on side of box; adjustable frame not mounted on hinge cover.
128	Felt not provided to protect mirror from frame.
129	Circular glass seal not as specified; not fitted to light inlet end of reflecting unit.
130	Glass not accessible for cleaning and replacement without removal of reflecting unit.
131	Reflecting mirror not free of flaws, bubbles, pits, scratches or foreign matter; not clear without perceptible tint; not ground to a true surface polish, front and back.
132	Reflective backing of mirror does not consist of heavy coating of metallic silver; silver not homogeneous; does not form airtight joint with glass.
133	Protective backing of reflective backing not provided.
134	Vision unit not complete; component parts missing.
135	No lock nut provided to vision unit and extension tube.
136	Light outlet end opening configuration and dimensions not as specified.
137	Mirror frame of vision unit not adjustable.
138	Drawing not provided as specified.
Minor:	
201	Identification plate and markings not attached or located as specified; not legible; data incomplete.
202	Repair parts not furnished; optical lens, sealing glass and reflecting mirror not as specified.

4.4 Test procedure.- Each of the sample smoke indicators selected in accordance with 4.2.3 shall be tested for satisfactory operation and ruggedness of construction. Failure of any sample to pass this test shall be cause for rejecting the lot. Possible test failures are defined as follows:

(a) Evidence of light beam not visible to operator; lamp and lamp socket not operable; optical lens does not give clear beam; dimensions nonconforming.
(b) Frame will not adjust to give light beam over specified range.
(c) Reflective backing coated not effective; evidence of pits, cracks; not watertight or air-proof.
(d) Indicator cannot show difference between no smoke and smoke of trace density at top of boiler smoke pipe.

4.5 Sampling and inspection of cleaning and packaging.- Sampling and inspection of cleaning and packaging shall be performed in accordance with MIL-P-116 to verify conformance with the requirements of section 5 herein.

5. PREPARATION FOR DELIVERY

5.1 Domestic shipment and early equipment installation and for storage of onboard repair parts.-

5.1.1 Smoke indicators.-

5.1.1.1 Preservation and packaging.- Preservation and packaging shall be sufficient to afford adequate protection against corrosion, deterioration and physical damage during shipment from the supply source to the using activity and until early installation and may conform to the suppliers commercial practice when such meets these requirements. All openings shall be sealed to prevent entrance of foreign matter.

5.1.1.2 Packing.- Packing shall be accomplished in a manner which will insure acceptance by common carrier at the lowest rate and will afford protection against physical or mechanical damage during direct shipment from the supply source to the using activity for early installation. The shipping containers or method of packing shall conform to the Uniform Freight Classification Rules and Regulations or other carrier regulations as applicable to the mode of transportation and may conform to the suppliers commercial practice when such meets these requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:58Z
Check the source to verify that this is the current version before use.

5.1.1.3 Marking.- Shipment marking information shall be provided on interior packages and exterior shipping containers in accordance with the supplier's commercial practice. The information shall include nomenclature, Federal stock number or manufacturer's part number, contract or order number, manufacturer's name and destination.

5.1.2 Onboard repair parts.- Onboard repair parts shall be preserved and packaged in accordance with the guide lines of MIL-P-116. Repair parts shall be individually packaged, except when used in sets.

5.2 Domestic shipment and storage or overseas shipment.- The requirements, and levels of preservation, packaging, packing and marking for shipment shall be specified by the procuring activity (see 6.1).

(5.2.1 The following provides various levels of protection during domestic shipment and storage or overseas shipment, which may be required when procurement is made:

5.2.1.1 Cleaning and packaging.-

5.2.1.1.1 Level A.- Components of the smoke indicator shall be cleaned by process C-1 and individually packaged in accordance with method III of MIL-P-116. Unit containers shall conform to PPP-B-566, PPP-B-676, PPP-B-665 or PPP-B-636, respectively, at the option of the contractor. The gross weight of paperboard boxes shall not exceed 10 pounds and fiber boxes shall not exceed 20 pounds. The components shall be cushioned within the containers in a manner to prohibit movement. Detached connecting hardware shall be placed in envelopes and sealed and included in the component containers. Packages containing glass shall be separated by fiberboard pads, and lined top, bottom and sides with double wall corrugated fiberboard.

5.2.1.2 Packing.-

5.2.1.2.1 Level A.- The components of the smoke indicator, packaged as specified (see 5.2.1.1.1), shall be packed as a unit in overseas type boxes conforming to any of the following: PPP-B-591, PPP-B-621 (class 2), PPP-B-585 (class 3), PPP-B-636 (class 2), MIL-B-10377 or PPP-B-601. Shipping containers shall have caseliners conforming to MIL-L-10547 and appendix thereto. Caseliners for boxes conforming to PPP-B-636 may be omitted provided all corners and joints of the boxes are sealed with minimum 1-1/2-inch tape conforming to PPP-T-76. Boxes shall be closed and strapped as specified in the applicable box specification or appendix thereto. The gross weight of wood boxes shall not exceed 200 pounds; fiberboard boxes shall not exceed the weight limitations of the applicable box specification.

5.2.1.2.2 Level B.- The components of the smoke indicator, packaged as specified (see 5.2.1.1.1), shall be packed in domestic type boxes conforming to any of the following: PPP-B-591, PPP-B-621 (class 1), PPP-B-585 (class 1 or 2), PPP-B-636 (class 1 or 2), PPP-B-601 or MIL-B-10377. Closures shall be as specified in the applicable box specification, or appendix thereto. The gross weight of wood boxes shall not exceed 200 pounds; fiberboard boxes shall not exceed the weight limitations of the applicable box specification.

5.2.1.3 Marking.- In addition to any special marking specified in the contract or order, interior packages and exterior shipping containers shall be marked in accordance with MIL-STD-129.

5.2.2 Repair parts.-

5.2.2.1 Onboard repair parts.- Onboard repair parts, packaged as specified in 5.1.2, shall be packed in accordance with 5.2.1.2.1 or 5.2.1.2.2.

5.2.2.2 Stock repair parts.- Stock repair parts shall be packed in accordance with 5.2.1.2.1 or 5.2.1.2.2.)

6. NOTES

6.1 Ordering data.- Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Whether 4-inch pipe or 4-1/2-inch outside diameter tubing is required with smoke indicators (see 3.2.1).
(c) Quantity of repair parts required (see 3.10.2).
(d) Cleaning, preservation and packaging, packing, and marking if other than as specified in 5.1 (see 5.2).

Source: https://assist.dla.mil -- Downloaded: 202640-16T13:58Z
Check the source to verify that this is the current version before use.

6.2 CHANGES FROM PREVIOUS ISSUE. THE EXTENT OF CHANGES (DELETIONS, ADDITIONS, ETC.) PRECLUDE THE ANNOTATION OF THE INDIVIDUAL CHANGES FROM THE PREVIOUS ISSUE OF THIS DOCUMENT.

Preparing activity:
Navy - Ships
(Project 6320-N026Sh)

Source: https://assist.dla.mil -- Downloaded: 202610-16T13:58Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO 12062 WASHINGTON D C
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Natick Research and Development
Laboratories
ATTN: DRDNA-ES (Mr. D. Luppino)
Natick, MA 01760

Source: https://assist.dla.mil -- Downloaded: 202640-16T13:58Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*:

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:58Z
Check the source to verify that this is the current version before use.