NOTICE OF
CHANGE

DOD-STD-35-131(MI)
NOTICE 2
18 SEPTEMBER 1992

MILITARY STANDARD

AUTOMATED ENGINEERING
DOCUMENT PREPARATION SYSTEM

TIMERS, INTERVAL, SEQUENTIAL, STOP

TO ALL HOLDERS OF DOD-STD-35-131(MI):

1. THE FOLLOWING PAGES OF DOD-STD-35-131(MI) HAVE BEEN REVISED AND SUPERSEDE THE PAGES LISTED.

NEW PAGE	DATE	SUPERSEDED PAGE	DATE
v	18 SEPTEMBER 1992	v	18 AUGUST 1978
1	18 AUGUST 1978	(Reprinted without change)	
2	18 SEPTEMBER 1992	2	18 AUGUST 1978
3	18 SEPTEMBER 1992	3	18 AUGUST 1978
4	18 SEPTEMBER 1992	4	18 AUGUST 1978
9	18 SEPTEMBER 1992	9	18 AUGUST 1978
10	18 SEPTEMBER 1992	10	18 AUGUST 1978
39	18 AUGUST 1978	(Reprinted without change)	
40	18 SEPTEMBER 1992	40	18 AUGUST 1978
41	18 SEPTEMBER 1992	41	18 AUGUST 1978
42	18 AUGUST 1978	(Reprinted without change)	
83	18 AUGUST 1978	(Reprinted without change)	
84	18 SEPTEMBER 1992	84	18 AUGUST 1978
85	18 SEPTEMBER 1992	85	18 AUGUST 1978
86	18 SEPTEMBER 1992	86	18 AUGUST 1978
89	18 AUGUST 1978	(Reprinted without change)	
90	18 SEPTEMBER 1992	90	18 AUGUST 1978
91	18 SEPTEMBER 1992	91	18 AUGUST 1978
92	18 AUGUST 1978	(Reprinted without change)	
97	18 AUGUST 1978	(Reprinted without change)	
98	18 SEPTEMBER 1992	98	18 AUGUST 1978
99	18 SEPTEMBER 1992	99	18 AUGUST 1978
100	18 AUGUST 1978	(Reprinted without change)	

AMSC N/A AREA EGDS

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:05Z
Check the source to verify that this is the current version before use.

2. RETAIN THIS NOTICE PAGE AND INSERT BEFORE THE TABLE OF CONTENTS.

3. Holders of DOD-STD-35-131(MI) will verify that page changes and additions indicated above have been entered. The notice page will be retained as a check sheet. This issuance, together with appended pages is a separate publication. Each notice is to be retained by stocking points until the Military Standard is completely revised or canceled.

Custodians:
Army-MI

Review activities:
Army-AT, AV, CR, ER
ME, MR, SC

User activity
Army - AR

Preparing activity:
Army - MI

(Project EGDS-A462)

Source: https://assist.dla.mil -- Downloaded: 202610-23T21:05Z
Check the source to verify that this is the current version before use.

CONTENTS

			Page
Paragraph	1.	SCOPE	1
	1.1	General	1
	1.2	Purpose	1
	1.3	Utilization	1
	1.4	Military Specification Exception Title Index	1
	2.	APPLICABLE DOCUMENTS	3
	2.1	Government documents	3
	2.2	Non-Government publications	4
	3.	DEFINITIONS	5
	4.	GENERAL REQUIREMENTS	7
	4.1	Introduction	7
	4.2	Specification Requirement Sheet (SRS)	7
	4.3	Configuration	7
	4.3.1	Dimensions	7
	4.3.2	Illustrations	7
	4.4	Units of measure	7
	5	DETAILED REQUIREMENTS	9
	5.1	Introduction	9
	5.2	MSE Formats	9
	5.3	Referenced documents	9
	5.4	Deleted	9
	5.5	Tabulation	10
	5.6	Keyword Code Index (KCI) and Standard Paragraphs	15
	5.6.1	Interrelationship of Codes	15
	5.6.2	Automatic MSE Data	15
	5.6.3	DOD-STD-35 Tables	15

TABLES

Table	I.	Title Index	2
	II.	Deleted	10
	III.	Tabulation Candidates	11

APPENDICES

Appendix	A.	Illustrations	123
	B.	Characteristic Code Index	127
		Index	133

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:05Z
Check the source to verify that this is the current version before use.

1. SCOPE

1.1 General. This dash-numbered part of the Automated Engineering Document Preparation System (AEDPS), provides detailed requirements for the preparation of Military Specification Exception (MSE) documentation for Timers, Interval, Sequential and Stop.

1.2 Purpose. This military standard provides to the user the necessary information for the preparation of a Specification Requirement Sheet (SRS) which will result in the generation of an MSE by automated data processing.

1.3 Utilization. General instructions, quality assurance provisions, packaging, and notes, applicable to all AEDPS dash-numbered parts have been included in the basic document (DOD-STD-35) to avoid redundancy. Unless otherwise specified in this standard, the following list contains subjects that are applicable to all AEDPS dash-numbered parts and are included in DOD-STD-35:

a. Writing Methodology
b. Document and Part Numbering
c. Applicable Documents
d. Single and Multi-item Specifications (Tabulation)
e. Keyword Code Index (KCI)
f. General Requirements of AEDPS

1.4 Military Specification Exception Title Index. The title code for an MSE shall be selected from one of the MSE titles listed in the Title Index (see table I). Data bases have been established for the generation of MSE's for the MSE titles indicated. If a suitable title code is not contained in the Title Index, leave the title code spaces on the SRS blank, and attach a request for the assignment of a title code. Include in the request the desired title and the base document identifier. A code will be assigned and the code, title, and base document will be made a part of the Title Index.

One of the six-digit codes listed in the Title Index, entered on an SRS, will specify that the title of the MSE will be the title shown in the Title Index.

Each MSE title listed in the Title Index is compatible with the document(s) listed with that title under base document. The list of base documents may or may not be a complete listing. The information shown under coverage is intended for the user's reference; when more than one document is listed for an MSE title, this information will be found useful in determining which of the documents is most suitable for use as the base document.

Source: https://assist.dla.mil -- Downloaded: 202610-23T21:05Z
Check the source to verify that this is the current version before use.

The MSE title may or may not be the same as the title used in DODISS, FIIG, or the base document. In general, the MSE title uses the basic federal item name listed in Cataloging Handbook H6. However, titles with additional modifying and identifying words are provided to assist in defining the scope of the MSE. Also, less restrictive titles are provided to prevent exclusion of items.

TABLE I. TITLE INDEX

MSE TITLE	TITLE CODE	BASE DOCUMENT NUMBER	BASE DOCUMENT COVERAGE
TIMER, INTERVAL	054001	A-A-1457 OR A-A-726	MANUALLY WOUND SPRING DRIVEN
		MIL-T-45603	TD-114/M
		MIL-T-82535	MARK 11 MOD 2 ASSEMBLY
TIMER, SEQUENTIAL	054002	MIL-T-22012	BATTERY CONDITIONING TD-267/U
TIMER, STOP	054003		
TIMER, ASSEMBLY	054004		

Source: https://assist.dla.mil -- Downloaded: 202640-23T21:05Z
Check the source to verify that this is the current version before use.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

FEDERAL

A-A-726	Timer, Mechanical (60 Minute,Interval)
A-A-1457	Timer, Mechanical (120 Minute, Maximum Interval)

MILITARY

MIL-S-901	Shock Tests, H.I. (High Impact) Shipboard Machinery, Equipment and Systems, Requirements for (Navy)
MIL-T-45603	Timer, Interval, TD-114/M
MIL-T-82535	Timer, Interval Mark 11 Mod 2 (Assembly)

STANDARDS

MILITARY

DOD-STD-35	Automated Engineering Document Preparation System
MIL-STD-130	Identification Marking of U.S. Property
MIL-STD-167/1	Mechanical Vibrations of Shipboard Equipment (Type I - Environmental and Type II Internally Excited)

Source: https://assist.dla.mil -- Downloaded: 202610-23T21:05Z
Check the source to verify that this is the currentversion before use.

MIL-STD-202	Test Methods for Electronic and Electrical Component Parts
MIL-STD-461	Electromagnetic Interference Characteristics Requirements for Equipment
MIL-STD-462	Electromagnetic Interference Characteristics Measurement of
MIL-STD-810	Environmental Test Methods
MIL-STD-1285	Marking of Electrical and Electronic Parts
MIL-STD-1523	Age Control of Age-Sensitive Elastomeric Materials

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Standardization Documents Order Desk, Bldg 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.2 Non-Government publications. The following document(s) form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation.

ASTM E 380	Metric Practice Guide

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race St., Philadelphia, PA 19103.)

NFPA-70	National Fire Protection Association (NFPA) National Electrical Code No. 70.

(Application for copies should be addressed to National Fire Protection Association, 470 Atlantic Ave., Boston, MA 02210.)

UL-863	Electric Time-Indicating and Recording Appliances.

(Application for copies should be addressed to the Underwriter's Laboratories, Inc., Walt Whitman Road, Melville, NY 11749; 207 East Ohio St., Chicago, IL 60611; or 1655 Scott Boulevard, Santa Clara, CA 95050.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:05Z
Check the source to verify that this is the current version before use.

5. DETAILED REQUIREMENTS

5.1 Introduction. This section provides instructions for completion of the SRS and references for instructions on specific requirements contained in DOD-STD-35.

5.2 MSE formats. AEDPS has the capability to prepare a six-section or a single-section document. The six-section document appears similar to a six-section military specification. The single-section document appears similar to a military specification sheet. Specification requirements described in DOD-STD-35 are applicable to either of the formats selected. It is mandatory that one of the two following codes and an "X" be entered on the SRS to create the desired MSE format:

a. 0700 for a six-section format

b. 0800 for a single-section format

5.3 Referenced documents. Section 2 of the MSE may contain a list of all referenced documents within Sections 3, 4, and 5 of the MSE. Instructions for referencing documents to appear in Section 2 of the forthcoming MSE are contained in DOD-STD-35.

5.4 Deleted

Source: https://assist.dla.mil -- Downloaded: 20261O-23T21:05Z
Check the source to verify that this is the currentversion before use.

5.5 Tabulation. Instructions for tabulation are provided in DOD-STD-35. Table III provides codes for column headings which may be used for timer characteristics. When different units of measure within one system (U.S. or SI) are available for specifying a characteristic, only one of the units may be tabulated; e.g. either ounces or pounds.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:05Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
1704	THE TIMER OPERATING TIME SHALL BE NOT GREATER THAN 1704 MINUTES.
1706	THE TIMER OPERATING TIME SHALL BE NOT GREATER THAN 1706 HOURS.
1708	THE TIMER OPERATING TIME SHALL BE NOT GREATER THAN 1708 DAYS.
1710	THE TIMER SHALL HAVE A TIME RANGE OF 1710.
	TIMER ALARM.
1722	A BELL ALARM SHALL BE PROVIDED WITH THE TIMER TO SIGNAL THE END OF A TIMING INTERVAL.
1724	A BUZZER ALARM SHALL BE PROVIDED WITH THE TIMER TO SIGNAL THE END OF A TIMING INTERVAL.
1726	THE AUDIBLE DISTANCE OF THE ALARM SHALL BE 1726 FEET.
1728	THE AUDIBLE DISTANCE OF THE ALARM SHALL BE 1728 METERS.
1730	ALARM VOLUME CONTROL. AN ALARM VOLUME CONTROL SHALL BE PROVIDED WITH THE TIMER.
1731	THE VOLUME CONTROL KNOB SHALL BE MOUNTED ON THE 1731 OF THE TIMER.
1732	CLUTCH MANUAL DISENGAGING LEVER. A CLUTCH DISENGAGING LEVER FOR RESETTING DIALS MANUALLY SHALL BE PROVIDED WITH THE TIMER.
1733	THE MOUNTING LOCATION SHALL BE 1733.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:05Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
DESIGN AND CONSTRUCTION (CONT)	
CORD AND PLUG ASSEMBLY	
PER (DOC DES)	1734
OTHER ____	1736
MAXIMUM CYCLE TIME	
(MINUTES)	1738
RESET PROVISIONS (SELECT ONE)	
MANUAL.	1740
AUTOMATIC.	1742
MANUAL AND AUTOMATIC.	1744
RESET CONTROL (SELECT ONE)	
LOCAL.	1746
REMOTE.	1748
LOCAL OR REMOTE.	1750
MAXIMUM RESET TIME (SELECT ONE)	
(MICROSECONDS)	1752
(MILLISECONDS)	1754
(SECONDS)	1756

Source: https://assist.dla.mil -- Downloaded: 202640-23T21:05Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
	CORD AND PLUG ASSEMBLY.
1734	A CORD AND PLUG ASSEMBLY SHALL BE PROVIDED WITH THE TIMER AND THE PLUG SHALL CONFORM TO 1734.
1736	THE CORD AND PLUG ASSEMBLY SHALL BE 1736.
	MAXIMUM CYCLE TIME.
1738	THE CYCLE TIME SHALL BE NOT GREATER THAN 1738.
	RESET PROVISIONS.
1740	THE TIMER SHALL BE CAPABLE OF BEING RESET MANUALLY.
1742	THE TIMER SHALL BE CAPABLE OF BEING RESET AUTOMATICALLY.
1744	THE TIMER SHALL BE CAPABLE OF BEING RESET MANUALLY OR AUTOMATICALLY.
	RESET CONTROL.
1746	A RESET CONTROL SHALL BE PROVIDED TO CONTROL THE TIMER LOCALLY.
1748	A RESET CONTROL SHALL BE PROVIDED TO CONTROL THE TIMER REMOTELY.
1750	A RESET CONTROL SHALL BE PROVIDED TO CONTROL THE TIMER LOCALLY OR REMOTELY.
	MAXIMUM RESET TIME.
1752	THE RESET TIME SHALL BE NOT GREATER THAN 1752 MICROSECONDS.
1754	THE RESET TIME SHALL BE NOT GREATER THAN 1754 MILLISECONDS.
1756	THE RESET TIME SHALL BE NOT GREATER THAN 1756 SECONDS.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:05Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
DESIGN AND CONSTRUCTION (CONT)	
ENCLOSURE TYPE (SELECT ONE)	
OPEN.	1758
CLOSED.	1760
SEALED.	1762
HERMETICALLY SEALED.	1764
OTHER ___	1766
TIMING MECHANISM (SELECT ONE)	
ELECTRONIC.	1768
ELECTRO-MECHANICAL.	1770
SPRING.	1772
FIRE AND CASUALTY PROVISIONS (SELECT AS REQUIRED)	
PER UL-863.	1774
PER NFPA-70.	1776
OTHER ___	1778
ELECTRICAL CONNECTORS	
(TYPE)	1780
INDICATOR LIGHT	
END OF TIMING CYCLE.	1782
MAXIMUM KNOB/POINTER TRAVEL	
(DEGREES)	1784

Source: https://assist.dla.mil -- Downloaded: 202610-23T21:05Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2402	LEAKAGE CURRENT. THE REQUIREMENT(S) SHALL BE AS FOLLOWS:
2404	THE LEAKAGE CURRENT PRIOR TO PULSE FOR A SINGLE TEST SHALL BE NOT GREATER THAN 2404 MILLIAMPERES.
2406	THE LEAKAGE CURRENT PRIOR TO PULSE FOR THE FIRST TEST SHALL BE NOT GREATER THAN 2406 MILLIAMPERES.
2408	THE LEAKAGE CURRENT PRIOR TO PULSE FOR THE SECOND TEST SHALL BE NOT GREATER THAN 2408 MILLIAMPERES.
2410	THE OUTPUT VOLTAGE FOR A SINGLE TEST SHALL BE NOT GREATER THAN 2410 MILLIVOLTS.
2412	THE OUTPUT VOLTAGE FOR THE FIRST TEST SHALL BE NOT GREATER THAN 2412 MILLIVOLTS.
2414	THE OUTPUT VOLTAGE FOR THE SECOND TEST SHALL BE NOT GREATER THAN 2414 MILLIVOLTS.
2416	THE ITEM(S) SHALL REMAIN WITHIN SPECIFIED TOLERANCE.
2418	THERE SHALL BE NO EVIDENCE OF PHYSICAL DAMAGE.
2420	LEAKAGE CURRENT. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2420.

Source: https://assist.dla.mil -- Downloaded: 202610-23T21:05Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
LEAKAGE CURRENT (CONT)	
TEST METHODS (CONT)	
PER MIL-T-82535.	2422
TIMER INTERVALS (SELECT ONE)	
(SECONDS)	2424
(MINUTES)	2426
TEST VOLTAGE (SELECT ONE)	
(VOLTS AC)	2428
(VOLTS DC)	2430
LIFE	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2500
AS FOLLOWS:	2502
MINIMUM OPERATIONAL LIFE (HOURS)	2504
PERCENT OF TOTAL REGISTRATION (PERCENT)	2506
REMAIN WITHIN SPECIFIED TOLERANCE.	2508
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2520
PER (DOC DES)	2522

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:05Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2422	LEAKAGE CURRENT. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH MIL-T-82535.
2424	THE TIMER INTERVAL(S) SHALL BE 2424 SECOND(S).
2426	THE TIMER INTERVAL(S) SHALL BE 2426 MINUTES.
2428	THE TEST VOLTAGE SHALL BE 2428 VOLTS AC.
2430	THE TEST VOLTAGE SHALL BE 2430 VOLTS DC.
2500	LIFE. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT EXCEPT 2500.
2502	LIFE. THE REQUIREMENT(S) SHALL BE AS FOLLOWS:
2504	THE OPERATIONAL LIFE SHALL BE NOT LESS THAN 2504 HOURS.
2506	THE TIMER LIFE SHALL BE 2506 PERCENT OF TOTAL REGISTRATION.
2508	THE ITEM(S) SHALL REMAIN WITHIN SPECIFIED TOLERANCE.
2520	LIFE. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2520.
2522	LIFE. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH 2522.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:05Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
LIFE (CONT)	
PER (DOC DES) (CONT)	
TEST TEMPERATURE (DEGREES CELSIUS)	2524
TEMPERATURE TOLERANCE PLUS OR MINUS (DEGREES CELSIUS)	2526
TEST DURATION (HOURS)	2528
MOTOR OPERATION (TIMING MECHANISM)	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2600
AS FOLLOWS:	2602
REMAIN WITHIN SPECIFIED TOLERANCE.	2604
DELAY TIME AFTER START RELAY CLOSES (MINUTES)	2606
DELAY TIME TOLERANCE (SECONDS)	2608
RECURRENT DELAY AFTER START RELAY OPENS (MINUTES)	2610
TIME TOLERANCE (SECONDS)	2612
INTERRUPTION TIME, POWER SUPPLY SWITCH OPEN (MINUTES)	2614
INTERRUPTION TIME TOLERANCE (SECONDS)	2616

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:05Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2618	THE MOTOR TIME DELAY CONTROL SHALL BE CAPABLE OF PROVIDING A RECURRENT DELAY TIME OF 2618 MINUTES AFTER THE END OF INTERRUPT TIME.
2620	THE RECURRENT DELAY TIME TOLERANCE AFTER INTERRUPT TIME SHALL BE 2620 SECONDS.
2630	MOTOR OPERATION TIMING MECHANISM. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2630.
2632	MOTOR OPERATION TIMING MECHANISM. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH 2632.
2634	THE TEST POWER SUPPLY VOLTAGE SHALL BE 2634 VOLTS AC.
2636	THE TEST POWER SUPPLY VOLTAGE SHALL BE 2636 VOLTS DC.
2638	THE TEST TIME SHALL BE MEASURED WITH AN APPROVED STOPWATCH.
2700	PREMATURE OUTPUT PULSE. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2700.
2702	PREMATURE OUTPUT PULSE. THE REQUIREMENT(S) SHALL BE AS FOLLOWS:
2704	ITEM(S) SHALL REMAIN WITHIN THE SPECIFIED TOLERANCE.
2706	THE OUTPUT PULSE VOLTAGE SHALL BE NOT GREATER THAN 2706 VOLTS DC.
2708	THERE SHALL BE NO OUTPUT PULSE DURING ELAPSED TIME PERIOD(S) OF 2708 SECONDS.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:05Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
PREMATURE OUTPUT PULSE (CONT)	
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2720
PER MIL-T-82535.	2722
MAXIMUM POTENTIAL (VOLTS DC)	2724
INPUT TIME INTERVALS (SECONDS)	2726
REOPENING INTERVAL (SWITCH CONTACTS)	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2800
AS FOLLOWS:	2802
MOTOR SWITCH CONTACTS SHALL OPEN.	2804
REMAIN WITHIN SPECIFIED TOLERANCE.	2806
OPENING TIME AFTER POWER SUPPLY INTERRUPTION (SECONDS)	2808
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2820
PER (DOC DES)	2822

Source: https://assist.dla.mil -- Downloaded: 202610-23T21:05Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2720	PREMATURE OUTPUT PULSE. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2720.
2722	PREMATURE OUTPUT PULSE. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH MIL-T-82535.
2724	THE APPLIED POTENTIAL SHALL BE NOT GREATER THAN 2724 VOLTS DC.
2726	THE INPUT TIME INTERVAL(S) SHALL BE 2726 SECONDS.
2800	REOPENING INTERVAL (SWITCH CONTACTS). THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2800.
2802	REOPENING INTERVAL (SWITCH CONTACTS). THE REQUIREMENT(S) SHALL BE AS FOLLOWS:
2804	THE MOTOR SWITCH CONTACTS SHALL OPEN.
2806	THE ITEM(S) SHALL REMAIN WITHIN SPECIFIED TOLERANCE.
2808	THE MOTOR SWITCH CONTACTS SHALL BE CAPABLE OF OPENING 2808 SECONDS AFTER INTERRUPTION OF THE 120 VOLT POWER SUPPLY.
2820	REOPENING INTERVAL (SWITCH CONTACTS). TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2820.
2822	REOPENING INTERVAL (SWITCH CONTACTS). TESTING SHALL BE PERFORMED IN ACCORDANCE WITH 2822.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:05Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
SEAL	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	4745
AS FOLLOWS:	6370
SPECIFIED TEST METHOD SENSITIVITY.	4746
NO BUBBLES INDICATIVE OF LEAKAGE.	4748
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	4734
PER MIL-STD-202, METHOD 112.	4732
*TEST CONDITION LETTER	
LETTER A.	4737
LIQUID FOR BATH (NAME)	4738
MINIMUM BATH TEMPERATURE (DEGREES CELSIUS)	4739
LETTER B.	6320
LIQUID FOR BATH (NAME)	6321
MINIMUM BATH TEMPERATURE (DEGREES CELSIUS)	6322
LETTER C.	6323

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:05Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
6330	GROSS LEAK TEST CONDITION LETTER 6330 SHALL APPLY.
6331	TEST CONDITION LETTER D SHALL APPLY.
4743	MOUNTING SHALL BE BY ANY SUITABLE METHOD.
6332	TEST CONDITION LETTER E SHALL APPLY.
6333	MOUNTING SHALL BE BY ANY SUITABLE METHOD.
2900	SETTING TORQUE. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2900.
2902	SETTING TORQUE. THE REQUIREMENT(S) SHALL BE AS FOLLOWS:
2904	THE TORQUE TO SET TIMER SHALL BE NOT GREATER THAN 2904 POUND-INCHES.
2906	THE TORQUE TO SET TIMER SHALL BE NOT GREATER THAN 2906 NEWTON METERS.
2908	THE TIMER SET POSITION TIME SHALL BE NOT LESS THAN 2908 SECONDS.
2910	THE TIMER SET POSITION TIME SHALL BE NOT GREATER THAN 2910 SECONDS.
2912	THERE SHALL BE NO DIAL MOVEMENT AFTER REMOVAL OF SETTING TORQUE.

Source: https://assist.dla.mil -- Downloaded: 202610-23T21:05Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
SETTING TORQUE (CONT)	
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2920
PER (DOC DES)	2922
MEASURE TORQUE WITH TORQUE WRENCH.	2924
SHOCK	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	7315
NO EVIDENCE OF PHYSICAL DAMAGE.	7316
NO LAMP IN TEST CIRCUIT SHALL LIGHT.	1551
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	7311
PER MIL-STD-810, METHOD 516.	7312
*PROCEDURE	
PROCEDURE I.	7313
*FIGURE (SELECT ONE)	
FIGURE 516-1 APPLIES.	7317
FIGURE 516-2 APPLIES.	7318

Source: https://assist.dla.mil -- Downloaded: 202610-23T21:05Z
Check the source to verify that this is the currenversion before use.

CHAR CODE	STANDARD PARAGRAPH
2920	SETTING TORQUE. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2920.
2922	SETTING TORQUE. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH 2922.
2924	MEASURE TORQUE WITH AN APPROVED TORQUE WRENCH.
7315	SHOCK. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 7315.
7316	SHOCK. THERE SHALL BE NO EVIDENCE OF PHYSICAL DAMAGE.
1551	NO LAMP IN THE TEST CIRCUIT SHALL LIGHT.
7311	SHOCK. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 7311.
7312	SHOCK. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH METHOD 516 OF MIL-STD-810.
7313	PROCEDURE NUMBER I SHALL APPLY.
7317	THE SHOCK PULSE SHAPE SHALL BE SAWTOOTH IN ACCORDANCE WITH FIGURE 516-1 OF METHOD 516 OF MIL-STD-810.
7318	THE SHOCK PULSE SHAPE SHALL BE HALF SINE WAVE IN ACCORDANCE WITH FIGURE 516-2 OF METHOD 516 OF MIL-STD-810.

Supersedes page 99 of 18 AUGUST 1978

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:05Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
SHOCK (CONT)	
PROCEDURE I. (CONT)	
*AMPLITUDE, A OR B (LETTER)	7305
*DURATION, C OR D (LETTER)	7306
PROCEDURE II.	6327
PROCEDURE III.	6338
*FIGURE (SELECT ONE)	
FIGURE 516-1 APPLIES.	6339
FIGURE 516-2 APPLIES	6340
*AMPLITUDE A OR B (LETTER)	6314
*DURATION C OR D (LETTER)	6342
PROCEDURE IV.	6343
*FIGURE (SELECT ONE)	
FIGURE 516-1 APPLIES.	6344
FIGURE 516-2 APPLIES.	6345
*AMPLITUDE, A OR B (LETTER)	6346
*DURATION, C OR D (LETTER)	6347
PROCEDURE V.	6348
PROCEDURE VI.	6349

Source: https://assist.dla.mil -- Downloaded: 202610-23T21:05Z
Check the source to verify that this is the current version before use.