MIL-C-50469 (MU)
14 January 1970
Superseding
(see para. 6.3.6)

MILITARY SPECIFICATION

CHARGE, SUPPLEMENTARY FOR DEEP
CAVITY LOADED PROJECTILE, PARTS FOR

1. SCOPE

1.1 This specification covers the metal parts, for supplementary charge, for deep cavity loaded projectiles.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposals form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-2550	-Ammunition and Special Weapons, General Specification for
MIL-I-45607	-Inspection Equipment, Supply and Maintenance of

STANDARDS

MILITARY

MIL-STD-105	-Sampling Procedures and Tables for Inspection by Attributes (ABC-STD-105)
MIL-STD-109	-Quality Assurance Terms and Defintions
MIL-STD-1168	-Lot Numbering of Ammunition
MIL-STD-1169	-Packing and Marking for Shipment of Inert Ammunition Components: General Specification for
MIL-STD-1235	-Single and Multilevel Continuous Sampling Procedures and Tables for Inspection by Attributes

DRAWINGS

ARMY

8838201 - Body
8838202 - Disc, Closing

FSC: 1315

Source: https://assist.dla.mil -- Downloaded: 20261O-22T20:26Z
Check the source to verify that this is the current version before use.

8838203 - Pad
8858820 - Disc
9248215 - Supplementary Charge Parts Arrangement

PUBLICATIONS

ARMY

ET-9248215 - Equipment Tabulation

(Copies of specifications, standards, drawings and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

Other publications.-The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on the date of invitation for bids or request for proposal shall apply.

ASTM-D461
Application for copies should be addressed to:
American Society for Testing and Materials 1916
Race St., Philadelphia, Pa. 19103

3. REQUIREMENTS

3.1 Materials.-Materials shall be in accordance with applicable drawings and specifications.

3.2 Parts.-The parts shall comply with all requirements specified on drawing (dwg) 8838201, 8838202, 8838203 and 8858820 as applicable and with all requirements specified in applicable specifications.

3.3 Workmanship.-All parts shall be dry and free of chips, burrs, dirt, grease, rust and other foreign material. The cleaning method shall not be injurious to any of the parts, nor shall the parts be contaminated by the cleaning agent.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.-Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order,

Source: https://assist.dla.mil -- Downloaded: 20261O-22T20:26Z
Check the source to verify that this is the currentversion before use.

the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements. Reference shall be made to Standard MIL-STD-109 in order to define terms used herein. The provisions of Specification MIL-A-2550 shall apply.

4.1.1 Submission of product.-At the time the completed lot of product is submitted to the Government for acceptance, the contractor shall supply the following information accompanied by a certificate which attests that the information provided is correct and applicable to the product being submitted:

a. A statement that the lot complies with all of the quality assurance provisions specified within this specification.

b. Number of units of product inspected.

c. Results obtained, by defect code, for all inspections performed.

d. Drawing, specification number and date, together with an identification and date of changes.

e. Certificates of conformance on all material purchased by the contractor when such material is controlled by the Government or commercial specifications referenced in any of the contractual documents.

f. Number of items in the lot.

g. Date submitted.

The certificate shall be signed by a responsible agent of the certifying organization. The initial certificate submitted shall be substantiated by evidence of the agent's authority to bind his principal. Substantiation of the agent's authority will not be required with subsequent certificates unless, during the course of the contract, this authority is vested in another agent of the certifying organization.

4.2 First Article Inspection

4.2.1 Submission.-The contractor shall submit a first article sample as designated by the contracting officer for evaluation in accordance with the provisions of 4.2.2. The first article sample shall consist of 25 sets of parts which have been produced by the contractor or furnished by a supplier and which have been manufactured using the same production processes, procedures and equipment which will be used in fulfilling the contract. All parts and materials, including packaging and packing, shall be obtained from the same source of supply as will be used in regular production. Prior to submission, the contractor shall inspect the sample to the degree necessary to assure that it conforms to the requirements of the contract and

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:26Z
Check the source to verify that this is the current version before use.

submit a record of this inspection with the sample, including statements of findings for materials, processes and tests. A sample containing known defects will not be submitted unless specifically authorized by the Contracting Officer. A first article sample, or portion thereof, as directed by the Contracting Officer, shall also be submitted whenever there is a lapse in production for a period in excess of 90 days or whenever a change occurs in manufacturing process, material used, drawing or specification such as to significantly affect product uniformity as determined by the Government.

4.2.2 Inspection to be performed.-Assemblies and components will be subjected by the Government to any or all the examinations or tests specified in 4.3.2 of this specification and any or all requirements of the applicable drawings.

4.2.3 Rejection.-If any assembly or part fails to comply with the applicable requirements, the initial production sample shall be rejected. In event of rejection, the Government reserves the right to require the contractor to take corrective action and submit new or supplemental quantities until such time as an acceptable sample is submitted or until otherwise directed by the contracting officer.

4.3 Inspection provisions

4.3.1 Lot formation.-The term "lot" as used throughout this specification refers to an inspection lot, which is defined as an essentially homogeneous collection of units of product from which a representative sample is drawn and inspected to determine conformance of the lot with applicable requirements. The sample selected shall represent only that quantity of units from which the sample was drawn and shall not be construed to represent any prior or subsequent quantities presented for inspection. Homogeneity shall be considered to exist provided the lot has been produced by one manfacturer in one unchanged process, in accordance with the same drawings, same drawing revisions, same specifications and same specification revisions. Changes to the process, specification, or drawings not affecting safety, performance, interchangeability, or storage, as determined by the Government, shall not be deemed to alter the homogeneity of the lot. Inspection lots shall comply with MIL-STD-105. Unless otherwise approved by the contracting officer, the inspection lot size of end items deliverable under the contract shall be not less than the smallest weekly estimate of quantities contractually scheduled for production during the contract period nor more than the largest monthly quantity contractually scheduled for delivery during the contract period. Inspection lot of components or subassemblies, other than the items of delivery, shall be homogeneous and of a size mutually convenient to both the

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:26Z
Check the source to verify that this is the current version before use.

contractor and the Government inspector. Lot numbering, as required, shall be in accordance with MIL-STD-1168.

4.3.2 Examination.-Inspection for Critical defects (and Major defects, when so specified), shall be 100 percent. Sampling plans and procedures for Major and Minor defects shall be in accordance with MIL-STD-105 except that continuous sampling plans in accordance with MIL-STD-1235 may be used if approved by the procuring activity. Also, at the option of the procuring activity, AQL's and sampling plans may be applied to individual characteristics listed using an AQL of 0.65 percent for each Minor defect and an AQL of 0.40 percent for each Major defect, except where 100 percent inspection is specified. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.3.3.

4.3.2.1 Pad (see dwg. 8838203)

Categories	Defects	Method of Inspection	Code No. (see 6.2)
Critical:	None defined.		
Major:	None defined.		
Minor:	AQL 1.5 percent		
101.	Thickness.....	Gage (see 4.3.2.7)	03001
102.	Diameter.....	Gage (see 4.3.2.7)	03002
103.	Weight (min).....	Scale (see 4.3.2.7)	03003
104.	Evidence of poor workmanship.	Visual	03004

4.3.2.2 Pad (alternative) (see dwg. 8838203)

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	None defined.		
Minor:	AQL 1.5 percent		
101.	Thickness.....	Gage (see 4.3.2.7)	04001
102.	Length, any side.....	Gage (see 4.3.2.7)	04002
103.	Evidence of poor workmanship.	Visual	04003

4.3.2.3 Disc (see dwg. 8858820)

Categories	Defects	Method of Inspection	Code No.

Source: https://assist.dla.mil -- Downloaded: 202640-22T20:26Z
Check the source to verify that this is the currenversion before use.

Critical: None defined

Major: None defined

Minor:		AQL 1.5 percent	
101.	Thickness.....	Gage (see 4.3.2.7)	05001
102.	Outside diameter.....	(see 4.3.2.7)	05002
103.	Inside diameter.....	(see 4.3.2.7)	05003
104.	Evidence of poor workmanship.....	Visual	05004

4.3.2.4 Body (see dwg. 8838201)

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major:	AQL 0.40 percent		
101.	Crack, split, puncture or similar damage extending through material.....	Visual	01001
Minor:	AQL 2.5 percent		
201.	Thickness.....	Gage	01002
202.	Inside diameter.....	Gage	01003
203.	Outside diameter.....	Gage	01004
204.	Total length.....	Gage	01005
205.	Damage (not extending through material) or distortion.....	Visual	01006
206.	Marking missing, misleading or unidentifiable.....	Visual	01007
207.	Evidence of poor workmanship (see 3.3).....	Visual	01008

4.3.2.5 Disc closing (see dwg. 8838202)

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major:	AQL 0.40 percent		
101.	Diameter, minimum (min).....	Gage	02001
102.	Crack, split, puncture or similar damage extending through material.....	Visual	02002
103.	Thickness, maximum (max)....	Gage	02006

Source: https://assist.dla.mil -- Downloaded: 202640-22T20:26Z
Check the source to verify that this is the currentversion before use.

Minor:		AQL 1.5 percent	
201.	Diameter, maximum (max).....	Gage	02003
202.	Damage (not extending through material) or distortion.....	Visual	02004
203.	Evidence of poor workmanship (see 3.3).....	Visual	02005

4.3.2.6 Dimensional Control of parts.-In place of the normal sampling associated with the classification of defects, and with the approval of the Contracting Officer, a sample of at least twenty-five (25) parts may be dimensionally inspected to qualify the tool used in the stamping process for use in production. In addition, a random sample of five (5) parts shall be selected from the last portion of each hours production for dimensional inspection as a control of the tool during production. If any defective parts are found during qualification of the tool, the tool producing the defective part shall not be used in production. If any defective parts are found when inspection is performed for control of the tool, the tool producing the defective part shall be removed from production. Further, that portion of production since the last tool control check shall be returned to the contractor for corrective action. All tools removed from production because of some fault, may, after reworking, be returned to production providing they pass the qualification test above.

4.3.2.7 Dimensional Control of Felt Parts.-Thickness of felt pads and discs shall be tested in accordance with ASTM-D-461. Verification of dimensional control of diameters may be exercised by dimensional inspection of production tooling with approval of the contracting officer.

4.3.3 Inspection Equipment.-Equipment Tabulation Number ET-9248215 identifies the inspection equipment required to perform the examinations and tests prescribed in this section. The contractor shall design inspection equipment in accordance with the instructions in paragraph 6.3.

4.3.3.1 Government rights to documentation.-Inspection equipment drawings and lists provided and revised in accordance with the requirements of the ET may be used by DOD activities for design, procurement, manufacture, testing, evaluation, production and receiving inspection, overhaul, shipping, storage, identification of stock, ordering and storage of replacement parts, inspection of items at overhaul, general maintenance of equipment, construction, survey and whenever inspection equipment drawings are needed.

4.3.3.2 Supply and maintenance.-Supply and maintenance of the equipment listed on the ET shall be in accordance with

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:26Z
Check the source to verify that this is the current version before use.

Specification MIL-I-45607.

4.3.3.3 Government use of contractor's inspection and test equipment.-The contractor shall make available to the Government all inspection and test equipment necessary for determining conformance with contract requirements. Personnel for operating the equipment, and verification of its accuracy, shall be supplied by the contractor for the performance of examination or test by the Government.

5. PREPARATION FOR DELIVERY

5.1 Preservation, packaging and marking.

5.1.1 Preservation, packaging, packing and marking shall be level C in accordance with MIL-STD-1169.

6. NOTES

6.1 Ordering data.-Procurement documents shall specify the following:

a. Title, number and date of this specification.
b. Data cards.-Data cards shall be prepared for each lot in accordance with the information specified in Standard MIL-STD-1167.

6.2 Inspection code number.-The five digit code numbers assigned to the inspections herein are to facilitate future data collection and analysis by the Government.

6.3 Inspection equipment.-The contractor shall design inspection equipment as required by the Inspection Equipment Lists (EL) in accordance with the instructions of paragraphs 6.3.1 through 6.3.5.

6.3.1 Inspection equipment lists (EL).-Inspection equipment lists indicate the availability of inspection equipment designs by showing in the "number" column of the list of inspection equipment (Form SMUPA 1010) the numbers of drawings or Federal Stock numbers of existing equipment designs, or codes as indicated in paragraph 6.3.2. Design action required of the contractor is described in paragraphs 6.3.3 and 6.3.4. The contractor will be required to prepare detailed drawings in accordance with 6.3.4 for all the equipment coded as "Contractor Design" in the number column. These contractor designs must be approved by the Government prior to fabrication or procuring of the equipment. Designs shall be submitted for approval as specified in 6.3.5.

6.3.2 Inspection equipment lists codes.-The inspection equipment as defined in 6.3.3 and 6.3.4 will be designated in

Source: https://assist.dla.mil -- Downloaded: 202640-22T20:26Z
Check the source to verify that this is the current version before use.

the EL by the following codes:

CD-Contractor design on controlled contractor format and/or commercial equipment.
MU-Army design, mandatory for use.

6.3.3 Army designs.-Army designs are reflected on detailed drawings which completely depict all the information necessary for the fabrication of the item of inspection equipment. The contractor need provide no design when an Army design is listed for an item of inspection equipment. Army designs fall into two basic classifications; mandatory (designated "MU") and non-mandatory (indicated by drawing or Federal Stock Number). When an inspection equipment list references mandatory Army designs, the contractor shall comply with, and use these designs accordingly. The contractor may, however, in connection with non-mandatory designs, and with the approval of the Government, design alternate inspection equipment or use comparable commercial equipment to facilitate his operations. Such contractor prepared designs or commercial equipment selections must be approved by the Government prior to fabrication or procuring of the equipment. Designs shall be submitted for approval as specified in 6.3.5.

6.3.4 Contractor designs.-Contractor designs are designs of inspection equipment for which the Government has assigned design responsibility to the contractor. Contractor designs shall be supported by detailed drawings which depict all information necessary to completely fabricate, calibrate and operate an item of inspection equipment. This requires that the necessary views, dimensions, materials, finish, notes, operating and calibration instruction be properly depicted in accordance with approved practices to the extent that further calculation or clarification will not be required. Unless otherwise specifed, contractor designs may be developed on the format the contractor normally employs in his equipment design procedure provided such format reflected the detail and information specified above, subject to the followings controls: All submitted contractor designs shall conform to MIL-D-1000, Category E, Form 2. Legibility and reproducibility shall permit conventional making of clearly understandable, high contrast reproductions. Contractors shall submit three copies of final designs as a flat set. Designs shall be submitted for approval as specified in 6.3.5.

6.3.5 Submission of contractor designs.-All submitted designs shall contain a reference to the applicable five digit Code Number contained in Section 4 of this specification and the appropriate component or assembly drawing number and revision letter to which the specific design applies. Unless otherwise specified on the EL, all designs of equipment for inspection

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:26Z
Check the source to verify that this is the currentversion before use.

of defects classified as critical and major shall be submitted for approval to the Commanding Officer, Picatinny Arsenal, ATTN: SMUPA-ND. All other designs of inspection equipment shall be approved by the inspection element of the agency administering the contract, submission shall be as directed by the contracting officer. Partial submission of inspection equipment designs is permissible and encouraged. However, the Arsenal completion date for design review will be based on the date of the final submission of designs. Picatinny Arsenal design review will be accomplished normally within one month after receipt.

6.3.6 Supersession data.-This specification includes the requirement of MIL-C-46684(MU) dated 11 October 1968 for parts for Charge, Supplementary, for deep cavity loaded projectiles.

Custodian:
Army-MU

Preparing activity:
Army-MU

Project Number: 1315-A-684

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:26Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity.

SPECIFICATION

ORGANIZATION	CITY AND STATE

CONTRACT NO.	QUANTITY OF ITEMS PROCURED	DOLLAR AMOUNT
		$

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)*	DATE

DD FORM 1 OCT 64 1426

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:26Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY
PICATINNY ARSENAL
DOVER, NEW JERSEY 07801

OFFICIAL BUSINESS

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY

COMMANDING OFFICER
United States Army
Picatinny Arsenal
ATTN: SMUPA-ND
Dover, New Jersey 07801

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:26Z
Check the source to verify that this is the current version before use.