MILITARY SPECIFICATION

# CUSHION AND SUPPORT COMPONENTS FOR METAL CONTAINER FOR VOLCANO MINE CANISTER

This Specification is approved for use within the U.S. Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

## 1. SCOPE

1.1 Scope. This specification covers the requirements, quality assurance provisions and packaging for cushion and support components used in VOLCANO Mine Canister Container.

## 2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specification and standards. The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

FEDERAL

| | | |
|---|---|---|
| PPP-C-1752 | - | Cushioning Material, Packaging, Unicellular Polyethylene Foam, Flexible |

Beneficial comments (recommendations additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to Commander U S Army Armament,Munitions and Chemical Command Attn AMSMC-QA Picatinny Arsenal, New Jersey 07806-5000 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter

AMSC N/A
FSC 8140

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-A-48078 - Ammunition, Standard Quality Assurance Provisions, General Specification for

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-1169 - Packaging, Packing, and Marking for Shipment of Inert Ammunition Components

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

DRAWINGS (see 6.4)

US ARMY ARMAMENT RESEARCH,DEVELOPMENT AND ENGINEERING CENTER (ARDEC)

12561551 - Body Cover
12561552 - Plug
12561553 - Pad Foam
12561555 - Spacer
12630919 - Strap and Filler Assembly
12630920 - Support Cover Assembly
12630931 - Strap
12630932 - Pad Foam

(Copies of specifications, standards and other Government documents required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity).

2.2 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, (except for associated detail specifications, specification sheets or MS standards), the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

## 3. REQUIREMENTS

3.1 Materials. Materials and parts shall be in accordance with applicable drawings and specifications.

3.2 Components. The components shall comply with all requirements specified on drawings 12561551, 12561552, 12561553, 12561555, 12630919, 12630920, 12630931, 12630932 and the drawings and specification referenced thereon.

3.3 Water absorption. Water absorption of the polyethylene foam parts, at time of packing, shall not exceed 0.08 pounds per square foot of cut surface when tested in accordance with PPP-C-1752.

3.4 First article inspection. This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

3.5 Workmanship. The components shall be regular, smooth and free from any creases, wrinkles, cracks, rips, tears, dirt and any other defects which might offset the serviceability, durability, safety and appearance of the assembly.

## 4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements. Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this specification.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all the requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.2 Classification of inspections. The following types of inspection shall be conducted on this item:

a. First Article Inspection

b. Quality Conformance Inspection

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article sample designated by the Contracting Officer for evaluation in accordance with provisions of 4.3.2. The first article sample shall consist of ten (10) each of every component.

4.3.2 Inspections to be performed. See MIL-A-48078.

4.3.3 Rejection. See MIL-A-48078.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection

## CLASSIFICATION OF DEFECTS & TESTS

MIL-C-70733(AR)

| PARAGRAPH | TITLE: Components | | SHEET 1 OF 1 | | DRAWING NUMBER: See Below |
|---|---|---|---|---|---|
| | | | | | NEXT HIGHER ASSEMBLY: --- |
| CATEGORY | EXAMINATION OR TEST | NO OF SAMPLE UNITS | AQL OR 100% | REQUIREMENT PARAGRAPH | PARAGRAPH REFERENCE /INSPECTION METHOD |
| | Body Cover (Dwg. 12561551)<br>Examination for Defects | 10 | | 3.2 | 4.4.2.1 |
| | Plug (Dwg. 12561552)<br>Examination for Defects<br>Water Absorption | 10 | | 3.2<br>3.3 | 4.4.2.2<br>4.5.1 |
| | PAD, Foam (Dwg. 12561553)<br>Examination for Defects<br>Water Absorption | 10 | | 3.2<br>3.3 | 4.4.2.3<br>4.5.1 |
| | Spacer (Dwg. 12561555)<br>Examination for Defects<br>Water Absorption | 10 | | 3.2<br>3.3 | 4.4.2.4<br>4.5.1 |
| | Strap and Filler Assembly (Dwg. 12630919)<br>Examination for Defects | 10 | | 3.2 | 4.4.2.5 |
| | Support Cover Assembly (Dwg. 12630920)<br>Examination for Defects | 10 | | 3.2 | 4.4.2.6 |
| | Strap (Dwg. 12630931)<br>Examination for Defects | 10 | | 3.2 | 4.4.2.7 |
| | PAD Foam (Dwg. 12630932)<br>Examination for Defects<br>Water Absorption | 10 | | 3.2<br>3.3 | 4.4.2.8<br>4.5.1 |

NOTES:



AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078. In addition, inspection lots of containers shall contain material from lots with the same interfix number from one manufacturer.

4.4.2 Examination. See MIL-A-48078. Unless otherwise specified in the Classification of Defects and Test Tables, sampling plans and procedures for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

## CLASSIFICATION OF DEFECTS & TESTS

MIL-C-70733(AR)

| PARAGRAPH | TITLE | | SHEET 1 OF 1 | | DRAWING NUMBER |
|---|---|---|---|---|---|
| 4.4.2.1 | Body Cover | | | | 12561551 |
| | | | | | NEXT HIGHER ASSEMBLY |
| | | | | | 12630920 |
| CATEGORY | EXAMINATION OR TEST | NO OF SAMPLE UNITS | AQL OR 100% | REQUIREMENT PARAGRAPH | PARAGRAPH REFERENCE /INSPECTION METHOD |
| Critical | None defined | | | | |
| Major | None defined | | | | |
| Minor | | | | | |
| 201 | Outside diameter incorrect | | 0.65% | 3.2 | Gage |
| 202 | Neck ring fabricated incorrectly | | 0.65% | 3.2 | Visual |
| 203 | Inner diameter incorrect | | 0.65% | 3.2 | Gage |
| 204 | Poor workmanship | | 0.65% | 3.5 | Visual |

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

## CLASSIFICATION OF DEFECTS & TESTS

MIL-C-70733(AR)

| PARAGRAPH | TITLE | | SHEET 1 OF 1 | | DRAWING NUMBER |
|---|---|---|---|---|---|
| 4.4.2.2 | Plug | | | | 12561552 |
| | | | | | NEXT HIGHER ASSEMBLY 12630920 |
| CATEGORY | EXAMINATION OR TEST | NO OF SAMPLE UNITS | AQL OR 100% | REQUIREMENT PARAGRAPH | PARAGRAPH REFERENCE /INSPECTION METHOD |
| Critical | None defined | | | | |
| Major | None defined | | | | |
| Minor | | | | | |
| 201 | Thickness incorrect | | 0.65% | 3.2 | Gage |
| 202 | Inner diameter improper | | 0.65% | 3.2 | Gage |
| 203 | Outer diameter improper | | 0.65% | 3.2 | Gage |
| 204 | Water Absorption | 3-0-1 | | 3.3 | 4.4.3.1 |
| 205 | Poor workmanship | | 0.65% | 3.5 | Visual |

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

## CLASSIFICATION OF DEFECTS & TESTS

MIL-C-70733(AR)

| PARAGRAPH | TITLE | SHEET 1 OF 1 | DRAWING NUMBER |
|---|---|---|---|
| 4.4.2.3 | Foam Pad | | 12561553 |
| | | | NEXT HIGHER ASSEMBLY 9392425 |

| CATEGORY | EXAMINATION OR TEST | NO OF SAMPLE UNITS | AQL OR 100% | REQUIREMENT PARAGRAPH | PARAGRAPH REFERENCE /INSPECTION METHOD |
|---|---|---|---|---|---|
| Critical | None defined | | | | |
| Major | None defined | | | | |
| Minor | | | | | |
| 201 | Thickness incorrect | | 0.65% | 3.2 | Gage |
| 202 | Inner diameter incorrect | | 0.65% | 3.2 | Gage |
| 203 | Outer diameter incorrect | | 0.65% | 3.2 | Gage |
| 204 | Water absorption | 3-0-1 | | 3.3 | 4.4.3.1 |
| 205 | Density of material | 3-0-1 | | 3.2 | 4.5.2 |
| 206 | Poor workmanship | | 0.65% | 3.5 | Visual |

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

## CLASSIFICATION OF DEFECTS & TESTS

MIL-C-70733(AR)

| PARAGRAPH | TITLE | SHEET | OF | DRAWING NUMBER |
|---|---|---|---|---|
| 4.4.2.4 | Spacer | 1 | 1 | 12561555 |
| | | | | NEXT HIGHER ASSEMBLY 9392425 |

| CATEGORY | EXAMINATION OR TEST | NO OF SAMPLE UNITS | AQL OR 100% | REQUIREMENT PARAGRAPH | PARAGRAPH REFERENCE /INSPECTION METHOD |
|---|---|---|---|---|---|
| Critical | None defined | | | | |
| Major | None defined | | | | |
| Minor | | | | | |
| 201 | Inner tubes thickness incorrect | | 0.65% | 3.2 | Gage |
| 202 | Adhesive missing | | 0.65% | 3.2 | Visual |
| 203 | Tubes not secured | | 0.65% | 3.2 | Visual |
| 204 | Poor workmanship | | 0.65% | 3.5 | Visual |

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

## CLASSIFICATION OF DEFECTS & TESTS

MIL-C-70733(AR)

| PARAGRAPH | TITLE | | SHEET 1 OF 1 | | DRAWING NUMBER |
|---|---|---|---|---|---|
| 4.4.2.5 | Strap and Filler Assembly | | | | 12630919 |
| | | | | | NEXT HIGHER ASSEMBLY 9392425 |
| CATEGORY | EXAMINATION OR TEST | NO OF SAMPLE UNITS | AQL OR 100% | REQUIREMENT PARAGRAPH | PARAGRAPH REFERENCE /INSPECTION METHOD |
| Critical | None defined | | | | |
| Major | None defined | | | | |
| Minor | | | | | |
| 201 | Material improper | | | 3.2 | Certification |
| 202 | Stitch not centered | | 0.65% | 3.2 | Visual |
| 203 | Stitch strap to filler improper | | 0.65% | 3.2 | Visual |
| 204 | Poor workmanship | | 0.65% | 3.5 | Visual |

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

## CLASSIFICATION OF DEFECTS & TESTS

MIL-C-70733(AR)

| PARAGRAPH | TITLE | | SHEET 1 OF 1 | | DRAWING NUMBER |
|---|---|---|---|---|---|
| 4.4.2.6 | Support Cover Assembly | | | | 12630920 |
| | | | | | NEXT HIGHER ASSEMBLY 9392425 |
| CATEGORY | EXAMINATION OR TEST | NO OF SAMPLE UNITS | AQL OR 100% | REQUIREMENT PARAGRAPH | PARAGRAPH REFERENCE /INSPECTION METHOD |
| Critical | None defined | | | | |
| Major | None defined | | | | |
| Minor | | | | | |
| 201 | Outside diameter incorrect | | 0.65% | 3.2 | Gage |
| 202 | Length incorrect | | 0.65% | 3.2 | Gage |
| 203 | Inside diameter incorrect | | 0.65% | 3.2 | Gage |
| 204 | Adhesive missing | | 0.65% | 3.2 | Visual |
| 205 | Plug not secure to body | | 0.65% | 3.2 | Visual |
| 206 | Poor workmanship | | 0.65% | 3.5 | Visual |
| NOTES: | | | | | |

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

## CLASSIFICATION OF DEFECTS & TESTS

MIL-C-70733(AR)

| PARAGRAPH | TITLE | | SHEET 1 OF 1 | | DRAWING NUMBER |
|---|---|---|---|---|---|
| 4.4.2.7 | Strap | | | | 12630931 |
| | | | | | NEXT HIGHER ASSEMBLY 12630919 |
| CATEGORY | EXAMINATION OR TEST | NO OF SAMPLE UNITS | AQL OR 100% | REQUIREMENT PARAGRAPH | PARAGRAPH REFERENCE /INSPECTION METHOD |
| Critical | None defined | | | | |
| Major | None defined | | | | |
| Minor | | | | | |
| 201 | Width improper | | 0.65% | 3.2 | Gage |
| 202 | Overall length improper | | 0.65% | 3.2 | Gage |
| 203 | Pinking improper | | 0.65% | 3.2 | See Note 3 of Dwg. |
| 204 | Poor workmanship | | 0.65% | 3.5 | Visual |
| NOTES: | | | | | |

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

## CLASSIFICATION OF DEFECTS & TESTS

MIL-C-70733(AR)

| PARAGRAPH | TITLE | SHEET 1 OF 1 | DRAWING NUMBER |
|---|---|---|---|
| 4.4.2.8 | Pad, Foam | | 12630932 |
| | | | NEXT HIGHER ASSEMBLY 9392425 |

| CATEGORY | EXAMINATION OR TEST | NO OF SAMPLE UNITS | AQL OR 100% | REQUIREMENT PARAGRAPH | PARAGRAPH REFERENCE /INSPECTION METHOD |
|---|---|---|---|---|---|
| Critical | None defined | | | | |
| Major | None defined | | | | |
| Minor | | | | | |
| 201 | Thickness incorrect | | 0.65% | 3.2 | Gage |
| 202 | Inner diameter improper | | 0.65% | 3.2 | Gage |
| 203 | Pinking improper | | 0.65% | 3.2 | See Note 3 of Dwg. |
| 204 | Water absorption | 3-0-1 | | 3.3 | 4.4.3.1 |
| 205 | Density of Material | 3-0-1 | | 3.2 | 4.5.2 |
| 206 | Poor workmanship | | 0.65% | 3.5 | Visual |

NOTES:

AMSMC Form 1570, 1 Feb 85 — Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

4.4.3 Testing.

4.4.3.1 Water absorption. Three samples per material lot shall be selected prior to start of production. If any sample fails to meet the requirements, the lot shall be rejected.

4.4.3.2 Density. Three samples per material lot shall be selected prior to start of production. If any sample fails to meet the requirements, the lot shall be rejected.

4.4.4 Inspection equipment. The inspection equipment required to perform the examinations and tests prescribed herein is described in the "Paragraph Reference/Inspection Method" column in the tables starting with paragraph 4.4.2.1. The contractor shall submit for approval, inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078 and 6.5 herein.

4.5 Methods of inspection.

4.5.1 Water absorption. The water absorption shall be determined in accordance with PPP-C-1752.

4.5.2 Density The density shall be determined in accordance with PPP-C-1752.

5. PACKAGING

5.1 Preservation and packaging. None required.

5.2 Packing.

5.2.1 Level A. The cushion components shall be packed in accordance with Level A of MIL-STD-1169.

5.2.2 Level B. The cushion components shall be packed in accordance with Level B of MIL-STD-1169.

5.2.3 Level C. The cushion components shall be packed in accordance with Level C or MIL-STD-1169.

5.3 Marking.

5.3.1 Level A. The cushion components shall be marked in accordance with Level A of MIL-STD-1169.

5.3.2 Level B. The cushion components shall be marked in accordance with Level B of MIL-STD-1169.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

5.3.3 Level C. The cushion components shall be marked in accordance with Level C of MIL-STD-1169 and the following additional instructions. Commercial shipping tags attached with wire shall be used unless otherwise specified. The following information shall be shown: Item name and model number, part number and revision, contract number, lot number and date, name and address of manufacturer. If components and assemblies are bundled or boxed, the gross weight and quantity shall be included. The above information may be placed on pallets or boxes by labeling or stenciling.

6. NOTES

6.1 Intended use. These cushion components are intended for use as the interior packaging and cushioning for the M87/M88 VOLCANO Mine Canister Containers.

6.2 Ordering data. See MIL-A-48078.

6.3 Definition of packaging and packing levels.

6.3.1 Level A. Full Military protection, for unrestricted (OCONUS) shipment and storage as defined in AR 700-15.

6.3.2 Level B. Limited Military protection for limited storage and (OCONUS) shipment as defined in AR 700-15.

6.3.3 Level C. For interplant (CONUS) shipment and very limited storage as defined in AR 700-15.

6.4 Drawings. Drawings listed in Section 2 of this specification under the heading US Army Armament Research, Development and Engineering Center (ARDEC) may also include drawings prepared by, and identified as US Army Armament Research and Development Command (ARRADCOM), Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal or Picatinny Arsenal drawings. Technical data originally prepared by these activities is now under the cognizance of ARDEC.

6.5 Submission of inspection equipment for design approvals - See MIL-A-48078. Submit designs as required to: Commander, US Army Armament Research, Development and Engineering Center, ATTN: AMSMC-QAT-I(D), Picatinny Arsenal, New Jersey 07806-5000. This address will be specified on the Contract Data Requirements List, DD Form 1423. Unless otherwise specified, data item DI-R-1714 will apply.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

6.6 Approval of equivalent test methods. Prior approval of the Contracting Officer is required for use of equivalent test methods. A description of the proposed method should be submitted through the Contracting Officer to: Commander, US Army Armament Research, Development and Engineering Center, ATTN: AMSMC-QAT-I(D), Picatinny Arsenal, New Jersey 07806-5000. This description should include but not be limited to the accuracy and precision and drawings of any special equipment required.

6.7 Subject term (key word) listing.

Canister
Mine Metal Container
Cushion Componets
Mine
Foam
Support

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 8140-A749)



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

**INSTRUCTIONS** In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

*NOTE* This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

*(Fold along this line)*

*(Fold along this line)*

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

**OFFICIAL BUSINESS**
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO 12062 WASHINGTON D C

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

COMMANDER
ARDEC
ATTN. AMSMC-QA
PICATINNY ARSENAL, NJ 07806-5000

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

# STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

*(See Instructions – Reverse Side)*

| 1. DOCUMENT NUMBER | 2. DOCUMENT TITLE |
|---|---|
| MIL-C-70733 | CUSHION AND SUPPORT COMPONENTS FOR METAL CONTAINER FOR VOLCANO MINE CANISTER |

| 3a. NAME OF SUBMITTING ORGANIZATION | 4. TYPE OF ORGANIZATION *(Mark one)* |
|---|---|
| | ☐ VENDOR<br>☐ USER<br>☐ MANUFACTURER<br>☐ OTHER *(Specify)* _____ |
| b. ADDRESS *(Street, City, State, ZIP Code)* | |

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording

c. Reason/Rationale for Recommendation

6. REMARKS

| 7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional | b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional |
|---|---|
| c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional | 8. DATE OF SUBMISSION *(YYMMDD)* |

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.