MIL-G-48165 (MU)
31 July 1973
SUPERSEDING
(See 6.6)

MILITARY SPECIFICATION

GRENADE, G.P.: M43A1 AND BOMB, BLU-18

CONTAINER ASSEMBLY FOR

1. SCOPE

1.1 This specification covers the container assembly for Grenade, G.P.: M43A1 and Bomb, BLU-18.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-2550	- Ammunition, General Specification For

STANDARDS

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes (ABC-STD-105)
MIL-STD-109	- Quality Assurance Terms and Definitions

FSC: 1330

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:15Z
Check the source to verify that this is the current version before use.

MIL-STD-286	-	Propellants, Solid: Sampling, Examination and Testing
MIL-STD-1168	-	Lot Numbering of Ammunition
MIL-STD-1235	-	Single and Multilevel Continuous Sampling Procedures and Tables for Inspection by Attributes

DRAWINGS

U. S. Army Munitions Command

B-8788853	-	Thickness, Portable
A-8870054	-	Data Plate
A-8870055	-	Data Plate
A-8870056	-	Data Plate
A-8870057	-	Holder
C-8875901	-	Container Assembly
C-8881922	-	Container Assembly
F-9206733	-	Box Set-Up Packing Ammunition Inner & Outer for Container Assembly
C-9206734	-	Box, Fiber for Container Assembly

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the Contracting Officer).

2.2 Other publications.-The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on the date of invitation for bids or request for proposal shall apply.

Source: https://assist.dla.mil -- Downloaded: 202640-22T19:15Z
Check the source to verify that this is the current version before use.

CODE OF FEDERAL REGULATIONS

Title 49 - Transportation, Parts 0-190

(The Code of Federal Regulations is available from the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20402. Orders should specify, "49 CFR 0-190 (latest revision)").

3. REQUIREMENTS

3.1 Material.-Materials shall be in accordance with the applicable drawings and specifications.

3.2 Container Assembly.-The container assembly shall comply with all requirements specified on Drawing (Dwg.) C-8875901 or C-8881922 as applicable, all associated drawings, and with all requirements specified in applicable specifications.

3.3 Workmanship.-All parts and assemblies shall be fabricated, loaded and assembled in a thorough, workmanlike manner. They shall be free of burrs, sharp edges, cracks, dirt, grease, rust, and other foreign matter. The cleaning method used shall not be injurious to any part, nor shall the parts be contaminated by the cleaning agents. Exterior surface coatings shall be continuous; however, a few light scratches not exposing base material may be permitted. All required marking and stamping shall be neat and sharply defined.

3.4 Submission of results of contractor-conducted examinations and tests.-The contractor shall forward copies of the results of any of his examinations or tests to the designated address as required by the contract. (See 6.5)

3.5 First article testing.-This specification makes provisions for first article testing. Submission of first article quantity by the contractor shall be as specified in the contract.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.-Unless otherwise specified in the contractor or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:15Z
Check the source to verify that this is the current version before use.

or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements. Reference shall be made to MIL-STD-109 to define terms used herein. The provisions of MIL-A-2550 shall apply.

4.1.1 Submission of product.-At the time the completed lot of items deliverable under the contract is submitted to the Government for acceptance, the contractor shall supply the following information accompanied by a certificate which attests that the information provided is correct and applicable to the product being submitted:

a. A statement that the lot complies with all the quality assurance provisions specified in this specification.
b. Drawing and specification number and date, together with identification and date of changes thereto.
c. A statement that all material purchased by the contractor meets requirements when such material is purchased by the contractor or commercial specifications referenced in any of the contractual documents, and that certificates of conformance are on file and available for review.
d. Number of items in the lot.
e. Date submitted.
f. Number of units of product inspected.
g. Results obtained, by code number, for all inspections performed.

The certificates shall be signed by a responsible agent of the certifying organization. The initial certificate submitted shall be substantiated by evidence of the agent's authority to bind his principal. Substantiation of the agent's authority will not be required with subsequent certificates unless, during the course of the contract, this authority is vested in another agent of the certifying organization.

4.2 First article inspection.

4.2.1 Submission.-The contractor shall submit a first article quantity as designated by the Contracting Officer for evaluation in accordance with the provisions of 4.2.2. (See 6.1.) The first article sample shall consist of the following:

a. Twenty-five (25) of each part.
b. Twenty-five (25) container assemblies.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:15Z
Check the source to verify that this is the current version before use.

All parts and completed assemblies submitted shall have been produced by the Contractor (or furnished by a supplier) using the same production processes, procedures and equipment as will be used in fulfilling the contract. All parts and materials, including packaging and packing, shall be obtained from the same sources of supply as will be used in regular production. The sample shall be accompanied by certificates of conformance. A first article quantity, or portion thereof, as directed by the Contracting Officer, shall also be submitted whenever there is a lapse in production for a period in excess of 90 days, or whenever a change occurs in manufacturing process (including heat treatment procedures and equipment, material used, drawing specification or source of supply as to significantly affect product uniformity as determined by the Government. Prior to submission, the contractor shall inspect the sample to the degree necessary to assure that it conforms to the requirements of the contract and submit a record of this inspection with the sample. A sample containing known defects will not be submitted unless specifically authorized by the Contracting Officer.

4.2.2 Inspection to be performed.-All parts and assemblies shall be subjected by the Government to any or all the examinations or tests specified in this specification and any or all requirements of the applicable drawing.

4.2.3 Rejection.-If any part or assembly fails to comply with any of the applicable requirements, the first article quantity shall be rejected. The Government reserves the right to terminate its inspection upon any failure of any part or assembly. In the event of rejection, the Government reserves the right to require the contractor to take corrective action and submit a new first article quantity or portion thereof. Until a first article quantity is accepted, the contractor is in no way authorized by the Government to resume regular production unless otherwise directed by the Contracting Officer.

4.3 Inspection provisions.-

4.3.1 Lot formation.-The term "inspection lot" as used in this specification is defined as an essentially homogeneous collection of units of product from which a representative sample is drawn and inspected to determine conformance with applicable requirements. The sample selected shall represent only that quantity of units from which the sample was drawn and shall not be construed to represent any prior or subsequent quantities presented for inspection. Homogeneity shall be considered to exist provided the inspection lot has been produced by one manufacturer, in one unchanged process in accordance with the same drawing, same drawing revision, same specification and

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:15Z
Check the source to verify that this is the current version before use.

same specification revision, and complies with the provisions for submission of product as specified in MIL-STD-105. Change to process, specification, or drawing not affecting safety, performance, interchangeability, or storage, as determined by the Government, shall not be deemed to alter the homogeneity of an inspection lot. All material submitted for inspection in accordance with this specification shall comply with the homogeneity criteria specified herein regardless of the type of sampling procedure which is being applied to determine conformance with requirements. Lot numbering, as required, shall be in accordance with MIL-STD-1168. Each inspection lot shall contain:

a. Parts of one lot interfix number from one manufacturer.
b. Propellant from one batch or blending of batches which results in homogeneity of all propellant used in loading the entire container assembly lot.

4.3.2 Examination.-The examintions listed in the following subparagraphs shall be performed on inspection lots (see 4.3.1) of the components or assemblies designated in the applicable paragraph headings. Inspection for critical defects (and major defects, when so specified) shall be 100 percent. Sampling plan for major and minor defects shall be in accordance with MIL-STD-105 except that continuous sampling plans in accordance with MIL-STD-1235 may be used if approved by the Government. Individual defects shall have an AQL of 0.40 percent for each major defect and an AQL of 0.65 percent for each minor defect. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.3.4.

4.3.2.1 Cover (See Dwg. C-8875903 or C-8881925, as applicable, covering a detail of Dwg. C-8875901 and C-8881922, resp.)

Categories	Defects	Method of Inspection	Code (See 6.2)
Critical:	None defined		
Major			
101.	Thickness at bottom	A8870057 A8870055	01001
102.	Outside diameter		01002
103.	Thickness of sidewall, minimum (min.)	A8870056 B8788853	01003
104.	Crack, perforation or distortion	Visual	01004
Major:	(See 4.3.3.1)		

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:15Z
Check the source to verify that this is the current version before use.

	105. Diameter of hole	Gage	01005
	106. Concentricity of diameter of hole with outside diameter	Gage	01006
Minor:			
	201. Evidence of poor workmanship (See 3.3)	Visual	01007

4.3.2.2 Container (See Dwg. C-8875902 or B-8881923, as applicable, covering a detail of Dwg. C-8875901 and C-8881922 resp.)

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major			
	101. Crack, perforation or distortion	Visual	02001
Major:	(See 4.3.3.1)		
	102. Inside diameter	Gage	02002
	103. Height	Gage	02003
	104. Thickness at bottom	Gage	02004
	105. Thickness of sidewall, min.	Gage	02005
Minor			
	201. Radius missing	Visual	02006
	202. Evidence of poor workmanship (See 3.3)	Visual	02007

4.3.2.3 Container Assembly, prior to assembly of disc and cover (See Dwg. C-8875901 or C-8881922, as applicable).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major			
	101. Weight of propellant	Balance	03001
Minor			
	201. Foreign matter (See 3.3)	Visual	03002

]

Source: https://assist.dla.mil -- Downloaded: 20261O-22T19:15Z
Check the source to verify that this is the current version before use.

4.3.2.4 Container Assembly, prior to assembly of cover (See Dwg. C-8875901 or C-8881922, as applicable).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major:	None defined		
Minor			
201.	Disc missing or damaged	Visual	04001
202.	Evidence of poor workmanship (See 3.3)	Visual	04002

4.3.2.5 Container Assembly (See Dwg. C-8875901 or C-8881922, as applicable).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major			
101.	Height	A8870054	05001
102.	Outside diameter, max.	Gage	05002
103.	Crimp less than 360°	Visual	05003
Minor:			
201.	Evidence of poor workmanship (See 3.3)	Visual	05004
202.	Cover, disc or container damaged, (dented, punctured etc.)	Visual	05005

4.3.2.6 Inner Set-up Box (prior to sealing (See Dwg. F-9206733).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major			
101.	Incorrect number of container assemblies	Visual	06001
102.	Packing cushion missing	Visual	06002
Minor:	None defined		

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:15Z
Check the source to verify that this is the current version before use.

4.3.2.7 Inner Set-Up Box (Sealed) (See Dwg. F-9206733).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major			
101.	Box damaged to the extent that contents are exposed	Visual	07001
Minor			
201.	Contents loose	Manual	07002
202.	Marking misleading or unidentifiable	Visual	07003

4.3.2.8 Outer Set-up box (prior to sealing) (See Dwg. F-9206733).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major			
101.	Incorrect number of inner set-up boxes	Visual	08001
Minor:			
201.	Filler material insufficient or missing	Visual	08002

4.3.2.9 Barrier Bag (prior to sealing) (See Dwg. F-9206733).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major			
101.	Corners not blunted	Visual	09001
102.	Sealing strap incomplete, badly wrinkled or missing	Visual	09002
Minor			
201.	Marking misleading or unidentifiable	Visual	09003

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:15Z
Check the source to verify that this is the current version before use.

4.3.2.10 Box, Fiber(prior to sealing) (See Dwg. C-9206734).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major			
101.	Heat seals missing, unsealed or improperly positioned on barrier bags	Visual	10001
Minor			
201.	Marking misleading or unidentifiable	Visual	10002

4.3.2.11 Box, Fiber (sealed) (See Dwg. C-9206734).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major			
101.	Box damaged exposing contents	Visual	11001
102.	Sealing strip incomplete, badly wrinkled or missing	Visual	11002
Minor			
201.	Contents loose	Manual	11003
202.	Marking misleading or unidentifiable	Visual	11004

4.3.3 Testing.

4.3.3.3 Dimensional control of stamped parts.-In place of the normal sampling associated with the Classification of Defects, and with the approval of the Contracting Officer, a sample of at least ten (10) parts may be dimensionally inspected to qualify the tool used in the stamping process for use in production. In addition, a random sample of five (5) parts shall be selected from the last portion of each hour's production for dimensional inspection as a control of the tool during production.

If any defective parts are found during qualification of the tool, the tool producing the defective part shall not be used in production.

If any defective parts are found when inspection is performed for control of the tool, the tool producing the

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:15Z
Check the source to verify that this is the current version before use.

defective part shall be removed from production. Further, that portion of production since the last tool control check shall be returned to the contractor for corrective action.

All tools removed from production because of some fault, may, after reworking, be returned to production providing they pass the qualification test above. The Contractor may request a change of inspection frequency providing he presents objective evidence to the Contracting Officer to substantiate the request.

4.3.3.2 Moisture and total volatiles content of propellant (See Dwg. C-8875901 or C-8881922), Major Defect (Code No. 12001).-The contractor shall provide adequate controls to insure compliance with the applicable requirements. The moisture and total volatiles content of the propellant shall be determined at the loading station at the time of loading This determination shall be made at least once each eight (8) hours of production. Sampling of the propellant shall be in accordance with MIL-STD-286, Method 101.2.2. In addition, if the moisture and total volatiles content fails to comply with the requirement specified on the applicable drawing, and loading has not begun, the propellant lot shall be rejected until corrective action has been taken as verified by repeating the moisture and total volatiles content determination. If loading has begun, container assemblies loaded with the non-conforming propellant shall be rejected. This determination shall be performed as specified in 4.4.1.

4.3.4 Inspection equipment.-The inspection equipment required to perform the examinations and tests prescribed in this section is identified under the "Method of Inspection" headings in 4.3.2 and in 4.3.3 (See 6.3).

4.4 Test methods and procedures

4.4.1 Moisture and total volatiles content of propellant. The moisture and total volatiles content of the propellant shall be determined at the time and place of loading and in accordance with MIL-STD-286, Method 101.2.2.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging.

5.1.1 Level C.-The container assembly shall be preserved and packaged in accordance with Dwg. F-9206733.

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:15Z
Check the source to verify that this is the current version before use.

5.2 Packing.

5.2.1 Level C.-The container assemblies, preserved and packaged as specified in 5.1.1, shall be packed for shipment in accordance with Dwg. C-9206734.

5.3 Marking.-Marking shall be in accordance with Dwgs. F-9206733 and C-9206734 and Code of Federal Regulations, Title 49, Parts 171-179.

5.4 Shipping.-When assemblies from more than one lot are shipped as a carload, each lot shall be kept separate, and the division between lots clearly indicated to prevent mixing of the lots in transit.

6. NOTES

6.1 Ordering data.-Procurement documents shall specify the following:

a. Title, number and date of this specification.

b. Data cards shall be prepared for each lot in accordance with the information specified in Standard MIL-STD-1167.

c. Provisions for submission of first article samples.

6.2 Inspection code numbers.-The five digit code numbers assigned to the inspections herein are to facilitate future data collection and analysis by the Government.

6.3 Inspection Equipment Designs.-Inspection equipment designs are of two types: Government Special Inspection Equipment (SIE) designs and contractor designs. SIE designs are designated by drawing numbers under the "Method of Inspection" headings in Section 4. Design responsibility for all other inspection equipment is assigned to the contractor. The contractor need not furnish any design when a complete Government SIE design is provided. Unless otherwise specified, however, the contractor may submit alternate or modified contractor designs of SIE in accordance with 6.3.2 and 6.3.3 should he elect to do so.

6.3.1 SIE designs.-SIE designs may consist of any of the following:

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:15Z
Check the source to verify that this is the current version before use.

a. Detailed drawings which completely depict all information necessary for the fabrication and use of the item of inspection equipment.

b. A source control drawing or a specification control drawing as defined in MIL-STD-100.

c. An envelope drawing, as defined in MIL-STD-100, which establishes the criteria which a detail design shall meet. When envelope drawings are specified, the contractor shall prepare designs which comply with the criteria therein.

6.3.2 Contractor designs.-Contractor designs are required for all inspection equipment for which SIE designs are not specified and may include commercial equipment which the contractor proposes to use. (Commercial equipment is defined as unmodified equipment which is catalogued and available for purchase by the general public). Contractor designs shall include appropriate operating instructions, calibration procedures and maintenance procedures. Commercial equipment shall be fully described by catalog listings or other means which provide sufficient information to permit identification and evaluation by the Government and may include illustrations and engineering data. Designs shall be prepared for any special fixture(s) required to be used with commercial equipment, or with SIE designs if not otherwise covered thereby (see 6.3.1c). Designs shall be of the categroy and form (per MIL-D-1000) specified in the Contract Data Requirement Lists (DD Form 1423).

The contractor is referred to MIL-HDBK-204, "Inspection Equipment Design" for guidance. The specification number and the applicable five-digit defect code number (or other specific identifying information) from Section 4 of this specification shall be referenced on each contractor design.

6.3.3 Submission of designs for approval.-Contractor designs shall be approved by the Government prior to fabrication or procuring the equipment. Designs shall be submitted for approval in accordance with the stipulations, time frame and distribution specified in the Contract Data Requirements List (DD Form 1423). Partial submission of inspection equipment designs is permissible and encouraged. However, the completion date for design review will be based on the date of the final submission of designs. Picatinny Arsenal design review will normally be accomplished within one month after receipt.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:15Z
Check the source to verify that this is the current version before use.

6.4 Submission of test data.-In addition to the normal distribution of records, when the container assembly is procured by the U.S. Army Munitions Command, one (1) copy of all ballistic data and ammunition data cards shall be forwarded to: Commanding Officer, Picatinny Arsenal, Attn: SARPA-QA-A-S.

6.5 Submission of results of contractor-conducted examinations and tests.-Unless otherwise specified by the Contracting Officer, the contractor shall forward requested records of examinations or tests to Commanding Officer, Picatinny Arsenal, Attn: SARPA-QA-A-S.

6.6 Supersession data.-This specification includes the requirements of, and supersedes, Purchase Specification AEI-287A dated 28 June 1968.

Custodian:
Army-MU

Preparing Activity:
Army-MU

Project Number: 1330-A003

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:15Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1 JAN 66 1426

REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:15Z
Check the source to verify that this is the current version before use.