MILITARY SPECIFICATION

MILLING MACHINES, WOODWORKING, PATTERNMAKERS

This specification is mandatory for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers electric motor-driven, patternmakers, woodworking, milling machines of the floor-mounting types.

1.2 Classification. The milling machines covered by this specification shall be of the following types and sizes as specified (see 6.2.1):

Type I - Knee Type

Size 1 - Throat depth, spindle C/L to column, 30 inches.

Type II - Bed Type

Size 1 - Throat depth, spindle C/L to column, 30 inches.

Size 2 - Throat depth, spindle C/L to column, 48 inches.

2. APPLICABLE DOCUMENTS

2.1 Government documents. The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein.

SPECIFICATIONS

Military

MIL-M-18058	Machinery, Metal and Woodworking Support Equipment and Associated Repair Parts, Preparation for Delivery

FSC 3220

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:45Z
Check the source to verify that this is the current version before use.

STANDARDS

Military

MIL-STD-130	Identification Marking of U. S. Military Property
MIL-STD-461	Electromagnetic Interference Characteristics Requirements for Equipment

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other documents. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on the date of invitation for bids or request for proposal shall apply.

NATIONAL BUREAU OF STANDARDS

Handbook H28	Screw Thread Standards for Federal Services

(Application for copies should be addressed to the Superintendent of Documents, Government Printing Office, Washington, D. C. 20402.)

AMERICAN GEAR MANUFACTURERS ASSOCIATION (AGMA)

360.01	Manual for Machine Tool Gearing

(Application for copies should be addressed to American Gear Manufacturers Association, One Thomas Circle, Washington, D. C. 20005.)

AMERICAN NATIONAL STANDARDS INSTITUTE (ANSI)

B5.1	T-Slots, Bolts, Nuts and Cutters
B5.9	Spindle Noses
B5.10	Machine Tapers

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:45Z
Check the source to verify that this is the current version before use.

(Application for copies should be addressed to American National Standards Institute, Inc., 1430 Broadway, New York, New York 10018.)

NATIONAL ELECTRICAL MANUFACTURERS ASSOCIATION (NEMA) STANDARDS

MG-1	Motors and Generators
IC-1	Industrial Controls

(Application for copies should be addressed to the National Electrical Manufacturers Association, 155 East 44th Street, New York, New York 10017.)

3. REQUIREMENTS

3.1 First article. When specified (see 6.2.1 and 6.3), the supplier shall furnish one complete milling machine of each type and size specified in the contract or order for first article inspection and approval in accordance with Section 4 herein.

3.2 Design. The milling machine shall be designed with a base, column, overarm, spindle, table, and an electric motor drive.

3.2.1 Type I. The Type I milling machine shall provide mechanical assist manual control to actuate the horizontal movements of the ram and vertical movements of the knee. Transverse and longitudinal table movements shall be provided by powered feed.

3.2.2 Type II. The Type II milling machine shall provide mechanical assist manual control and powered controls shall be provided to actuate overarm and carriage movements. The base or bed of Type II milling machines shall be designed to accept extensions to increase the capacity of longitudinal table movement. Type II milling machines shall provide pendant mounted controls for direction of electric motor rotation, continuous or intermittent operation, including a stop control for the electric motor.

3.2.3 Safety devices. The milling machines shall be furnished with safety devices or covers for all parts that present safety hazards with the exception of the spindle or working surface of the cutters. All guards shall swing clear or be removable to provide access to the guarded parts. When special safety devices are required, they shall be as specified (see 6.2.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:45Z
Check the source to verify that this is the current version before use.

3.2.4 Lubrication. All bearings (except sealed, permanently-lubricated type), mating gears, rotating and sliding parts shall be provided with means for lubrication. All oil holes, grease fittings, and filler caps shall be easily accessible.

3.2.5 Interchangeability. All parts shall be manufactured to such standards as will permit replacement or adjustment without modification of parts or the milling machine.

3.2.6 Material. All material used in the manufacture of the milling machine shall be new and of the quality necessary to produce a machine to meet the requirements described herein.

3.3 Construction. The milling machine shall be constructed so that when installed and connected to the specified power source they can be used for any purpose for which they were designed. The milling machines shall be constructed of parts which are sound in structure and free from repair.

3.3.1 Castings and forgings. All castings and forgings shall be free from defects and mismatching. In no event shall processes such as welding, peening, plugging, or filling with solders or metallic pastes be used on castings or forgings to reclaim defective parts for use on the machines. Such processes may be used only for enhancing surface finish and appearance.

3.3.2 Welding, brazing, or soldering. Welding, brazing, or soldering shall be employed only where required in the original design. These methods shall not be employed as repair measures for defective parts.

3.3.3 Fastening devices. All screws, pins, bolts, and similar fasteners shall be installed with means for preventing loss of tightness. Parts subject to removal or adjustment shall not be swaged, peened, staked, or otherwise permanently deformed.

3.3.4 Surfaces. All surfaces of castings, forgings, molded parts, stampings, and welded parts shall be clean and free from harmful or extraneous materials such as sand, dirt, fins, sprues, scale, and flux. External surfaces shall be smooth and all edges shall be either rounded or beveled unless sharpness is required to perform a necessary function. The condition and finish of all surfaces shall be in accordance with the manufacturer's standard commercial practice.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:45Z
Check the source to verify that this is the current version before use.

3.3.5 Painting. Unless otherwise specified (see 6.2.1), the milling machine shall be painted in accordance with the manufacturer's standard commercial practice.

3.3.6 Threads. All threaded parts shall be in the inch system and shall conform to Handbook H28.

3.3.7 Gears. All gears used shall conform to the applicable requirements of AGMA 360.01.

3.3.8 Dials and scale. Graduations to indicate tool movements shall be identified progressively in increments of not more than 1/8 of an inch and one degree. Dials and scales shall be permanently and legibly engraved or etched.

3.3.9 Plates. Instruction plates shall be in the English language using plain bold faced letters.

3.4 Performance. The milling machine shall be capable of performing patternmaking operations on wood workpieces and shall also provide performance capabilities for plastics and non-ferrous metal workpieces. Straight, concave, convex, and circular milling operations, including limited boring capabilities, shall be provided by the milling machine covered by this specification to perform patternmaking operations.

3.5 Components.

3.5.1 Base and column. The base and column shall be constructed of cast iron or fabricated of steel. The design and construction of the base and column shall be such as to minimize the effects of vibration and deflection during maximum operating capacity. The base shall provide not less than four holes for securing to the floor.

3.5.1.1 Type I. The base and column of Type I milling machines shall be constructed with ways on the front and top of the column. Column ways shall provide alignment and transverse movements of the knee in vertical motions and the ram movements on a horizontal plane. Mechanical assist manual control shall be incorporated for actuating movements of both the knee and the ram.

3.5.1.2 Type II. The base and column of Type II milling machines shall be constructed with ways on top of the base and on the front of the column. Ways on the base and column shall provide alignment and

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:45Z
Check the source to verify that this is the current version before use.

transverse vertical motions for the overarm and provide transverse table movements on a horizontal plane. Both mechanical assist manual and powered controls shall be incorporated for actuating movements of the table and overarm.

3.5.2 Table. The table shall be constructed of iron or steel to secure and support workpieces in milling operations. Table slots shall conform to ANSI B5.1.

3.5.2.1 Type I. The Type I milling machine table shall be mounted on the ways of the knee and constructed to provide mechanical assist manually controlled compound movements. The table shall provide tilting capability of not less than 30 degrees in both directions of the horizontal plane on the longitudinal axis. Means shall be provided to secure the table in angular positions, over the entire tilting range graduated in increments not greater than one degree.

3.5.2.2 Type II. The Type II milling machine work support table shall be saddle mounted to provide compound movements upon a carriage providing 360 degrees of swivel on ball or roller bearings. Linear motions of the carriage, swivel and saddle assembly shall be provided by longitudinal ways on top of the base or main table. The ways shall be provided with adjustable gibs. Means shall be incorporated to facilitate attachment of main table extensions providing extended capacity of longitudinal work support table movement. The main table and extensions shall be provided with a linear scale graduated in increments not greater than one eighth of an inch to indicate longitudinal movement of the saddle, carriage and work support table. Table extensions shall be supported by legs or pedestal. Table extension ways shall be covered with either a spring loaded roller and cover or a telescoping metal slide to protect exposed ways. Special length main table extensions shall be furnished as specified (see 6.2.1). Means shall be provided to prevent over travel along the ways. The compound and rotary motions of the work support table shall be provided by mechanical assistance by either handwheels or cranks. Means shall be provided to secure linear and rotary motions of the work support table over their entire working range. The workpiece support table shall be grooved on each of the four edges and drilled and tapped to facilitate installation of work clamps. The top of the workpiece support table shall be graduated in squares, not to exceed one inch, to facilitate workpiece positioning.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:45Z
Check the source to verify that this is the current version before use.

3.5.3 Head and head support. The milling head and either a ram or an overarm shall be constructed of cast iron or steel. The ram or overarm shall be fitted to the column by adjustable gibs.

3.5.3.1 Type I. The horizontal adjustment range of the ram shall be not less than the dimension contained in TableI. The head shall be supported by the ram in such a manner to provide 90 degrees of swivel in either direction off the spindle vertical axis. Angular positioning of the head on the ram shall be manual, with the flange of the housing, graduated in increments of one degree to facilitate angular adjustment for operations. Ram adjustment along the horizontal ways of the column shall be manual with mechanical assistance by either a crank or a handwheel. Means shall be provided to secure the horizontal position of the ram and the angular position of the head over their entire adjustment range.

3.5.3.2 Type II. The vertical adjustment range of the overarm shall be not less than the spindle to table dimensions contained in Table II. The overarm shall be raised and lowered by an electric motor driven screw. The head shall be supported by the overarm in such a manner to provide angular positioning of the head manually by mechanical assistance through a worm and gear drive with a handwheel or crank. Degrees of swivel shall conform to the requirements of Table II and be indicated by a dial around the periphery of the head. Means shall be provided to secure the vertical position of the overarm and the angular position of the head over their entire adjustment range. Means shall be provided to secure the vertical position of the overarm and the angular position of the head over their entire adjustment range.

3.5.4 Spindle. Milling machine spindles shall be constructed of alloy steel and heat treated to a hardness of not less than 45 Rockwell C and conform to ANSI B5.9 and B5.10. The spindle shall be supported on not less than two ball or roller bearings. The spindle shall be manual positioned to the head by handwheel, lever or crank through mechanical assistance. Means shall be provided to lock and hold the spindle over the entire adjustment range. Spindle speeds, diameter, travel and taper or collet size shall be as specified in Tables I and II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:45Z
Check the source to verify that this is the current version before use.

TABLE I

Type I - Sizes and Characteristics
(Dimensions in Inches)

Characteristics	Size 1
Center of Spindle to Column	30
Ram Travel	26
Spindle Travel, Graduated	7
Spindle Speeds	12
Minimum RPM	160
Maximum RPM	5000
Spindle Motor HP	5
Spindle Size (Collet Capacity)	1
Table Size	18 x 48
Table Height from Floor	33 ± 1
Table Travel	
Longitudinal	30
Cross	16
Vertical	23
Table Swivel, Degrees (Both Directions)	30
Head Swivel, Degrees	
Left	90
Right	90

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:45Z
Check the source to verify that this is the current version before use.

TABLE II

Type II - Sizes and Characteristics
(Dimensions in Inches)

Characteristics	Size 1	Size 2
Center of Spindle to Column	30	48
Spindle to Table		
Spindle Vertical	20	34
Spindle Horizontal	22	42
Spindle Speeds	8	6
Minimum RPM	1500	1000
Maximum RPM	4000	4000
Spindle Motor HP (RPM 1800-3600)	2-1/2 - 5	2-1/5 - 5
Spindle Size	#4 Morse Taper	3" Diameter (Cutters Attach)
Table Size	24 x 24	36 x 36
Table Height from Floor	33 ± 1	39 ± 1
Top Surface Graduated Squares	1	1
Table Travel, Longitudinal		
Spindle C/L Right	59	* 28 + Extensions
Spindle C/L Left	11	* 28 + Extensions
Compound Travel, Top	22	18
Compound Travel, Bottom	23	18
Power Feed Motor, HP	3/4 (Variable Speed)	1 (2 Speed)
Head Swivel, Degrees		
Left	45	45
Right	90	90
Motor Drive, Raise & Lower (HP)	3/4	3/4
Radius Cut Capacity		
From Swiveling Table	30	N/A
With Table Plate	35	N/A

* See 3.5.2.2 and 6.2.1

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:45Z
Check the source to verify that this is the current version before use.

3.5.5 Pendant control. A swivel type pendant control shall be provided on Type II milling machines. The push button controls on the pendant shall control circuits of 115 volts or less. Forward and reverse, continuous running and jogging or inching, including stop controls, shall be mounted on the pendant.

3.6 Characteristics of sizes. Unless otherwise specified (see 6.2.1), characteristics of the milling machine shall be not less than those specified in Table I or II for the type and size machine required.

3.7 Electrical equipment.

3.7.1 Motors. Motors shall be 230 or 460 volts, 3 phase, 60 Hz, wired for operation on the voltage specified (see 6.2.1), and shall be rated for continuous duty. Motor characteristics shall conform to NEMA MG-1. Motors shall have sealed, permanently lubricated ball or roller bearings. The spindle drive motor on Type I milling machine shall be single speed. The spindle drive motor on Type II milling machine shall be reversible, two speed, 1800 and 3600 RPM, and shall be totally enclosed. The head of Type II milling machines shall be raised and lowered by a reversible electric motor gear box combination. Power feed to the table shall be by a variable or two speed, 900 and 1800 RPM, reversible, electric motor. Motor HP shall be not less than the HP specified in Table II.

3.7.2 Controls. The milling machines shall be completely wired through the controls and ready for connection to the applicable power source. Unless otherwise specified (see 6.2.1), the controls shall conform to NEMA IC-1 and shall be installed in a NEMA Type I enclosure. Motor controls shall include a magnetic starter with overload and under voltage protection and a manual reset. Start-stop, forward-reverse, left-right, up-down, and jog control buttons on Type II milling machines, shall be installed on a pendant station, (3.5.5) readily accessible to the operator.

3.8 Equipment.

3.8.1 Standard equipment. Unless otherwise specified (see 6.2.1), standard equipment shall consist of a tool cabinet, one set of wrenches, tools, cutters, and cutter holders normally furnished with the milling machine by the contractor.

3.8.2 Optional equipment. Optional equipment shall be as specified (see 6.2.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:45Z
Check the source to verify that this is the current version before use.

3.8.3 Repair parts. Such repair parts as are specified (see 6.2.1), shall be furnished.

3.9 Electromagnetic interference control. When specified (see 6.2.1), the milling machines procured under this specification shall have electromagnetic interference control in accordance with the applicable requirements of MIL-STD-461.

3.10 Nameplate. Unless otherwise specified (see 6.2.1), a corrosion resistant metal nameplate, marked in accordance with MIL-STD-130, shall be securely attached to each machine. The nameplate shall contain the information listed below. If the machine is a special model, the model designation shall include the model of the basic standard machine and a suffix keyed to the manufacturer's permanent records.

Nomenclature

Manufacturer's name

Manufacturer's model designation

Manufacturer's serial number

Power input characteristics and ratings

Date of manufacture

Contract or order number

Federal Stock Number or Plant Equipment Code

U S

3.11 Identification plate. When specified (see 6.2.1), a separate identification plate of corrosion resistant metal permanently and legibly marked in letters 3/16 inches high with the caption "Departmental or Activity Identification" shall be securely attached to each machine. The plate shall have blank space for the Government to stamp 25 letters or numbers of the same size as the caption.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:45Z
Check the source to verify that this is the current version before use.

3.12 Workmanship. Workmanship of the milling machine and accessories shall be commensurate with the requirements specified herein and shall be of a quality prevailing among manufacturers normally producing equipment of the type specified herein.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).

b. Quality conformance inspection (see 4.4).

4.3 First article inspection. First article inspection shall be applied to the first article when required in accordance with 3.1. Failure of the first article to pass the examination or one or more first article tests shall be cause for rejection. Unless otherwise specified (see 6.2.1), first article inspection shall consist of the examination in 4.5 and all tests in 4.6.

4.4 Quality conformance inspection. Quality conformance inspection shall be applied to each item prior to being offered for acceptance under the contract. Unless otherwise specified (see 6.2.1), quality conformance inspection shall consist of the examination in 4.5, the test in 4.6.1, and the inspection in 4.7. Failure of the milling machine to pass the examination, test, or inspection shall be cause for rejection.

4.5 Examination. Each milling machine and associated equipment shall be examined for design, construction, materials, components, electrical equipment, workmanship, and conformance to Table I to determine compliance with the requirements of this specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:45Z
Check the source to verify that this is the current version before use.

4.6 Tests.

4.6.1 Operational test. The milling machine shall be operated at no load for not less than 15 minutes. Proper operation of all controls, motors, adjusting mechanisms, and accessories shall be proved during this operational period.

4.6.2 Cutting test. The cutting test shall be performed using workpieces of both white pine wood and aluminum.

4.6.2.1 Wood workpiece. The top surface and opposing ends shall be milled at not less than one inch depth of cut, using a four inch diameter cutter, at not less than 4000 RPM, with a feed rate of two feet per minute. The tolerance of the milled workpiece shall not exceed 0.010 inch, flat, square, and parallel.

4.6.2.2 Aluminum workpiece. A two inch round nose cutter shall be used to mill a three inch radius, one inch in depth. A finish cut of not less than 0.010 inch depth of cut, with a feed rate of 0.020 inch per minute or more, at a cutter speed of not less than 1480 RPM shall be made using the rotary table to swing the six inch circle. The milled radius shall be round within 0.010 inch and the surface finish shall not exceed 125 microinches arithmetical average.

4.6.3 Electromagnetic interference control test. Unless otherwise specified (see 6.2.1), equipment having electromagnetic interference control shall be tested in accordance with the applicable requirements of MIL-STD-461 to determine compliance with 3.9.

4.7 Inspection of preparation for delivery. Preservation, packaging, packing, and marking for shipment and storage shall be inspected to determine conformance to the requirements of Section 5.

5. PREPARATION FOR DELIVERY

5.1 Preservation, packaging, packing, and marking. Preservation, packaging, packing, and marking shall be in accordance with MIL-M-18058. Level of preservation, packaging, and packing shall be as specified (see 6.2.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:45Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Intended use. The milling machines covered in this specification are intended for use in patternmaking shops.

6.2 Ordering data. Purchasers should exercise any desired options offered herein and procurement documents should specify the following:

6.2.1 Procurement requirements.

a. Title, number, and date of this specification.

b. Type and size of milling machine required (see 1.2).

c. First article, if required (see 3.1).

d. Special safety devices, if required (see 3.2.3).

e. Painting, if different (see 3.3.5).

f. Specify table extensions required (see 3.5.2.2).

g. Sizes and capacities, if different (see 3.6).

h. Specify voltage for initial wiring (see 3.7.1).

i. Electrical controls, if different (see 3.7.2).

j. Standard equipment, if different (see 3.8.1).

k. Optional equipment, if required (see 3.8.2).

l. List of repair parts required (see 3.8.3).

m. Electromagnetic interference suppression, if required (see 3.9).

n. Nameplate data, if different (see 3.10).

o. Identification plate, if required (see 3.11).

p. First article inspection, if different (see 4.3).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:45Z
Check the source to verify that this is the current version before use.

q. Quality conformance inspection, if different (see 4.4).

r. Electromagnetic interference control test, if different (see 4.6.3).

s. Specify level of preservation, packaging, and level of packing required (see 5.1).

6.2.2 Contract data requirements. Technical data such as the manufacturer's standard operators manual, parts list, foundation and anchor bolt plans, lubrication charts, and wiring diagrams will usually be required for delivery in connection with this specification. When technical data is required, it will be delivered as identified on a numbered DD Form 1664 when specified on a DD Form 1423 incorporated into the contract.

6.3 Instructions for first article approval. When first article inspection and approval is required for equipment furnished under this specification, the solicitation should conform to the applicable requirements of Section I, Part 19 of the Armed Services Procurement Regulation.

Custodians:
Army - ME
Navy - SH
Air Force - 84

Review Activities:
Army - ME
Navy - SH
Air Force - 84

User Activities:
Navy - AS, OS, YD, MC

Preparing Activity:
DSA-IP

Project Number:
3220-0070

☆U.S. GOVERNMENT PRINTING OFFICE: 1970-393-094/S8235

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:45Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID
DEFENSE SUPPLY AGENCY

HEADQUARTERS
DEFENSE INDUSTRIAL PLANT EQUIPMENT CENTER
MEMPHIS, TENNESSEE 38102

DEFENSE SUPPLY AGENCY
OFFICIAL BUSINESS

Commander
Defense Industrial Plant Equipment Center
ATTN: DIPEC-TP
Memphis, Tennessee 38102

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:45Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1 JAN 66 1426

REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:45Z
Check the source to verify that this is the current version before use.