MIL-P-48089 (MU)
13 March 1973
SUPERSEDING
(See 6.6)

MILITARY SPECIFICATION

PROPELLANT, M5
(FOR USE IN SPECIAL APPLICATIONS)

1. SCOPE

1.1 This specification covers M5 Flake Propellant for use in propelling charges for special applications.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

O-A-51	-	Acetone, Technical

MILITARY

MIL-G-155	-	Graphite, Dry (For Use in Ammunition)
MIL-P-156	-	Potassium Nitrate
MIL-B-162	-	Barium Nitrate
MIL-N-244	-	Nitrocellulose
MIL-N-246	-	Nitroglycerin
MIL-E-255	-	Ethyl Centralite (Carbamite)
MIL-E-463	-	Alcohol, Ethyl (For Ordnance Use)
MIL-A-2550	-	Ammunition and Special Weapons; General Specification for.

STANDARDS

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes (ABC-STD-105)
MIL-STD-109	-	Quality Assurance Terms and Definitions
MIL-STD-129	-	Marking for Shipment and Storage
MIL-STD-286	-	Propellants Solid: Sampling, Examination and Testing

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:12Z
Check the source to verify that this is the current version before use.

MIL-STD-652	-	Propellants, Solid for Cannons Requirements and Packing
MIL-STD-1168	-	Lot Numbering of Ammunition
MIL-STD-1235	-	Single and Multilevel Continuous Sampling Procedures and Attributes

DRAWINGS

U.S. ARMY MUNITIONS COMMAND

76-4-46	-	Box, Packing with Metal Liner, M24 for Smokeless Powder, Assembly and Details
76-4-53	-	Box, Steel, M2 for Smokeless Powder, Assembly
76-4-56	-	Box, Packing, Metalwood, M17 for Smokeless Powder Assembly
20-4-616	-	Marking Diagram and Sealing of Steel Packing Boxes for Shipment of Propellants
138439	-	Packing Box, MARK VII
7549033	-	Container, Metal, Universal M25 for Propellants and Explosives Assembly and Detail
8858577	-	Marking Diagram and Sealing of Container, Metal, Universal M25 for Shipping of Propellants
8858848	-	Marking Diagram and Sealing of Metal Lined Wooden Packing Boxes for Shipment of Propellants

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the Contracting Officer).

2.2 Other publications.-The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on the date of invitation for bids or request for proposal shall apply.

CODE OF FEDERAL REGULATIONS

. Title 49	-	Transportation, Parts 0-190

(The Code of Federal Regulations is available from the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20402. Orders should specify, "49 CFR 0-190 (latest revision)").

3. REQUIREMENTS

3.1 Material.-The constituent materials shall comply with the requirements of the applicable specifications as follows:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:12Z
Check the source to verify that this is the current version before use.

Constituent Materials	Conforming to Specification
Nitrocellulose	MIL-N-244, Grade C, Type 2
Nitroglycerin	MIL-N-246
Potassium Nitrate	MIL-P-156, Class 2
Barium Nitrate	MIL-B-162, Class 3
Ethyl Centralite	MIL-E-255
Graphite	MIL-G-155, Grades III or IV
Ethyl Alcohol	MIL-E-463, Grade II
Acetone	O-A-51

3.2 Total volatiles.-The total volatiles content shall not exceed 1.25 percent when determined as specified in 4.4.2.

3.3 Total moisture.-The moisture content shall not exceed 0.70 percent when determined as specified in 4.4.3.

3.4 Composition.-The composition of the propellant, exclusive of total volatiles, shall be as shown in Table 1 when determined as specified in the applicable sub-paragraphs of 4.4.1. After drying, the propellant shall be graphite-glazed in addition to the graphite used in making up the basic composition. The maximum graphite content allowed, including glaze, shall be 0.70 percent.

TABLE 1 - COMPOSITION

Ingredient	Percentage
Nitrocellulose	81.95 ± 2.00
Nitroglycerin	15.00 ± 1.00
Potassium Nitrate	0.75 ± 0.25
Barium Nitrate	1.40 ± 0.25
Ethyl Centralite	0.60 ± 0.15
Graphite	0.30 ± 0.10

3.5 120 degree centigrade (°C) heat test.-The propellant shall not cause complete fading of the methyl violet test paper to a salmon-pink color in less than 40 minutes when tested as specified in 4.4.4.

3.6 Grain characteristics.

3.6.1 Grain dimensions.-The dimensions of the grains (Flakes) shall be as follows when determined at 70 ± 5 degrees fahrenheit (°F):

Diameter (advisory)	-0.035 inch
Thickness (advisory)	-0.0027 inch

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:12Z
Check the source to verify that this is the current version before use.

3.6.2 Gravimetric density.-The gravimetric density of the propellant at 70° ± 5°F shall be 0.42 gm/cc, minimum (min), when tested as specified in 4.4.5.

3.7 Ballistics.-The propellant shall be a ballistic match to a standard propellant furnished by the Government and shall comply with one of the following requirements, the use of any one of these requirements to be specified in the contract or purchase order.

a. Caliber .30 U.S. Rifle
b. Caliber .45 Pistol, ACP
c. Closed bomb, 190-200 cc.

(For the purpose of this specification, a standard propellant lot is defined as any lot tested and found acceptable in the item for which manufacture). Testing shall be as specified in 4.4.6.

3.7.1 Rifle Test.-Caliber .30 U.S. Rifle testing shall be as specified in 4.4.6.1.

3.7.1.1 Ballistic Match.-The propellant shall be a ballistic match to a standard propellant, furnished by the Contracting Officer, as determined by ballistic testing in a caliber .30 U.S. Rifle.

3.7.1.2 Velocity and pressure.-The test propellant, for the caliber .30 rifle test, when fired at the same charge as that charge from a standard propellant lot which gives a pressure of 35,000 ± 5,000 pounds per square inch (psi), shall impart an average muzzle velocity not lower than that for the standard propellant lot by more than 10 feet per second (fps) with a resulting pressure within ± 5% of that obtained for the standard propellant.

3.7.2 Caliber .45 pistol, ACP.

3.7.2.1 Ballistic performance level.-The corrected mean velocity, when determined as specified in paragraphs 4.4.6.2 and 4.4.6.2.1, shall be 801 ± 35 feet per second (fps). The corrected mean pressure, when determined as specified in paragraphs 4.4.6.2 and 4.4.6.2.2, shall be 16,400 ± 1,700 psi.

3.7.2.2 Ballistic performance uniformity.-The range of the 20 velocity values, when determined as specified in paragraphs 4.4.6.2 and 4.4.6.2.3, shall not exceed 78 fps. The range of the 20 pressure values, when determined as specified in paragraph 4.4.6.2 and 4.4.6.2.3, shall not exceed 3,800 psi.

3.7.2.3 Ballistic standard propellant.-The standard propellant to be used as specified in paragraph 4.4.6.2, shall satisfy the requirements of this specification and exhibit a corrected mean velocity of 801 ± 8 fps and a corrected mean pressure of 16,400 ±

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:12Z
Check the source to verify that this is the current version before use.

200 psi: The assessed velocity and pressure of the standard shall be the corrected mean as established in comparison firing with the test propellant in paragraph 4.4.6.2.

3.7.3 Closed bomb.-The propellant shall be a closed bomb quickness match to a reference sample of the standard propellant provided by the Government. A quickness match is defined as a minimum average relative quickness of 97% when tested as specified in paragraph 4.4.7 and when Vx (max) specified in MIL-STD-286, Method 801.1.1, falls between 1.75 and 2.00 volts.

3.8 Process.-Details of the manufacturing process and equipment used by the contractor shall be submitted in writing to the contracting activity and shall be approved in writing before the contractor proceeds with the manufacture and packing of the propellant. Any deviation from the approved manufacturing process shall be submitted in writing to the contracting activity and written approval received prior to use (see 6.1).

3.9 Workmanship.-The best commercial practices shall be used in the formulation of the propellant furnished under this specification and all other applicable documents. The propellant and its standard ingredients shall be protected from the action of direct sunlight and acid fumes. No reground propellant or nitrocellulose shall be used in the manufacture of the propellant procured under this specification unless otherwise specified.

3.10 Submission of results of contractor-conducted examinations and tests.-The contractor shall forward copies of the results of any of his examinations or tests to the designated address as required by the contract (see 6.4).

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.-Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements. Reference shall be made to MIL-STD-109 to define terms used herein. The provisions of MIL-A-2550 shall apply.

4.1.1 Submission of product.-At the time the completed lot of product is submitted to the Government for acceptance, the contractor shall supply the following information accompanied

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:12Z
Check the source to verify that this is the current version before use.

by a certificate which attests that the information provided is correct and applicable to the product being submitted:

a. A statement that the lot complies with all of the quality assurance provisions specified within this specification.

b. Number of batches of product inspected (shall be made available upon request by the Contracting Officer).

c. Results obtained, by defect code, for all inspections performed (shall be made available upon request by the contracting officer).

d. Drawing, specification number, and date, together with an identification and date of changes.

e. Certificates of conformance on all material purchased by the contractor when such material is controlled by Government or commercial specifications referenced in any of the contractual documents (shall be made available upon request by the contracting officer).

f. Number of items in the lot.

g. Date submitted.

h. Eight copies of propellant description sheet SMU Form 1060 containing the applicable data (see 6.5).

The certificate shall be signed by a responsible agent of the certifying organization. The initial certificate submitted shall be substantiated by evidence of the agent's authority to bind his principal. Substantiation of the agent's authority will not be required with subsequent certificates unless, during the course of the contract, this authority is vested in another agent of the certifying organization.

4.2 Inspection provisions.

4.2.1 Lot formation.-The term "lot" as used throughtout this specification refers to an inspection lot, which is defined as an essentially homogeneous quantity of propellant from which the sample was drawn and shall not be construed to represent any prior or subsequent quantities presented for inspection. A lot shall consist of one or more batches of M5 propellant produced by one manufacturer, in accordance with the same specification, and same specification revision under the continuous set of operating conditions. Each lot shall consist of that quantity of M5 propellant which has been subjected to the same unit chemical or physical process intended to make the final product homogeneous. The criteria and procedures for the assignment of lot numbers shall be in accordance with Standard MIL-STD-1168.

4.2.2 Examination.-The examinations listed in the following subparagraphs shall be performed on inspection lots (see 4.3.1) of the components or assemblies designated in the applicable paragraph headings. Inspection for critical defects (and major defects, when so specified) shall be 100 percent. Sampling plans for major

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:12Z
Check the source to verify that this is the current version before use.

and minor defects shall be in accordance with MIL-STD-105 except that continuous sampling plans in accordance with MIL-STD-1235 may be used if approved by the Government. Individual defects shall have an AQL of 0.40 percent for each major defect and an AQL of 0.65 percent for each minor defect. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.3.4.

4.2.2.1 Box or container prior to filling (see dwg. 76-4-46, 76-4-53, 76-4-56, 20-4-616, 138439, 7549033, 8858848, 8858577 and MIL-STD-129).

Categories	Defects	Method of Inspection	Code No.
Major:			
101.	Foreign matter or corrosion on interior	Visual	01001
Minor:	None defined.		

4.2.2.2 Sealed box or container (see dwgs. 76-4-46, 76-4-53, 76-4-56 and 7549033).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:			
101.	Cover improperly closed	Visual/Manual	02001
102.	Gasket missing or broken	Visual	02002
103.	Crack or hole in metal container	Visual	02003
104.	Foreign matter or corrosion on interior	Visual	02004
Minor:			
201.	Car seal missing, unsealed or improperly positioned	Visual/Manual	02005
202.	Hardware improperly engaged	Visual	02006
203.	Marking misleading or unidentifiable	Visual	02007

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:12Z
Check the source to verify that this is the current version before use.

204.	Bare areas on exterior coating of metal container, the sum of which is in excess of 1/4 square inch	Visual	02008
205.	Wood split terminating at edge of board	Visual	02009
206.	Board broken or piece missing	Visual	02010
207.	Loose boards	Visual	02011
208.	Nails protruding or loose	Visual	02012
209.	Split boards insufficiently nailed	Visual	02013
210.	Wood rot	Visual	02014

4.2.2.3 Sealed metal container (see dwgs. 7549033, 8858577 and 138439).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:			
101.	Holes in metal container	Visual	03001
102.	Damaged seams	Visual	03002
103.	Damaged locking devices	Visual	03003
104.	Foreign matter or corrosion in interior	Visual	03004
Minor:			
201.	Car seal missing, unsealed or improperly position	Visual	03005
202.	Hardware improperly engaged	Visual	03006
203.	Marking misleading or unidentifiable	Visual	03007
204.	Excess dents	Visual	03008

4.2.2.4 Fiber containers.

Categories	Defects	Method of Inspection	Code No.
Major:			
101.	Gasket missing or incomplete	Visual	04001
102.	Locking devised, damaged or improperly closed	Visual	04002
103.	Holes or breaks in cover or body	Visual	04003
104.	Damage to coating or cover	Visual	04004
105.	Foreign matter or corrosion in interior	Visual	04005

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:12Z
Check the source to verify that this is the current version before use.

Minor:			
201.	Marking misleading or unidentifiable	Visual	04006
202.	Interior or exterior torn or delaminated	Visual	04007

4.3 Testing.

4.3.1 Chemical composition and stability Major defect Code Number 05001.-Ten pounds of propellant shall be selected at random from the lot. Five pounds shall be provided for chemical and stability tests. The remaining five pounds shall be forwarded to the installation designated by the procuring activity, for 65.5°C surveillance tests. All samples shall be packed in air-tight containers and shall be marked to show the propellant designation, lot number, manufacturer, date of sampling, contract number and number of pounds in the lot.

4.3.2 Form and dimension of grains Major defect Code Number 06001.-Sixty (60) grains shall be selected from each lot for examination, and results thereof recorded for information only. Examination for form shall be visual. Measurement of grain diameter shall be made of the sixty grains by means of a microscope, having a magnification of not less than 25 diameters. Thickness measurement of the same grains shall be made by micrometer.

4.3.3 Ballistic test Major defect Code Number 07001.-Sufficient propellant to load 30 sample rounds shall be selected at random from each lot for tests at a Government proving ground. Testing shall be performed as specified in 4.4.6 and 4.4.7.

4.4 Test Methods And Procedures.

4.4.1 Determination of composition.-Test methods specified below are in accordance with MIL-STD-286.

4.4.1.1 Nitrocellulose.-The percentage of nitrocellulose shall be determined as specified in Method 209.2.1.

4.4.1.2 Nitroglycerin.-The percentage of nitroglycerin shall be determined as specified in Method 208.1.3, using absolute ether or methylene chloride as the solvent for extraction.

4.4.1.3 Potassium nitrate.-The percentage of potassium nitrate shall be determined as specified in Method 310.4.2.

4.4.1.4 Bariun nitrate.-The percentage of bariun nitrate shall be determined as specified in Method 304.1.2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:12Z
Check the source to verify that this is the current version before use.

4.4.1.5 Ethyl centralite.-The percentage of ethyl centralite shall be determined as specified in Method 202.2.3, using absolute ether or methylene chloride as the solvent for extration.

4.4.1.6 Graphite.-The percentage of graphite shall be determined as specified in Method 308.1.3.

4.4.2 Total volatiles.-The total volatiles content shall be in accordance with MIL-STD-286, Method 103.3.3.

4.4.3 Total moisture.-The moisture content shall be in accordance with MIL-STD-286, Method 102.1.3.

4.4.4 120°C Heat test.-The 120°C heat test shall be conducted as specified in MIL-STD-286, Method 404.1.2.

4.4.5 Gravimetric density (gms/cc).

4.4.5.1 Apparatus.-A cylinder shall be obtained with a length of approximately 6 inches and an inside diameter of approximately 2 5/16 inches (a 1,000 milliliter (ml) graduate, severed at the 400 ml mark has been found suitable). A counterpoise shall be made by filling an 8-ounce bottle (or other suitalbe container) with sand until the weight of the counterpoise is equal to the weight of the empty cylinder.

4.4.5.2 Procedures.-The cylinder shall be weighed, while empty, by means of a trip balance and the counterpoise. The cylinder shall be filled completely with distilled water, weighed on the trip balance and the weight recorded. The propellant to be tested shall be allowed to attain approximately room temperature. The empty cylinder shall be balanced against the counterpoise on the trip balance. The cylinder shall be filled to the over-flowing with the propellant, by allowing it to fall loosely through a funnel which has its lowest point 2 1/2 inches above the top of the cylinder. The excess propellant in the cylinder shall be struck off with a straight edge and the cylinder tapped gently so that no propellant will be spilled in handling. Equilibrium shall be restored to the balance by means of the rider and weights. The gravimetric density shall be calculated as follows:

$$\frac{\text{Wt of sample in grams}}{\text{Wt of equal volume of water in grams}} = \text{Gravemetric Density (gms/cc)}$$

4.4.6 Ballistic.

4.4.6.1 Rifle.-The following weapon and components shall be used in the rifle tests:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:12Z
Check the source to verify that this is the current version before use.

Caliber .30 U.S. Rifle, Model 1903
Cartridge Case M1
Bullet, M2, 152 grains

The preparations of the rifle, a mechanical stand, and ammunition loading and handling, shall be in accordance with the applicable TECOM materiel test procedures. At least three warning shots shall be fired at one-minute intervals using small charges of the propellant to be tested. Using the standard F.A. pressure gage (short piston) and F.A. coppers of zero initial compression, assess a weight of charge for the standard propellant lot to give a pressure of 35,000 ± 5,000 psi. Fire a uniformity series of ten rounds, at the assessed charge weight, recording velocity at any convenient point.

Fire the test propellant at increasing charge weights to determine whether or not the propellant can be fired at the same charge level as the standard propellant with a resulting pressure within ± 5% of that obtained for the standard propellant. Fire a ten-round uniformity series with the test propellant at this charge level, recording velocities and pressures in the same manner as above.

The details of the test procedure shall have prior approval of the Government.

4.4.6.2 Caliber .45 pistol, ACP.-The following weapon, components and conditions shall be used in this test:

GUN: Caliber .45 ACP, Velocity and pressure
Barrel, 5" length.
Cartridge: Remington Arms Co.
Bullet: Remington M.C., 230 grain.
Loading: Hand, with bullet seating depth of 0.305
Velocity: Measured over 20 ft. at 15 ft. from muzzle.
Pressure: Crushers 0.146" x 0.400"

Twenty (20) powder charges, each weighing 4.3 ± 0.1 grains avoirdupois, shall be drawin from the propellant samples, which shall be maintained at 70°F. Each of the twenty charges shall be loaded in a .45 ACP cartridge employing a 230 grain bullet seated at a depth of 0.3 inches. Simultaneously, twenty (20) cartridges shall be identifically loaded by the same technician employing the standard propellant defined in paragraph 3.7.2.3. The twenty test lot cartridges and the twenty standard powder cartridges shall be fired alternately in a 5-inch velocity pressure barrel maintaining a cartridge temperature of 70°F and retating each cartridge to assure primer-end-load (PEL) of the powder prior to chamber insertion. The uncorrected velocity of the 230 grain bullet shall be determined by employing a chronograph to measure the time of flight over a 20 ft. range, the mid-point of which shall be 15 ft. from the muzzle. The uncorrected chamber pressure shall be determined by using a crusher gage, having a diameter of 0.146 inch and a length of 0.400 inch.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:12Z
Check the source to verify that this is the current version before use.

4.4.6.2.1 Corrected mean velocity determination.-The arithmetic mean and the 20 uncorrected velocities for the standard cartridge shall be calculated. The arithmetic mean of the 20 uncorrected test-lot velocities shall be calculated. The corrected factor shall be calculated by subtracting the mean of the 20 standard velocities from the assessed velocity of the standard propellant. The corrected mean velocity of the test lot shall be determined by adding algebraically the dorrection factor to the uncorrected mean of the 20 test-lot velocities.

4.4.6.2.2 Corrected mean pressure determination.-The arithmetic mean of the 20 uncorrected pressures for the standard cartridges shall be calculated. The arithmetic mean of the 20 uncorrected test lot pressures shall be calculated. The correction factor shall be calculated by subtracting the mean of the 20 standard pressures from the assessed pressure of the standard propellant. The correct mean pressure of the test lot shall be determined by adding, algebraically, the correction factor to the uncorrected mean of the 20 test lot pressures.

4.4.6.2.3 Ballistic uniformity determination.-The velocity range, or extreme variation among the 20 uncorrected lot velocities shall be calculated by subtracting the lowest uncorrected test velocity from the highest uncorrected test velocity. The pressure range, or extreme variation among the 20 uncorrected lot pressures, shall be calculated by subtracting the lowest uncorrected test pressure from the highest uncorrected test pressure. The details of the test procedure shall have prior approval to the Government.

4.4.7 Closed bomb.-The propellant shall be tested in accordance with MIL-STD-286, Method 801.1.1, with the following exceptions:

Volume of bomb	200 cc nominal
Loading density	0.075 gm/cc

The test shall be either conducted by the Government or by the contractor, provided the Government, as stipulated in the contract or order, approves the equipment and test methods to be used by the contractor prior to manufacturing.

5. PREPARATION FOR DELIVERY

5.1 Packing and marking.-Packing and marking shall be in accordance with MIL-STD-652 and Code of Federal Regulations, Title 49, Parts 171-179.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:12Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Ordering data.-Procurement documents shall specify the following:

a. Title, number and date of this specification.
b. Data cards shall be prepared for each lot in accordance with the information specified in Standard MIL-STD-1167.
c. Process.-Details of the manufacturing process and the equipment used by the Contractor will be submitted to the procuring activity in writing prior to commencement of manufacture.

6.2 Inspection code numbers.-The five-digit code numbers assigned to the inspections herein are to facilitate future data collection and analysis by the Government.

6.3 Submission of test data.-In addition to the normal distribution of records, when the propellant is procured by the U.S. Army Munitions Command, one (1) copy of all ballistic data and ammunition data cards shall be forwarded to: Commanding Officer, Picatinny Arsenal, ATTN: SMUPA-QA-A-S.

6.4 Submission of results of contractor-conducted examinations and tests.-Unless otherwise specified by the Contracting Officer, the contractor shall forward requested records of examinations or tests to Commanding Officer, Picatinny Arsenal, ATTN: SMUPA-QA-A-S.

6.5 Submission of SMU Form 1060.-Information contained in propellant description sheet, SMU Form 1060, need not be resubmitted in the form of a certificate provided the provisions regarding certifying of responsible agents is adhered to.

6.6 Supersession data.-This specification includes the requirements of, and supersedes, Purchase Specification AEI-94, Rev. 1 dated 28 Aug. 1962.

6.7 Surveillance samples.-Samples shall be forwarded to Picatinny Arsenal, Dover, New Jersey, ATTN: SMUPA-FR-G for the propellant surveillance test program in accordance with MIL-STD-652.

Custodian:
Army-MU

Preparing activity:
Army-MU

Project Number: 1376-A-013.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:12Z
Check the source to verify that this is the current version before use.