MILITARY SPECIFICATION

SCREW, CAP, SOCKET HEAD

1. SCOPE

1.1 This specification covers requirements, quality assurance provisons, and the preparation for delivery criteria for one type of screw, cap, socket head used on Test Plug for XM455 Projectile.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein:

SPECIFICATIONS

MILITARY

MIL-P-116 - Preservation, Methods of

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-1168 - Lot Numbering of Ammunition
MIL-STD-1169(MU) - Packaging, Packing and Marking for Shipments of Inert Ammunition Components
MS-16997 - Screw, Cap, Socket Head

DRAWINGS

ORDNANCE CORPS

8808362 - Packing and Marking for Storage and Shipments

FSC 5305

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:13Z
Check the source to verify that this is the current version before use.

8883536 - Bag, Packing, for Repair Parts
10522829 - Screw, Cap, Socket Head
EL-10522829 - Equipment List

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Materials. The contractor shall furnish objective evidence (see 6.2) that the material complies with the specifications listed on the applicable drawing.

3.2 Assembly. The screw shall comply with all requirements specified on the drawing (dwg) , with all requirements specified herein, and with the requirements of all applicable specifications to the extent specified on the drawing and herein.

3.3 Workmanship.

3.3.1 Plastic and metal characteristics. All components shall be free from cracks, splits, cold flow, shrinkage, cold shuts, inclusions, porosity, or any similar characteristic.

3.3.2 Threads. Threads shall be full and undamaged for the entire minimum length or depth as required on the applicable drawing.

3.3.3 Burrs. Parts shall be free from burrs.

3.3.4 Foreign matter. Parts shall be free from chips, dirt, grease, rust, corrosion, or any embedded foreign material.

3.3.5 Cleaning. The cleaning method shall not be injurious to any of the parts, nor shall the parts be contaminated by the cleaning agent.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 First article inspection. Not applicable.

4.3 Quality conformance inspection.

Source: https://assist.dla.mil -- Downloaded: 20260-22T19:13Z
Check the source to verify that this is the current version before use.

4.3.1 Lot formation.

4.3.1.1 Production lot. A lot shall consist of parts and assemblies produced by one manufacturer in one unchanged process, in accordance with the same drawing, same drawing revision, same specification and same specification revision. Drawing, specification and process changes not affecting safety, performance, storage, or interchangeability, as determined by the Government, shall not necessitate changing the lot interfix number. The criteria and procedures for the assignment of lot numbers shall be in accordance with MIL-STD-1168.

4.3.1.2 Inspection lot. A lot or batch and its formation, size, and presentation is described in MIL-STD-105, Section 5. Accordingly, a lot shall mean an inspection lot and a batch shall mean an inspection batch for the purpose of this specification. The manner in which each inspection lot or batch is to be presented and identified by the contractor, shall be designated or approved by the Government representative.

4.3.2 Product inspection examination. Critical characteristics shall require 100 percent inspection of all items in the inspection lot. A sample shall be selected at random from each inspection lot in accordance with the applicable major or minor characteristic table (see Table I and Table II), and inspected for all characteristics in the applicable classification. Any characteristics in the sample found to be defective shall reject the inspection lot. Sequence for the inspection of characteristics in each classification need not be followed as long as all characteristic inspections are performed.

Table I
Major Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-16	all	28-29	23	52-56	31	132-156	39
17	16	30-31	24	57-62	32	157-191	40
18	17	32-34	25	63-69	33	192-244	41
21	19	37-40	27	77-86	35	335-519	43
22-23	20	41-43	28	87-97	36	520-1120	44
24-25	21	44-47	29	98-112	37	over 1120	45
26-27	22	48-51	30	113-131	38		

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:13Z
Check the source to verify that this is the current version before use.

Table II
Minor Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-9	all	14-16	12	28-33	16	77-121	20
10	9	17-18	13	34-41	17	122-273	21
11	10	19-22	14	42-54	18	over 273	22
12-13	11	23-27	15	55-76	19		

4.3.2.1 Classification of characteristics (see 3.2). Critical, major and minor characteristics are defined in MIL-STD-105. Inspection shall be conducted as follows:

4.3.2.1.1 Screw, cap, socket head (see dwg. 10522829).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Distance from thread to head (.28)	Gage
102.	Pitch diameter of thread after plating	Gage
103.	Major diameter of thread after plating	Gage
104.	Diameter adjacent to head (.19)	Gage
105.	Diameter of 2 holes thru head, min (1/16)	Gage
106.	Length from head to right side of groove (.14)	Gage
107.	Length from head to end of screw (.625)	Gage
108.	Width of groove (.106)	Gage
109.	Diameter of groove (.121)	Gage
110.	Objective evidence (see 6.2) for screw in accordance with MS-16997	Visual
111.	Objective evidence (see 6.2) for protective finish in accordance with dwg. 10522829	Visual
112.	Objective evidence (see 6.2) for heat treatment in accordance with dwg. 10522829	Visual
Minor:		
201.	Workmanship (see 3.3)	Visual-Manual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:13Z
Check the source to verify that this is the current version before use.

4.3.2.1.2 Preparation for delivery (see 5.1).

Categories	Characteristics	Method of Inspection
Critical:	None defined	
Major:		
101.	Preservation, packaging, packing and marking in accordance with MIL-STD-1169(MU)	Visual-Manual
Minor:	None defined	

4.3.2.1.3 Bag, packing, for repair parts (see dwg. 8883534 covering dwg. part number 8883534-1 and 5.2).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Material (see 3.1)	Visual
102.	Length before packing, min	*Measure
103.	Width before packing, min	*Measure
104.	Properly packed	Visual-Manual
105.	Proper heat seal	Visual-Manual
106.	No crack or hole in bag	Visual
107.	Objective evidence (see 6.2) for heat seal test in accordance with MIL-P-116	Visual

*Measure with suitable scale.

Minor:		
201.	Marking	Visual
202.	Workmanship (see 3.3)	Visual-Manual

4.3.2.1.4 Packing and marking for storage and shipments (see dwg. 8808362 and 5.2).

Categories	Characteristics	Method of Inspection
Critical:	None defined	
Major:		
101.	Gross load weight, max	*Measure
102.	Contents tight in package	Manual
103.	Properly packed	Visual-Manual
104.	Material (see 3.1)	Visual

*Determine weight with suitable scale.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:13Z
Check the source to verify that this is the current version before use.

Minor:

201.	Marking	Visual
202.	Workmanship	Visual-Manual

4.3.3 Testing. Not applicable.

4.3.4 Acceptance inspection equipment.

4.3.4.1 Critical and major characteristics and tests. Inspection and testing shall be performed with the acceptance inspection equipment, operating instructions, and calibration instructions specified on the Equipment Lists (EL) (See EL-10522829). When either of the conditions listed below exist, the contractor shall design required equipment or specify suitable commercial equipment and obtain approval prior to use on the contract.

a. Any deviation from equipment or procedures specified on the EL is desired (see 6.3).
b. The code "CD" is listed in the "Part or Identifying Number" column on the EL (see 6.1.2).

4.3.4.2 Minor characteristics and tests. Acceptance inspection equipment for minor characteristics is not specified on ELs. The acceptance inspection equipment, operating instructions and calibration instructions used by the contractor for minor classification inspection shall be approved by the Government representative authorized by the procuring agency.

4.4 Test methods. Not applicable.

5. PREPARATION FOR DELIVERY

5.1 Production items.

5.1.1 Preservation and packaging. Preservation and packaging shall be level A or C as specified (see 6.1).

5.1.1.1 Level A. The screw shall be preserved and packaged in accordance with instructions contained in MIL-STD-1169(MU).

5.1.1.2 Level C. The screw shall be preserved and packaged in accordance with instructions contained in MIL-STD-1169(MU).

5.1.2 Packing.

5.1.2.1 Levels A and C. The screw shall be packed in accordance with the applicable instructions contained in MIL-STD-1169(MU).

5.1.3 Marking. Marking shall be in accordance with MIL-STD-1169(MU).

5.2 Repair parts.

5.2.1 Preservation and packaging. Preservation and packaging shall be level A or C as specified (see 6.1).

5.2.1.1 Level A. The screw shall be packaged in accordance with dwgs. 8883534 and 8808362 using the specified moisture barrier.

Source: https://assist.dla.mil -- Downloaded: 202640-22T19:13Z
Check the source to verify that this is the currentversion before use.

5.2.1.2 Level C. The screw shall be packaged in accordance with dwg. 8808362 except that the moisture barrier may be omitted.

5.2.2 Packing.

5.2.2.1 Level A and C. The screw shall be packed in accordance with dwgs. 8883534 and 8808362

5.2.3 Marking. Marking shall be as specified in accordance with dwgs. 8883534 and 8808362 as applicable.

6. NOTES

6.1 Ordering data. Procurement documents should specify the following:

6.1.1 Procurement requirements.

a. Title, number, and date of this specification.
b. Production or Repair Parts.
c. Selection of applicable level of packaging and packing required (see 5.1 and 5.2).

6.1.2 Contract data requirements (see 4.3.4.1). Data specified in 4.3.4.1 will be delivered as identified on a numbered DD Form 1664 or specification when specified on a DD Form 1423 incorporated in the contract.

6.2 Objective evidence. Records of contractor quality control and inspections which can be verified.

6.3 Acceptance inspection equipment (see 4.3.4.1). The contractor shall obtain approval from the Commanding Officer, Picatinny Arsenal, Dover, New Jersey 07801, ATTN: SMUPA-QA-I.

Custodian:
Army - MU

Preparing activity:
Army - MU

Project No. 5305-A006

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:13Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No 22-R255

INSTRUCTIONS This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost Comments and the return of this form will be appreciated Fold on lines on reverse side, staple in corner, and send to preparing activity Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements

SPECIFICATION
MIL-S-48102(MU) Screw, Cap, Socket head

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A
☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1 HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2 COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3 IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4 REMARKS *(Attach any pertinent data which may be of use in improving this specification If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1 JAN 66 1426

REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:13Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS

Commanding Officer
Picatinny Arsenal
ATTN: SMUPA-NR
Dover, New Jersey 07801

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:13Z
Check the source to verify that this is the current version before use.