MILITARY SPECIFICATION

WARHEAD SECTION, ATOMIC, TRAINING: M240 (TYPE X)

1. SCOPE

1.1 This specification covers special requirements not included on the drawings, and provides quality assurance provisions for the fabrication of parts, assembling, and the preparation for delivery of Warhead Section, Atomic, Training: M240, which is used for training on the Lance warhead section.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein:

SPECIFICATIONS

MILITARY

MIL-S-48525	- Shipping and Storage Container, Atomic Warhead Section, M511.
MIL-C-48521	- Cable Assembly, Special Purpose, Electrical: W47U Through W55U And W65U And W72U.
MIL-I-6866	- Inspection, Penetrant, Method Of.
MIL-F-81177	- Fasteners, Blind, High Strength, Pull Type Positive Mechanical Lock.
MS-51835	- Inserts and Studs, Locked In - Key Locked, Hole Dimensions For And Assembly Of.

STANDARDS

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-810	- Environmental Test Methods.

DRAWINGS

ORDNANCE CORPS

9219390	- Shipping and Storage Container, M511 for Warhead Section.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:17Z
Check the source.to verify that this is the current version before use.

9219584 - Combination Lock (Trainer) MC2118TRB.
9231724 - Coded Switch Simulator MC2607TRA.
9236943 - Cable Assembly, Interior, PAL, Training.
9246011 - Control Unit Assembly.
9248161 - Warhead Section, Training, M240.
9249024 - Cable Assembly, Exterior, PAL, Training.
9251644 - Command Disable Trainer MC2242TR.
9293495 - Packing and Marking for Shipping and Storage Container for Lance Warhead Sections TRNG, Type X, M240.
EL-9248161 - Equipment List.

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer).

3. REQUIREMENTS

3.1 Materials. The contractor shall furnish objective evidence (see 6.2) that the material complies with the specifications listed on the applicable drawing.

3.2 Assembly. The training warhead section shall comply with all requirements specified on the drawing (dwg) 9248161, with all requirements specified herein, and with the requirements of all applicable specifications to the extent specified on the drawing and herein.

3.3 First article testing. Requirements for the submission of first article samples by the contractor shall be as specified in the contract (see 4.2).

3.4 Serialization. The contractor shall assign serial numbers as required by drawings. The contractor may select any number which complies with the drawing requirement. These numbers shall not be duplicated.

3.5 Environmental testing. The control unit assembly shall comply with MIL-STD-810, visual inspection and failure criteria, section 3. The control unit assembly shall also comply with 4.3.3.1 before and after each environmental test. Testing shall be as specified in 4.4.3. Tests shall be conducted in the order specified.

3.5.1 High temperature. The control unit assembly shall withstand exposure to a temperature of 140 ± 5°F without damage when tested as specified in 4.4.3.1.

3.5.2 Low temperature. The control unit assembly shall withstand exposure to a temperature of -40 ± 5°F without damage when tested as specified in 4.4.3.2.

3.5.3 Vibration. The warhead section shall be subjected to sinusoidal vibration and there shall be no evidence of damage. Testing shall be as specified in 4.4.3.3.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:17Z
Check the source to verify that this is the current version before use.

3.6 Components. The shipping and storage container, atomic warhead section, M511, dwg 9219390, prior to being utilized, shall have complied with MIL-S-48525. The exterior PAL Cable 9249024 and interior PAL Training Cable 9236943, prior to being utilized, shall conform to the requirements of MIL-C-48521, Cable Assemblies, Training.

3.7 Weight. The training warhead section shall weigh as specified on dwg 9248161 when weighed as specified in 4.4.1.

3.8 Center of gravity. The training warhead section shall have a center of gravity as specified on dwg 9248161 when determined as specified in 4.4.2.

3.9 Function.

3.9.1 Combination lock trainer. Combination lock trainer (see dwg 9219584) shall be tested in accordance with 4.4.4.1 without impairment of operation.

3.9.2 Command disable simulator. The command disable simulator (see dwg 9251644) shall be tested in accordance with 4.4.4.1 without impairment of operation.

3.9.3 Coded switch simulator. The coded switch simulator (see dwg 9231742) shall be tested in accordance with 4.4.4.2 without impairment of operation.

3.9.4 Control unit assembly. The control unit assembly (see dwg 9246011) shall be tested in accordance with 4.4.4.3 without impairment of operation.

3.9.5 Quick access door assembly. The quick access door assembly (see dwg 9248161) shall be tested in accordance with 4.4.4.4.

3.9.6 Parameter setting door assembly. The parameter setting door (PSD) assembly (see dwg 9248161) shall be tested in accordance with 4.4.4.5.

3.10 Workmanship.

3.10.1 Plastic and metal characteristics. All components shall be free from cracks, splits, cold flow, shrinkage, cold shuts, inclusions, porosity, or any similar characteristic.

3.10.2 Threads. Threads shall be full and undamaged for the entire minimum length or depth as required on the applicable drawing.

3.10.3 Burrs. Parts shall be free from burrs.

3.10.4 Foreign matter. Parts shall be free from chips, dirt, grease, rust, corrosion, or any embedded foreign material.

3.10.5 Cleaning. The cleaning method shall not be injurious to any of the parts, nor shall the parts be contaminated by the cleaning agent.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:17Z
Check the source to verify that this is the current version before use.

contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 First article inspection.

4.2.1 Quantity to be submitted. When the contract requires first article inspection, the contractor shall submit 1 complete assembly (see dwg 9248161) for first article testing to the testing facility designated in the invitation for bids or request for proposal.

4.2.2 Inspection and testing to be performed. The first article inspection sample shall be subjected to the inspections and tests specified in Table I. Tests shall be conducted in order specified in Table I.

Table I

Inspection or Test	Dest	Non-Dest
1. Classification of characteristics (see 4.3.2.1)		X
2. *Function (see 3.9)		X

*Within 15 minutes after removal from condition chamber.
*Control Unit Assembly shall be tested for function at high temperature (3.5.1), low temperature (3.5.2), and at ambient temperature, either separately or assembled into warhead section.
*The following assemblies shall be tested for function at ambient conditions only, as assembled in the warhead section:

a. The PSD Assembly and Quick Access Door Assembly.
b. The Combination Lock (Trainer) and Command Disable Simulator as a CDS support assembly.
c. The Coded Switch Simulator connected to an interior PAL Cable (Training).

4.2.3 Inspection equipment. The inspection and testing specified in 4.2.2 shall be accomplished by using the gages and test equipment specified in 4.3.4.1.

4.2.4 Rejection. If any item fails to comply with any of the applicable requirements, the first article sample shall be rejected.

4.3 Quality conformance inspection.

4.3.1 Lot formation. The formation of an inspection lot and related functions shall be in accordance with Section 5, MIL-STD-105. A lot shall consist of parts and assemblies produced by one manufacturer in one unchanged process, in

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:17Z
Check the source to verify that this is the current version before use.

accordance with the same drawing, same drawing revision, same specification and same specification revision.

4.3.1.1 Inspection lot. An inspection lot shall be the quantity of parts, subassemblies, or assemblies from the same lot, which are submitted to inspection for Government acceptance.

4.3.2 Product inspection examination. A sample shall be selected at random from each inspection lot in accordance with the major characteristic Table II, inspected for all characteristics, tested for operation of the Combination Lock (Trainer) Command Disable Simulator, Coded Switch Simulated, Control Unit Assembly, Parameter Setting Door (PSD) Assembly, and the Quick Access Door Assembly, as part of the completely assembled warhead section at ambient temperature. If any characteristics or functions in the sample are found to be defective, 100% inspection of the characteristic or function that failed shall be required of the entire lot. Sequence for the inspection of characteristics in each classification need not be followed as long as all characteristic inspections are performed. All M240 warhead sections that fail to comply with any of the applicable requirements, shall be rejected. Subsequent acceptance, after correction of defects, will be based upon 100% reinspection of applicable functions and characteristics.

Table II

Major Characteristic

Lot Size	Sample Size
1 - 25	100% inspection
26 - 30	25
31 - 35	26
36 - 40	27
41 - 45	28
46 - 50	29
51 - 55	30
56 - 60	31
61 - 65	32
66 - 70	33
71 - 75	34
76 - 85	35
86 - 95	36
96 - 110	37
111 - 130	38
131 - 156	39
157 - 190	40
191 - 240	41
241 - 340	42
341 - 520	43
521 - 1120	44
1121 - and over	45

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:17Z
Check the source to verify that this is the current version before use.

4.3.2.1 Classification of characteristics (see 3.2). Critical, major and minor characteristics are defined in MIL-STD-105. Inspection shall be conducted as follows:

4.3.2.1.1 Warhead section, atomic training (see dwg 9248161).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
	101. Station 100 interface incorrect	Gage
	102. Gasket for Quick Access Door not cemented securely	Visual/Manual
	103. Gasket for Parameter Setting Door (control unit access) not cemented securely	Visual/Manual
	104. Marking missing, incorrect, illegible	Visual
	105. Protective finish damaged or missing exposing base metal "D" section	Visual
	106. Improper installation of blind fasteners (see MIL-F-81177)	Visual/Gage
	107. Any component parts missing, damaged or incorrectly assembled	Visual
	108. Objective evidence relative to material missing or improper (see 3.1)	Visual
	109. Incorrect dial readings (6) on control unit	Visual
	110. Incorrect torque on mounting screws, mounting nuts (or in making dial settings)	Gage
	111. Incorrect installation of inserts (see MS-51835)	Visual/Gage
	112. Incorrect assembly of access doors (2)	Visual/Manual
	113. Incorrect welding (see MIL-I-6866)	Visual/Manual
	114. Serialization missing or improper (see 3.4)	Visual
Minor:		
	201. Evidence of poor workmanship (see 3.10)	Visual

4.3.2.1.2 M511 Shipping and Storage Container prior to insertion of Warhead Section (Training) (see dwg 9293495).

Critical: None defined.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:17Z
Check the source to verify that this is the current version before use.

Major:

101. Hardware missing, unserviceable, or loose.....Visual/Manual
102. Corrosion, fungus, or other foreign material present.....Visual
103. Cover alignment pins damaged (2).....Visual
104. Drain plug (2) loose, missing or unserviceable.....Visual/Manual
105. Paint peeling, scratched, inadequate coverage or wrong color.....Visual
106. Electronic shielding gasket unserviceable.....Visual
107. Non-metallic channels loose, unserviceable, protection strip (2) missing or unserviceable.....Visual/Manual
108. H-4267 key unserviceable or missing.....Visual
109. Resilient mounts unserviceable.....Visual
110. Desiccant missing.....Visual
111. Hardware box contents missing.....Visual
112. Structural damage to cradle assembly mounting plate, hardware box, H4267 key mounting bracket, desiccant basket unserviceable or missing.....Visual
113. Cable W53U loose, damaged or unserviceable.....Visual/Manual

Minor: None defined.

4.3.2.1.3 Packing of Warhead Section (Training) in M511 Shipping and Storage Container before closing (see dwg 9293495).

Categories	Characteristics	Method of Inspection

Critical: None defined.

Major:

101. Warhead section component and hardware loose or missing.....Visual
102. Warhead section guide pins not properly engaged in station 100 support plate.....Visual
103. Incorrect torque at station 100 swing bolts at support plate (4 places).....Gage
104. Incorrect torque for securing hold down strap assembly over warhead section.....Gage
105. Protective cover assembly torque incorrect.....Gage

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:17Z
Check the source to verify that this is the current version before use.

106. Cable W53U connector A2P2 not properly connected to A2J2 on warhead section. Loose or disengaged at A2J3 container mounting.....Visual/Manual
107. PAL access cover not connected properly to protective cover assembly on support plate.....Visual
108. Incorrect torque for humidity indicator.....Gage
109. Incorrect torque for valves (2).....Gage
110. Incorrect torque for W53U Cable.....Gage
111. Marked mailing bags with contents missing or improper.....Visual

Minor: None defined.

4.3.2.1.4 Packing and marking of M511 Shipping and Storage Container after closing cover (see dwg 9293495).

Categories	Characteristics	Method of Inspection

Critical: None defined.

Major:

101. Identification plate missing, NSN Ser No, Contract No, nomenclature, date of manufacture, missing or illegible.....Visual
102. Wooden runner (skid) unserviceable, splits more than 3" long regardless of depth.....Visual
103. Desiccant access cover loose, unserviceable.....Visual/Manual
104. Stacking bolt holes, skid guides on cover and grooves on skids missing or incorrectly located.....Visual
105. Fork lift bars missing, loose, or damaged.....Visual/Manual
106. Lift handle clips unserviceable or missing.....Visual/Manual
107. Lift bars and handles cracked, broken or loose.....Visual/Manual
108. External PAL connector cover missing or unserviceable.....Visual
109. Coded switch simulator MC2607TRA does not function properly.....Test
110. Presence of corrosion, fungus, other foreign material.....Visual
111. Quick access cover loose, damaged, unserviceable.....Visual/Manual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:17Z
Check the source to verify that this is the current version before use.

112. Flange bolts torque incorrect (22).....Gage
113. Humidity indicator assembly loose or unserviceable.....Visual/Manual
114. Humidity indicator card reads 30 percent or more.....Visual
115. Pressure equalizer valves loose, unserviceable.....Visual/Manual
116. Hardware missing, unserviceable, loose.....Visual/Manual
117. Paint peeling, scratched, inadequate coverage, wrong color.....Visual
118. Structural damage which will preclude use of container for its intended purpose.....Visual
119. Marking illegible or does not agree with EML.....Visual
120. H-4244 wrench(es) unserviceable, missing (2 required), EML missing.....Visual
121. Records container cover loose, missing, unserviceable, gasket missing, unserviceable.....Visual/Manual
122. Lead wire seals missing (8 required)....Visual

Minor: None defined.

4.3.2.1.5 Preparation for delivery (see dwgs 9216660 and 9219390).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
	101. Packaging and packing not in accordance with dwgs	Visual
	102. Marking not in accordance with dwgs	Visual
Minor:		
	201. Evidence of poor workmanship (see 3.10)	Visual

4.3.3 Testing. All tests shall be performed. Tests shall be performed in the order specified below:

Test	Test Classification
a. Function (at ambient temperature only)	Major
b. Weight	Major
c. Center of gravity	Major

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:17Z
Check the source to verify that this is the current version before use.

None of these tests are considered destructive and samples so tested may be returned to the lot.

4.3.3.1 Weight and center of gravity. Each training warhead section shall be tested in accordance with 4.4.1 and 4.4.2. If any item fails to comply with 3.7 and 3.8, the item shall be rejected and removed from the lot.

4.3.4 Acceptance inspection equipment.

4.3.4.1 Major characteristics and tests. Inspection and testing shall be performed with the acceptance inspection equipment, operating instructions, and calibration instructions specified on the Equipment Lists (EL) (see EL-9248161). When either of the conditions listed below exist, the contractor shall design required equipment or specify suitable commercial equipment and obtain approval prior to use on the contract.

a. Any deviation from equipment or procedures specified on the EL is desired (see 6.3).
b. The code "CD" is listed in the "Part or Identifying Number" column on the EL (see 6.1.2).

4.3.4.2 Minor characteristics and tests. Acceptance inspection equipment for minor characteristics is not specified on ELs. The acceptance inspection equipment, operating instructions and calibration instructions used by the contractor for minor classification inspection shall be approved by the Government representative authorized by the procuring agency.

4.4 Test methods. The tolerances specified herein are absolute with no allowance for test equipment inaccuracy. The tolerances used by the manufacturer shall be equal to the absolute tolerances less the accuracy tolerances of the test equipment used.

4.4.1 Weight. The warhead section shall be weighed on an approved weighing device to determine the weight specified in 3.7.

4.4.2 Center of gravity. The warhead section shall be attached to an approved device to determine its center of gravity at the station specified in 3.8.

4.4.3 Environmental testing (see 3.5).

4.4.3.1 High temperature. The training warhead section or control unit assembly shall be placed in a test chamber. The chamber's temperature shall be raised and stabilized at 140 ± 5°F (see 6.4). The training warhead section, or required lower assemblies, shall be subjected to this stabilized temperature for a minimum of four hours.

4.4.3.2 Low temperature. The training warhead section or control unit assembly shall be placed in a test chamber. The chamber's temperature shall be lowered and stabilized at -40 ± 5°F (see 6.4). The training warhead section, or required lower assemblies, shall be subjected to this stabilized temperature for a minimum of four hours.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:17Z
Check the source to verify that this is the current version before use.

4.4.3.3 Sinusoidal vibration. The warhead section shall be placed in a suitable fixture and subjected to sinusoidal vibration in the longitudinal axis using a logarithmic sweep of fifteen minutes per cycle (5-500-5 Hz) with the following parameters:

Frequency (Hz)	Input
5-18.5	0.2" da
18.5-80	3g
80-115	4g
115-500	5g

4.4.4 Function.

4.4.4.1 Combination lock (trainer) and command disable simulator (see dwg 9219584). The simulated command disable system shall operate properly when the following procedures are followed:

1. Verify combination lock combination as below with caution to insure buttons are not depressed or levers operated except as specified:

a. Depress Reset Level (at end of assembly farthest from T-handle) to clear lock.

b. Numbering combination buttons as 1, 2, 3 from the reset lever to the T-handle, enter combination:

Key 1 push x times
Key 2 push y times
Key 3 push z times

where xyz is the combination set into lock by lock manufacturer.

c. Turn T-handle 90° counterclockwise. If correct combination has been entered, T-handle will remain in this position. (If the lock has not received the correct combination, the T-handle will not remain in the 90° position but will return to its original position when released).

d. If correct combination has been entered, return T-handle to original position by rotating 90° clockwise.

e. Depress reset lever to clear lock.

2. Verify changing combination in combination lock assembly as follows:

a. Perform 4.4.4.1 steps 1a thru c inclusive above.

b. Raise recode lever (at the nearest T-handle) to the vertical position. (If the correct combination is not used, the lever will not remain in the vertical position).

c. Depress the reset lever to erase the existing combination from the lock.

d. Punch a new combination into the lock by pushing buttons (see 4.4.4.1 step 1b).

e. Lower the recode lever to the horizontal position to retain the ew combination.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:17Z
Check the source to verify that this is the current version before use.

f. Depress the reset lever to reset the lock with the new combination.

g. Perform 4.4.4.1 steps 1a thru e inclusive to verify new combinations.

3. Verify reset capability using disable trainer assembly (see dwg 9251644) as follows:

a. Perform 4.4.4.1 steps 1 a thru c.

b. Pull the T-handle out of the lock. (The indicator pin of the disable trainer assembly will move to an extended position if the lock operates properly).

c. Depress the indicator pin until the T-handle, oriented perpendicular to the lock, re-engages with the lock when reinserted. Slowly release pressure on the indicator pin while retaining pressure of the T-handle.

d. Repeat 4.4.4.1 steps 1d and then 2b thru g, inserting the original xyz combination into the lock.

4.4.4.2 Coded switch simulator (see dwg 9231724). The PAL Component Simulated shall operate as specified in the drawing when a T1527 Encoder is connected to the PAL Component Simulated using the A2J2 Connector after removal of the PAL access cover.

4.4.4.3 Control unit assembly.

a. The control unit assembly (see dwg 9246011) settings should rotate from each position to any adjacent functional position with a torque of 8 + 5 inch lbs. and present a clearly visible letter/number indication for each test position.

b. Depression of the lever on the control unit assembly should allow the simulated go, no-go indicator button to protrude from the surface of the control unit assembly.

c. Check to insure retention of the simulated go, no-go indicator when the lever assembly on the control unit assembly has been adjusted to retain this indicator. This should be checked after each environmental test.

4.4.4.4 Quick access door assembly. The quick access door assembly (see dwg 9248161) shall be capable of being operated and removed by pushing the button per marking and rotating the handle one quarter turn counterclockwise.

4.4.4.5 PSD Door Assembly. The PSD Door Assembly (see dwg 9248161) shall be capable of being operated and removed by rotating the center socket, one quarter turn in the direction of marked arrow.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging. Preservation and packaging shall be level A or C as specified (see 6.1).

Source: https://assist.dla.mil - Downloaded: 2026-10-22T20:17Z
Check the source to verify that this is the current version before use.

5.1.1 Level A. The training warhead section shall be packaged in accordance with dwg 9219390 and 9293495 using the specified moisture barrier.

5.1.2 Level C. The training warhead section shall be packaged in accordance with dwg 9219390 and 9293495 except that the moisture barrier may be omitted.

5.2 Packing.

5.2.1 Level A and C. The training warhead section shall be packed in accordance with dwg 9219390 and 9293495.

5.3 Marking. Marking shall be as specified in accordance with dwg 9293495.

6. NOTES

6.1 Ordering data. Procurement documents should specify the following:

6.1.1 Procurement requirements.

a. Title, number, and date of this specification.
b. Selection of applicable level of packaging and packing required (see 5.1 and 5.2).

6.1.2 Contract data requirements (see 4.3.4.1). Data specified in 4.3.4.1 will be delivered as identified on a numbered DD Form 1664 when required on a DD Form 1423 incorporated in the contract.

6.2 Objective evidence. Records of contractor quality control and inspections which can be verified.

6.3 Acceptance inspection equipment (see 4.3.4.1). The contractor shall obtain approval from the Commander, Picatinny Arsenal, Dover, New Jersey 07801, ATTN: SARPA-QA-T.

6.4 Temperature stabilization. The temperature is considered stabilized when the greatest peaks (both highest and lowest) continually observed over 5 minutes min. do not exceed the nominal temperature plus tolerance specified.

6.5 Supersession data. This specification supersedes the requirements of Purchase Description PA-PD-2021 dated 17 February 1971, with Amendment 3 dated 29 June 1973.

Custodian:
Army - PA

Preparing activity:
Army - PA

Project No. 1115-A069

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:17Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 68 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:17Z
Check the source to verify that this is the current version before use.