MILITARY SPECIFICATION SHEET

RELAYS, ELECTRICAL, 1 PST TO 4 PDT CONTACTS
LOW-LEVEL TO 1/2 AMPERE (DRY REED)

This amendment forms a part of MIL-R-5757/29D, dated 22 July 1985, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 8

TABLE IV, delete table IV in its entirety and substitute:

" TABLE IV. Part numbers and characteristics. 1/

Part no. M5757/29	Nominal coil voltage	Coil resistance ohms ±10%	No. of poles	No. of capsules (contact arrangement) Form A	Form C	Configuration
-001	26.5	2350	1	1	0	A
-002	"	1450	1	0	1	"
-003	"	925	2	2	0	B
-004	"	925	2	1	1	"
-005	"	925	2	0	2	"
-006	"	650	3	3	0	C
-007	"	650	3	2	1	"
-008	"	650	3	1	2	"
-009	"	650	3	0	3	"
-010	"	460	4	4	0	"
-011	"	460	4	3	1	"
-012	"	460	4	2	2	"
-013	"	460	4	1	3	"
-014	"	460	4	0	4	"
-015	12	420	1	1	0	A
-016	"	420	1	0	1	"
-017	"	280	2	2	0	B
-018	"	185	2	1	1	"
-019	"	185	2	0	2	"
-020	"	130	3	3	0	C
-021	"	130	3	2	1	"
-022	"	130	3	1	2	"
-023	"	130	3	0	3	"
-024	"	100	4	4	0	"
-025	"	100	4	3	1	"
-026	"	100	4	2	2	"
-027	"	100	4	1	3	"
-028	"	100	4	0	4	"
-029	6	100	1	1	0	A
-030	"	70	1	0	1	"
-031	"	40	2	2	0	B
-032	"	40	2	1	1	"
-033	"	40	2	0	2	"
-034	"	30	3	3	0	C
-035	"	30	3	2	1	"
-036	"	30	3	1	2	"
-037	"	30	3	0	3	"
-038	"	22	4	4	0	"
-039	"	22	4	3	1	"
-040	"	22	4	2	2	"
-041	"	22	4	1	3	"
-042	"	22	4	0	4	"

1/ Relays possess high-level capability and low-level capability."

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.
Copyright https://assist.dla.mil - Downloaded: 20240417T054417Z
Check the source to verify that this is the current version before use.

Custodians:
Army - ER
Navy - EC
Air Force - 85

Review activities:
Army - AT, MI, MU

User activities:
Army - AV, ME
Navy - MC

Preparing activity:
Navy - EC

Agent:
DLA - ES

(Project 5945-0730)

Source: https://assist.dla.mil Downloaded: 2026-10-17T05:41Z
Check the source to verify that this is the current version before use.