INCH-POUND

MIL-R-5757/29D
AMENDMENT 2
14 January 2000
SUPERSEDING
AMENDMENT 1
17 March 1986

MILITARY SPECIFICATION SHEET

Inactive for new design after 22 July 1985. No superseding specification.

RELAYS, ELECTRICAL, 1 PST TO 4 PDT CONTACTS LOW-LEVEL TO 1/2 AMPERE (DRY REED)

This amendment forms a part of MIL-R-5757/29D, dated 22 July 1985 and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 6

* Environmental data: delete "Seal: Enclosure 3, test I."

PAGE 7

* Quality Assurance, Group A, Subgroup 1: delete “60 operations” and substitute “60 operations/second”.

PAGE 8

* Table II delete and substitute:

" TABLE II. Data.

	Coil voltage		
Nominal voltage	6.0	12.0	26.5
Pickup voltage – max (dc)	4.0	8.0	18.0
Dropout voltage – min (dc)	0.8	1.0	2.5
Coil resistance – ohms	See table III		
Operate time (max) including bounce (in milliseconds) at 25°C at 85°C	1 ms 2 ms	1 ms 2 ms	1 ms 2 ms
Dropout time (max) including bounce (in milliseconds) over temperature range Contact arrangement: Form A Form C	1 ms 2.5 ms	1 ms 2.5 ms	1 ms 2.5 ms

"

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T05:41Z
Check the source to verify that this is the current version before use.

TABLE IV, delete table IV and substitute:

" TABLE IV. Part numbers and characteristics. 1/

Part no. M5757/29	Nominal coil voltage (Vdc)	Coil resistance Ohms ±10%	No. of poles	No. of capsules (contact arrangement)		Configuration
				Form A	Form C	
-001	26.5	2340	1	1	0	A
-002	26.5	1450	1	0	1	A
-003	26.5	925	2	2	0	B
-004	26.5	925	2	1	1	B
-005	26.5	925	2	0	2	B
-006	26.5	650	3	3	0	C
-007	26.5	650	3	2	1	C
-008	26.5	650	3	1	2	C
-009	26.5	650	3	0	3	C
-010	26.5	460	4	4	0	C
-011	26.5	460	4	3	1	C
-012	26.5	460	4	2	2	C
-013	26.5	460	4	1	3	C
-014	26.5	460	4	0	4	C
-015	12	420	1	1	0	A
-016	12	420	1	0	1	A
-017	12	280	2	2	0	B
-018	12	185	2	1	1	B
-019	12	185	2	0	2	B
-020	12	130	3	3	0	C
-021	12	130	3	2	1	C
-022	12	130	3	1	2	C
-023	12	130	3	0	3	C
-024	12	100	4	4	0	C
-025	12	100	4	3	1	C
-026	12	100	4	2	2	C
-027	12	100	4	1	3	C
-028	12	100	4	0	4	C
-029	6	100	1	1	0	A
-030	6	70	1	0	1	A
-031	6	40	2	2	0	B
-032	6	40	2	1	1	B
-033	6	40	2	0	2	B
-034	6	30	3	3	0	C
-035	6	30	3	2	1	C
-036	6	30	3	1	2	C
-037	6	30	3	0	3	C
-038	6	22	4	4	0	C
-039	6	22	4	3	1	C
-040	6	22	4	2	2	C
-041	6	22	4	1	3	C
-042	6	22	4	0	4	C

1/ Relays possess high-level capability and low-level capability. "

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T05:41Z
Check the source to verify that this is the current version before use.

Custodians:
Army - CR
Navy - EC
Air Force - 11
DLA - CC

Review activities:
Army - AT, AV, CR4, MI
Navy - MC
Air Force - 99

Preparing activity:
DLA - CC

(Project 5945-1086)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T05:41Z
Check the source to verify that this is the current version before use.