INCH-POUND

MIL-M-5776C(USAF)
30 August 1990
SUPERSEDING
MIL-M-5776B(USAF)
11 June 1965

MILITARY SPECIFICATION

MAINTENANCE PLATFORM, AIRCRAFT ADJUSTABLE, 13 TO 20 FEET TYPE B-2

This specification is approved for use by the Department of the Air Force and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers one type of aircraft maintenance platform designated Type B-2.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids of request for proposal, form a part of the specification to the extent specified herein.

SPECIFICATION

FEDERAL

UU-T-81	Tags, Shipping and Stock

MILITARY

MIL-C-104	Crates; Wood, Lumber and Plywood Sheathed, Nailed and Bolted
MIL-P-116	Preservation, Methods of
MIL-B-26195	Box, Wood-Cleated, Skidded, Load Bearing Base

STANDARDS

MILITARY

MIL-STD)-129	Marking for Shipment and Storage
MIL-STD-130	Identification Marking of US Military Property

Beneficial comments, recommendations, additions, deletions, clarifications, etc., and any data which may improve this document should be sent to: Support Division, SA-ALC/MMDEM, Kelly AFB TX 78241

AMSC N/A FSC 1730

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T05:44Z
Check the source to verify that this is the current version before use.

MIL-STD-1186	Cushioning, Anchoring, Bracing, Blocking, and Waterproofing; with Appropriate Test Methods
MIL-STD-2073	DOD Material Procedures for Development and Application of Packaing Requirements

(Copies of specifications and standards required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer).

* 2.1.2 Other Government documents, drawings and publications. The following other Government documents form a part of this specification to the extent specified herein.

AIR FORCE

48J20090	Maintenance Platform, Aircraft, Adjustable, 13 to 20 Feet Type B-2

(Copies of specification, standards, drawings and publications required by suppliers in connection with specific procurement functions shall be obtained from the procuring activity or as directed by the contracting officer.)

* 2.2 Non-Government publications. The following document forms a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

ASTM-D-3951	Packaging, Commerical

(Application for copies of ASTM publications should be addressed to the’ American Society for Testing and Materials, 1916 Race Street, Philadelphia PA 19103).

3. REQUIREMENTS

3.1 The requirements specified in AF Drawing 48J20090 are applicable as requirements shall be as specified herein.

3.1.1 Where the requirements of the drawings and this specification conflict, the requirements of this specification shall govern.

3.2 Selection of specifications and standards. Specifications and standards for necessary commodities and services not specified herein shall be selected in accordance with MIL-STD-143.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T05:44Z
Check the source to verify that this is the current version before use.

3.2.1 Standards parts. AN or MIL Standard parts shall be used wherever they are suitable for the purpose, and shall be identified by their part numbers. Commercial utility parts such as screws, bolts, nuts, cotter pins, et cetera, may be used, provided they have suitable properties and are replaceable by the AN or MIL Standard parts without alteration and provided the corresponding AN of MIL part numbers are referenced on the drawings and in the parts lists. In applications for which no suitable corresponding AN or MIL part is in effect on date of invitation for bids, commercial parts may be used provided they conform to all requirements of this specification.

3.3 Design and construction. The maintenance platform shall be designed and constructed so that no parts will work loose in service. It shall be built to withstand the strains, jars, vibrations, and other conditions incident to shipping, storage installation, and service.

3.3.1 The maintenance platform shall be constructed so that adjustments and repairs can be easily made by the personnel of operation units and overhaul bases.

3.4 Identification of product. Equipment, assemblies, and parts shall be marked for identification in accordance with MIL-STD-130.

3.5 Workmanship. The maintenance platform, including all parts and accessories, shall be constructed and finished in a thoroughly workmanlike manner. Particular attention shall be given to neatness and thoroughness of marking of parts and assemblies, welding and brazing, painting, riveting, machine-screw assemblies, and freedom of parts from burrs and sharp edges.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Classification of tests. The inspection and testing of the platform shall be classified as acceptance tests.

4.3 Acceptance tests. Acceptance tests shall consist of:

a. Individual tests.
b. Sampling tests.

4.3.1 Individual tests. Each maintenance platform shall be subjected to the following test:

4.3.1 Examination of product. Each maintenance platform shall be inspected to determine compliance with the requirements specified herein and the drawing with respect to materials, workmanship, and marking.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T05:44Z
Check the source to verify that this is the current version before use.

4.3.2 Sampling tests. The first 3 maintenance platforms on the order, and one maintenance platform from each lot of 25 or fraction thereof on the order shall be selected at random and subjected to the following tests:

4.3.2.1 A lot shall consist of the maintenance platforms manufactured under essentially the same conditions, of the same material, and submitted for inspection at substantially the same time.

4.3.2.2 Rejection and retest. When one or more maintenance platforms form a lot fail to meet the specification, acceptance of all items in the lot shall be withheld until the extent and cause of failure have been determined. The contractor shall explain fully to the government representative the cause of failure and the action taken to preclude recurrence. After correction all of the sampling tests shall be repeated.

4.3.2.3 Individual test may continue. For production reasons, individual test or other sampling plans may be continued pending the investigation of a sampling test failure. But final acceptance of the entire lot or lots produced later (or items on hand or items produced later) shall not be made until it is determined that all items meet all the requirements of the specification.

4.3.3 Defects in items already accepted. The investigation of a test failure could indicate that defects may exist in items already accepted. If so, the contractor shall fully advise the procuring activity of all the defects likely to be found and the methods of correcting them.

4.4 Test methods. The maintenance platform shall be assembled completely and loaded with a static load of 1500 pounds, at or near the center of the platform. The maintenance platform shall then be operated through its entire range twice. The load shall then be removed and the maintenance platform operated through its entire range twice. There shall be no leakage of hydraulic fluid, elongation of bolt holes, or failure of welding, material, or workmanship.

4.4.1 With the load applied, as specified in 4.4 the maintenance platform shall be left at the 17 foot level for a period of one hour without the locking device in use. The rate of settling of the piston shall not exceed 0.02 inch per hour.

4.4.2 Each step of the maintenance platform shall be individually tested with a static load of 400 pounds at or near the center of the step. The deflection of each step under the load shall not exceed 1/4 inch and there shall be no permanent deflection when the load is removed.

4.5 Inspection of the preservation, packaging and marking for shipment and storage. Sample items of packs and the inspection of the preservation, packaging, packing and marking for shipment and storage shall be in accordance with the requirements of section 5, or the documents specified therein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T05:44Z
Check the source to verify that this is the current version before use.

* 5. PACKAGING

5.1 Preservation. Preservation shall be level A, C or Commercial as specified (see 6.2).

5.1.1 Disassembly and matchmarking. Disassembly shall be the minimum necessary to safeguard parts known to be subject to damage, loss or breakage in transit and to accomplish reduction in cube. Bolts, nuts, screws, pins, washers and other attaching parts removed shall be reinstalled in one of the mating parst and secured to prevent their loss. When necessary to facilitate reassembly, parts removed and mating parts shall be matchmarked. Matchmaking shall be printed on shipping tags conforming to UU-T-81, Type A. The printed tags shall be waterproofed in accordance with MIL-STD-129.

* 5.1.2 Level A. Preserve bare metal surfaces on the maintenance platform using P-2 preservatives in accordance with Method I of MIL-P-116. Cap all hydraulic lines to prevent contamination. Wrap preserved areas and hydraulic assemblies with MIL-B-121 and secure.

* 5.1.3 Level C. The level C preservation for the maintenance platform shall conform to the requirements of MIL-STD-2073.

* 5.1.4 Commercial. The commercial preservation of the maintenance platform shall be in according to ASTM-D-3951.

* 5.2 Packing. Packing shall be level A, B, or Commerical, as specified (see 6.2).

* 5.2.1 Level A. The components of the maintenance platform shall be packed in containers conforming to MIL-B-26195, Type 11 or MIL-C-104, Type II, Class 2, Style A. Closure and strapping shall be in accordance with applicable container specification.

* 5.2.2 Level B. The component of the maintenance platform shall be packed in containers conforming to MIL-B-26195, Type I or MIL-C-104, Type II, Class 2, Style A. Closure and strapping shall be in accordance with applicable container specification.

* 5.2.3 Level C. The components of the maintenance platform shall be packed in containers conforming to MIL-B-26195, Type I, or MIL-C-104, Type I, Style A. Closure and strapping shall be in accordance with applicable container specifications.

* 5.2.4 Commercial. The preserved components of the maintenance platform shall be packed in accordance with the requirements of ASTM-D-3951.

* 5.3 Marking.

* 5.3.1 Levels A, B and C. In addition to any special or other identification markings required by the contract (see 6.2) each unit pack, intermediate and exterior and unitized load shall be marked in accordance with MIL-STD-129.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T05:44Z
Check the source to verify that this is the current version before use.

5.4 Physical protection. All cushioning, blocking, bracing and bolting shall be in accordance with MIL-STD-1186.

6. NOTES

6.1 Intended use. The Type B-2 maintenance platform covered by this specification is intended to facilitate maintenance and inspection of inaccessible portions of heave aircraft.

6.2 Ordering data. Procurement documents should specify the following:

a. Selection of applicable levels of preservation and packaging and packing (see section 5).

6.3 Subject terms (key word) listing.

Aircraft maintenance platform
Maintenance platform
Platform
Type B-2, Maintenance platform
Work platform

Custodian:
Air Force - 99

Preparing activity:
Air Force - 82

(Project 1730-F297)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T05:44Z
Check the source to verify that this is the current version before use.