MIL-M-5777C
23 MARCH 1960

SUPERSEDING
MIL-M-5777B(ASG)
27 MAY 1953

MILITARY SPECIFICATION

MAINTENANCE PLATFORM, AIRCRAFT, ADJUSTABLE, 3 TO 10 FEET, TYPE B-1

This specifiction has been apprpoved by the Department of Defense and is mandatory for use by the Departments of the Army, the Navy, and the Air Force.

1. SCOPE

1.1 This specification covers one type of aircraft maintenance platform, designated Type B-1.

2. APPLICABLE DOCUMENTS

2.1 The documents, of the issue in effect on date of invitation for bids, form a part of this specification:

SPECIFICATIONS

FEDERAL

QQ-S-633 – Steel Bars, Carbon, Cold Finished and Hot Rolled, (General Purpose).

QQ-S-636 – Steel; Carbon (Low-Carbon) Sheets and Strips.

QQ-T-830 – Tube, Steel, Carbon, Mechanical, Round, Seamless and Welded.

TT-P-G64 –Primer, Coating, Synthetic, Rust - Inhibiting, Lacquer-Resisting.

PPP-B-636 – Boxes, Fiber.

MILITARY

JAN-P-100 – Packaging and Packing for Overseas Shipment, General Specification.

MIL-P-116 – Preservation, Methods of.

MIL-G132 – Crate, Wood, Open; Maximum Capacity 2,500 Pounds.

MIL-T-3345 – Trailers, Semitrailers, and Trailer Dollies, Packaging of.

MIL-P-8585 – Primer Coating, Zinc Chromate, Low-Moisture-Sensitivity.

FSC 1730

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T05:44Z
Check the source to verify that this is the current version before use.

MIL-A-25175 – Air Transport, Non-tactical, Packing For.

MIL-D-70327 – Drawings, Engineering and Associated Lists.

STANDARDS

FEDERAL

695 – Colors.

MILITARY

MIL-STD-129 – Marking f o r Shipment and Storage.

MIL-STD-130 – Identification Marking of U. S. Military Property.

DRAWING

AIR FORCE

47R16420 – Maintenance Platform – Aircraft, Adjustable, 3 to 10 Ft, be B-L

PUBLICATIONS

AIR FORCE-NAVY AERONAUTICAL BULLETIN

143 – Specifications and Standards; Use of.

AIR FORCE BULLETIN

F49 – Codes for Ground Equipment in Finishing Schemes.

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the cent ratting officer.)

2.2 Other publication The following documents form a part of this specification. Unless otherwise indicated, the issues in effect on date of invitation for bids shall apply.

CONSOLIDATED CLASSIFICATION COMMITTEE

Uniform Freight Classification Rules.

(Application for cop ies of these freight class ification rules should be addressed to the Consolidated Classification Committee, 202 Chicago Union Station, Chicago 6, Illinois.)

3. REQUIREMENTS

3.1 Assembly drawing. The requirements of Drawing 47R1 6420 apply as requirements of this specification with the exceptions and additions specified herein. Whn the drawing and this specification conflict, this specification shall govern.

3.1.1 Exceptions to the requirements of Drawing 47R1 6420.

3.1.1.1 commercial materials. Commercial materials of equivalent type are acceptable in lieu of materials conforming to QQ-S-633 and QQ_S-636.

3.1.1.2 Steel tubing Where tubing conforming to QQ-S-643 is specified, seamless, electric resistance welded, or fusion welded tubing conforming to QQ-T-830 shall be used,

3.1.1.3 Finish The maintenance platform shall be finished as specified on the drawing, except that the color shall be gloss yellow, color No. 13538 of Standard 895. Lettering and other marking applied to the equipment shall be gloss black, color No. 17038 of Standard 595.

3.1.1.3.1 Primer. Primer conforming to TT-P-664 may be applied cold in lieu of hot linseed oil or rust-preventive compound conforming to Bulletin F49.

3.2 Selection of specifications and standards. Specifications and standards for necessary commodities and services not specified herein shall be selected in accordance with Bulletin 143 except as specified in %2.1 and 3.2.2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T05:44Z
Check the source to verify that this is the current version before use.

3.2.1 Commercial parts. Commercial parts having suitable properties may be used where. on the date of invitation for bids. there are no suitable standard parts. In any case, commercial utility parts such as screws, bolts, nuts, and cotter pins having suitable properties may be used provided:

(a) They can be replaced by the standard parts (MS or AN) without alteration.

(b) The corresponding standard part numbers are referenced in the parts list and, if practical, on the contractor's drawings.

3.2.2 Standard parts. With the exception specified in 3.2.1, MS and AN standard parts shall be used where they suit the purpose. They shall be identified on the drawings by their part numbers.

3.3 Performance.

3.3.1 Lifting capacity. The maintenance platform shall be capable of lifting a static load of 1,500 pounds placed at or near the center of the platform, from its retractable height of 3 feet ±6 inches to an extended height of at least 10 feet, The maintenance platform shall be capable of raising and lowering this load through its complete range of travel.

3.3.2 Weight-holding capacity. The maintenance platform shall be capable of holding a minimum load of 1,500 pounds at any intermediate level between 3 and 10 feet for 1 hour without settling of the piston more than 0.02 inch per hour.

3.3.3 Step capacity. Each step of the maintenance platform shall be capable of supporting a minimum load of 400 pounds at or near the center of the step. The deflect-ion caused by the load shall not exceed ¼ inch at the point of maximum deflection. There shall be no permanent deflection or deformation of the step when the load is removed.

3.4 Interchangeability. All parts having the same manufacturer's part number shall be functionally and dimensionally interchangeable. Where changes are required in the contractor's drawings, such changes shall be governed by the applicable portions of MIL-D-70327.

3.5 Identification of product. Equipment, assemblies, and parts shall be marked for identification in accordance with MIHTD-130.

3.6 Workmanship. The maintenance platform, including all parts and accessories, shall be fabricated and finished in a workmanlike manner. Particular attention shall be given to:

(a) Freedom from blemishes. defects, burrs, and sharp edges.

(b) Accuracy of dimensions, radii of fillets, and marking of parts and assemblies.

(c) Thoroughness of welding, brazing, painting, and riveting, and

(d) Alignment of parts and tightness of assembly screws and bolts, et cetera.

3.6.1 Riveting. Riveting operations shall be carefully performed to insure tightness and satisfactory heading of rivets. Surfaces to be riveted shall be painted with primer zinc-chromate conforming to MIL-P-8585 prior to assembly. Rivet heads when not countersunk or flattened shall be of buttonhead shape and of uniform size for the same diameter of rivet.

3.6.2 Cleaning. The maintenance platform shall be thoroughly cleaned and loose, spattered, or excess weld; metal chips; and other foreign material removed during and after final assembly.

4. QUALITY ASSURANCE PROVISIONS

Source: https://assist.dla.mil -- Downloaded: 202610-17T05:44Z
Check the source to verify that this is the current version before use.

4.1 Unless otherwise specified herein, the supplier is responsible for the performance of all inspection requirements prior to submission for Government inspection and acceptance. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. Inspection records of the examinations and tests shall be kept complete and available to the Government as specified in the contract or order.

4.2 Classification of tests. The inspection and testing of the maintenance platform shall be classified as acceptance tests.

4.3 Acceptance tests. The acceptance tests shall consist of the following tests:

(a) Individual test.

(b) Sampling plan and tests.

4.3.1 *Individual test.* Each maintenance platform shall be subjected to the test specified in 4.4.1.

4.3.2 Sa mpling plan and tests. Maintenance platforms shall be subjected to the following tests until 10 maintenance platforms in succession have been accepted. Thereafter, one maintenance platform selected at random from each thirty produced shall be assembled, loaded, and inspected until a maintenance platform is rejected, at which time the inspection sequence shall be repeated.

(a) Platform static load test (see 4.4.2).

(b) Load holding test (see 4.4.3).

(c) Step weight test (see 4.4.4).

4.3,2.1 Rejection and retest. When one maintenance platform selected from a production run fails to meet the specification, maintenance platforms still on hand or later produced shall not be accepted until the extent and cause of failure are determined.

4.3.2.2 Individual tests may continue. For operational reasons, individual tests may be continued pending the investigation of a sampling test failure. Final acceptance of maintenance platforms on hand or produced later shall not be made until it is determined that the maintenance platforms meet all the requirements of the specification

4.2.3 Defects in maintenance platforms already accepted. The investigation of a test failure could indicate that defects may exist in maintenance platforms already accepted. If so, the contractor shall fully advise the procuring activity of all defects likely to he found and methods of correcting them.

4.4 Ted methods.

4.4.1 Examination of product. The maintenance platform shall be inspected to determine compliance with the requirements specified herein and on the drawings with respect to materials, workmanship. dimensions, finishes. and markings. The maintenance platform shall be inspected for operation of controls and locking devices.

4.4.2 Plat form static load test. The maintenance platform shall be completely assembled and loaded with a static load of 1,500 pounds at or near the center of the platform. The maintenance platform shall then be operated through its entire range twice. The load shall then be removed and the maintenance platform operated through its entire range twice. There shall be no leakage of hydraulic fluid, elongation of boltholes, or failures of welding, material, or workmanship as a result of this test.

4.4.3 Load holding test. With the load applied as specified in 4.4.2, the maintenance platform shall be left at the 7-foot level for 1 hour without the locking device in use. The rate of settling of the piston shall not exceed 0.02 inch per hour.

Source: https://assist.dla.mil -- Downloaded: 202610-17T05:44Z
Check the source to verify that this is the current version before use.

4.4.4 Step weight test. Each step of the maintenance platform shall be individually tested with a static load of 400 pounds at or near the center of the step. The deflection of each step under load shall not exceed ¼ inch, and there shall be no permanent deflection when the load is removed.

4.5 Inspection of the preservation, packaging, and packing. The inspection of the preservation, packaging, and packing shall be in accordance with the instructions in section 5, or the specifications referenced therein.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging.

5.1.1 Level A. The maintenance platform shall be cleaned, dried and preserved in accordance with MIL-P-116. Bare corrosive surfaces shall be preserved method I. Surfaces adequately protected by painting, plating or physical properties shall be protected by method III. The hydraulic system shall be preserved in accordance with the section of MIL-P-3345 applicable to hydraulic systems,

5.1.1.1 The handrails and other maintenance platform parts shall be disassembled as practical without the use of special tools. Small parts shall be packaged in a container conforming to class 2 of PPP-B-636.

5.1.2 Level C. The maintenance platform shall be preserved and packaged to minimum required to insure against deterioration or damage during transit to the initial point of delivery.

5.2 Packing.

5.2.1 Level A. The maintenance platform, including all loose and boxed parts, shall be secured within a crate conforming to MIL-C-132, style B. The maintenance platform shall be packed in such a manner as to maintain a minimum gross weight and cube.

5.2.2 Level B. Same as level A.

52.3 Level C. Maintenance platforms shall be packed the minimum required by carrier rules and regulations to insure safe delivery to the initial receiving activity. Containers shall comply with Uniform Freight Classification Rules or other common carrier regulations applicable to the mode of transportation.

5.2.4 Air sh ipments. Maintenance platforms shall be prepared for air shipment in accordance with MIL-A-25 175.

5.3 Physical protection. All cushioning, blocking, bracing and bolting shall be in accordance with JAN-P-100. The drop tests of JAN-P-100 shall be waived when packaging and packing of the item is for immediate use or when the drop test of MIL-P-116 as applicable.

5.4 Marking. All marking shall be in accordance with MIL-STD-129. The shipment marking nomenclature shall be as follows:

Maintenance Platform, Aircraft, Adjustable, 3 to 10 Feet, Type B-1.

6. NOTES

6.1 Intended use. The Type B-1 maintenance platform covered by this specification is intended to facilitate maintenance and inspection of heavy aircraft.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.

(b) Selection of applicable levels of preservation and packaging, and packing (see section 5).

Source: https://assist.dla.mil -- Downloaded: 202640-17T05:44Z
Check the source to verify that this is the current version before use.

Notice. When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data, Is not to be regarded by implication or otherwIse as in any manner licensing the holder or any other person or corporation, or sell any patented invention that may in any way be related thereto.

Custodians:
Army—Transportation Corps
Navy—Bureau of Aeronautics
Air Force

Prt'paring activity:
Air Force

Source: https://assist.dla.mil -- Downloaded: 2026l0-17T05:44Z
Check the source to verify that this is the current version before use.