MILITARY SPECIFICATION SHEET

RELAYS, ELECTRICAL, HERMETICALLY SEALED, SPDT AND DPDT, LOW LEVEL AND 1.0 AMPERE (VOLTAGE SENSITIVE - 100 MILLIWATT)

Specification MIL-R-5757/19F dated 30 December 1975, is hereby canceled and superseded by MIL-R-39016/34, Relays, Electromagnetic, Established Reliability, DPDT, Low Level to 1.0 Ampere, (0.100 - inch Terminal Spacing), part numbers as shown in table I.

Supersession data: See table I.

TABLE I. Supersession data.

Superseded part number M5757/19-	New part number 1/ M39016/34-
001	007
002	No replacement
003	012
004	007
005	No replacement
006	012
007	007
008	No replacement
009	008
010	007
011	No replacement
012	008
013-036	No replacement

1/ Complete part number shall contain suffix letter L, M, P, or R to designate failure rate level (see MIL-R-39016/34). A part with any failure rate supersedes the applicable MIL-R-5757 part. The lowest (best) failure rate available is preferred.

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

Preparing activity:
Navy - EC

Agent:
DLA - ES

☆U.S. GOVERNMENT PRINTING OFFICE: 1977—703-122/6554

FSC 5945

Source: https://assist.dla.mil -- Downloaded: 202610-17T05:40Z
Check the source to verify that this is the current version before use.