MILITARY SPECIFICATION SHEET

RELAYS, ELECTRICAL, HERMETICALLY SEALED, DPDT,

LOW-LEVEL TO 2 AMPERE (LATCHING)

Specification MIL-R-5757/21E, dated 8 March 1971, is hereby canceled, and is superseded by MIL-R-39016/32. Future procurement of Relays, Electrical, Hermetically Sealed, DPDT, Low Level to 2 Ampere (Latching) should be made under Military Specification MIL-R-39016/32 Relays, Electromagnetic, Established Reliability, DPDT, Low Level to 2 Amperes (Latching).

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

Supersession data: See table I.

TABLE I. Supersession data

Superseding part no. M39016/32 1/	Superseded part no. M5757/21	Superseded type designation
-001 No replacement	-001 -002	RY4VV4B3L01 RY4VV4B3W01
-002 -019	-003 -004	RY4WW4B3L01 RY4WW4B3W01
-003 -004	-005 -006	RY4XX4B3L01 RY4XX4B3P01
-001 No replacement	-007 -008	RY4VV4B3L02 RY4VV4B3W02
-002 -019	-009 -010	RY4WW4B3L02 RY4WW4B3W02
-003 -004	-011 -012	RY4XX4B3L02 RY4XX4B3P02

1/ Complete part number shall contain suffix letter L,M, P or R to designate failure level rate (see note 2 of table I). A part with any failure rate supersedes the applicable MIL-R-5757 part. The lowest (best) failure rate available is preferred.

Preparing activity:
Navy - EC

Agent:
DSA - ES

☆U.S. GOVERNMENT PRINTING OFFICE: 1976-603-766/3897

FSC 5945

Source: https://assist.dla.mil -- Downloaded: 202640-17T05:40Z
Check the source to verify that this is the current version before use.