MILITARY SPECIFICATION SHEET

RELAYS, ELECTRICAL, HERMETICALLY SEALED, DPDT
LOW LEVEL TO 2 AMPERES

Specification MIL-R-5757/37C, dated 14 March 1974, is hereby canceled. Future procurement of Relays, Electrical, Hermetically Sealed, DPDT, Low Level to 2 Amperes, should be made under Military Specification Sheet MIL-R-39016/13, Relays, Electromagnetic, Established Reliability, DPDT, Low Level to 2 Amperes (0.150-Inch Terminal Spacing). The cross reference of superseded part numbers is shown in table I.

TABLE I. Supersession data.

Superseded part number M5757/37-		New part number M39016/13- 1/
001	010	055
002	011	056
003	012	057
004	013	089
005	014	090
006	015	091
007	016	074
008	017	076
009	018	078
019	028	099
020	029	107
021	030	115
022	031	058
023	032	059
024	033	060
025	034	061
026	035	062
027	036	063
037	046	070
038	047	071
039	048	072
040	049	064
041	050	065
042	051	066
043	052	067
044	053	068
045	054	069

1/ Complete part number shall contain suffix letter L, M, P, or R to designate failure rate level. A part with any failure rate supersedes the applicable MIL-R-5757 part. The lowest (best) failure rate available is preferred.

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

Preparing activity:
Navy - EC

Agent:
DLA - ES

FSC 5945

☆U.S. GOVERNMENT PRINTING OFFICE: 1981 — 703-023/1497

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T05:41Z
Check the source to verify that this is the current version before use.