MIL-R-5757/38E
Notice-2
10 February 1976
SUPERSEDING
Notice-1
1 October 1975

MILITARY SPECIFICATION SHEET

RELAYS, ELECTRICAL, HERMETICALLY SEALED, SPDT, LOW LEVEL TO 1 AMPERE

Specification MIL-R-5757/38E, dated 14 March 1974, is hereby canceled and superseded by MIL-R-39016/7, Relays, Electromagnetic, Established Reliability, SPDT, Low Level to 1 Ampere, part number as shown in table I.

Supersession data: See table I.

TABLE I. Supersession data.

Superseded part no. M5757/38-	New part no. M39016/7- 1/
001	009
002	007
003	003
004	005
005	011
006	010
007	008
008	004
009	006
010	012
011	001
012	002

1/ Complete part number shall contain suffix letter L, M, P or R to designate failure level rate (see MIL-R-39016/7). A part with any failure rate supersedes the applicable MIL-R-5757 part. The lowest (best) failure rate available is preferred.

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

Preparing activity:
Navy - EC

Agent:
DSA - ES

FSC 5945

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T05:41Z
Check the source to verify that this is the current version before use.