MILITARY SPECIFICATION SHEET

RELAYS, ELECTRICAL, HERMETICALLY SEALED, DPDT, LOW LEVEL TO 1.0 AMPERE

Specification MIL-R-5757/40F, dated 14 March 1974, is hereby canceled and superseded by MIL-R-39016/9, Relays, Electromagnetic, Established Reliability, DPDT, Low Level to 1.0 Ampere, part number as shown in table I.

Supersession data: See table I.

TABLE I. Supersession data.

Superseded part no. MS757/40-	New part no. M39016/9- 1/
001	002
002	003
003	004
004	005
005	006
006	008
007	009
008	010
009	011
010	012
011	026
012	027
013	028
014	029
015	030
016	032
017	033
018	034
019	035
020	036
021	014
022	015
023	016
024	017
025	018
026	020
027	021
028	022
029	023
030	024
031	038
032	039
033	040
034	041
035	042
036	044
037	045
038	046
039	047
040	048
041	001
042	025
043	007
044	031
045	013
046	037
047	019
048	043

1/ Complete part number shall contain suffix letter L, M, P or R to designate failure level rate (see MIL-R-39016/9). A part with any failure rate supersedes the applicable MIL-R-5757 part. The lowest (best) failure rate available is preferred.

FSC 5945

Source: https://assist.dla.mil -- Downloaded: 202610-17T05:41Z
Check the source to verify that this is the current version before use.

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

Preparing activity:
Navy - EC

Agent:
DSA - ES

Source: https://assist.dla.mil -- Downloaded: 202610-17T05:41Z
Check the source to verify that this is the current version before use.