MILITARY SPECIFICATION SHEET

RELAYS, ELECTRICAL, HERMETICALLY SEALED, DPDT, LOW-LEVEL TO 1.0 AMPERE (SENSITIVE, 60 MILLIWATTS)

Specifications MIL-R-5757/70C, dated 29 March 1974, is hereby canceled and superseded by MIL-R-39016/11, Relays, Electromagnetic, Established Reliability, DPDT, Low Level to 1.0 Ampere (Sensitive, 60 Milliwatts), part number as shown in table I.

Supersession data: See table I.

TABLE I Supersession data.

Superseded part no. MS7S7/70-	New part no. M39016/11- 1/
001	003
002	005
003	007
004	009
005	011
006	004
007	006
008	008
009	010
110	012
011	001
012	002
013	013
014	014
015	015
016	016

1/ Complete part number shall contain suffix letter L, M, P or R to designate failure level rate (see MIL-R-39016/11). A part with any failure rate supersedes the applicable MIL-R-5757 part. The lowest (best) failure rate available is preferred.

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

Preparing activity:
Navy - EC

Agent:
DSA - ES

FSC 5945

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T05:42Z
Check the source to verify that this is the current version before use.