MILITARY SPECIFICATION SHEET

RELAYS, ELECTRICAL, HERMETICALLY SEALED, DPDT, LOW-LEVEL TO 1.0 AMPERE (LATCHING)

Specification MIL-R-5757/71C, dated 29 March 1974, is hereby canceled and superseded by MIL-R-39016/12, Relays, Electromagnetic, Established Reliability, DPDT, Low Level to 1.0 Ampere (Latching), part number as shown in table I.

Supersession data: See table I.

TABLE I. Supersession data.

Superseded part no. M5757/71-	New part no. M39016/12- 1/
001	002
002	003
003	004
004	005
005	006
006	008
007	009
008	010
009	011
010	012
011	001
012	007
013	013
014	014
015	015
016	016
017	017
018	018
019	019
020	020
021	021
022	022
023	023
024	024

1/ Complete part number shall contain suffix letter L, M, P or R to designate failure level rate (see MIL-R-39016/12). A part with any failure rate supersedes the applicable MIL-R-5757 part. The lowest (best) failure rate available is preferred.

FSC 5945

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T05:42Z
Check the source to verify that this is the current version before use.

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

Preparing activity:
Navy - EC

Agent:
DSA - ES

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T05:42Z
Check the source to verify that this is the current version before use.