MILITARY SPECIFICATION SHEET

RELAYS, ELECTRICAL, HERMETICALLY SEALED, DPDT LOW LEVEL TO 2 AMPERES (LATCHING)

Specification MIL-R-5757/76C, dated 27 January 1981, is hereby canceled. Future procurement of Relays, Electrical, Hermetically Sealed, DPDT, Low Level to 2 Amperes Latching should be made under Military Specification Sheet MIL-R-39016/45 Relays, Electromagnetic, Established Reliability, DPDT, Low Level to 2 Amperes (Latching). The cross reference of superseded part numbers is shown in table I.

TABLE I. Supersession data.

Superseded part number M5757/76-	New part number M39016/45-1/
001	008
002	014
003	020
004	026
013	009
014	015
015	021
016	027
017	011
018	017
019	023
020	029

1/ Complete part number shall contain suffix letter L, M, P, or R to designate failure rate level. A part with any failure rate supersedes the applicable MIL-R-5757 part. The lowest (best) failure rate available is preferred.

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

Agent:
DLA - ES

Preparing activity:
Navy - EC

☆U.S. GOVERNMENT PRINTING OFFICE: 1982 — 505-022/4652

FSC 5945

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T05:42Z
Check the source to verify that this is the current version before use.