MILITARY SPECIFICATION
CARTRIDGE, DUMMY, 152MM, XM596

1. SCOPE

1.1 This specification covers Dummy Cartridge, 152MM, XM596.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

Military

MIL-A-2550	- Ammunition and Special Weapons, General Specification for

STANDARDS

Military

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-109	- Quality Assurance Terms and Definitions
MIL-STD-1169	- Packaging, Packing and Marking for Shipment of Inert Ammunition Components
MIL-STD-1235	- Single and Multilevel Continuous Sampling Procedures and Tables for Inspection by Attributes

DRAWINGS

Munitions Command

F8430306	- Cartridge, Dummy, 152MM, XM596
C8880418	- Box, Packing, Ammunition for Cartridge, 152MM, TP-T, XM411E2
F8880419	- Container, Ammunition, Fiber M516 for Cartridge, 152MM TP-T, XM411E2
IEL-8430306	- Inspection Equipment List for Cartridge, Dummy, 152MM XM596

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:59Z
Check the source to verify that this is the current version before use.

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other Publications.- The following document forms a part of the specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

ASA-B46.1 - Surface Texture, Surface Roughness, Waviness and Lay

Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal Agencies.

3. REQUIREMENTS

3.1 General.- Materials shall comply with the requirements shown on the applicable component drawing, referenced specifications and the following:

3.2 Protective coating.- Protective coating shall be in accordance with the applicable drawing and specifications referenced therein.

3.3 Burr.- No burrs are permitted which may be injurious to personnel handling the item.

3.3.1 Metal defects.- The external surfaces and the rear handle (crossbar) area shall be free of cracks, cold shuts, tears or evidence of porosity. Unsound metal or pipe is permitted at the bottom center of the rear cavity provided that weight and other requirements of the applicable drawing are met.

3.3.3 Foreign matter.- The cartridge shall be free of chips, dirt, grease, products of corrosion, or other foreign matter.

3.4 Abrasion resistance and color.- The abrasion resistance and color requirement of specification MIL-C-60536 shall not apply. The color (Blue, No. 35109 of Federal Standard 595) shall be within limits established by treated pieces agreed upon between the supplier and the procuring activity.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:59Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.- Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Quality Assurance terms and definitions.- Reference is made to MIL-STD-109 to define Quality Assurance terms used.

4.1.2 Inspection.- Inspection shall be in accordance with MIL-A-2550, except as specified herein.

4.2 First article sample.

4.2.1 Initial production sample.- At the beginning of regular production, a sample shall be submitted in accordance with contract requirements and shall consist of five cartridges. The sample shall be manufactured in the same manner using the same materials, equipment, processes and procedures as will be used in regular production. All parts and packing shall be the same as used for regular production and shall be obtained from the same source of supply.

4.2.1.1 Examination and test.- After inspection and provisional acceptance at source, the sample shall be inspected for all the requirements of the drawing and specifications at a Government laboratory or such other facility specified in the contract.

4.2.1.2 Initial production sample failure.- Failure of the sample to comply with the requirements of the drawings and specifications shall result in sample disapproval.

4.3 Inspection provisions.

4.3.1 Lot.

4.3.1.1 Submission of product.- The product shall be submitted in accordance with MIL-STD-105 or MIL-STD-1235, as applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:59Z
Check the source to verify that this is the current version before use.

4.3.2 Examination.- Examination for major and minor defects shall be performed on a defect basis in accordance with the classification of defects contained herein, using the sampling plans contained in MIL-STD-105. Continuous sampling plans in accordance with MIL-STD-1235 may be used if approved by the procuring activity. An AQL of 0.65 percent for each major defect and an AQL of 1.0 percent for each minor defect shall be used. All nonconforming material shall be rejected. The roughness comparison specimens prescribed by ASA-B46.1 shall be used as a basis for roughness determination.

4.3.2.1 Cartridge, Dummy, 152MM, XM596, Drawing F8430306

Defect	Method of Inspection
CRITICAL	
None defined	
MAJOR	
101. Concentricity of large outside diameter with bourrelet diameters	Gage
102. Concentricity of simulated rotating band diameter with the bourrelets	Gage
103. Concentricity of taper forward of the large outside diameter with the bourrelets	Gage
104. Concentricity of firing pin hole with bourrelets	Gage
105. Diameter of bourrelet to rear of ogive	Gage
106. Diameter of bourrelet forward of simulated rotating band	Gage
107. Diameter of simulated rotating band	Gage
108. Diameter of large outside diameter	Gage
109. Length from shoulder to datum diameter forward of large outside diameter	Gage
110. Length from rear shoulder of simulated rotating band to shoulder rear of rear bourrelet	Gage
111. Length from shoulder rear of rear bourrelet to rear end	Gage
112. Angle of surface forward of large outside diameter	Gage
MINOR	
201. Weight	Approved Scale
202. Width of rear handle	Gage
203. Firing pin hole not functionally symmetrical with rear handle	Gage

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:59Z
Check the source to verify that this is the current version before use.

4.3.2.1 (Cont'd)

Defect	Method of Inspection
MINOR (Cont'd)	
204. Diameter of bourrelet to rear of simulated rotating band	Gage
205. Diameter rear of forward bourrelet	Gage
206. Length from front end of simulated rotating band to shoulder rear of rear bourrelet	Gage
207. Angle of ogive	Gage
208. Presence of angular surface on forward end of simulated rotating band	Visual (See 6.1)
209. Marking missing, incorrect or illegible	Visual
210. Surface finish improper	Visual (See 6.1)
211. Sharp edges and burrs	Visual/Tactile
212. Protective coating inadequate or damaged	Visual
213. Color, protective coating	Visual
214. Foreign matter	Visual

4.3.2.2 Unsealed Fiber Container, Drawing F8880419

CRITICAL

None defined

MAJOR

None

MINOR

201. Nose support missing	Visual
202. Support tube missing	Visual
203. Round cannot be removed by hand	Manual
204. Glue or asphalt on round	Visual
205. Cushion missing	Visual

4.3.2.3 Sealed Fiber Container, Drawing F8880419

CRITICAL

None defined

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:59Z
Check the source to verify that this is the current version before use.

4.3.2.3 (Cont'd)

Defect	Method of Inspection
MAJOR	
None defined	
MINOR	
201. Container damaged or cut through all impregnated layers	Visual
202. Sealing strip applied improperly	Visual
203. Metal end loose or distorted	Visual/Manual
204. Contents loose	Manual
205. Marking missing, incorrect or illegible	Visual

4.3.2.4 Sealed Wooden Packing Box, Drawing C8880418

CRITICAL	
None defined	
MAJOR	
None defined	
MINOR	
201. Hardware or strapping missing, broken or loose	Visual
202. Hardware or strapping improperly assembled or located	Visual
203. Box damaged, exposing contents	Visual
204. Car seal missing, unsealed or improperly positioned	Visual
205. Marking missing, incorrect or illegible	Visual

4.3.3 Inspection testing.- The following tests shall be performed in accordance with provisions of 4.4.

4.3.3.1 Cleaning and application of protective coating.

4.3.3.1.1 Salt spray test.- Two cartridges from each lot shall be subjected to a salt spray test to determine compliance with the applicable drawing and specification referenced thereon. Failure of any cartridge to comply shall be cause for rejection of the lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:59Z
Check the source to verify that this is the current version before use.

4.3.3.1.2 Coating thickness test.- Twenty cartridges from each lot shall be subjected to this test to determine compliance with the applicable drawing and specification referenced thereon. Failure to comply shall result in rejection of the lot.

4.4 Test methods and procedures.

4.4.1 Cleaning and application of protective coating.- Procedures for application and testing of protective coating shall be in accordance with the applicable drawing and specification with the exception that in the testing for coating thickness only the nondestructive test methods referenced in the applicable specification shall be used.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packing.

5.1.1 The cartridge shall be packaged in accordance with container Drawing F8880419.

5.2 Packing.

5.2.1 The containers shall be packed in accordance with Box Drawing F 8880419.

5.3 Marking.- Containers and Boxes shall be marked in accordance with MIL-STD-1169, Level "C", for Cartridge, Dummy, 152MM, XM596 for Gun XM81.

6. NOTES

6.1 Visual examination qualification.- When compliance with the applicable requirements is in doubt as a result of visual examination, this characteristic may be measured or gaged to determine acceptability.

CUSTODIAN:

Army - MU

PREPARING ACTIVITY:

Army - MU

Project No. 1320-A125

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:59Z
Check the source to verify that this is the current version before use.