INCH-POUND

MIL-C-70950 (AR)
AMENDMENT 1
24 June 1991

# MILITARY SPECIFICATION

## CASE, CARTRIDGE, 105MM, M148A1B1E1 (M148A2B1)

This amendment forms a part of Military Specification MIL-C-70950 (AR), dated 12 January 1990, and is approved for use by the U.S. Army Armament, Munitions and Chemical Command and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Title: Delete "M148A1B1E1" and substitute "M148A2B1".

1.1: Delete "M148A1B1E1" and substitute "M148A2B1".

PAGE 2

2.1.2: Delete "M148A1B1E1" and substitute "M148A2B1".

PAGE 5

4.4.1: Delete "M148A1B1E1" and substitute "M148A2B1".

PAGE 6

Table I Title: Delete: "M148A1B1E1" and substitute "M148A2B1".

PAGE 7

Table I Title: Delete: "M148A1B1E1" and substitute "M148A2B1".



DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:15Z
Check the source to verify that this is the current version before use.

4.5.2.1 Table II: Delete:

"Table II. Sampling

| Lot Size | Inspection Level | |
|---|---|---|
| | I Major Defects | II Minor Defects |
| 2 to 13 | * | * |
| 14 to 90 | * | 13 |
| 91 to 150 | 125 | 13 |
| 151 to 500 | 125 | 30 |
| 501 to 1200 | 125 | 35 |
| 1201 to 3200 | 125 | 43 |
| 3201 to 10000 | 125 | 50 |
| 10001 to 35000 | 296 | 61 |

Numbers under inspection levels indicate sample size.

* Indicates one hundred percent inspection.
If sample size exceeds lot size, perform one hundred percent inspection. Accept on zero and reject on one or more for both inspection levels."



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:15Z
Check the source to verify that this is the current version before use.

and substitute:

"Table II Sampling
Sampling Plan for Quality Conformance
(Accept on Zero Defects)

| Lot Size | Sample Size (Characteristic) | |
|---|---|---|
| | Major | Minor |
| 2 to 8 | * | * |
| 9 to 150 | 32 | 13 |
| 151 to 500 | 32 | 30 |
| 501 to 1200 | 74 | 35 |
| 1201 to 3200 | 74 | 43 |
| 3201 to 10000 | 87 | 50 |
| 10001 to 35000 | 109 | 61 |

* 100% inspection
** If sample size equals or exceeds lot or batch size, do 100% inspection."

Page 10

4.5.5.1: Delete 4.5.5.1 in its entirety and substitute included 4.5.5.1.

Page 11

4.5.5.2: Delete 4.5.5.2 in its entirety and substitute included 4.5.5.2.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:15Z
Check the source to verify that this is the current version before use.

Page 12

4.5.5.3 Next Higher Assembly: Delete "9323901" and substitute "11735736".

Characteristics 118 and 119, delete "protrusion" and substitute "boss".

PAGE 14

4.5.5.4: Delete 4.5.5.4 in its entirety and substitute included 4.5.5.4.

PAGE 15

Add new page 15a, paragraph 4.5.5.5 included.

Add new page 15b, paragraph 4.5.5.6 included.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:15Z
Check the source to verify that this is the current version before use.

## QUALITY CONFORMANCE INSPECTION

## CLASSIFICATION OF CHARACTERISTICS

MIL-C-70950 (AR)
AMENDMENT 1

| PARAGRAPH | TITLE | SHEET | DRAWING NUMBER |
|---|---|---|---|
| 4.5.5.1 | Cup | 1 OF 1 | 11735732 |
| | | | NEXT HIGHER ASSEMBLY 11735736 |

| CLASSIFICATION | EXAMINATION OR TEST | CONFORMANCE CRITERIA | REQUIREMENT PARAGRAPH | INSPECTION METHOD REFERENCE |
|---|---|---|---|---|
| Critical | None defined | | | |
| Major | | | | |
| 101 | Outside diameter | Table II | 3.1 | Gage |
| 102 | Inside diameter | Table II | 3.1 | Gage |
| 103 | Length, total | Table II | 3.1 | Gage |
| 104 | Thickness of lip | Table II | 3.1 | Gage |
| 105 | Taper on diameter | Table II | 3.1 | Gage |
| 106 | Hardness | 4.5.6.1 | 3.3 | 4.6.1.3 |
| 107 | Thickness | Table II | 3.1 | Gage |
| 108 | Protective coating missing or inadequate | Table II | 3.4 | Visual |
| 109 | Surface finish | Table II | 3.1 | Visual |
| 110 | True position of I.D. | Table II | 3.1 | Gage |
| 111 | Radius at corner | Table II | 3.1 | Gage |
| 112 | Coating thickness | 4.5.6.2.1 | 3.4 | Gage |
| 113 | Salt spray | 4.5.6.2.2 | 3.4 | 4.6.2.1 |
| Minor | | | | |
| 201 | Workmanship | Table II | 3.8 | Visual |

NOTES:





Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:15Z
Check the source to verify that this is the current version before use.

## QUALITY CONFORMANCE INSPECTION

## CLASSIFICATION OF CHARACTERISTICS

MIL-C-70950 (AR)
AMENDMENT 1

| PARAGRAPH | TITLE | SHEET | DRAWING NUMBER |
|---|---|---|---|
| 4.5.5.2 | Collar | 1 OF 1 | 11735733 |
| | | | NEXT HIGHER ASSEMBLY 11735736 |

| CLASSIFICATION | EXAMINATION OR TEST | CONFORMANCE CRITERIA | REQUIREMENT PARAGRAPH | INSPECTION METHOD REFERENCE |
|---|---|---|---|---|
| Critical | None defined | | | |
| Major | | | | |
| 101 | Small outside diameter (boss dia.) | Table II | 3.1 | Gage |
| 102 | Width of boss | Table II | 3.1 | Gage |
| 103 | Depth of boss groove | Table II | 3.1 | Gage |
| 104 | Large outside diameter (flange dia.) | Table II | 3.1 | Gage |
| 105 | Circumferential taper angle of boss | Table II | 3.1 | Gage |
| 106 | Circumferential taper depth of boss | Table II | 3.1 | Gage |
| 107 | True position of large outside diameter | Table II | 3.1 | Gage |
| 108 | Large radius of flange | Table II | 3.1 | Gage |
| 109 | Hardness | 4.5.6.1 | 3.3 | 4.6.1.2 |
| 110 | Protective coating missing or inadequate | Table II | 3.4 | Visual |
| 111 | Surface finish | Table II | 3.1 | Visual |
| 112 | Coating thickness | 4.5.6.2.1 | 3.4 | Gage |
| 113 | Salt spray | 4.5.6.2.2 | 3.4 | 4.6.2.1 |
| Minor | | | | |
| 201 | Small radius of flange | Table II | 3.1 | Gage |
| 202 | Workmanship | Table II | 3.8 | Visual |

NOTES:

(11) 6



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:15
Check the source to verify that this is the current version before use.

## CLASSIFICATION OF CHARACTERISTICS



| PARAGRAPH | TITLE | SHEET | DRAWING NUMBER |
|---|---|---|---|
| 4.5.5.4 | M148A2B1 Cartridge Case Assembly | 1 OF 2 | 11735736 |
| | | | NEXT HIGHER ASSEMBLY |

| CLASSIFICATION | EXAMINATION OR TEST | CONFORMANCE CRITERIA | REQUIREMENT PARAGRAPH | INSPECTION METHOD REFERENCE |
|---|---|---|---|---|
| Critical | None defined | | | |
| Major | | | | |
| 101 | Thickness of body material prior to wrapping | Table II | 3.1 | Gage |
| 102 | Total length | Table II | 3.1 | Gage |
| 103 | Distance from flange (base) to first basic diameter | Table II | 3.1 | Gage |
| 104 | Distance from flange (base) to second basic diameter | Table II | 3.1 | Gage |
| 105 | Distance from flange (base) to third basic diameter | Table II | 3.1 | Gage |
| 106 | Distance from flange (base) to fourth basic diameter | Table II | 3.1 | Gage |
| 107 | Inside diameter of mouth | Table II | 3.1 | Gage |
| 108 | True position of mouth I.D. | Table II | 3.1 | Gage |
| 109 | O. D. of mouth | Table II | 3.1 | Gage |
| 110 | Improper number of wraps at mouth | Table II | 3.1 | Visual |
| 111 | Protective coating missing or inadequate | Table II | 3.4 | Visual |
| 112 | Location of weld to edge of inner wrap | Table II | 3.1 | Gage |
| 113 | Location of weld to edge of outer wrap | Table II | 3.1 | Gage |
| 114 | Hardness of body blank | 4.5.6.1 | 3.3 | 4.6.1.4 |
| 115 | Assembly tightness | 100% | 3.5 | 4.6.5 |

NOTES:





Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:15Z
Check the source to verify that this is the current version before use.

# QUALITY CONFORMANCE INSPECTION

## CLASSIFICATION OF CHARACTERISTICS

| PARAGRAPH | TITLE | SHEET | DRAWING NUMBER |
|---|---|---|---|
| 4.5.5.4 | M148A2B1 Cartridge Case Assembly | 2 OF 2 | 11735736 |
| | | | NEXT HIGHER ASSEMBLY |

| CLASSIFICATION | EXAMINATION OR TEST | CONFORMANCE CRITERIA | REQUIREMENT PARAGRAPH | INSPECTION METHOD REFERENCE |
|---|---|---|---|---|
| Major | (cont'd) | | | |
| 116 | Metal defects | 100% | 3.8.1 | 4.6.3 |
| 117 | Salt spray (test panel) | 4.5.6.2.2 | 3.4 | 4.6.2 |
| 118 | Salt spray (assembly) | 4.5.6.2.2 | 3.4 | 4.6.2 |
| 119 | Distance from base O.D. to inner and outer plies | 4.5.6.3 | 3.1 | 4.6.6 |
| 120 | Profile and alignment | 100% | 3.6 | Gage |
| 121 | Ballistics | 4.5.6.4.2 | 3.7 | 4.6.7.2 |
| Minor | | | | |
| 201 | Stamping incorrect or illegible | Table II | 3.1 | Visual |
| 202 | 45° overlap of body wraps at mouth | Table II | 3.1 | Gage |
| 203 | Workmanship | Table II | 3.8 | Visual |

NOTES:



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:15Z
Check the source to verify that this is the current version before use.

8 (15)

## CLASSIFICATION OF CHARACTERISTICS



| PARAGRAPH | TITLE | SHEET | DRAWING NUMBER |
|---|---|---|---|
| 4.5.5.5 | Cartons, Ammo, for Interplant Shipment of Steel Cartridge Cases, Empty 37mm to 120mm Inclusive (before sealing) | 1 OF 1 | 7548235 |
| | | | NEXT HIGHER ASSEMBLY |

| CLASSIFICATION | EXAMINATION OR TEST | CONFORMANCE CRITERIA | REQUIREMENT PARAGRAPH | INSPECTION METHOD REFERENCE |
|---|---|---|---|---|
| Critical | None defined | | | |
| Major | None defined | | | |
| Minor | | | | |
| 201 | Improper assembly | Table II | 3.1 | Visual |
| 202 | Incorrect number of cartridge cases in carton | Table II | 3.1 | Visual |
| 203 | Separator missing or damaged | Table II | 3.1 | Visual |
| 204 | Workmanship | Table II | 3.8 | Visual |

NOTES:





Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:15Z
Check the source to verify that this is the current version before use.

## QUALITY CONFORMANCE INSPECTION
## CLASSIFICATION OF CHARACTERISTICS

| PARAGRAPH | TITLE | SHEET | DRAWING NUMBER |
|---|---|---|---|
| 4.5.5.6 | Cartons, Ammo, for Interplant Shipment of Steel Cartridge Cases, Empty 37mm to 120mm Inclusive (after sealing) | 1 OF 1 | 7548235 |
| | | | NEXT HIGHER ASSEMBLY |

| CLASSIFICATION | EXAMINATION OR TEST | CONFORMANCE CRITERIA | REQUIREMENT PARAGRAPH | INSPECTION METHOD REFERENCE |
|---|---|---|---|---|
| Critical | None defined | | | |
| Major | None defined | | | |
| Minor | | | | |
| 201 | Carton damaged, cut or gouged through all layers | Table II | 3.1 | Visual |
| 202 | Carton improperly sealed | Table II | 3.1 | Visual |
| 203 | Contents loose | Table II | 3.1 | Visual/Manual |
| 204 | Marking missing, incorrect or illegible | Table II | 3.1 | Visual |
| 205 | Workmanship | Table II | 3.8 | Visual |

NOTES:



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:15Z
Check the source to verify that this is the current version before use.

PAGE 16

4.5.6.2.2: Delete: "Five samples shall be randomly selected for testing." and substitute:

"Five samples of each cartridge case component, five 4" x 6" test panel samples with a minimum of one sample per coil, and five cartridge case assemblies shall be randomly selected for testing."

Custodian:
Army - AR

Preparing activity:
Army - AR

(Project 1315-AC86)



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:15Z
Check the source to verify that this is the current version before use.