MILITARY SPECIFICATION

DISC, SOLID, PLAIN AND DISC, SOLID, PLAIN, TRAINING

1. SCOPE

1.1 This specification covers special requirements, quality assurance provisions, and the preperation for delivery criteria for one type of plain solid disc and training plain solid disc used on M423 projectile loading assembly.

SPECIFICATIONS

MILITARY

MIL-P-116-Preservation, Methods of

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-1168 - Lot Numbering of Ammunition
MIL-STD-1169(MU) - Packaging, Packing and Marking for Shipments of Inert Ammunition Components

DRAWINGS

ORDANCE CORPS

8808362 - Packing and Marking for Storage and Shipments
8787112 - Disc, Solid, Plain
8787200 - Disc, Solid, Plain, Training
8883534 - Bag, Packing for Repair Part
EL - 8787112 - Equipment list
EL - 8787200 - Equipment list

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:40Z
Check the source to verify that this is the current version before use.

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Materials. The contractor shall furnish objective evidence (see 6.2) that the material complies with the specifications listed on the applicable drawing.

3.2 Assembly. The disc shall comply with all requirements specified on Drawing (dwg 8787112 or 8787200 as applicable), with all requirements specified herein, and with the requirements of all applicable specifications to the extent specified on the drawing and herein.

3,3 Serialization. The contractor shall assign serial numbers as required by drawings. The contractor may select any number which complies with the drawing requirement, These numbers shall not be duplicated.

3.4 Workmanship.

3.4.1 Plastic and metal characteristics. All components shall be free from cracks, splits, cold flow, shrinkage, cold shuts, inclusions, porosity, or any similar characteristic.

3.4.2 Burrs. Parts shall be free from burrs.

3.4.3 Foreign matter. Parts shall be free from chips, dirt, grease, rust, corrosion, or any embedded foreign material.

3.4.4 Cleaning. The cleaning method shall not be injurious to any of the parts, nor shall the parts be contaminated by the cleaning agent.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspections Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to Prescribed requirements.

4.2 First article inspection. "Not Applicable".

4.3 Product acceptance inspection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:40Z
Check the source to verify that this is the current version before use.

4.3.1 Lot formation. A lot shall consist of parts and. assemblies produced by one manufacturer in one unchanged process, in accordance with the same drawing, same drawing revision, same specification and same specification revision. Drawing, specification and process changes not affecting safety, performance, storage, or interchangeability, as determined by the Government, shall not necessitate changing the lot interfix number. The criteria and procedures for the assignment of lot numbers shall be in accordance with MIL-STD-1168.

4.3.1.1 Inspection lot. An inspection lot shall be the quanitity of parts, subassemblies, or assemblies from the same lot, which are submitted to inspection for Government acceptance.

4.3.2 Product inspection examination. Critical characteristics shall require 100 percent inspection of all items in the inspection lot. A sample shall be selected at random from each inspection lot in accordance with the applicable classification. Any characteristic in the sample found to be defective shall reject the inspection lot. Sequence for the inspection of characteristics in each classification need not be followed as long as all characteristic inspections are performed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:40Z
Check the source to verify that this is the current version before use.

Table I
Major Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-16	all	28-29	23	52-56	31	132-156	39
17	16	30-31	24	57-62	32	157-191	40
18	17	32-34	25	63-69	33	192-244	41
19-20	18	35-36	26	70-76	34	245-334	42
21	19	37-40	27	77-86	35	335-519	43
22-23	20	41-43	28	87-97	36	520-1120	44
24-25	21	44-47	29	98-112	37	over 1120	45
26-27	22	48-51	30	113-131	38		

Table II
Minor Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-9	all	14-16	12	28-33	16	77-121	20
10	9	17-18	13	34-41	17	122-273	21
11	10	19-22	14	42-54	18	over 273	22
12-13	11	23-27	15	55-76	19		

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:40Z
Check the source to verify that this is the current version before use.

4.3.2.1 Classification of characteristics. Critical, major and minor characteristics are defined in MIL-STD-105. Inspection shall be conducted as follows:

4.3.2.1.1 Disc, solid, plain (see dwg. 8787112) and disc, solid, plain, training (see dwg 8787200).

Categories	Characteristics	Method of Inspection
Critical:	None defined	
Major:		
101.	Parallelism of left face (see dwg. 8787112)	Gage
102.	Chamfer present (see dwg. 8787112)	Visual
103.	Diameter	Gage
104.	Thickness	Gage
105.	Material (see 3.1)	Visual
106.	Objective evidence (see 6.2) for protective finish In accordance with dwg. 8787112	Visual
Minor :		
201.	Surface finish	Visual
202.	Stamping	Visual
203.	Serialization (see S. S)	Visual
204.	Workmanship (see 3. 4)	Visual\Manual

4.3.2.1.2 Preparation for delivery (see 5,1).

Categories	Characteristics	Method of Inspection
Critical:	None defined	
Major:		
101.	Preservation, packaging, packing and marking in accordance with MIL-STD-1169 (MU)	Visual/Manual
Minor:		
201.	Workmanship (see 3.4).	Visual\Manual

4.3.2.1.3 Bag, packing for repair parts (see dwg. 8883534 covering part number 883534-4 and 5.2)

Categories	Characteristics	Method of Inspection
Critical:	None defined	
Major:		
101.	Material (see 3.1)	Visual
102.	Length before packing, min	*Measure
103.	Width before packing, min.	*Measure

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:40Z
Check the source to verify that this is the current version before use.

Categories	Characteristics	Method of Inspection
Major: (con't)		
104.	Proper heat seal	Visual/Manual
105.	Objective evidence (see 6.2) for heat seal test in accordance with MIL-P-116	Visual
106.	Properly packed	Visual/Manual
107.	No tear, split, crack or hole in bag	Visual
*Measure with suitable scale.		
Minor:		
201.	Marking	Visual
202.	Workmanship (see 3.4)	Visual/Manual

4.3.2.1.4 Packing and marking for storage and shipments (see dwg. 8808362-and 5.2).

Categories	Characteristics	Method of Inspection
Critical:	None defined	
Major:		
101.	Gross load weight, max	*Measure
102.	Contents tight in package	Manual
103.	Correctly packed	Visual/Manual
104.	Packaging material (see 3.1)	Visual
*Determine weight with suitable scale		
Minor:		
201.	Marking	Visual
202.	Workmanship	Visual/Manual

4.3.3 Testing. Not Applicable

4.3.4 Acceptance inspection equipment.

4.3.4.1 Critical and major characteristics and tests, Inspection and testing shall be performed with the acceptance inspectin equipment, operating instructions, and calibration instructions specified on the Equipment Lists (EL) (See EL-8787112 or 8787200). When either of the conditions listed below exist, the contractor shall design required equipment or specify suitable commercial equipment. The contractor shall obtain approval of such designs, operating instructions, and special calibration instructions as specified in 6.3 prior to use on the contract.

a. Any deviation from equipment or procedures specified on the EL is desired.
b. The code "CD" is listed in the "Part or Identifying Number" column on the EL.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:40Z
Check the source to verify that this is the current version before use.

4.3.4.2 Minor characteristics and tests. Acceptance inspection equipment for minor characteristics is not specified on ELs. The acceptance inspection equipment, operating instructions and calibration instructions used by the contractor for minor classification inspection shall be approved by the procuring agency.

4.4 Test Methods. Not Applicable

5. PREPARATION FOR DELIVERY

5.1 Production items.

5.1.1 Preservation and packaging. Preservation and packaging shall be level A or C as specified (see 6.1).

5.1.1.1 Level A. The disc shall be preserved and packaged in accordance with instructions contained in MIL-STD-1169(MU).

5.1.1.2 Level C. The disc shall be preserved and packaged in accordance with instructions contained in MIL-STD-1169(MU).

5.1.2 Packing.

5.1.2.1 Levels A and C. The disc shall be packed in accordance with the applicable instructions contained in MIL-STD-1169(MU).

5.1.3 Marking. Marking shall be in accordance with MIL-STD-1169 (MU).

5.2 Repair parts.

5.2.1 Preservation and packaging. Preservation and packaging shall be level A or C as specified (see 6.1).

5.2.1.1 Level A. The disc shall be packaged in accordance with dwgs. 8883534 and 8808362 using the specified moisture barrier.

5.2.1,2 Level C. The disc shall be packaged in accordance with dwg 8808362 except that the moisture barrier may be omitted.

5.2.2 Packing.

5.2.2.1 Level A and C. The disc hall be packed in accordance with dwgs 8883534 and 8808362

5.2.3 Marking. Marking shall be as specified in accordance with dwgs 8883534 and 8808362.

6. NOTES

6.1 Ordering data. Procurement documents should specify the following:

a. Title, number, and date of this specification.
b. Production or Repair Part,
c. Selection of applicable level of packaging and packing required (see 5.1 and 5.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:40Z
Check the source to verify that this is the current version before use.

6.2 Objective evidence. Records of contractor quality control and inspections which can be verified.

6.3 Acceptance inspection equipment. The contractor shall obtain approval of equipment designs, operating instructions , and calibration instructions from the Commanding Officer, Picatinny Arsenal, Dover, New Jersey 07801, ATTN: SMUPA-NR4.

6.4 Supersession data. This specification includes the requirements of Purchase Description PA-PD-1131 (Rev 2) dated 1 February 1961.

Custodian:
Army - MU

Preparing activity:
Army - MU

Project No. 1110-A018

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:40Z
Check the source to verify that this is the current version before use.