INCH-POUND

MIL-S-48686 (AR
AMENDMENT 1
16 February 1990

MILITARY SPECIFICATION

SAFETY AND ARMING DEVICE, GUIDED MISSILE: M143E1
MECHANICAL PARTS AND ASSEMBLY FOR

This Amendment forms a part of Military Specification MIL-S-48686 (AR), dated 4 February 1987, and is approved for use within the US Army Armament, Munitions and Chemical Command and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

2.1.1, under FEDERAL, Add: "A-A-113 - Tape, Pressure Sensitive Adhesive."

2.2, under AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM):

Add the following:

"ASTM 209 - Standard Specification for Aluminum-Alloy Sheet and Plate

ASTM 211 - Standard Specification for Aluminum-Alloy Bars, Rod and Wires

ASTM 221 - Standard Specification for Aluminum-Alloy, Extruded Bars, Rods, Wire, Shapes and Tubes"

PAGE 3

2.3, Next to last line: Delete "uspersede" and substitute "supersede".

PAGE 4

TABLE I, Solenoid (Left) and Solenoid (Right) under Safe & Locked: Delete "12.3 to 14.9" and substitute "11.8-14.1".

PAGE 13

4.3.1, Drawing 9390604: Delete in its entirety.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

PAGE 17

4.4.2.1, Sheet 1 of 1, next higher assembly: Delete "12630880" and substitute "12630888".

PAGE 18

4.4.2.2, Sheet 1 of 1, next higher assembly: Delete "12630880" and substitute "12630888".

PAGE 19

4.4.2.3, Sheet 1 of 1, Major 101, under requirement para: Delete "3.2.3" and substitute "3.2.2.4".

PAGE 20

4.4.2.4, Sheet 1 of 1, next higher assembly: Delete "12630880" and substitute "12630891".

PAGE 21

4.4.2.5, Sheet 1 of 1: Delete in its entirety and replace with included sheet.

PAGE 22

4.4.2.6, Sheet 1 of 1, Major 101, under requirement para: Delete "3.2.3" and substitute "3.2.2.4".

PAGE 23

4.4.2.7, Sheet 1 of 1, next higher assembly: Delete "12630880" and substitute "12630885".

PAGE 24

4.4.2.8, Sheet 1 of 1, next higher assembly: Delete "12630880" and substitute "12630885".

PAGE 25

4.4.2.9, Sheet 1 of 1, Major 101, under requirement para: Delete "3.2.3" and substitute "3.2.2.4".

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-S-48686 (AR)
AMENDMENT 1

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 12630892
4.4.2.5	Gear, Escapement				NEXT HIGHER ASSEMBLY 12630891
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	True position of tooth to tooth length (.2159)		Ø.40%	3.2	Gage
102	Gear profile		Ø.40%	3.2	Gage
103	Coating, thickness	1	Coupon	3.1.2	Gage/4.5.6.3
104	Coating, adhesion	1	Coupon	3.1.2	Test/4.5.6.4
Minor					
201	Coating missing, incomplete or improper		Ø.65%	3.4	Visual
202	Evidence of poor workmanship		1.Ø%	3.4	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- (U) Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

PAGE 26

4.4.2.10, Sheet 1 of 1, next higher assembly: Delete "12630880" and substitute "12630894".

PAGE 27

4.4.2.11, Sheet 1 of 1, Major 103, under EXAMINATION OR TEST: Add "(2 places)".

PAGE 30

4.4.2.14, Sheet 1 of 1: Delete in its entirety and replace with included sheet.

PAGE 32

4.4.2.16, Sheet 1 of 1, Under Category, Minor: Delete "210" and substitute "201".

PAGE 33

4.4.2.17, Sheet 1 of 1: Delete in its entirety and replace with included sheet.

PAGE 34

4.4.2.18, Sheet 1 of 1: Delete in its entirety and replace with included sheet.

PAGE 37

4.4.2.21, Sheet 1 of 1: Delete in its entirety and replace with included sheet.

PAGE 38

4.4.2.22, Sheet 1 of 2: Delete in its entirety and replace with included sheet.

PAGE 39

4.4.2.22, Sheet 2 of 2: Delete in its entirety and replace with included sheet.

PAGE 40

4.4.2.23, Sheet 1 of 1, Major 101 and 102, under EXAMINATION OR TEST: Add "(2 places)".

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 12630881
4.4.2.14	Plate, Bottom				NEXT HIGHER ASSEMBLY 12630880
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Diameter of #2 Gear & Pinion (G&P) hole		0.40%	3.2	Gage
102	Location of #2 (G&P) hole		0.40%	3.2	Gage
103	Diameter of #1 pivot hole (3 places)		0.40%	3.2	Gage
104	Location of #1 pivot hole (3 places)		0.40%	3.2	Gage
105	Diameter of large pillar hole (max) (2 places)		0.40%	3.2	Gage
106	Location of large pillar hole (max) (2 places)		0.40%	3.2	Gage
107	Diameter of small pillar hole		0.40%	3.2	Gage
108	Location of small pillar hole		0.40%	3.2	Gage
109	Coating, thickness	1	Coupon	3.1.2	Gage/4.5.6.3
110	Coating, adhesion	1	Coupon	3.1.2	Test/4.5.6.4
Minor					
201	Coating missing, incomplete or imporper		0.65%	3.4	Visual
202	Evidence of poor workmanship		0.65%	3.4	Visual

NOTES:

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil - Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 12630884
4.4.2.17	Pillar, Number 2				NEXT HIGHER ASSEMBLY 12630880
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Diameter, large end, min.		0.40%	3.2	Gage
102	Diameter, small end, min. (.094)		0.40%	3.2	Gage
103	Length, large diameter end (.187)		0.40%	3.2	Gage
104	Length, small diameter end		0.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		1.0%	3.4	Visual

NOTES:

Source: https://assist.dla.mil (32) Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-S-48686 (AR)
AMENDMENT 1

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 12630880
4.4.2.18	Escapement Assembly				NEXT HIGHER ASSEMBLY 9390600
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Stake missing, pillar above flush, Pillar #1 (bottom plate)		0.40%	3.2	Visual
102	Stake missing, pillar #2 (2 places, top plate)		0.40%	3.2	Visual
103	Stake missing, pillar #2 (2 places, bottom plate)		0.40%	3.2	Visual
104	Push-off, partial assembly, top plate (Nondestructive)		0.40%	3.2.2.1	Test
105	Push-off, partial assembly, bottom plate (Nondestructive)		0.40%	3.2.2.2	Test
Minor					
201	Evidence of poor workmanship		1.0%	3.4	Visual

NOTES:

Source: https://assist.dla.mil - Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 12630822
4.4.2.21	Switch Board Assembly				NEXT HIGHER ASSEMBLY 9390600
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Location of contact in operating position (6 places)		0.40%	3.2	Gage
102	Contact force at operating position (6 places)		0.40%	3.2	Gage/Test
Minor					
201	Improper copper wire		0.65%	3.2	Visual
202	Adhesive in area of contact bend or operating area		0.65%	3.2	Visual
203	Evidence of solder bridging prior to adhesive application		0.65%	3.2	Visual
204	Evidence of poor workmanship		1.0%	3.4	Visual

NOTES:

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil (37) Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 2		DRAWING NUMBER 9390601
4.4.2.22	Plate, Center				NEXT HIGHER ASSEMBLY 9390600
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Diameter of pivot hole (4 places)		0.40%	3.2	Gage
102	Location of pivot hole (4 places)		0.40%	3.2	Gage
103	Diameter of base dowel hole (2 places)		0.40%	3.2	Gage
104	Location of base dowel hole (2 places)		0.40%	3.2	Gage
105	Diameter of tee spacer dowel hole (4 places)		0.40%	3.2	Gage
106	Location of tee spacer dowel hole (4 places)		0.40%	3.2	Gage
107	Pitch diameter of switch board assy. hole (4 places)		0.40%	3.2	Gage
108	Location of switch board assy. threaded hole (4 places)		0.40%	3.2	Gage
109	Diameter of switch Board (pin) hole (4 places)		0.40%	3.2	Gage
110	Location of switch Board (pin) (4 places)		0.40%	3.2	Gage
111	Diameter of escapement hole (2 places)		0.40%	3.2	Gage
112	Width of escapement slot (2 places)		0.40%	3.2	Gage
113	Location of escapement hole (2 places)		0.40%	3.2	Gage
114	Length of escapement slot (2 places)		0.40%	3.2	Gage

NOTES:

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil - Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER 9390601
4.4.2.22	Plate, Center				NEXT HIGHER ASSEMBLY 9390600
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
115	Diameter of tee spacer mtg. hole (6 places)		0.40%	3.2	Gage
116	Location of tee spacer mtg. hole (6 spaces)		0.40%	3.2	Gage
117	Pitch diameter of base mtg. hole (2 places)		0.40%	3.2	Gage
118	Location of base mtg. hole (2 places)		0.40%	3.2	Gage
119	Diameter of top plate dowel pin hole (2 places)		0.40%	3.2	Gage
120	Location of top plate dowel pin hole (2 places)		0.40%	3.2	Gage
Minor					
201	Protective finish improper, incomplete or missing		0.65%	3.2	Visual
202	Evidence of poor workmanship		1.0%	3.4	Visual

NOTES:

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- (39) -- Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

PAGE 41

4.4.2.24, Sheet 1 of 1: Delete in its entirety and replace with included sheet.

PAGE 42

4.4.2.25, Sheet 1 of 1, Major 101: Delete in its entirety.

PAGE 43

4.4.2.26, Sheet 1 of 1, Major 103, under EXAMINATION OR TEST: Add ", end to end".

PAGE 49

4.4.2.32, Sheet 1 of 1, Major 101, under Examination or test: Delete "MIL-STD-1460" and substitute "Note 3 of drawing".

PAGE 50

4.4.2.33, Sheet 1 of 1: Delete in its entirety and replace with included sheet.

PAGE 52

4.4.2.35, Sheet 1 of 1: Delete in its entirety and replace with included sheet.

PAGE 55

4.4.2.38, Sheet 1 of 1, Major 103, under requirement para: Delete "3.2.3" and substitute "3.2.1".

PAGE 56

4.4.2.39, Sheet 1 of 1, Minor 201: Delete in its entirety.

PAGE 58

4.4.2.41, Sheet 1 of 2: Delete in its entirety and replace with included sheet.

PAGE 59

4.4.2.41, Sheet 2 of 2: Delete in its entirety and replace with included sheet.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9390612
4.4.2.24	Housing "G" Weight Latch				NEXT HIGHER ASSEMBLY 9390813
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Diameter of mounting hole		0.40%	3.2	Gage
102	Location of mounting hole		0.40%	3.2	Gage
103	Location of latch hole		0.40%	3.2	Gage
104	Diameter of locating hole		0.40%	3.2	Gage
105	Location of locating hole		0.40%	3.2	Gage
106	Width of locating slot		0.40%	3.2	Gage
107	Location of locating slot		0.40%	3.2	Gage
108	Diameter oflatch hole		0.40%	3.2	Gage
109	Location of slot for latch pin		0.40%	3.2	Gage
110	Width of slot		0.40%	3.2	Gage
111	Surface finish in slot and large hole		0.40%	3.2	Visual
112	Coating, thickness	1	Coupon	3.1.2	Gage/4.5.6.3
113	Coating, adhesion	1	Coupon	3.1.2	Test/4.5.6.4
Minor					
201	Radius around edge of slot missing (intersection with latch hole)		0.65%	3.2	Visual
202	Evidence of foreign material in large diameter hole		0.65%	3.4	Visual
203	Evidence of poor plating adhesion in large diameter hole		0.65%	3.4	Visual
204	Evidence of poor workmanship		1.0%	3.4	Visual

NOTES:

Source: https://assist.dla.mil - Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-S-48686 (AR)
AMENDMENT 1

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.33	Housing, Detonator	1 OF 1	12630807
			NEXT HIGHER ASSEMBLY 12630802

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Diameter of hole for detonator		0.40%	3.2	Gage
102	Depth of hole for detonator		0.40%	3.2	Gage
103	Location of hole for detonator		0.40%	3.2	Gage
104	Diameter of mounting hole (2 places)		0.40%	3.2	Gage
105	Location of mounting hole (2 places)		0.40%	3.2	Gage
106	Location of shorting plate mounting holes (max)		0.40%	3.2	Gage
107	Diameter of shorting plate mounting holes (2 places)		0.40%	3.2	Gage
Minor					
201	Sharp edges at intersection of detonator hole and wire feed through hole		0.65%	3.4	Visual
202	White "S" missing from green field		0.65%	3.2	Visual
203	Paint incorrect or improperly located		0.65%	3.2	Visual
204	Evidence of poor workmanship		1.0%	3.4	Visual

NOTES:

Source: https://assist.dla.mil (Downloaded: 2026-10-22T19:36Z)
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9390589
4.4.2.35	Spring, "G" Weight				NEXT HIGHER ASSEMBLY 9390590
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Load at 1.300 in.		0.40%	3.2	Gage
102	Load at .575 in.		0.40%	3.2	Gage
Minor					
201	End Open		0.65%	3.2	Visual
202	Inside diameter		0.65%	3.2	Gage
203	Evidence of poor workmanship		1.0%	3.4	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-S-48686 (AR)
AMENDMENT 1

PARAGRAPH	TITLE	SHEET 1 OF 2	DRAWING NUMBER
4.4.2.41	Rotor, Detonator		9392415
			NEXT HIGHER ASSEMBLY
			12630810

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Diameter of pivots (2 places)		0.40%	3.2	Gage
102	Shoulder to shoulder distance of mid-diameter shaft and pivot shaft		0.40%	3.2	Gage
103	Tooth-to-tooth composite tolerance		0.40%	3.2	Gage
104	Total composite tolerance		0.40%	3.2	Gage
105	Surface finish on pivot diameters (2 places)		0.40%	3.2	Gage
106	Location of holes for detonator housing		0.40%	3.2	Gage
107	Pitch diameter of threads for detonator		0.40%	3.2	Gage
108	Surface finish on shoulder (2 places)		0.40%	3.2	Gage
109	Coating, thickness	1	Coupon	3.1.2	Gage/4.5.6.3
110	Coating, adhesion	1	Coupon	3.1.2	Visual/4.5.6.4
Minor					
201	Location of screw thread hole in side (2 places)		0.65%	3.2	Gage
202	Pitch diameter (max) of screw threads		0.65%	3.2	Gage
203	Location of hole for pin		0.65%	3.2	Gage
204	Diameter of hole for pin (max)		0.65%	3.2	Gage

NOTES:

Source: https://assist.dla.mil -- (5980) Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-S-48686 (AR)
AMENDMENT 1

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER 9392415
4.4.2.41	Rotor, Detonator				NEXT HIGHER ASSEMBLY 12630810
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Minor					
205	End of gear teeth to centerline (2 places)		0.65%	3.2	Gage
206	Width of slots (2 places)		0.65%	3.2	Gage
207	Location of slots (2 places)		0.65%	3.2	Gage
208	Presence of timing mark		0.65%	3.2	Visual
209	Location of hole for lead weight		0.65%	3.2	Gage
210	Finish missing or improper		0.65%	3.2	Visual
211	Coating missing, incomplete or improper		0.65%	3.4	Visual
212	Improper color or location of paint		0.65%	3.4	Visual
213	Black "A" missing on red field		0.65%	3.4	Visual
214	Evidence of poor paint adhesion		0.65%	3.2	Test/4.5.8
215	Evidence of poor workmanship		1.0%	3.4	Visual

NOTES:

Source: https://assist.dla.mil (Downloaded: 2026-10-22T19:36Z)
Check the source to verify that this is the current version before use.

PAGE 61

4.4.2.43, Sheet 1 of 1, Major 103: Delete in its entirety.

PAGE 62

4.4.2.44, Sheet 1 of 2: Delete in its entirety and replace with included sheet.

PAGE 66

4.4.2.47, Sheet 1 of 1, next higher assembly: Delete "9390692" and substitute "9390602".

PAGE 68

4.4.2.49, Sheet 1 of 1: Delete in its entirety.

PAGE 69

4.4.2.50, Sheet 1 of 1: Delete in its entirety and replace with included sheet.

PAGE 73

4.4.2.54, Sheet 1 of 1, under Major: Add "112, Location of threaded hole, 0.40%, 3.2, Gage".

PAGE 74

4.4.2.55, Sheet 1 of 1, Major 101, under EXAMINATION OR TEST: Delete in its entirety and substitute "maximum gap between latch and pin".

PAGE 75

4.4.2.56, Sheet 1 of 1, Major 102: Delete in its entirety.

PAGE 76

4.4.2.57, Sheet 1 of 1, Major 105, under EXAMINATION OR TEST: Delete "Shoulder to groove thickness" and substitute "groove width".

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 2		DRAWING NUMBER 12630826/9390608
4.4.2.44	Latch Actuator Solenoid Assembly Solenoid, Rotary				NEXT HIGHER ASSEMBLY 9390606
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Distance to latch actuator assembly from bottom of solenoid		0.40%	3.2	Gage
102	Location of latch actuator assembly with mounting studs		0.40%	3.2	Gage
103	Spring pin missing		0.40%	3.2	Visual
104	Dimple missing (4 places)		0.40%	3.2	Visual
	SEQUENCE REQUIRED (105, 106, 107)				
105	Output torque with 5 oz. weight @ -40°F		0.40%	3.2	Test
106	Output torque with 5 oz. weight @ 70°F	1/	100%	3.2	Test
107	Output torque with 5 oz. weight @ 150°F		0.40%	3.2	Test
108	Diameter of rotating shaft		0.40%	3.2	Gage
109	Spring torque @ 2° rotation		0.40%	3.2	Test
110	Spring torque @ 43° rotation, max.		0.40%	3.2	Test
111	Rotation		0.40%	3.2	Gage
112	Stroke direction		0.40%	3.2	Manual
113	Resistance @ 70°F		0.40%	3.2	Test
114	Axial shaft movement, max.		0.40%	3.2	Gage

NOTES:

1/ Input current shall be limited to 1.65 ADC MAX.

Source: https://assist.dla.mil - Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-S-48686 (AR)
AMENDMENT 1

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9390605
4.4.2.50	Rail				NEXT HIGHER ASSEMBLY 9390590
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Diameter, min.		0.40%	3.2	Gage
102	Length, min.		0.40%	3.2	Gage
103	Surface finish		0.40%	3.2	Gage
104	Straightness		0.40%	3.2	Gage
Minor					
201	Protective finish missing, incomplete or improper		0.65%	3.2	Visual
202	Evidence of poor workmanship		1.0%	3.4	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:36Z
Check the source to verify that the current version before use.

PAGE 80

4.4.2.61, Sheet 1 of 3, under Major: Add "109a Location of Slot for Latch, Ø.40%, 3.2, Gage".

PAGE 82

4.4.2.61, Sheet 3 of 3: Delete in its entirety and replace with included sheet.

PAGE 84

4.4.2.63, Sheet 1 of 1, Major 103 and 108: Delete in their entirety.

PAGE 86

4.4.2.65, Sheet 1 of 1: Delete in its entirety and replace with included sheet.

PAGE 87

4.4.2.66, Sheet 1 of 1, Minor 202, under EXAMINATION OR TEST: Delete "sink" and substitute "bore".

PAGE 88

4.4.2.67, Sheet 1 of 1, under Major: Add "104, Diameter of Large center hole, Ø.40%, 3.2, Gage"

PAGE 89

4.4.2.68, Sheet 1 of 1, under Major: Add "108, Diameter of gear mount, Ø.40%, 3.2, Gage".

PAGE 90

4.4.2.69, Sheet 1 of 1: Delete in its entirety and replace with included sheet.

PAGE 91

4.4.2.70, Sheet 1 of 1, Major 108: Under EXAMINATION OR TEST: Delete "2 places" and substitute "4 places".

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 3 OF 3		DRAWING NUMBER 9390594
4.4.2.61	Plate, Outer				NEXT HIGHER ASSEMBLY 9390592
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Major					
120	Pitch diameter of "G" wgt. latch mtg. hole		0.40%	3.2	Gage
121	Location of "G" wgt. latch mtg. hole		0.40%	3.2	Gage
122	Pitch diameter of switch mtg. hole		0.40%	3.2	Gage
123	Location of switch mtg. hole		0.40%	3.2	Gage
124	Width of switch mtg. slot		0.40%	3.2	Gage
125	Location of switch mtg. slot		0.40%	3.2	Gage
126	Height of switch mtg. slot		0.40%	3.2	Gage
127	Thickness for lower "G" wgt. surface		0.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		1.0%	3.4	Visual

NOTES:

Source: https://assist.dla.mil - Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-S-48686 (AR)
AMENDMENT 1

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.65	Board, Stiffener		9390611
			NEXT HIGHER ASSEMBLY 9390590

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Diameter of mounting hole (4 places)		0.40%	3.2	Gage
102	Location of mounting hole (4 places)		0.40%	3.2	Gage
103	Diameter of hole (12 places)		0.40%	3.2	Gage
104	Location of hole (12 places)		0.40%	3.2	Gage
105	Location of solenoid lead cutout (2 places)		0.40%	3.2	Gage
Minor					
201	Diameter of clearance hole (2 places)		0.65%	3.2	Gage
202	Location of clearance hole (2 places)		0.65%	3.2	Gage
203	Edge chamfer missing		0.65%	3.2	Visual
204	Radius missing on corners (8 places)		0.65%	3.2	Visual
205	Profile of cutouts (2 places)		0.65%	3.2	Gage
206	Diameter of solenoid mtg hole (4 places)		0.65%	3.2	Gage
207	Location of solenoid mtg hole (4 places)		0.65%	3.2	Gage
208	Evidence of poor workmanship		1.0%	3.4	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9392416
4.4.2.69	Balance Rotor Assembly				NEXT HIGHER ASSEMBLY 9390590
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Weight		0.40%	3.2	Scale
Minor					
201	Escapement gear not against rotor		0.65%	3.2	Visual/Manual
202	Escapement gear loose		0.65%	3.2	Visual/Manual
203	Pan head screw not seated (2 places)		0.65%	3.2	Visual/Manual
204	Evidence of poor workmanship		1.0%	3.4	Visual

NOTES:

Source: https://assist.dla.mil -- (2026-10-22T19:36Z
Downloaded:
Check the source to verify that this is the current version before use.

PAGE 93

4.4.2.71, Sheet 1 of 1, Major 105, under para reference/ inspection method: Delete "4.5.5" and substitute "4.5.4".

4.4.2.71, Sheet 1 of 1, Major 109, under para reference/ inspection method: Delete "4.5.6" and substitute "4.5.5".

PAGE 95

4.5.4.2, line 5: Delete "2a" and substitute "3a".

4.5.4.2, line 10: Delete "2b" and substitute "3b".

4.5.5.2, line 3: Delete "2b" and substitute "3b".

PAGE 96

4.4.6.2.1, Under Table IV: Add:

"A1	aluminum alloy, bar or wire, 7075-T6	ASTM B211
A2	aluminum alloy, sheet, 6061-T6	ASTM B209
A3	aluminum alloy, rod 6061-T6	ASTM B221
A4	aluminum alloy, rod 7075-T6	ASTM B221
A5	aluminum alloy, bar or wire, 6061-T6	ASTM B211"

PAGE 97

Add new paragraph 4.5.8 as follows:

"4.5.8. Paint adhesion. A 3/4" wide pressure-sensitive adhesive tape conforming to Federal Specification A-A-113, is to be applied to the entire red field. The tape is to be applied flush to the surface, the inspector is to use manual pressure to remove entrapped air. After waiting 10 seconds to allow return to ambient temperature, the tape is to be sharply pulled in a direction approximately 180 to that which it was applied.

The tape is to be inspected for evidence of paint removed from the component. Paint removed around the perimeter of the red field resulting from overspray of the lacquer beyond the primer shall not constitute rejection. Evidence of removal of paint inside the perimeter of the painted field shall constitute rejection of the lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

Upon rejection of a lot of painted components, the adhesion test may be performed 100% to serve as a screening test. Those components which pass this adhesion test are then to be considered acceptable.

Custodian:
Army - AR

Preparing activity:
Army - AR

(Project: 1336-A576)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.