MIL-C-45820C(AL)
22 May 1984
SUPERSEDING
MIL-C-45820B(WC)
29 March 1968

MILITARY SPECIFICATION

# CABLE ASSEMBLIES, ELECTRICAL

This specification is approved for use by the US Army Armament, Munitions and Chemical Command, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

## 1 SCOPE

1.1 Scope. This specification covers special flexible electric cable assemblies to be used in repair shops and field applications.

* 1.2 Classification. The cable assemblies shall be furnished in the following types and lengths as specified (see 6.2).

| Type | Length (Feet) |
|---|---|
| I | 25 |
| II | 7 |
| III | 20 |
| IV | 15 |
| V | 10 |
| VI | 25 |
| VII | 50 |
| VIII | 50 |
| IX | 50 |

## 2 APPLICABLE DOCUMENTS

2.1 Government documents.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament, Munitions, and Chemical Command, ATTN: DRSMC-LEE-S, Rock Island, IL 61299 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 4910

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:57Z
Check the source to verify that this is the current version before use.

* 2.1.1 Specifications, standards, and handbooks. Unless otherwise specified, the following specifications, standards, and handbooks of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

PPP-B-601 - Boxes, Wood, Cleated-Plywood
PPP-B-636 - Boxes, Shipping, Fiberboard
PPP-T-60 - Tape: Packaging, Waterproof

MILITARY

MIL-P-116 - Preservation-Packaging, Methods of
MIL-C-3432 - Cable and Wire, Electrical (Power and Control; Semi-Flexible, and Extra-Flexible, 300 and 600 Volts)
MIL-C-3930 - Insulating and Jacketing Compounds, Electrical (for Cables, Cords and Wires)
MIL-C-5501 - Caps and Plugs, Protective, Dust and Moisture Seal, General Specification for
MIL-B-43436 - Band Markers, Blank, General Specification for

STANDARDS

FEDERAL

FED-STD-H28 - Screw Thread Standards for Federal Services

MILITARY

MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-130 - Identification Marking of US Military Property
MIL-STD-810 - Environmental Test Methods
MIL-STD-1184 - Electrical Components for Automotive Vehicles; Waterproofness Tests

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein.

DRAWINGS

ARMY

5645772 - Cable-Assembly, for Director M5 and M6
7550025 - Cable-Assembly, PWR, Electrical-Shelter to Shelter
7550251 - Cable Assembly, PWR, Electrical-Generator to Shelter
7729732 - Extension, Cable-24 Volts

(Copies of specifications, standards, handbooks, drawings, and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:57Z
Check the source to verify that this is the current version before use.

* 2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

D3951-82 Standard Practice for Commercial Package

(Application for copies should be addressed to the American Society for Testing Materials, 1916 Race Street, Philadelphia, PA 19103.)

NATIONAL FIRE PROTECTION ASSOCIATION (NFPA)

NFPA No. 70-National Electrical Code

(Application for copies should be addressed to the National Fire Protection Association, 470 Atlantic Avenue, Boston, MA 02210.)

Technical society and technical association specification and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.

* 2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

## 3 REQUIREMENTS

3.1 First article. When specified (see 6.2), the contractor shall furnish one or more, as specified, complete cable assemblies for first article inspection. The first article may be either a preproduction model or an initial production item which conforms to the requirements of this specification. In either case, the approved first article and the production items shall be identical and in accordance with the terms of the contract. Approval of the first article shall not relieve the contractor of the responsibility to furnish equipment in accordance with the requirements of this specification.

3.2 Design. The cable assemblies shall be new and of the design meeting the requirements as specified herein. Cable assemblies not covered by drawings shall be designed to shield the connectors within the plugs and receptacles against water, dust, and oil when connected to their mating components. All cable assembly parts that are not covered on a drawing and are subject to wear or replacement shall be accessible.

3.3 Materials. Materials shall be as specified herein. Further, all materials shall be free of defects and imperfections that might affect the serviceability and appearance of the finished product. Contact between dissimilar metals, especially brass, copper, or steel in contact with aluminum or magnesium, shall be avoided.

* 3.3.1 Reclaimed materials. The cable assemblies may contain reclaimed materials provided such materials will not jeopardize their intended use and performance. The reclaimed materials shall have been reprocessed, remanufactured, or recycled in a manner which restores them to the same chemical composition and physical properties as the materials originally selected for use.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:57Z
Check the source to verify that this is the current version before use.

3.3.2 Corrosion resistance. All metallic materials shall be inherently corrosion resistant or shall be treated to resist corrosion.

3.3.3 Conductors. The conductors sha11 be made of stranded copper wire and shall conform to Table I.

3.4 Construction. Each cable assembly shall be complete so that when installed, it can be used for the operations specified herein. If there is a conflict between this specification and the Army drawing, the requirement specified on the applicable drawing shall have preference.

3.4.1 Fastening devices. All screws,pins,bolts and similar fasteners used shall be installed with means for preventing loss of tightness. Such parts subject to removal or adjustment shall not be swaged,peened, staked or otherwise permanently deformed.

* 3.4.2 Threads. All threaded parts of the cable assemblies shall conform to FED-STD-H28 and the applicable "Detailed Standard" section referenced therein.

* 3.4.3 Electrical connections. Electrical connections shall be mechanically secured and soldered, or brazed; except connections on screw type terminals which shall be mechanically secured. Resin base fluxes shall be used in all soldering operations.

3.4.4 Welding, brazing or soldering. Welding, brazing or soldering shall be employed only where those operations are included in fabrication of the original design. These operations shall not be employed as repair measures for defective parts.

* 3.4.5 Safety and health requirements. Safety devices shall be provided for all parts presenting safety hazards which can be guarded without substantial interference to operation of the cable assemblies. All guards shall be removable to provide easy access to guarded parts. Exceptions and additional requirements for safety and health shall be as specified (see 6.2 and 6.3).

3.4.6 Interchangeability. All replaceable parts shall be manufactured to permit replacement or adjustment without the need for modification.

* 3.4.7 Surfaces. All castings, forgings, molded parts, stampings, and welded parts shall be cleaned and free of sand, dirt, fins, sprues, scale, flux, and other harmful or extraneous materials. All external surfaces of parts subjected to handling shall be smooth and all edges shall be rounded or beveled.

3.4.8 Casting and forgings. All castings and forgings shall be free from defects, scale, and mismatching.

3.5 Performance and product characteristics. The cable assemblies shall function under any of the following conditions or combination of conditions.

3.5.1 Temperature and humidity conditions.

3.5.1.1 Storage temperatures. Unless otherwise specified (see 6.2), the cable assembly shall be able to withstand storage without damage in an ambient temperature from plus 155 degrees Fahrenheit (F.) for periods of 4 hours per day to minus 65 degrees F. for periods up to 72 hours.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:57Z
Check the source to verify that this is the current version before use.

3.5.1.2 Operating temperature. Unless otherwise specified (see 6.2), the cable assembly shall be capable of performing in an ambient temperature from plus 115 degrees F. for at least 4 hours to minus 25 degrees F. for at least 72 hours.

3.5.1.3 Humidity conditions. Unless otherwise specified (see 6.2), the cable assembly shall be capable of performing in an atmosphere having a relative humidity of 95 percent and an ambient temperature of 85 degrees F. for 20 hours, followed by an atmosphere having a relative humidity of 100 percent and an ambient temperature of 80 degrees F. for 4 hours.

3.5.2 Dielectric strength. Unless otherwise specified (see 6.2), the cable assembly shall be capable of withstanding without damage, an alternating current voltage of 1,000 volts root mean square (RMS), plus twice the rated voltage, applied to the mutually insulated terminals or conductors for a period of 1 minute.

3.5.3 Strain relief. Strain relief shall be provided in the plug and receptacle so that a pull of 30 pounds exerted on the cable will not be transmitted directly to the terminals.

* 3.5.4 General. When specified (see 6.2), the cable for manufacturing the cable assemblies shall meet the requirements of MIL-C-3432 and MIL-I-3930 including Tables IV and V.

* 3.5.5 Fungus. When specified (see 6.2), the cable assembly shall be capable of resistance to fungus growth under conditions of high humidity, warm atmosphere and the presence of inorganic salts.

* 3.5.6 Continuity. The conductors of the cable assembly shall provide an electrical path between specified pins, sockets and wires as indicated on the applicable drawing.

* 3.5.7 Waterproofness. When specified (see 6.2), the plugs and receptacles of Type I, II and VIII cable assemblies shall be waterproof when mated with their specified connector.

* 3.6 Design details of Type I, II and VIII cable assemblies. Type I, II and VIII cable assemblies shall be constructed in accordance with Table I.

3.6.1 Cable. Unless otherwise specified (see 6.2), cable shall be fabricated of an oil and moisture resistant, heavy duty, hard service flexible cable conforming to the requirements of National Fire Protection Association (NFPA) No. 70. When specified (see 6.2), the cable for the type I, II and VIII cable assemblies shall conform to MIL-C-3432.

* 3.6.2 Plugs and receptacles for type I, II and VIII cable assemblies. Connectors shall be constructed to provide watertight seal upon connection with plug or receptacle of similar design.

* 3.6.2.1 Plug. Unless otherwise specified (see 6.2), the plug for the type I, II and VIII cable assemblies shall be a 600 volt, 60 ampere, two-pole, grounded through shell with rubber bushings and shall be watertight. The plug shall be equal to and interchangeable with the Crouse-Hinds, style 1, APJ6275-M54, Clark Cable Corp., APJ6275 and Barlow Electric Products, AL2606MP.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:57Z
Check the source to verify that this is the current version before use.

* 3.6.2.2 End. The sheath, filler, and binder shall be removed from the other end of type II and VIII cable for a length of 6 inches to expose the insulation of the conductors.

3.6.2.3 Receptacle. Unless otherwise specified (see 6.2), the receptacle for the type I cable assembly shall be a 600 volt, 60 ampere, two-pole, grounded through shell with rubber bushings, and shall be watertight. The receptacle shall be equal to and interchangeable with the Crouse-Hinds, style 1, APR 62555-M54, Clark Cable Corp., APR6255 and Barlow Electric Products, AL2605 FRC and shall mate with plug specified in 3.6.2.1.

3.7 Type III cable assembly. Type III cable assembly shall be in accordance with table I and shall conform to Army Drawing 7729732.

3.8 Type IV cable assembly. Type IV cable assembly shall be in accordance with Table I and shall conform to Army Drawing 5645772. When specified (see 6.2), the cable for type IV cable assembly shall conform to MIL-C-3432.

3.9 Type V, VI and IX. Type V, VI and IX cable assemblies shall be in accordance with Table I and shall conform to Army Drawing 7550251.

3.10 Type VII cable assembly. Type VII cable assembly shall be in accordance with Table I and shall conform to Army Drawing 7550025.

* 3.11 Identification marking. The cable assemblies shall be marked for identification in accordance with MIL-STD-130 and shall include the National Stock Number (NSN) unless otherwise specified, (see 6.2). As a minimum the following information shall be listed:

(a) Supplier's name or trademark.
(b) Date of manufacture (year).
(c) National Stock Number.
(d) Rated cable voltage.

The marking shall be either by indent lettering, by raised lettering on the sheath itself, on thin rubber slips molded into the sheath that do not project above the surface of the sheath more than 1/16 inch, or by a metal wrap-around tag conforming to MIL-B-43436.

3.12 Workmanship. Standards of workmanship shall be such that equipment specified herein shall comply with the requirements in section 3. All components, subassemblies, parts, and the final assembly shall comply with tests in section 4.

## 4 QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:57Z
Check the source to verify that this is the current version before use.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

(a) First Article Inspection (see 4.2.1).
(b) Quality Conformance Inspection (see 4.2.2).

4.2.1 First article inspection. First article inspection shall be applied to the preproduction model or initial production item noted in 3.1. Unless otherwise specified (see 6.2), first article inspection shall consist of the examination in 4.3 and all tests under 4.4. Failure of the first article to pass the examination or any of the tests shall be cause for rejection.

* 4.2.2 Quality conformance inspection. Quality conformance inspection shall be applied to each production unit offered for acceptance under the contract. Unless otherwise specified (see 6.2), quality conformance inspection shall consist of (a) through (c) as follows, and failure of a production unit to pass conformance inspection shall be cause for rejection of the unit.

(a) Product examination (see 4.3).
(b) Continuity test (see 4.4.4).
(c) Packaging inspection (see 4.5).

4.2.2.1 Sampling. When specified (see 6.2), sampling inspection shall be as specified by the procuring activity.

* 4.3 Product examination. Each cable assembly shall be examined to determine compliance with the requirements of section 3 and the contract. Failure to pass any examination shall be cause for rejection of that cable assembly. As a minimum, the following characteristics shall be examined:

| CHARACTERISTIC | REQUIREMENT PARAGRAPH |
|---|---|
| Design | 3.2 |
| Materials | 3.3 through 3.3.3 |
| Construction | 3.4 through 3.4.8 |
| Strain relief | 3.5.3 |
| Type I, II and VIII cable assemblies | 3.6 through 3.6.2.3 |
| Type III cable assembly | 3.7 |
| Type IV cable assembly | 3.8 |
| Type V, VI and IX cable assemblies | 3.9 |
| Type VII cable assembly | 3.10 |

4.4 Test methods.

* 4.4.1 Storage tests. Unless otherwise specified (see 6.2), the cable assemblies shall be subjected to the storage tests specified herein.

* 4.4.1.1 Low temperatures test. Unless otherwise specified (see 6.2), the cable assembly shall be placed in an ambient air temperature of minus 60 degrees F. to minus 65 degrees F. for a period of 72 hours. The cable assembly shall be removed and allowed to stabilize at an air temperature of plus 80 degrees F. plus or minus 10 degrees F. The cable assembly shall be inspected for damage and tested in accordance with 4.4.2 (see 3.5.1.1).



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:57Z
Check the source to verify that this is the current version before use.

4.4.1.2 High temperature test. Unless otherwise specified (see 6.2), the cable assembly shall be submitted to a 24 hour cycle of temperature starting with 10 hours of plus 90 degrees F., plus or minus 5 degrees F., followed by 5 hours of steady increase to plus 150 degrees F., to plus 155 degrees F., 4 hours at plus 150 degrees F., to plus 155 F., and 5 hours of steady decrease to plus 90 degrees F., plus or minus 5 degrees F. The cable assembly shall then be inspected for damage and tested in accordance with 4.4.2 (see 3.5.1.1).

4.4.1.3 Humidity test. Unless otherwise specified (see 6.2), the cable assembly shall be subjected to 20 hours exposure with relative humidity between 93 and 97 percent and at air temperature from plus 80 degrees F. to plus 85 degrees F., followed by 4 hours of 100 percent relative humidity with condensation at plus 75 degrees F. to plus 80 degrees F. Air movement and radiation are negligible. At the conclusion of the humidity test, the cable assembly shall be inspected for damage and tested in accordance with 4.4.2 (see 3.5.1.3).

4.4.2 Dielectric strength test. Unless otherwise specified (see 6.2), the alternating current potential specified in 3.5.3 shall be applied to the mutually insulated terminals or conductors for a period of 1 minute. Any evidence of breakdown of the finished cable assemblies during or after the test shall be cause for rejection.

4.4.3 Strain relief test. With the plug and receptacle securely held, a pull of 30 pounds shall be applied to the cable for 1 minute. The direction of the pull shall be in the normal plane of the cable entry hole. Any evidence of pull upon the conductor-terminal connection, shall be cause for rejection (see 3.5.3).

* 4.4.4 General test. When specified (see 6.2), the cable shall be subjected to the tests specified in MIL-C-3930 to determine conformance to 3.5.4.

* 4.4.5 Fungus test. When specified (see 6.2), the cable assembly shall be subjected to test procedure I, Method 508 of MIL-STD-810 to determine conformance to 3.5.5.

4.4.6 Continuity test. The cable assembly shall be tested for continuity of each conductor and its correct connections (see 3.5.6 or applicable drawing).

* 4.4.7 Waterproofness test. When specified (see 6.2), the cable assembly shall be subjected to the test specified in MIL-STD-1184, Method 100, Procedure I, for Type II, Class 1 components. The end of a cable assembly without a plug or receptacle need not be submerged in water. No later than two hours following the waterproofness test the dielectric strength and insulation resistance performance requirements of MIL-C-3432. Only the exterior surfaces of the test cable assembly directly in contact with the water during the specified test may be dried.

* 4.5 Packaging inspection. Preservation, packing and marking of supplies and equipment for shipment and storage shall be inspected to determine compliance with section 5.

5 PACKAGING

5.1 Preservation. Preservation shall be Level A or Industrial, as specified (see 6.2).



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:57Z
Check the source to verify that this is the current version before use.

5.1.1 Level A.

5.1.1.1 Cleaning. The cable assemblies shall be cleaned in accordance with process of C-1 of MIL-P-116.

5.1.1.2 Drying. The cable assemblies shall be dried in accordance with procedures D-1 and D-4 of MIL-P-116.

5.1.1.3 Preservation. The cable assemblies shall be preserved in accordance with method III of MIL-P-116. The plug openings and receptacle shall be covered with tape conforming to PPP-T-60 or with plastic plugs or caps conforming to MIL-C-5501. Coil cable to a minimum safe diameter and secure with at least three ties of twine or cotton tape, of sufficient strength to prevent breaking or uncoiling of cable.

5.1.1.4 Unit pack. The method of unit protection for the cable assemblies shall be fiberboard containers conforming to PPP-B-636, class weather-resistance. Containers shall be closed in accordance with the appendix of the box specification.

* 5.1.2 Industrial. The cable assemblies shall be preserved and provided with unit protection in accordance with ASTM D3951-82.

5.2 Packing. Packing shall be Level A or Industrial, as specified (see 6.2).

5.2.1 Level A. Unless otherwise specified (see 6.2), the cable assemblies shall be packed in cleated plywood boxes conforming to PPP-B-601, overseas type. Closure shall be in accordance with the appendix of the box specification.

* 5.2.2 Industrial. The cable assemblies preserved as specified in 5.1.2 shall be packed in accordance with the requirements of ASTM D3951-82.

5.3 Marking.

* 5.3.1 Military. When military levels of protection are specified, interior wraps of containers and exterior shipping containers shall be marked in accordance with the requirements of MIL-STD-129 and any special markings required by the contract or purchase order.

* 5.3.2 Industrial. When industrial packaging is specified, interior containers and exterior shipping containers shall be marked in accordance with ASTM D3951-82 and any special markings required by contract or purchase order.

6 NOTES

* 6.1 Intended use. The cable assemblies are intended to be used on maintenance and repair shop specialized equipment. They may be subjected to the most severe usage and to the action of salt air, moisture, extremely dry, dusty atmospheric conditions, and extremes of temperature. The specific uses are as follows:

| | |
|---|---|
| Type I | - For automotive field maintenance shop sets |
| Type II | - For automotive field maintenance shop sets |
| Type III | - For automotive field maintenance shop sets |
| Type IV | - For director M5 and M6 |
| Type V | - For generator to field shop shelter |
| Type VI | - For generator to field shop shelter |
| Type VII | - For field shop shelter to field shop shelter |
| Type VIII | - For automotive field maintenance shop sets |



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:57Z
Check the source to verify that this is the current version before use.

Type IX - For generator to field shop shelter

6.2 Ordering data. Procurement documents should specify:

(a) Title, number, and date of this specification.
(b) Type and length required (see 1.2).
(c) First article, when required (see 3.1).
(d) Special safety devices, when required (see 3.4.5 and 6.3).
(e) Storage temperatures, if different (see 3.5.1.1).
(f) Operating temperatures, if different (see 3.5.1.2).
(g) Humidity conditions, if different (see 3.5.1.3).
(h) Dielectric strength, if different (see 3.5.2).
(i) Cable conformance to MIL-C-3432 and MIL-I-3930, when required (see 3.5.4).
(j) Resistance to fungus, when required (see 3.5.5).
(k) Waterproofness, when required (see 3.5.7).
(l) Fabrication, if different (see 3.6.1).
(m) Plug requirements, if different (see 3.6.2.1).
(n) Receptacle requirements, if different (see 3.6.2.3).
(o) Identification marking, if different (see 3.11).
(p) First article inspection, when required (see 4.2.1).
(q) Quality conformance inspection, if different (see 4.2.2).
(r) Sampling, when required (see 4.2.2.1).
(s) Storage tests: low temperature, high temperature and humidity, if different (see 4.4.1, 4.4.1.1, 4.4.1.2 and 4.4.1.3).
(t) Dielectric strength test, if different (see 4.4.2).
(u) General test, when required (see 4.4.4).
(v) Fungus test, when required (see 4.4.5).
(w) Waterproofness test, when required (see 4.4.7).
(x) Preservation level required (see 5.1).
(y) Packing level required (see 5.2).
(z) Cleated plywood boxes, when required (see 5.2.1).

* 6.3 Safety and health determinations. In order that equipment integrated into the user's operational environment will comply with OSHA limitation and control of noise levels, radiation, electromagnetic emission, noxious vapors, heat, etc. as applicable, specific requirements concerning guarding the point(s) of operation, and other safety and health requirements should be specified by the user/requisitioner (see 6.2).

* 6.4 The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodian:
Army - AL

Preparing Activity:
Army - AL

Review activities:
Army - SM, AT, CS, CR, ER

Project No. 4910-A493



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:57Z
Check the source to verify that this is the current version before use.

TABLE I. Cable characteristics.

| Type | Cable | Conductors Under One Cover | | | Volts | |
|---|---|---|---|---|---|---|
| | | Qty | Size AWG | Min. Strands per conductor | DC | AC |
| I | Power Electric | 3 | (1) No. 4<br>(1) No. 4<br>(1) No. 8 white minimum ground | 133<br>133<br>49 | 250 | 600 |
| II | Power Electric | 3 | (1) No. 4<br>(1) No. 4<br>(1) No. 8 white minimum ground | 133<br>133<br>49 | 250 | 600 |
| III | Power Electric | 2 | (2) No. 1 | 812 | 24 | |
| IV | Director | 3 | (3) No. 12 | 65 | | 600 |
| V | Power Electric | 4 | (4) No. 4 | 133 | | 600 |
| VI | Power Electric | 4 | (4) No. 4 | 133 | | 600 |
| VII | Power Electric | 4 | (4) No. 4 | 133 | | 600 |
| VIII | Power Electric | 3 | (1) No. 4<br>(1) No. 4<br>(1) No. 8 white minimum ground | 133<br>133<br>49 | 250 | 600 |
| IX | Power | 4 | (4) No. 4 | 133 | | 600 |



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:57Z
Check the source to verify that this is the current version before use.

TABLE I. Cable characteristics (continued).

| Type | Amps | Cover | Fittings | Over-all assembly length ft |
|---|---|---|---|---|
| I | 60 | SBR or Cloroprene Jacket | 1 Plug: 2 Pole 1 Receptacle: 2 Pole Para. 3.6.2 & 3.6.2.3 | 25 |
| II | 60 | SBR or Cloroprene Jacket | 1 Plug: 2 Pole, Para 3.6.2 & 3.6.2.1, Exposed Insulated conductors - other end of cable, Para 3.6.2.2 | 7 |
| III | | SBR | As specified on applicable Drawing | 20 |
| IV | 20 | SBR | As specified on applicable Drawing | 15 |
| V | | Cloroprene | As specified on applicable Drawing | 10 |
| VI | | Cloroprene | As specified on applicable Drawing | 25 |
| VII | | Cloroprene | As specified on applicable Drawing | 50 |
| VIII | 60 | SBR or Cloroprene Jacket | 1 Plug: 2 Pole, Para. 3.6.2 & 3.6.2.1, Exposed Insulated conductors other end of cable Para. 3.6.2.2 | 50 |
| IX | | Cloroprene | As specified on applicable Drawing | 50 |



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:57Z
Check the source to verify that this is the current version before use.

**INSTRUCTIONS:** In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

*NOTE:* This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

*(Fold along this line)*

*(Fold along this line)*

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

**OFFICIAL BUSINESS**
**PENALTY FOR PRIVATE USE $300**

**BUSINESS REPLY MAIL**
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Armament, Munitions
and Chemical Command
ATTN: DRSMC-LEE-S (R)
Rock Island, IL 61299

13

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:57Z
Check the source to verify that this is the current version before use.

# STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

*(See Instructions – Reverse Side)*

| 1. DOCUMENT NUMBER | 2. DOCUMENT TITLE |
|---|---|
| MIL-C-45820C | |

| 3a. NAME OF SUBMITTING ORGANIZATION | 4. TYPE OF ORGANIZATION *(Mark one)* |
|---|---|
| | ☐ VENDOR |
| b. ADDRESS *(Street, City, State, ZIP Code)* | ☐ USER |
| | ☐ MANUFACTURER |
| | ☐ OTHER *(Specify)*: |

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

| 7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional | b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional |
|---|---|
| c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional | 8. DATE OF SUBMISSION *(YYMMDD)* |

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:57Z
Check the source to verify that this is the current version before use.