MILITARY SPECIFICATION

DESTRUCTOR, WARHEAD, SINGLE POINT, TRAINING M15E1, LESS SAFING AND ARMING DEVICE

1. SCOPE

1.1 This specification covers requirements, quality assurance provisions, and the preparation for delivery criteria for one type of destructor entitled Destructor, Warhead, Single Point, Training, M15E1, which is used with the Nike Hercules warhead section.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein:

STANDARDS

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-1168	- Lot Numbering of Ammunition.

DRAWINGS

ORDNANCE CORPS

8808442	- Destructor Assembly Training.
8808885	- Carton, Packing, Ammunition, for Plate, Mounting, Safety Arming Device - M2E2.
8824893	- Carton, Packing, Ammunition, for Destructor Loading Assembly - Training.
8824894	- Carton, Packing, Ammunition, for Destructor Lead Assembly - Training.
8824895	- Container, Metal, Ammunition, for Adaption Kit, M109, GM, Warhead, Package 3 of 5.
8831014	- Destructor, Warhead, Single Point, Training, M15E1.
ET-8831014	- Equipment Tabulation.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:01Z
Check the source to verify that this is the current version before use.

PUBLICATIONS

PICATINNY ARSENAL

SQAP-8831015 - Destructor Lead Assembly, Training (XM15E1).
SQAP-8831016 - Detonating Lead Assembly, Training (XM15E1).
SQAP-8831017 - Detonating Fuze Assembly, Training (XM15E1).

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Materials. The contractor shall furnish objective evidence (see 6.2) that the material complies with the specifications listed on the applicable drawing.

3.2 Assembly. The training destructor shall comply with all requirements specified on the drawing (dwg) 8831014, Supplementary Quality Assurance Provisions, SQAP-8831015, SQAP-8831016, and SQAP-8831017, with all requirements specified herein, and with the requirements of all applicable specifications to the extent specified on the drawing and herein.

3.3 First article testing. Requirements for the submission of first article samples by the contractor shall be as specified in the contract (see 4.2).

3.4 Serialization. The contractor shall assign serial numbers as required by drawings. The contractor may select any number which complies with the drawing requirement. These numbers shall not be duplicated.

3.5 Container vibration. The container assembly shall withstand vibration from 10 to 55 Hertz (Hz) at a double amplitude of 0.064 inch without evidence of damage or movement of the packed items when tested as specified in 4.4.1.

3.6 Workmanship.

3.6.1 Plastic and metal characteristics. All components shall be free from cracks, splits, cold flow, shrinkage, cold shuts, inclusions, porosity, or any similar characteristic.

3.6.2 Threads. Threads shall be full and undamaged for the entire minimum length or depth as required on the applicable drawing.

3.6.3 Burrs. Parts shall be free from burrs.

3.6.4 Foreign matter. Parts shall be free from chips, dirt, grease, rust, corrosion, or any embedded foreign material.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:01Z
Check the source to verify that this is the current version before use.

3.6.5 Cleaning. The cleaning method shall not be injurious to any of the parts, nor shall the parts be contaminated by the cleaning agent.

3.6.6 Electrical. Cable assemblies and wires shall be dressed in such a manner as to prevent pinching or chafing of the wire insulation. Ends of wires shall be free from burrs, sharp edges, or points. All parts shall be free from flux, chips, dirt, grease, rust or foreign material.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 First article inspection.

4.2.1 Quantity to be submitted. When the contract requires first article inspection, the contractor shall submit 3 complete assemblies (see dwg 8831014) for first article testing to the testing facility designated in the invitation for bids or request for proposal.

4.2.2 Inspection and testing to be performed. The first article inspection sample shall be subjected to the inspections and tests specified in Table I. Tests shall be conducted in order specified in Table I.

Table I

First article inspection and tests

Inspection or Test	Dest	Non-Dest
1. Classification of characteristics (see 4.3.2.1)		X
2. Container vibration (see 3.5)	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:01Z
Check the source to verify that this is the current version before use.

4.2.3 Inspection equipment. The inspection and testing specified in 4.2.2 shall be accomplished by using the gages and test equipment specified in 4.3.4.1.

4.2.4 Rejection. If any item fails to comply with any of the applicable requirements, the first article sample shall be rejected.

4.3 Quality conformance inspection.

4.3.1 Lot formation.

4.3.1.1 Production lot. A lot shall consist of parts and assemblies produced by one manufacturer in one unchanged process, in accordance with the same drawing, same drawing revision, same specification and same specification revision. Drawing, specification and process changes not affecting safety, performance, storage, or interchangeability, as determined by the Government, shall not necessitate changing the lot interfix number. The criteria and procedures for the assignment of lot numbers shall be in accordance with MIL-STD-1168.

4.3.1.2 Inspection lot. A lot or batch and its formation, size, and presentation is described in MIL-STD-105, Section 5. Accordingly, a lot shall mean an inspection lot and a batch shall mean an inspection batch for the purpose of this specification. The manner in which each inspection lot or batch is to be presented and identified by the contractor, shall be designated or approved by the Government representative.

4.3.2 Product inspection examination. A sample shall be selected at random from each inspection lot in accordance with the applicable major or minor characteristic table (see Table II and Table III), and inspected for all characteristics in the applicable classification. Any characteristics in the sample found to be defective shall reject the inspection lot. Sequence for the inspection of characteristics in each classification need not be followed as long as all characteristic inspections are performed.

Table II
Major Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-16	all	28-29	23	52-56	31	132-156	39
17	16	30-31	24	57-62	32	157-191	40
18	17	32-34	25	63-69	33	192-244	41
19-20	18	35-36	26	70-76	34	245-334	42
21	19	37-40	27	77-86	35	335-519	43
22-23	20	41-43	28	87-97	36	520-1120	44
24-25	21	44-47	29	98-112	37	over 1120	45
26-27	22	48-51	30	113-131	38		

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:01Z
Check the source to verify that this is the current version before use.

Table III
Minor Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-9	all	14-16	12	28-33	16	77-121	20
10	9	17-18	13	34-41	17	122-273	21
11	10	19-22	14	42-54	18	over 273	22
12-13	11	23-27	15	55-76	19		

4.3.2.1 Classification of characteristics (see 3.2). Critical, major and minor characteristics are defined in MIL-STD-105. Inspection shall be conducted as follows:

4.3.2.1.1 Destructor assembly, training (see dwg 8808442 covering a detail of dwg 8831014).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
	101. Cup protrusion, maximum (max.)	Gage
	102. Marking missing, incorrect, or illegible	Visual
	103. Any component damaged	Visual
	104. Any component missing	Visual
	105. Objective evidence relating to material missing or improper (see 3.1)	Visual
Minor:		
	201. Evidence of poor workmanship (see 3.6)	Visual

4.3.2.1.2 Cartons, prior to sealing (see dwgs. 8824893, 8824894 and 8808885).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
	101. Bottom flaps not secure	Visual
	102. Any required packing component missing	Visual
	103. Rust or corrosion on any component part	Visual
	104. Components wrapper missing or torn	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:01Z
Check the source to verify that this is the current version before use.

105. Contents improperly wrapped.....Visual
106. Destructor assembly dust cap loose.....Manual
107. Connector of mounting plate assembly not mounted tight and flush with shoulder.....Visual/Manual
108. Connector pins or threads of mounting plate assembly damaged.....Visual
109. Any component of mounting plate assembly missing, loose, broken or disconnected (including screws and lock washers).....Visual
110. Destructor leads improperly coiled.....Visual
111. Plastic closures for destructor lead assembly missing.....Visual
112. Objective evidence relating to material missing or improper (see 3.1).....Visual

Minor:
201. Evidence of poor workmanship (see 3.6).....Visual

4.3.2.1.3 Cartons, sealed (see dwgs 8824893, 8824894 and 8808885).

Categories	Characteristics	Method of Inspection

Critical: None defined.

Major:
101. Carton insecurely sealed.....Visual
102. Marking misleading or unidentifiable.....Visual
103. Corners not blunted.....Visual
104. Carton fractured, exposing contents.....Visual
105. Contents loose.....Manual
106. Label missing.....Visual

Minor:
201. Evidence of poor workmanship (see 3.6).....Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:01Z
Check the source to verify that this is the current version before use.

4.3.2.1.4 Container, prior to sealing (see dwg 8824895).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Package containing destructor assembly missing or damaged	Visual
102.	Package containing lead assembly missing or damaged	Visual
103.	Package containing mounting plate assembly missing or damaged	Visual
104.	Any packing component missing	Visual
105.	Packing list missing or mutilated	Visual
106.	Objective evidence relating to material missing or improper (see 3.1)	Visual
Minor:		
201.	Evidence of poor workmanship (see 3.6)	Visual

4.3.2.1.5 Container, sealed (see dwg 8824895).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Container damaged	Visual
102.	Car seal mislocated or damaged	Visual
103.	Marking missing, incorrect, or illegible	Visual
104.	Cover loose or improperly assembled	Visual/Manual
105.	Contents loose	Manual
Minor:		
201.	Evidence of poor workmanship (see 3.6)	Visual

4.3.3 Testing. All tests shall be performed. Tests shall be performed in the order specified below:

Test	Test Classification
a. Container vibration	Major

This test is considered destructive and samples so tested shall not be returned to the lot. Destructive samples are over and above the deliverable quantity of items required by the contract.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:01Z
Check the source to verify that this is the current version before use.

4.3.3.1 Container vibration. One sample container assembly shall be selected at random from every 50 consecutively produced container assemblies. The sample shall be tested in accordance with 4.4.1. If a sample fails to comply with 3.5, the 50 container assemblies from which the sample was taken shall be rejected.

4.3.4 Acceptance inspection equipment.

4.3.4.1 Major characteristics and tests. Inspection and testing shall be performed with the acceptance inspection equipment, operating instructions, and calibration instructions specified on the Equipment Lists (EL). Els for assemblies are listed on the Equipment Tabulation, ET-8831014. When either of the conditions listed below exist, the contractor shall design required equipment or specify suitable commercial equipment and obtain approval prior to use on the contract.

a. Any deviation from equipment or procedures specified on the EL is desired (see 6.3).
b. The code "CD" is listed in the "Part or Identifying Number" column on the EL (see 6.1.2).

4.3.4.2 Minor characteristics and tests. Acceptance inspection equipment for minor characteristics is not specified on ELs. The acceptance inspection equipment, operating instructions and calibration instructions used by the contractor for minor classification inspection shall be approved by the Government representative authorized by the procuring agency.

4.4 Test methods. The tolerances specified herein are absolute with no allowance for test equipment inaccuracy. The tolerances used by the manufacturer shall be equal to the absolute tolerances less the accuracy tolerances of the test equipment used.

4.4.1 Container vibration. The packed assembly shall be secured to a vibration table and vibrated for 15 minutes in each of three mutually perpendicular directions at a double amplitude of 0.064 inch. The frequency shall be varied uniformly from 10 to 55 to 10 Hz, making approximately one cycle per minute. After this test the cover shall be removed and the contents examined to insure compliance with the packing requirements of dwg 8824895.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging. Preservation and packaging shall be level A or C as specified (see 6.1).

5.1.1 Level A. The training destructor shall be packaged in accordance with dwgs 8808885, 8824893, 8824894 and 8824895 using the specified moisture barrier.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:01Z
Check the source to verify that this is the current version before use.

5.1.2 Level C. The training destructor shall be packaged in accordance with dwgs 8808885, 8824893, 8824894 and 8824895 except that the moisture barrier may be omitted.

5.2 Packing.

5.2.1 Level A and C. The training destructor shall be packed in accordance with dwgs 8808885, 8824893, 8824894 and 8824895.

5.3 Marking. Marking shall be as specified in accordance with dwgs 8808885, 8824893, 8824894 and 8824895.

6. NOTES

6.1 Ordering data. Procurement documents should specify the following:

a. Title, number, and date of this specification.
b. Selection of applicable level of packaging and packing required (see 5.1 and 5.2).

6.2 Objective evidence. Records of contractor quality control and inspections which can be verified.

6.3 Acceptance inspection equipment (see 4.3.4.1). The contractor shall obtain approval from the Commander, Picatinny Arsenal, Dover, New Jersey 07801, ATTN: SARPA-QA-T.

6.4 Supersession data. This specification supersedes the requirements of Purchase Description PA-PD-1575 Rev. A dated 11 January 1966.

Custodian:
Army - PA

Preparing activity:
Army - PA

Project No. 1135-A189

☆ U. S. GOVERNMENT PRINTING OFFICE: 1975 -603-766/0633

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:01Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/ vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 **1426** REPLACES EDITION OF 1 JAN 68 WHICH MAY BE USED

Source: https://assist.dla.mil - Downloaded: 2026-10-02T04:01Z
Check the source to verify that this is the current version before use.

633 SKS

FOLD

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD – 314

U.S.MAIL

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

COMMANDER
Picatinny Arsenal
ATTN: SARPA-QA-N-Q
Dover, New Jersey 07801

FOLD

80% $33

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:01Z
Check the source to verify that this is the current version before use.