MIL-S-45875(PA)
9 June 1975
SUPERSEDING
See Section 6

MILITARY SPECIFICATION

SYNCHRO TRANSMITTER, for M5 BAROSWITCH

1. SCOPE

1.1 This specification covers requirements, quality assurance provisions, and the preparation for delivery criteria for one type of Synchro Transmitter which is used on the Nike Hercules warhead section.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein:

SPECIFICATIONS

MILITARY

MIL-E-5272	- Environmental Testing, Aeronautical and Associated Equipment, General Specification For.

STANDARDS

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-202	- Test Methods for Electronic and Electric Component Parts.
MIL-STD-810	- Environmental Test Methods.
MIL-STD-1167	- Ammunition Data Card.
MIL-STD-1168	- Lot Numbering of Ammunition.
MIL-STD-1169	- Packaging, Packing and Marking of Inert Ammunition Components.
MIL-STD-1460	- Soldering of Electrical Connections and Printed Wiring Assemblies, Procedure For.

DRAWINGS

ORDNANCE CORPS

8803903 - Transmitter.
EL-8803903 - Equipment Lists.

FSC NUOR

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:03Z
Check the source to verify that this is the current version before use.

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Materials. The contractor shall furnish objective evidence (see 6.2) that the material complies with the specifications listed on the applicable drawing.

3.2 Assembly. The synchro transmitter shall comply with all requirements specified on the drawing (dwg) 8803903, with all requirements specified herein, and with the requirements of all applicable specifications to the extent specified on the drawing and herein.

3.3 First article testing. Requirements for the submission of first article samples by the contractor shall be as specified in the contract (see 4.2).

3.4 Serialization. The contractor shall assign serial numbers as required by drawings. The contractor may select any number which complies with the drawing requirement. These numbers shall not be duplicated.

3.5 Brush contact resistance. The brush contact resistance shall not exceed 0.5 ohm maximum at any rotor speed up to 300 revolutions per minute (rpm) when tested as specified in 4.4.1

3.6 Insulation resistance. The insulation resistance shall be a minimum of 25 megohms when measured with a 500 ± 50 volts dc potential for a period of five seconds minimum when tested as specified in 4.4.2.

3.7 Nulls. The residual voltage shall not exceed 70 millivolts maximum when tested as specified in 4.4.3.

3.8 Transmitter error. The transmitter error shall not exceed ± 15 minutes of arc at any position from a normal zero to 360 degrees rotation when tested as specified in 4.4.4.

3.9 Shaft end play. The shaft end play, parallel to the longitudinal axis of the transmitter, shall be 0.0003 to 0.0015 inch total indicator reading maximum when tested as specified in 4.4.5.

3.10 Radial play. The radial play perpendicular to the longitudinal axis of the transmitter shall be within 0.0008 inch total indicator reading maximum when tested as specified in 4.4.6.

3.11 Environmental testing. The synchro transmitter shall comply with MIL-STD-810, visual inspection and failure criteria, section 3. The synchro transmitter shall also comply with applicable requirements of 4.3.3.1 before and after each environmental test. Testing shall be as specified in 4.4.7. Tests shall be conducted in the order specified.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:03Z
Check the source to verify that this is the current version before use.

3.11.1 Vibration. The synchro transmitter shall withstand vibration through all frequencies, ranges, and times when tested as specified in 4.4.7.1.

3.11.2 Acceleration. The synchro transmitter shall withstand acceleration up to 50 g in any direction when tested as specified in 4.4.7.2.

3.11.3 Impack shock. The synchro transmitter shall withstand impact shocks of 30 g applied in any direction when tested as specified in 4.4.7.3.

3.11.4 Life. The synchro transmitter shall be capable of continuous operation at a speed of 50 rpm for a minimum of 2000 hours when tested as specified in 4.4.7.4.

3.11.5 Pull test. The leads shall withstand a two pound pull when tested as specified in 4.4.7.5.

3.11.6 Low temperature. The synchro transmitter shall meet the requirements of 3.8 after subjection to -65 ± 5°F when tested as specified in 4.4.7.6.

3.11.7 High temperature. The synchro transmitter shall meet the requirements of 3.8 after subjection to 300° ± 5°F when tested as specified in 4.4.7.7.

3.11.8 Fungus. The synchro transmitter shall show no evidence of fungus growth when tested as specified in 4.4.7.8.

3.12 Soldering. All soldering shall comply with the requirements specified in MIL-STD-1460.

3.13 Workmanship.

3.13.1 Plastic and metal characteristics. All components shall be free from cracks, splits, cold flow, shrinkage, cold shuts, inclusions, porosity, or any similar characteristic.

3.13.2 Threads. Threads shall be full and undamaged for the entire minimum length or depth as required on the applicable drawing.

3.13.3 Burrs. Parts shall be free from burrs.

3.13.4 Foreign matter. Parts shall be free from chips, dirt, grease, rust, corrosion, or any embedded foreign material.

3.13.5 Cleaning. The cleaning method shall not be injurious to any of the parts, nor shall the parts be contaminated by the cleaning agent.

3.13.6 Electrical. Cable assemblies and wires shall be dressed in such a manner as to prevent pinching or chafing of the wire insulation. Ends of wires shall be free from burrs, sharp edges, or points. All parts shall be free from flux, chips, dirt, grease, rust or foreign material.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise speci-

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:03Z
Check the source to verify that this is the current version before use.

fied in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 First article inspection.

4.2.1 Quantity to be submitted. When the contract requires first article inspection, the contractor shall submit 3 complete assemblies (see dwg 8803903) for first article testing to the testing facility designated in the invitation for bids or request for proposal.

4.2.2 Inspection and testing to be performed. The first article inspection sample shall be subjected to the inspections and tests specified in Table I. Tests shall be conducted in order specified in Table I.

Table I
First article inspection and tests

Inspection or Test	Dest	Non Dest
1. Classification of characteristics (see 4.3.2.1)		X
2. Brush contact resistance (see 3.5)		X
3. Insulation resistance (see 3.6)		X
4. Nulls (see 3.7)		X
5. Transmitter error (see 3.8)		X
6. Shaft end play (see 3.9)		X
7. Radial play (see 3.10)		X
8. Vibration (see 3.11.1)	X	
9. Acceleration (see 3.11.2)	X	
10. Impact shock (see 3.11.3)	X	
11. Life (see 3.11.4)		X
12. Pull test (see 3.11.5)	X	
13. Low temperature (see 3.11.6)		X
14. High temperature (see 3.11.7)		X
15. Fungus (see 3.11.8)		X

4.2.3 Inspection equipment. The inspection and testing specified in 4.2.2 shall be accomplished by using the gages and test equipment specified in 4.3.4.1.

4.2.4 Rejection. If any item fails to comply with any of the applicable requirements, the first article sample shall be rejected.

4.3 Quality conformance inspection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:03Z
Check the source to verify that this is the current version before use.

4.3.1 Lot formation.

4.3.1.1 Production lot. A lot shall consist of parts and assemblies produced by one manufacturer in one unchanged process, in accordance with the same drawing, same drawing revision, same specification and same specification revision. Drawing, specification and process changes not affecting safety, performance, storage, or interchangeability, as determined by the Government, shall not necessitate changing the lot interfix number. The criteria and procedures for the assignment of lot numbers shall be in accordance with MIL-STD-1168.

4.3.1.2 Inspection lot. A lot or batch and its formation, size, and presentation is described in MIL-STD-105, Section 5. Accordingly, a lot shall mean an inspection lot and a batch shall mean an inspection batch for the purpose of this specification. The manner in which each inspection lot or batch is to be presented and identified by the contractor, shall be designated or approved by the Government representative.

4.3.2 Product inspection examination. A sample shall be selected at random from each inspection lot in accordance with the applicable major or minor characteristic table (see Table II and Table III), and inspected for all characteristics in the applicable classification. Any characteristics in the sample found to be defective shall reject the inspection lot. Sequence for the inspection of characteristics in each classification need not be followed as long as all characteristic inspections are performed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:03Z
Check the source to verify that this is the current version before use.

Table II
Major Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-72	all	140-141	124	256-259	177	541-549	230
73	72	142	125	260-262	178	550-559	231
74	73	143-144	126	263-265	179	560-569	232
75	74	145	127	266-268	180	570-579	233
76	75	146-147	128	269-271	181	580-590	234
77	76	148-149	129	272-275	182	591-601	235
78	77	150	130	276-278	183	602-613	236
79	78	151-152	131	279-282	184	614-625	237
80	79	153-154	132	283-285	185	626-637	238
81-82	80	155-156	133	286-289	186	638-649	239
83	81	157	134	290-293	187	650-662	240
84	82	158-159	135	294-296	188	663-676	241
85	83	160-161	136	297-300	189	677-690	242
86	84	162-163	137	301-304	190	691-704	243
87	85	164-165	138	305-308	191	705-719	244
88-89	86	166-167	139	309-312	192	720-735	245
90	87	168	140	313-316	193	736-751	246
91	88	169-170	141	317-320	194	752-768	247
92	89	171-172	142	321-324	195	769-785	248
93	90	173-174	143	325-329	196	786-804	249
94-95	91	175-176	144	330-333	197	805-823	250
96	92	177-178	145	334-338	198	824-842	251
97	93	179-180	146	339-342	199	843-863	252
98	94	181-182	147	343-347	200	864-884	253
99-100	95	183-184	148	348-352	201	885-907	254
101	96	185-187	149	353-356	202	908-930	255
102	97	188-189	150	357-361	203	931-955	256
103	98	190-191	151	362-366	204	956-981	257
104-105	99	192-193	152	367-372	205	982-1008	258
106	100	194-195	153	373-377	206	1009-1036	259
107	101	196-197	154	378-382	207	1037-1066	260
108-109	102	198-200	155	383-388	208	1067-1098	261
110	103	201-202	156	389-393	209	1099-1131	262
111	104	203-204	157	394-399	210	1132-1166	263
112-113	105	205-207	158	400-405	211	1167-1204	264
114	106	208-209	159	406-411	212	1205-1243	265
115	107	210-212	160	412-417	213	1244-1285	266
116-117	108	213-214	161	418-424	214	1286-1330	267
118	109	215-217	162	425-430	215	1331-1378	268
119	110	218-219	163	431-437	216	1379-1429	269
120-121	111	220-222	164	438-443	217	1430-1483	270
122	112	223-224	165	444-450	218	1484-1542	271
123-124	113	225-227	166	451-457	219	1543-1605	272
125	114	228-230	167	458-465	220	1606-1673	273
126-127	115	231-232	168	466-472	221	1674-1747	274
128	116	233-235	169	473-480	222	1748-1827	275
129-130	117	236-238	170	481-488	223	1828-1914	276
131	118	239-241	171	489-496	224	1915-2010	277
132-133	119	242-243	172	497-504	225	2011-2115	278
134	120	244-246	173	505-513	226	2116-2232	279
135-136	121	247-249	174	514-521	227	2233-2361	280
137	122	250-252	175	522-530	228	over 2361	298
138-139	123	253-255	176	531-540	229		

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:03Z
Check the source to verify that this is the current version before use.

Table III
Minor Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-16	all	28-29	23	52-56	31	132-156	39
17	16	30-31	24	57-62	32	157-191	40
18	17	32-34	25	63-69	33	192-244	41
19-20	18	35-36	26	70-76	34	245-334	42
21	19	37-40	27	77-86	35	335-519	43
22-23	20	41-43	28	87-97	36	520-1120	44
24-25	21	44-47	29	98-112	37	over 1120	45
26-27	22	48-51	30	113-131	38		

4.3.2.1 Classification of characteristics (see 3.2). Critical, major and minor characteristics are defined in MIL-STD-105. Inspection shall be conducted as follows:

4.3.2.1.1 Assembly (see dwg 8803903).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
	101. Any outside diameter on case out of tolerance	Gage
	102. Shaft diameter out of tolerance	Gage
	103. Length of lead, min	Gage
	104. Damaged lead such as a break, split, etc	Visual
	105. Marking misleading or unidentifiable	Visual
	106. Retaining ring loose or missing	Visual/Manual
	107. Shaft not free to turn	Visual/Manual
	108. Lead loose or missing	Visual/Manual
	109. Solder improper (see 3.12)	Visual
	110. Objective evidence relating to material missing or improper (see 3.1)	Visual
Minor:		
	201. Finish damaged to the extent of exposing base metal	Visual
	202. Evidence of burr or a sharp edge	Visual
	203. Evidence of poor workmanship (see 3.13)	Visual
	204. Serialization improper or missing (see 3.4)	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:03Z
Check the source to verify that this is the current version before use.

4.3.2.1.2 Preparation for delivery (see 5).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Preservation, packing and packaging not in accordance with MIL-STD-1169	Visual
102.	Marking not in accordance with MIL-STD-1169	Visual
Minor:		
201.	Evidence of poor workmanship (see 3.13)	Visual

4.3.3 Testing. All tests shall be performed. Tests shall be performed in the order specified below:

Test	Test Classification
a. Brush contact resistance	Major
b. Insulation resistance	Major
c. Nulls	Major
d. Transmitter error	Major
e. Shaft end play	Major
f. Radial play	Major
g. Vibration	Major
h. Pull test	Major
i. Low temperature	Major
j. High temperature	Major

Of these tests, (g) and (h) are considered destructive and samples so tested shall not be returned to the lot. Destructive samples are over and above the deliverable quantity of items required by the contract.

4.3.3.1 Brush contact resistance, insulation resistance, nulls, transmitter error, shaft end play and radial play. Each synchro transmitter in the lot shall be tested in accordance with 4.4.1 through 4.4.6. If any item fails to comply with 3.5 through 3.10, the item shall be rejected and removed from the lot.

4.3.3.2 Vibration, pull test, low temperature and high temperature. Two sample synchro transmitters shall be selected from random from each lot and shall be tested in accordance with 4.4.7.1, 4.4.7.5, 4.4.7.6 and 4.4.7.7. If any item fails to comply with 3.11.1, 3.11.5, 3.11.6 and 3.11.7 the lot shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:03Z
Check the source to verify that this is the current version before use.

4.3.4 Acceptance inspection equipment.

4.3.4.1 Major characteristics and tests. Inspection and testing shall be performed with the acceptance inspection equipment, operating instructions, and calibration instructions specified on the Equipment Lists (EL) (see EL-8803903). When either of the conditions listed below exist, the contractor shall design required equipment or specify suitable commercial equipment and obtain approval prior to use on the contract.

a. Any deviation from equipment or procedures specified on the EL is desired (see 6.3).
b. The code "CD" is listed in the "Part or Identifying Number" column on the EL (see 6.1.2).

4.3.4.2 Minor characteristics and tests. Acceptance inspection equipment for minor characteristics is not specified on ELs. The acceptance inspection equipment, operating instructions and calibration instructions used by the contractor for minor classification inspection shall be approved by the Government representative authorized by the procuring agency.

4.4 Test methods. The tolerances specified herein are absolute with no allowance for test equipment inaccuracy. The tolerances used by the manufacturer shall be equal to the absolute tolerances less the accuracy tolerances of the test equipment used.

4.4.1 Brush contact resistance. The rotor leads shall be connected to a direct reading ohmmeter. The rotor shall be rotated slowly and rapidly (300 rpm max). The ohmmeter indication shall not change more than 0.5 ohm maximum for either condition of rotation.

4.4.2 Insulation resistance. Apply a minimum voltage of 500 ± 50 volts dc between rotor and case and between stator and case. The insulation resistance shall be a minimum of 25 megohms. To protect the component from excessive stresses resultant from retesting, it is required that any testing to this paragraph, subsequent to the tests performed by the manufacturer, shall be performed at a voltage of 375 ± 25 volts dc.

4.4.3 Nulls. The residual voltage measured by a Weston Model 982 or equivalent Voltmeter (10 megohms dc input impedance) shall not exceed 70 millivolts max.

4.4.4 Transmitter error. The synchro transmitter shall be calibrated by a test device whose inherent accuracy will insure that at 45 degree increments through 360 degrees, the maximum error of the synchro shall be ± 15 minutes.

4.4.5 Shaft end play. A three ounce reversing gage load shall be applied to the end of the shaft in a direction parallel to the longitudinal axis of the rotor with the rotor axis in its horizontal position. When shaft movement has ceased, the direction of the applied load shall be reversed. The rotor shaft shall be observed for maximum movement when the load is reversed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:03Z
Check the source to verify that this is the current version before use.

4.4.6 Radial play. A 40-gram reversing gage load shall be applied to the shaft not more than 1/8 inch from the housing, perpendicular to the longitudinal axis of the rotor, with the rotor axis in its horizontal position. When shaft movement has ceased, the direction of the applied load shall be reversed. The rotor shaft shall be observed for maximum movement when the load is applied. Measurements shall be taken along the shaft at 1/8 inch from the housing.

4.4.7 Environmental testing (see 3.11).

4.4.7.1 Vibration. The synchro transmitter shall be mounted on a vibration table and vibrated in each of three mutually perpendicular axes under the following conditions for a total of 10 cycles.

Frequency Range (Hz)	Constant Acceleration (g)	Cycle Time (Minutes)
10-20	1	1
20-30	4	1
30-80	10	1
80-100	6	1
100-500	5	5

After completion of these tests, the synchro transmitter shall be tested as specified in 4.4.4.

4.4.7.2 Acceleration. The synchro transmitter shall be mounted on the apparatus (centrifuge), and subjected to an acceleration of 50 g in each direction along its three perpendicular axes, one of which is its axis of rotation. This acceleration shall be stabilized and maintained for a period of not less than one minute for each of the six directions. After the completion of this test, the synchro transmitter shall be tested as specified in 4.4.1 through 4.4.4. There shall be no evidence of mechanical failure or malfunctions due to the applied acceleration.

4.4.7.3 Impact shock. The synchro transmitter shall be mounted on a suitable acceleration device as outlined in MIL-STD-202, Method 202A and shall be subjected to two impack shocks of 30 g in each of three mutually perpendicular axes in both the positive and negative directions. Each of the 12 shocks shall reach maximum in 5.5 milliseconds and shall have a minimum duration of 11 milliseconds. After test the synchro transmitter shall be tested as specified in 4.4.4.

4.4.7.4 Life. The synchro transmitter shall be mounted on a suitable fixture and with rated voltage applied, the rotor shall be driven at a speed of 50 rpm for 2000 hours. After each 500 hours of testing and completion of 2000 hours the synchro shall be tested as specified in 4.4.4.

4.4.7.5 Pull test. A force shall be applied at a point one inch from the free end of each lead. The force shall be

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:03Z
Check the source to verify that this is the current version before use.

applied in any direction, including the weakest, and shall be increased gradually to 2 pounds and held at this value for at least thirty seconds. There shall be no evidence of damage to the solder connections after completion of this test, and the synchro transmitter shall be tested as specified in 4.4.4.

4.4.7.6 Low temperature. The synchro transmitter shall be placed in a suitable chamber and stabilized (see 6.4) at -65 ± 5°F. The unit shall then meet a friction requirement of not more than 15 gram-centimeters while being rotated at approximately 1 rpm. After this test the temperature shall be gradually increased to ambient room temperature (75 ± 10°F) and the synchro transmitter shall be tested as specified in 4.4.4.

4.4.7.7 High temperature. The synchro transmitter shall be placed in a suitable chamber and stabilized (see 6.4) at 300 ± 5°F. The unit shall then meet a friction requirement of not more than 15 gram-centimeters while being rotated at approximately 1 rpm. After this test the temperature shall be gradually decreased to amibient room temperature (75 ± 10°F) and the synchro transmitter shall be tested as specified in 4.4.4.

4.4.7.8 Fungus. The synchro transmitter shall be subjected to the action of fungi in accordance with section 4.8 or MIL-E-5272. At the end of the test period, the synchro transmitter shall be disassembled and carefully examined to ascertain that no fungus growth has occured on the synchro transmitter.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging. Preservation and packaging shall be level A or C as specified (see 6.1).

5.1.1 Level A. The synchro transmitter shall be preserved and packaged in accordance with instructions contained in MIL-STD-1169.

5.1.2 Level C. The synchro transmitter shall be preserved and packaged in accordance with instructions contained in MIL-STD-1169.

5.2 Packing.

5.2.1 Levels A and C. The synchro transmitter shall be packed in accordance with the applicable instructions contained in MIL-STD-1169.

5.3 Marking. Marking shall be in accordance with MIL-STD-1169.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:03Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Ordering data. Procurement documents should specify the following:

6.1.1 Procurement requirements.

a. Title, number, and date of this specification.

b. Selection of applicable level of packaging and packing required (see 5.1 and 5.2).

6.1.2 Contract data requirements (see 4.3.4.1). Data specified in 4.3.4.1 will be delivered as identified on a numbered DD Form 1664 when required on a DD Form 1423 incorporated in the contract.

6.2 Objective evidence. Records of contractor quality control and inspections which can be verified.

6.3 Acceptance inspection equipment (see 4.3.4.1). The contractor shall obtain approval from the Commander, Picatinny Arsenal, Dover, New Jersey 07801, ATTN: SARPA-QA-T.

6.4 Temperature stabilization. The temperature is considered stabilized when the greatest peaks (both highest and lowest) continually observed over 5 minutes min. do not exceed the nominal temperature plus tolerance specified.

6.5 Supersession data. This specification supersedes the requirements of Purchase Description PA-PD-1164 (Rev. 1) dated 28 September 1962.

Custodian:
Army - PA

Preparing activity:
Army - PA

Project No. NUOR-A042

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:03Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/ vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426

REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:03Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD – 314

U.S. MAIL

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

COMMANDER
Picatinny Arsenal
ATTN: SARPA-QA-N-Q
Dover, New Jersey 07801

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:03Z
Check the source to verify that this is the current version before use.